

- RF Exposure

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

| Frequency Range | Electric Field Strength [V/m] | Magnetic Field Strength [A/m] | Power Density [mW/cm ²] | Averaging Time [minute] |
|---|-------------------------------|-------------------------------|-------------------------------------|-------------------------|
| Limits for General Population / Uncontrolled Exposure | | | | |
| 0.3 ~ 1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34 ~ 30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30 ~ 300 | 27.5 | 0.073 | 0.2 | 30 |
| 300 ~ 1 500 | / | / | f/1 500 | 30 |
| 1 500 ~ 15 000 | / | / | 1.0 | 30 |

f=frequency in MHz, * = plane-wave equivalent power density

MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm²]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.

3. Calculation Result of RF Exposure

| Mode | Target power [dBm] | Tune up tolerance [dB] | Max tune up power [dBm] | Max tune up power [mW] | Ant Gain [dBi] | Ant Gain [mW] | Power Density at 20 cm [mW/cm ²] | Limit [mW/cm ²] |
|----------------|--------------------|------------------------|-------------------------|------------------------|----------------|---------------|--|-----------------------------|
| Bluetooth_GFSK | 0 | ±2.0 | 2.00 | 1.58 | 2.85 | 1.93 | 0.000 61 | 1.000 00 |
| Total | | | - | | | | 0.000 61 | 1.000 00 |

4. Target power and tolerance, Max tuneup power

| Mode | Target power [dBm] | Tolerance [dB] | Max tuneup power [dBm] | Average Power [dBm] |
|----------------------------|--------------------|----------------|------------------------|---------------------|
| Bluetooth_GFSK Lowest | 0 | ±2.0 | 2.00 | 0.98 |
| Bluetooth_GFSK Middle | 0 | ±2.0 | 2.00 | 1.16 |
| Bluetooth_GFSK Highest | 0 | ±2.0 | 2.00 | 0.68 |
| Bluetooth_π/4DQPSK Lowest | -4.00 | ±2.0 | -2.00 | -2.89 |
| Bluetooth_π/4DQPSK Middle | -4.00 | ±2.0 | -2.00 | -3.09 |
| Bluetooth_π/4DQPSK Highest | -4.00 | ±2.0 | -2.00 | -3.78 |
| Bluetooth_8DPSK Lowest | -4.00 | ±2.0 | -2.00 | -2.91 |
| Bluetooth_8DPSK Middle | -4.00 | ±2.0 | -2.00 | -3.11 |
| Bluetooth_8DPSK Highest | -4.00 | ±2.0 | -2.00 | -3.77 |