

FCC Report

Applicant: Huizhou Tuoying Technology Limited Company
Address of Applicant: Second Floor No.1 Factory, Lianhong Industrial Park, Sanhe Development Zone, Huiyang District, Huizhou City, China
Manufacturer/Factory: Huizhou Tuoying Technology Limited Company
Address of Manufacturer/Factory: Second Floor No.1 Factory, Lianhong Industrial Park, Sanhe Development Zone, Huiyang District, Huizhou City, China

Equipment Under Test (EUT)

Product Name: 2.4G multi-channel folding RC

Model No.: TE-T8

Trade Mark: TOPE

FCC ID: 2ASBP-TE-T8

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: December 26, 2018

Date of Test: December 27, 2018-January 06, 2019

Date of report issued: January 07, 2019

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	January 07, 2019	Original

Prepared By:



Date:

January 07, 2019

Project Engineer

Check By:



Date:

January 07, 2019

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY	7
5.5 TEST LOCATION	7
5.6 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED OUTPUT POWER	14
7.4 CHANNEL BANDWIDTH	16
7.5 POWER SPECTRAL DENSITY	18
7.6 BAND EDGES	20
7.6.1 Conducted Emission Method	20
7.6.2 Radiated Emission Method	21
7.7 SPURIOUS EMISSION	24
7.7.1 Conducted Emission Method	24
7.7.2 Radiated Emission Method	26
8 TEST SETUP PHOTO	37
9 EUT CONSTRUCTIONAL DETAILS	37

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	2.4G multi-channel folding RC
Model No.:	TE-T8
Test sample(s) ID:	GTS201812000160-1
Sample(s) Status	Engineer sample
Operation Frequency:	2405MHz-2475MHz
Channel Numbers:	15
Channel Separation:	5MHz
Modulation Type:	GFSK
Antenna Type:	Integral Antenna
Antenna Gain:	2.0dBi(declare by manufacturer)
Power Supply:	DC 3.7V 450mAh 1.665Wh

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2405MHz	5	2425MHz	9	2445MHz	13	2465MHz
2	2410MHz	6	2430MHz	10	2450MHz	14	2470MHz
3	2415MHz	7	2435MHz	11	2455MHz	15	2475MHz
4	2420MHz	8	2440MHz	12	2460MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2405MHz
The middle channel	2440MHz
The Highest channel	2475MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

5.3 Description of Support Units

None

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

- **CNAS (No. CNAS L5775)**

CNAS has accredited Global United Technology Services Co., Ltd., to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.6 Additional Instructions

EUT Software Settings:

Special test software was pre-built-in by manufacturer. Power set default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	June. 27 2018	June. 26 2019
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna: <i>The antenna is Integral antenna, the best case gain of the antenna is 2.0dBi</i>	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																
Test Method:	ANSI C63.10:2013																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<small>* Decreases with the logarithm of the frequency.</small>																
Test setup:	<p>Reference Plane</p> <p>Remark: <i>E.U.T: Equipment Under Test</i> <i>LISN: Line Impedance Stabilization Network</i> <i>Test table height=0.8m</i></p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2009 on conducted measurement. 																
Test Instruments:	Refer to section 6.0 for details																
Test mode:	Refer to section 5.2 for details																
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar											
Test voltage:	AC 120V, 60Hz																
Test results:	Pass																


Measurement data

Line:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.15	49.00	0.40	0.07	49.47	65.87	-16.40	QP
0.15	40.81	0.40	0.07	41.28	55.87	-14.59	Average
0.20	42.72	0.40	0.11	43.23	63.54	-20.31	QP
0.20	32.43	0.40	0.11	32.94	53.54	-20.60	Average
0.25	38.89	0.40	0.10	39.39	61.64	-22.25	QP
0.25	29.35	0.40	0.10	29.85	51.64	-21.79	Average
0.63	29.94	0.28	0.12	30.34	56.00	-25.66	QP
0.63	23.85	0.28	0.12	24.25	46.00	-21.75	Average
2.16	18.23	0.20	0.18	18.61	56.00	-37.39	QP
2.16	11.67	0.20	0.18	12.05	46.00	-33.95	Average
12.65	29.49	0.20	0.21	29.90	60.00	-30.10	QP
12.65	22.98	0.20	0.21	23.39	50.00	-26.61	Average

Neutral:




Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.15	48.74	0.40	0.07	49.21	65.87	-16.66	QP
0.15	41.00	0.40	0.07	41.47	55.87	-14.40	Average
0.20	40.83	0.40	0.11	41.34	63.62	-22.28	QP
0.20	33.54	0.40	0.11	34.05	53.62	-19.57	Average
0.25	39.55	0.40	0.10	40.05	61.64	-21.59	QP
0.25	31.83	0.40	0.10	32.33	51.64	-19.31	Average
0.63	34.44	0.28	0.12	34.84	56.00	-21.16	QP
0.63	28.69	0.28	0.12	29.09	46.00	-16.91	Average
2.26	24.49	0.20	0.18	24.87	56.00	-31.13	QP
2.26	17.79	0.20	0.18	18.17	46.00	-27.83	Average
12.65	30.16	0.20	0.21	30.57	60.00	-29.43	QP
12.65	23.16	0.20	0.21	23.57	50.00	-26.43	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. *Final Level = Receiver Read level + Correct factor*
4. *Correct factor = LISN Factor + Cable Loss*
5. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*


7.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	8.58	30.00	Pass
Middle	8.53		
Highest	8.32		


Test plot as follows:



Lowest channel




Middle channel



Highest channel


7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	Channel Bandwidth (kHz)	Limit(KHz)	Result
Lowest	556.606	>500	Pass
Middle	561.279		
Highest	553.939		

Test plot as follows:



Lowest channel




Middle channel



Highest channel


7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Test channel	Power Spectral Density (dBm/3KHz)	Limit(dBm/3kHz)	Result
Lowest	-1.09	8.00	Pass
Middle	-1.00		
Highest	-1.38		


Test plot as follows:



Lowest channel




Middle channel




Highest channel

7.6 Band edges


7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:




7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2390MHz, 2483.5MHz to 2500MHz) data was showed.						
Test site:	Measurement Distance: 3m						
Receiver setup:	Frequency	Detector	RBW	VBW	Value		
	Above 1GHz	Peak	1MHz	3MHz	Peak		
Limit:	Frequency		Limit (dBuV/m @3m)		Value		
	Above 1GHz		54.00		Average		
	Above 1GHz		74.00		Peak		
Test setup:							
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. 						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	
Test results:	Pass						


Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test channel:	Lowest
---------------	--------


Horizontal:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	33.50	27.14	6.19	42.04	24.79	54.00	-29.21	Average
2310.000	53.15	27.14	6.19	42.04	44.44	74.00	-29.56	Peak
2390.025	33.50	27.37	6.31	42.11	25.07	54.00	-28.93	Average
2390.025	63.96	27.37	6.31	42.11	55.53	74.00	-18.47	Peak


Vertical:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	33.50	27.14	6.19	42.04	24.79	54.00	-29.21	Average
2310.000	45.11	27.14	6.19	42.04	36.40	74.00	-37.60	Peak
2390.025	34.50	27.37	6.31	42.11	26.07	54.00	-27.93	Average
2390.025	61.88	27.37	6.31	42.11	53.45	74.00	-20.55	Peak

Test channel:	Highest
---------------	---------

Horizontal:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	39.50	27.66	6.45	42.01	31.60	54.00	-22.40	Average
2483.500	61.78	27.66	6.45	42.01	53.88	74.00	-20.12	Peak
2490.658	42.50	27.68	6.46	42.01	34.63	54.00	-19.37	Average
2490.658	62.60	27.68	6.46	42.01	54.73	74.00	-19.27	Peak
2500.000	33.50	27.70	6.47	42.00	25.67	54.00	-28.33	Average
2500.000	44.53	27.70	6.47	42.00	36.70	74.00	-37.30	Peak

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	34.50	27.66	6.45	42.01	26.60	54.00	-27.40	Average
2483.500	53.29	27.66	6.45	42.01	45.39	74.00	-28.61	Peak
2500.000	33.50	27.70	6.47	42.00	25.67	54.00	-28.33	Average
2500.000	44.60	27.70	6.47	42.00	36.77	74.00	-37.23	Peak

Remark:

1. Final Level = Receiver Read level + Correct factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Correct factor = Antenna Factor + Cable Loss – Preamplifier Factor


7.7 Spurious Emission

7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The E.U.T is placed on a Non-Conducted Table. The entire setup is positioned above a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Test plot as follows:

Lowest channel




30MHz~25GHz

Middle channel



30MHz~25GHz




Highest channel



30MHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	PK/AV	200Hz	600Hz	PK/AV
	150KHz-30MHz	PK/AV/QP	9KHz	30KHz	PK/AV/QP
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance 3m	
	0.009MHz-0.490MHz	2400/F(KHz)	QP		
	0.490MHz-1.705MHz	24000/F(KHz)	QP		
	1.705MHz-30MHz	30	QP		
	30MHz-88MHz	100	QP		
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				

Test setup:	<p>Below 30MHz</p>  <p>Below 1GHz</p>  <p>Above 1GHz</p> 
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both

	horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test results:	Pass

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement Data

■ 9 kHz ~ 30 MHz


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
34.517	46.73	11.29	0.60	35.32	23.30	40.00	-16.70	QP
103.080	40.23	11.83	1.22	36.75	16.53	43.50	-26.97	QP
204.238	44.46	10.58	1.86	37.33	19.57	43.50	-23.93	QP
545.183	49.34	18.34	3.50	37.52	33.66	46.00	-12.34	QP
576.644	46.68	19.00	3.63	37.53	31.78	46.00	-14.22	QP
656.530	40.78	19.56	3.94	37.59	26.69	46.00	-19.31	QP


Vertical:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
39.437	43.37	12.11	0.65	35.63	20.50	40.00	-19.50	QP
48.332	45.73	12.29	0.75	36.10	22.67	40.00	-17.33	QP
100.581	45.65	12.10	1.19	36.73	22.21	43.50	-21.29	QP
204.238	43.49	10.58	1.86	37.33	18.60	43.50	-24.90	QP
545.183	42.41	18.34	3.50	37.52	26.73	46.00	-19.27	QP
576.644	40.61	19.00	3.63	37.53	25.71	46.00	-20.29	QP


■ Above 1GHz

Test channel:	Lowest
---------------	--------

Horizontal:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
3414.000	34.75	28.35	3.66	37.44	29.32	54.00	-24.68	Average
3414.000	39.75	28.35	3.66	37.44	34.32	74.00	-39.68	Peak
7375.000	27.33	36.30	6.69	35.48	34.84	54.00	-19.16	Average
7375.000	33.33	36.30	6.69	35.48	40.84	74.00	-33.16	Peak
9279.000	24.40	37.63	7.77	34.66	35.14	54.00	-18.86	Average
9279.000	33.40	37.63	7.77	34.66	44.14	74.00	-29.86	Peak
11489.000	25.10	39.80	8.73	36.45	37.18	54.00	-16.82	Average
11489.000	33.10	39.80	8.73	36.45	45.18	74.00	-28.82	Peak
14090.000	24.71	41.75	9.66	36.50	39.62	54.00	-14.38	Average
14090.000	33.71	41.75	9.66	36.50	48.62	74.00	-25.38	Peak
16827.000	23.86	39.87	11.13	36.21	38.65	54.00	-15.35	Average
16827.000	33.86	39.87	11.13	36.21	48.65	74.00	-25.35	Peak


Vertical:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4810.000	33.27	31.36	4.61	37.58	31.66	54.00	-22.34	Average
4810.000	38.27	31.36	4.61	37.58	36.66	74.00	-37.34	Peak
7069.000	26.45	35.57	6.32	35.41	32.93	54.00	-21.07	Average
7069.000	34.45	35.57	6.32	35.41	40.93	74.00	-33.07	Peak
10690.000	25.74	39.48	8.40	36.14	37.48	54.00	-16.52	Average
10690.000	33.74	39.48	8.40	36.14	45.48	74.00	-28.52	Peak
14277.000	23.97	41.63	9.76	36.29	39.07	54.00	-14.93	Average
14277.000	31.97	41.63	9.76	36.29	47.07	74.00	-26.93	Peak
16419.000	24.29	39.44	11.04	35.77	39.00	54.00	-15.00	Average
16419.000	32.29	39.44	11.04	35.77	47.00	74.00	-27.00	Peak

Test channel:	Middle
---------------	--------

Horizontal:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	31.46	31.48	4.69	37.59	30.04	54.00	-23.96	Average
4880.000	36.46	31.48	4.69	37.59	35.04	74.00	-38.96	Peak
10146.000	25.74	38.83	8.18	35.48	37.27	54.00	-16.73	Average
10146.000	34.74	38.83	8.18	35.48	46.27	74.00	-27.73	Peak
11710.000	25.99	39.34	8.82	36.43	37.72	54.00	-16.28	Average
11710.000	33.99	39.34	8.82	36.43	45.72	74.00	-28.28	Peak
15059.000	25.54	40.48	10.17	35.49	40.70	54.00	-13.30	Average
15059.000	32.54	40.48	10.17	35.49	47.70	74.00	-26.30	Peak
17371.000	25.67	41.90	11.49	36.36	42.70	54.00	-11.30	Average
17371.000	32.67	41.90	11.49	36.36	49.70	74.00	-24.30	Peak


Vertical:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	32.64	31.48	4.69	37.59	31.22	54.00	-22.78	Average
4880.000	37.64	31.48	4.69	37.59	36.22	74.00	-37.78	Peak
9466.000	26.64	37.52	7.91	34.83	37.24	54.00	-16.76	Average
9466.000	34.64	37.52	7.91	34.83	45.24	74.00	-28.76	Peak
11268.000	26.19	39.71	8.64	36.47	38.07	54.00	-15.93	Average
11268.000	34.19	39.71	8.64	36.47	46.07	74.00	-27.93	Peak
13937.000	25.24	41.66	9.58	36.60	39.88	54.00	-14.12	Average
13937.000	33.24	41.66	9.58	36.60	47.88	74.00	-26.12	Peak
16453.000	25.02	39.59	11.05	35.81	39.85	54.00	-14.15	Average
16453.000	33.02	39.59	11.05	35.81	47.85	74.00	-26.15	Peak


Test channel:

Highest

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV	Limit level dBuV/m	Over limit dB	Remark
4950.000	31.97	31.61	4.77	37.60	30.75	54.00	-23.25	Average
4950.000	36.97	31.61	4.77	37.60	35.75	74.00	-38.25	Peak
6984.000	26.90	35.37	6.23	35.42	33.08	54.00	-20.92	Average
6984.000	34.90	35.37	6.23	35.42	41.08	74.00	-32.92	Peak
10282.000	28.14	39.05	8.24	35.65	39.78	54.00	-14.22	Average
10282.000	34.14	39.05	8.24	35.65	45.78	74.00	-28.22	Peak
11319.000	27.62	39.73	8.66	36.47	39.54	54.00	-14.46	Average
11319.000	34.62	39.73	8.66	36.47	46.54	74.00	-27.46	Peak
15025.000	25.53	40.60	10.14	35.49	40.78	54.00	-13.22	Average
15025.000	32.53	40.60	10.14	35.49	47.78	74.00	-26.22	Peak

Vertical:


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4950.000	32.60	31.61	4.77	37.60	31.38	54.00	-22.62	Average
4950.000	37.60	31.61	4.77	37.60	36.38	74.00	-37.62	Peak
8276.000	27.00	37.59	6.95	35.25	36.29	54.00	-17.71	Average
8276.000	34.00	37.59	6.95	35.25	43.29	74.00	-30.71	Peak
10639.000	27.45	39.46	8.38	36.08	39.21	54.00	-14.79	Average
10639.000	34.45	39.46	8.38	36.08	46.21	74.00	-27.79	Peak
14073.000	26.02	41.76	9.65	36.52	40.91	54.00	-13.09	Average
14073.000	33.02	41.76	9.65	36.52	47.91	74.00	-26.09	Peak
15246.000	25.68	39.77	10.33	35.45	40.33	54.00	-13.67	Average
15246.000	33.68	39.77	10.33	35.45	48.33	74.00	-25.67	Peak

8 Test Setup Photo

Reference to the [appendix I](#) for details.

9 EUT Constructional Details

Reference to the [appendix II](#) for details.

-----End-----