

## MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

### EUT Specification

<b>FCC ID</b>	2ASCB-55ROTDIG
<b>EUT</b>	55inch Indoor Floor Standing Rotary Screen All-in-one Machine, IR Touch
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> BT: 2.402GHz ~ 2.480GH <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> RLAN: 5.180GHz ~ 5.240GHz <input checked="" type="checkbox"/> RLAN: 5.260GHz ~ 5.320GHz <input checked="" type="checkbox"/> RLAN: 5.500GHz ~ 5.700GHz <input checked="" type="checkbox"/> RLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others:
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others: ___
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure <input checked="" type="checkbox"/> General Population/Uncontrolled exposure
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	BLE: 8.53 dBm (0.0071W) WiFi 2.4G: 16.46 dBm (0.0443W) WiFi 5.2G: 21.66 dBm (0.1466W) WiFi 5.3G: 16.44 dBm (0.0441W) WiFi 5.6G: 16.92 dBm (0.0492W) WiFi 5.8G: 16.73 dBm (0.0471W)
<b>Antenna gain (Max)</b>	BLE: 4.92dBi WiFi 2.4G: 4.92dBi WiFi 5.2G: 5.06dBi WiFi 5.3G: 5.17dBi WiFi 5.6G: 5.21dBi WiFi 5.8G: 5.28dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation

#### Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.  
 Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline  
400-003-0500  
www.anbotek.com.cn



SAR Evaluation

### Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

### Friis transmission formula: $Pd=(Pout*G)/(4*pi*R^2)$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pout=output power to antenna in Mw

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### Max Measurement Result

Operating Mode	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits
	(dBm)	(dBm)	(dBm)	(dBi)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
BLE	8.53	8.53 ±1	9.53	4.92	0.0055	1
WiFi 2.4G	16.46	16.46 ±1	17.46	4.92	0.0344	1
WiFi 5.2G	21.66	21.66 ±1	22.66	5.06	0.1177	1
WiFi 5.3G	16.44	16.44 ±1	17.44	5.17	0.0363	1
WiFi 5.6G	16.92	16.92 ±1	17.92	5.21	0.0409	1
WiFi 5.8G	16.73	16.73 ±1	17.73	5.28	0.0398	1

The ratios cannot simultaneous transmission.

Result: No Standalone SAR test is required.

