

APPLICATION CERTIFICATION FCC Part 15C & IC
On Behalf of
The StayWell Company, LLC

FITNESS TRACKER
Model No.: ID107L

FCC ID: 2ASDE-SWTV2
IC: 24709-SWTV2

Prepared for : The StayWell Company, LLC
Address : 800 Township Line Road, Suite 100, Yardley, PA, USA 19067

Prepared by : Shenzhen Accurate Technology Co., Ltd.
Address : 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report No. : ATE20190173
Date of Test : January 9-January 18, 2019
Date of Report : February 22, 2019

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Carrier Frequency of Channels	5
1.3. Special Accessory and Auxiliary Equipment	6
1.4. Description of Test Facility	6
1.5. Measurement Uncertainty	6
2. MEASURING DEVICE AND TEST EQUIPMENT	7
3. OPERATION OF EUT DURING TESTING	8
3.1. Operating Mode.....	8
3.2. Configuration and peripherals	8
4. TEST PROCEDURES AND RESULTS	9
5. 6DB BANDWIDTH TEST.....	10
5.1. Block Diagram of Test Setup.....	10
5.2. The Requirement For Section 15.247(a)(2).....	10
5.3. The Requirement For RSS-247 Section 5.2(a)	10
5.4. EUT Configuration on Measurement	10
5.5. Operating Condition of EUT	10
5.6. Test Procedure	10
5.7. Test Result	11
6. 99% OCCUPIED BANDWIDTH TEST	13
6.1. Block Diagram of Test Setup.....	13
6.2. The Requirement for RSS-Gen Clause 6.7	13
6.3. EUT Configuration on Measurement	13
6.4. Operating Condition of EUT	13
6.5. Test Procedure	14
6.6. Test Result	14
7. MAXIMUM PEAK OUTPUT POWER TEST	17
7.1. Block Diagram of Test Setup.....	17
7.2. The Requirement For Section 15.247(b)(3).....	17
7.3. The Requirement For RSS-247 Section 5.4(d)	17
7.4. EUT Configuration on Measurement	17
7.5. Operating Condition of EUT	17
7.6. Test Procedure	17
7.7. Test Result	18
8. POWER SPECTRAL DENSITY TEST.....	20
8.1. Block Diagram of Test Setup.....	20
8.2. The Requirement For Section 15.247(e).....	20
8.3. The Requirement For RSS-247 Section 5.2(b)	20
8.4. EUT Configuration on Measurement	20
8.5. Operating Condition of EUT	20
8.6. Test Procedure	21
8.7. Test Result	21
9. BAND EDGE COMPLIANCE TEST	24
9.1. Block Diagram of Test Setup.....	24

9.2.	The Requirement For Section 15.247(d)	24
9.3.	The Requirement For RSS-247 Section 5.5.....	24
9.4.	EUT Configuration on Measurement	24
9.5.	Operating Condition of EUT	25
9.6.	Test Procedure	25
9.7.	Test Result	25
10.	RADIATED SPURIOUS EMISSION TEST	31
10.1.	Block Diagram of Test Setup.....	31
10.2.	The Limit For Section 15.247(d)	32
10.3.	The Limit For RSS-247 Section 5.5	32
10.4.	Transmitter Emission Limit	33
10.5.	Restricted bands of operation	34
10.6.	Operating Condition of EUT	36
10.7.	Test Procedure	36
10.8.	Data Sample	37
10.9.	Test Result	37
11.	CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST	65
11.1.	Block Diagram of Test Setup.....	65
11.2.	The Requirement For Section 15.247(d)	65
11.3.	The Requirement For RSS-247 Section 5.5.....	65
11.4.	EUT Configuration on Measurement	65
11.5.	Operating Condition of EUT	66
11.6.	Test Procedure	66
11.7.	Test Result	66
12.	POWER LINE CONDUCTED EMISSION TEST	69
12.1.	Block Diagram of Test Setup.....	69
12.2.	Test System Setup.....	69
12.3.	Test Limits	70
12.4.	Configuration of EUT on Measurement	70
12.5.	Operating Condition of EUT	70
12.6.	Test Procedure	70
12.7.	Data Sample	71
12.8.	Test Result	71
13.	ANTENNA REQUIREMENT.....	74
13.1.	The Requirement	74
13.2.	Antenna Construction	74

Test Report Certification

Applicant : The StayWell Company, LLC
Address : 800 Township Line Road, Suite 100, Yardley, PA, USA 19067
Factory : Shenzhen DO Intelligent Technology Co.,Ltd
Address : 11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Product : FITNESS TRACKER
Model No. : ID107L

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10: 2013

RSS-247 Issue 2 February 2017

RSS-Gen Issue 5 April 2018

The EUT was tested according to DTS test procedure of August 24, 2018 KDB558074 D01 DTS Meas Guidance v05 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by Shenzhen Accurate Technology Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 and IC limits. The measurement results are contained in this test report and Shenzhen Accurate Technology Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Shenzhen Accurate Technology Co., Ltd.

Date of Test :

January 9-January 18, 2019

Date of Report :

February 22, 2019

Prepared by :



Approved & Authorized Signer :

(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : FITNESS TRACKER
Model Number : ID107L
Bluetooth Version : Bluetooth 4.0, single mode
Frequency Range : 2402-2480MHz
Modulation Type : GFSK
Number of Channels : 40 channels
Channel Spacing : 2MHz
Antenna Gain : -2.4dBi
Antenna Type : Integral Antenna
Power Supply : DC 3.7V (Powered by Lithium battery) or DC 5V (Powered by USB port)
HVIN : ID107L
Trade Mark : N/A

1.2. Carrier Frequency of Channels

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channe 1	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.3.Special Accessory and Auxiliary Equipment

N/A

1.4.Description of Test Facility

EMC Lab : Recognition of accreditation by Federal Communications Commission (FCC)
The Designation Number is CN1189
The Registration Number is 708358

Listed by Innovation, Science and Economic Development Canada (ISED)
The Registration Number is 5077A-2

Accredited by China National Accreditation Service for Conformity Assessment (CNAS)
The Registration Number is CNAS L3193

Accredited by American Association for Laboratory Accreditation (A2LA)
The Certificate Number is 4297.01

Name of Firm : Shenzhen Accurate Technology Co., Ltd.
Site Location : 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

1.5.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 05, 2019	One Year
EMI Test Receiver	Rohde&Schwarz	ESR	101817	Jan. 05, 2019	One Year
Spectrum Analyzer	Rohde&Schwarz	FSV-40	101495	Jan. 05, 2019	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 05, 2019	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 05, 2019	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 05, 2019	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 05, 2019	One Year
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 05, 2019	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 05, 2019	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 05, 2019	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 05, 2019	One Year
Conducted Emission Measurement Software: ES-K1 V1.71					
Radiated Emission Measurement Software: EZ_EMC V1.1.4.2					

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **Transmitting mode**

Low Channel: 2402MHz

Middle Channel: 2440MHz

High Channel: 2480MHz

Its duty cycle setting is greater than 98%.

3.2.Configuration and peripherals





Figure 1 Setup: Transmitting mode

4. TEST PROCEDURES AND RESULTS

FCC & IC Rules	Description of Test	Result
FCC Section 15.247(a)(2) RSS-247 Section 5.2(a)	6dB Bandwidth Test	Compliant
RSS-Gen Section 6.7	99% Occupied Bandwidth Test	Compliant
FCC Section 15.247(b)(3) RSS-247 Section 5.4(d)	Maximum Peak Output Power Test	Compliant
FCC Section 15.247(e) RSS-247 Section 5.2(b)	Power Spectral Density Test	Compliant
FCC Section 15.247(d) RSS-247 Section 5.5 RSS-Gen Section 8.10	Band Edge Compliance Test	Compliant
FCC Section 15.247(d) FCC Section 15.209 RSS-247 Section 5.5 RSS-Gen Section 6.13 RSS-Gen Section 8.9	Radiated Spurious Emission Test	Compliant
FCC Section 15.207 RSS-Gen Section 8.8	Power Line Conducted Emission Test	Compliant
FCC Section 15.203 RSS-Gen Section 6.8	Antenna Requirement	Compliant

5. 6DB BANDWIDTH TEST

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3. The Requirement For RSS-247 Section 5.2(a)

The minimum 6 dB bandwidth shall be 500 kHz.

5.4. EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.5. Operating Condition of EUT

5.5.1. Setup the EUT and simulator as shown as Section 5.1.

5.5.2. Turn on the power of all equipment.

5.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

5.6. Test Procedure

5.6.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.


5.6.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

5.6.3. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.


5.7. Test Result

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit(MHz)	Result
0	2402	0.742	0.5	Pass
19	2440	0.747	0.5	Pass
39	2480	0.742	0.5	Pass


The spectrum analyzer plots are attached as below.



Channel 19




Channel 39



6. 99% OCCUPIED BANDWIDTH TEST

6.1. Block Diagram of Test Setup



6.2. The Requirement for RSS-Gen Clause 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

6.3. EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

6.5. Test Procedure

- 6.5.1. The transmitter shall be operated at its maximum carrier power measured under normal test conditions. The transmitter output was connected to the spectrum analyzer through a low loss cable.
- 6.5.2. The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- 6.5.3. The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- 6.5.4. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

6.6. Test Result


Channel	Frequency (MHz)	99% Bandwidth (MHz)	Result
0	2402	1.046	Pass
19	2440	1.046	Pass
39	2480	1.046	Pass

The spectrum analyzer plots are attached as below.

Channel 0



Channel 19




Channel 39



7. MAXIMUM PEAK OUTPUT POWER TEST

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

7.3. The Requirement For RSS-247 Section 5.4(d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

7.4. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.5. Operating Condition of EUT

7.5.1. Setup the EUT and simulator as shown as Section 7.1.

7.5.2. Turn on the power of all equipment.

7.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

7.6. Test Procedure

7.6.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.


7.6.2. Set RBW of spectrum analyzer to 3MHz and VBW to 10MHz.

7.6.3. Measurement the maximum peak output power.

7.7. Test Result


Channel	Frequency (MHz)	Peak Power Output (dBm)	E.I.R.P (dBm)	Peak Power Limit (dBm)	Result
0	2402	0.68	-1.72	30	Pass
19	2440	0.39	-2.01	30	Pass
39	2480	-0.01	-2.41	30	Pass

The spectrum analyzer plots are attached as below.




Date: 9.JAN.2019 09:49:32

Channel 19




Channel 39



8. POWER SPECTRAL DENSITY TEST

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3. The Requirement For RSS-247 Section 5.2(b)

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

8.4. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.5. Operating Condition of EUT

8.5.1. Setup the EUT and simulator as shown as Section 8.1.

8.5.2. Turn on the power of all equipment.

8.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

8.6. Test Procedure

8.6.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

8.6.2. Measurement Procedure PKPSD:

8.6.3. This procedure must be used if maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit, and is optional if the maximum (average) conducted output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS Channel center frequency.
2. Set the span to 1.5 times the DTS Channel bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3kHz) and repeat.


8.6.4. Measurement the maximum power spectral density.

8.7. Test Result


Channel	Frequency (MHz)	PSD (dBm/3KHz)	Limit (dBm/3KHz)	Result
0	2402	-14.84	8	Pass
19	2440	-15.05	8	Pass
39	2480	-15.48	8	Pass

The spectrum analyzer plots are attached as below.


Channel 0



Channel 19




Channel 39



9. BAND EDGE COMPLIANCE TEST

9.1. Block Diagram of Test Setup



9.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3. The Requirement For RSS-247 Section 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

9.4. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.5.Operating Condition of EUT

9.5.1.Setup the EUT and simulator as shown as Section 9.1.

9.5.2.Turn on the power of all equipment.

9.5.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2480MHz TX frequency to transmit.

9.6.Test Procedure

Conducted Band Edge:

9.6.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

9.6.2.Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

Radiate Band Edge:

9.6.3.The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.

9.6.4.The turntable was rotated for 360 degrees to determine the position of maximum emission level.

9.6.5.EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

9.6.6.Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

9.6.7.RBW=1MHz, VBW=1MHz

9.6.8.The band edges was measured and recorded.

9.7.Test Result


Pass.

Conducted Band Edge Result


Channel	Frequency	Delta peak to band emission	Limit(dBc)
0	2402MHz	47.13	>20
39	2480MHz	53.63	>20

The spectrum analyzer plots are attached as below.

Channel 0



Channel 39





Radiated Band Edge Result

ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #103
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: FITNESS TRACKER
Mode: TX 2402MHz
Model: ID107L
Manufacturer: The StayWell Company, LLC

Polarization: Horizontal
Power Source: DC 3.7V
Date: 19/01/14/
Time:
Engineer Signature: WADE
Distance: 3m


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2389.680	37.79	0.79	38.58	74.00	-35.42	peak			
2	2389.680	27.62	0.79	28.41	54.00	-25.59	AVG			

Job No.: LGW2019 #102	Polarization: Vertical
Standard: FCC (Band Edge)	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp. (C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2402MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2389.760	45.09	0.79	45.88	74.00	-28.12	peak			
2	2389.760	34.89	0.79	35.68	54.00	-18.32	AVG			

Job No.:	LGW2019 #108	Polarization:	Horizontal
Standard:	FCC (Band Edge)	Power Source:	DC 3.7V
Test item:	Radiation Test	Date:	19/01/14/
Temp.(C)/Hum.(%)	23 C / 48 %	Time:	
EUT:	FITNESS TRACKER	Engineer Signature:	WADE
Mode:	TX 2480MHz	Distance:	3m
Model:	ID107L		
Manufacturer:	The StayWell Company, LLC		


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.682	44.73	1.10	45.83	74.00	-28.17	peak			
2	2483.682	34.31	1.10	35.41	54.00	-18.59	AVG			

Job No.: LGW2019 #109	Polarization: Vertical
Standard: FCC (Band Edge)	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp. (C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2480MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2484.012	40.72	1.09	41.81	74.00	-32.19	peak			
2	2484.012	30.15	1.09	31.24	54.00	-22.76	AVG			

Note:


1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

10. RADIATED SPURIOUS EMISSION TEST

10.1. Block Diagram of Test Setup


10.1.1. Block diagram of connection between the EUT and peripherals




Setup: Transmitting mode

10.1.2. Semi-Anechoic Chamber Test Setup Diagram


(A) Radiated Emission Test Set-Up, Frequency below 30MHz



(B) Radiated Emission Test Set-Up, Frequency 30MHz-1GHz



(C) Radiated Emission Test Set-Up. Frequency above 1GHz



10.2.The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

10.3.The Limit For RSS-247 Section 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

10.4. Transmitter Emission Limit

Radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μ V/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz ¹	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

10.5.Restricted bands of operation

10.5.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

10.5.2.RSS-Gen 8.10 Restricted bands of operation

Restricted frequency bands, identified in table 7, are designated primarily for safety-of-life services (distress calling and certain aeronautical activities), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following conditions related to the restricted frequency bands apply:

- (a) The transmit frequency, including fundamental components of modulation, of licence-exempt radio apparatus shall not fall within the restricted frequency bands listed in table 7 except for apparatus compliant with RSS-287, *Emergency Position Indicating Radio Beacons (EPIRB), Emergency Locator Transmitters (ELT), Personal Locator Beacons (PLB), and Maritime Survivor Locator Devices (MSLD)*.
- (b) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.
- (c) Unwanted emissions that fall into restricted frequency bands listed in table 7 shall comply with the limits specified in table 5 and table 6.

Table 7 – Restricted frequency bands*

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	

* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

10.6.Operating Condition of EUT

10.6.1.Setup the EUT and simulator as shown as Section 10.1.

10.6.2.Turn on the power of all equipment.

10.6.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

10.7.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

The bandwidth of test receiver is set at 9 kHz in below 30MHz. and set at 120 kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The final measurement in band 9-90 kHz, 110-490 kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector. The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading.

10.8.Data Sample

Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Remark
X.XX	43.85	-22.22	21.63	43.5	-21.87	QP

Frequency(MHz) = Emission frequency in MHz

Reading(dB μ V) = Uncorrected Analyzer/Receiver reading

Factor (dB/m) = Antenna factor + Cable Loss – Amplifier gain

Result(dB μ V/m) = Reading(dB μ V) + Factor(dB/m)

Limit (dB μ V/m) = Limit stated in standard

Margin (dB) = Result(dB μ V/m) - Limit (dB μ V/m)

QP = Quasi-peak Reading

Calculation Formula:

Margin(dB) = Result (dB μ V/m)–Limit(dB μ V/m)

Result(dB μ V/m)= Reading(dB μ V)+ Factor(dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit.

10.9.Test Result

Pass.

The frequency range from 9kHz to 26.5GHz is checked.

Emissions attenuated more than 20 dB below the permissible value are not reported.

The spectrum analyzer plots are attached as below.

9kHz-30MHz test data


ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2402MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: X
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70		
Start	Stop	Step	Detector	Meas.	IF
Frequency	Frequency	Width		Time	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz 1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz 1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2402MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: Y
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description:		SUB STD VTERM2 1.70				
Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2402MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: Z
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width	SUB_STD VTERM2 1.70		Time	Bandw.
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2440MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: X
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70		IF	Transducer
Start	Stop	Step	Déctector	Meas.	Bandw.	
Frequency	Frequency	Width		Time		
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2440MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: Y
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description: _SUB_STD_VTERM2 1.70
Start Stop Step Detector Meas. IF Transducer
Frequency Frequency Width Time Bandw.
9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz 1516M
150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz 1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2440MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: Z
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description:		_SUB_STD_VTERM2 1.70		Detector	Meas.	IF	Transducer
Start	Stop	Step	Width				
Frequency	Frequency				Time	Bandw.	
9.0 kHz	150.0 kHz	100.0 Hz		QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz		QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2480MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: X
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF Time	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD**FCC Part 15C 3M Radiated**

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2480MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: Y
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description:		-SUB_STD_VTERM2 1.70				
Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M




ACCURATE TECHNOLOGY CO., LTD

FCC Part 15C 3M Radiated

EUT: FITNESS TRACKER M/N:ID107L
Manufacturer: The StayWell Company, LLC
Operating Condition: TX 2480MHz
Test Site: 2# Chamber
Operator: WADE
Test Specification: DC 3.7V
Comment: Z
Start of Test: 2019-1-18 /

SCAN TABLE: "LFRE Fin"

Short Description:		- SUB_STD_VTERM2 1.70				
Start	Stop	Step	Detector	Meas.	IF	Transducer
Frequency	Frequency	Width		Time	Bandw.	
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



30MHz-1000MHz test data



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.ChinaSite: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #171

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2402MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.8293	47.68	-15.11	32.57	43.50	-10.93	QP			
2	287.9904	50.18	-9.34	40.84	46.00	-5.16	QP			
3	801.7862	36.30	0.87	37.17	46.00	-8.83	QP			

Job No.: LGW2019 #170 Polarization: Vertical
 Standard: FCC Part 15C 3M Radiated Power Source: DC 3.7V
 Test item: Radiation Test Date: 19/01/14/
 Temp.(C)/Hum.(%) 23 C / 48 % Time:
 EUT: FITNESS TRACKER Engineer Signature: WADE
 Mode: TX 2402MHz Distance: 3m
 Model: ID107L
 Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	228.4903	45.12	-11.15	33.97	46.00	-12.03	QP			
2	311.0867	43.06	-8.70	34.36	46.00	-11.64	QP			
3	798.9796	33.92	0.81	34.73	46.00	-11.27	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #172

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2440MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	276.1235	49.79	-9.70	40.09	46.00	-5.91	QP			
2	307.8312	49.70	-8.80	40.90	46.00	-5.10	QP			
3	801.7862	36.95	0.87	37.82	46.00	-8.18	QP			

Job No.: LGW2019 #173

Polarization: Vertical

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2440MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	330.1949	36.91	-8.03	28.88	46.00	-17.12	QP			
2	492.4685	37.66	-4.63	33.03	46.00	-12.97	QP			
3	801.7862	39.37	0.87	40.24	46.00	-5.76	QP			

Job No.: LGW2019 #175	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp. (C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2480MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	292.0582	49.00	-9.23	39.77	46.00	-6.23	QP			
2	312.1792	48.54	-8.66	39.88	46.00	-6.12	QP			
3	798.9796	36.10	0.81	36.91	46.00	-9.09	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #174

Polarization: Vertical

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2480MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	345.5951	36.23	-7.53	28.70	46.00	-17.30	QP			
2	504.7062	35.30	-4.19	31.11	46.00	-14.89	QP			
3	798.9796	37.49	0.81	38.30	46.00	-7.70	QP			

1GHz-18GHz test data



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.ChinaSite: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #100

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2402MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	89.54	0.89	90.43	/	/	peak			
2	4804.026	42.08	7.40	49.48	74.00	-24.52	peak			
3	4804.026	34.14	7.40	41.54	54.00	-12.46	AVG			

Job No.: LGW2019 #101

Polarization: Vertical

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2402MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	88.53	0.89	89.42	/	/	peak			
2	4804.027	41.58	7.40	48.98	74.00	-25.02	peak			
3	4804.027	32.83	7.40	40.23	54.00	-13.77	AVG			

Job No.: LGW2019 #104

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2440MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC


Note:



No.	Freq. (MHz)	Reading (dB _{uV/m})	Factor (dB)	Result (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	90.35	1.04	91.39	/	/	peak			
2	4880.025	40.78	8.10	48.88	74.00	-25.12	peak			
3	4880.025	32.11	8.10	40.21	54.00	-13.79	AVG			

Job No.: LGW2019 #105	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2440MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	88.25	1.04	89.29	/	/	peak			
2	4880.028	39.64	8.10	47.74	74.00	-26.26	peak			
3	4880.028	31.46	8.10	39.56	54.00	-14.44	AVG			

Job No.: LGW2019 #107

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2480MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	89.47	1.10	90.57	/	/	peak			
2	4960.031	41.17	8.60	49.77	74.00	-24.23	peak			
3	4960.031	32.64	8.60	41.24	54.00	-12.76	AVG			




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #106	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2480MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	88.46	1.10	89.56	/	/	peak			
2	4960.027	40.73	8.60	49.33	74.00	-24.67	peak			
3	4960.027	32.71	8.60	41.31	54.00	-12.69	AVG			

18GHz-26.5GHz test data



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.ChinaSite: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #111

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2402MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	21730.791	11.10	38.92	50.02	74.00	-23.98	peak			
2	21730.791	1.65	38.92	40.57	54.00	-13.43	AVG			

Job No.: LGW2019 #110	Polarization: Vertical
Standard: FCC Part 15C 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2402MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	24948.361	8.93	41.04	49.97	74.00	-24.03	peak			
2	24948.361	-1.50	41.04	39.54	54.00	-14.46	AVG			


Job No.: LGW2019 #112	Polarization: Horizontal
Standard: FCC Part 15C 3M Radiated	Power Source: DC 3.7V
Test item: Radiation Test	Date: 19/01/14/
Temp. (C)/Hum.(%) 23 C / 48 %	Time:
EUT: FITNESS TRACKER	Engineer Signature: WADE
Mode: TX 2440MHz	Distance: 3m
Model: ID107L	
Manufacturer: The StayWell Company, LLC	

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	22086.679	10.44	39.47	49.91	74.00	-24.09	peak			
2	22086.679	0.07	39.47	39.54	54.00	-14.46	AVG			

Job No.:	LGW2019 #113	Polarization:	Vertical
Standard:	FCC Part 15C 3M Radiated	Power Source:	DC 3.7V
Test item:	Radiation Test	Date:	19/01/14/
Temp.(C)/Hum.(%)	23 C / 48 %	Time:	
EUT:	FITNESS TRACKER	Engineer Signature:	WADE
Mode:	TX 2440MHz	Distance:	3m
Model:	ID107L		
Manufacturer:	The StayWell Company, LLC		
Note:			



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	22736.752	10.06	39.58	49.64	74.00	-24.36	peak			
2	22736.752	-0.04	39.58	39.54	54.00	-14.46	AVG			

Job No.: LGW2019 #115

Polarization: Horizontal

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2480MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC

Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	21413.741	11.32	38.50	49.82	74.00	-24.18	peak			
2	21413.741	0.91	38.50	39.41	54.00	-14.59	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: LGW2019 #114

Polarization: Vertical

Standard: FCC Part 15C 3M Radiated

Power Source: DC 3.7V

Test item: Radiation Test

Date: 19/01/14/

Temp.(C)/Hum.(%) 23 C / 48 %

Time:

EUT: FITNESS TRACKER

Engineer Signature: WADE


Mode: TX 2480MHz

Distance: 3m

Model: ID107L

Manufacturer: The StayWell Company, LLC


Note:



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	19290.334	12.15	37.97	50.12	74.00	-23.88	peak			
2	19290.334	2.60	37.97	40.57	54.00	-13.43	AVG			

11. CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST

11.1. Block Diagram of Test Setup



11.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

11.3. The Requirement For RSS-247 Section 5.5

Section 5.5: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

11.4. EUT Configuration on Measurement

The equipment is installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

11.5.Operating Condition of EUT

11.5.1.Setup the EUT and simulator as shown as Section 11.1.

11.5.2.Turn on the power of all equipment.

11.5.3.Let the EUT work in TX modes measure it. The transmit frequency are 2402-2480MHz. We select 2402MHz, 2440MHz, and 2480MHz TX frequency to transmit.

11.6.Test Procedure

11.6.1.The transmitter output was connected to the spectrum analyzer via a low loss cable.

11.6.2.Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz


11.6.3.The Conducted Spurious Emission was measured and recorded.

11.7.Test Result

Pass.


The spectrum analyzer plots are attached as below.

Channel 0




Date: 9.JAN.2019 09:48:15

Channel 19



Date: 9.JAN.2019 09:46:54


Channel 39




Date: 9.JAN.2019 09:45:45

12. POWER LINE CONDUCTED EMISSION TEST

12.1. Block Diagram of Test Setup



12.2. Test System Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

12.3. Test Limits

Frequency (MHz)	Limit dB(μ V)	
	Quasi-peak Level	Average Level
0.15 - 0.50	66.0 – 56.0 *	56.0 – 46.0 *
0.50 - 5.00	56.0	46.0
5.00 - 30.00	60.0	50.0

NOTE1: The lower limit shall apply at the transition frequencies.
NOTE2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

12.4. Configuration of EUT on Measurement

The equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

12.5. Operating Condition of EUT

12.5.1. Setup the EUT and simulator as shown as Section 12.1.

12.5.2. Turn on the power of all equipment.

12.5.3. Let the EUT work in test mode and measure it.

12.6. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Measurement.

The bandwidth of test receiver (R & S ESCS30) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

12.7.Data Sample

Frequency (MHz)	Transducer value (dB)	QuasiPeak Level (dB μ V)	Average Level (dB μ V)	QuasiPeak Limit (dB μ V)	Average Limit (dB μ V)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
X.XX	10.5	51.1	34.2	56.0	46.0	4.9	11.8	Pass

Frequency(MHz) = Emission frequency in MHz

Transducer value(dB) = Insertion loss of LISN + Cable Loss

Level(dB μ V) = Quasi-peak Reading/Average Reading + Transducer value

Limit (dB μ V) = Limit stated in standard

Calculation Formula:

Margin = Limit (dB μ V) - Level (dB μ V)

12.8.Test Result

Pass.

The frequency range from 150kHz to 30MHz is checked.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

Emissions attenuated more than 20 dB below the permissible value are not reported.

All data was recorded in the Quasi-peak and average detection mode.

The spectral diagrams are attached as below.


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: FITNESS TRACKER M/N:ID107L
 Manufacturer: The StayWell Company, LLC
 Operating Condition: BT Communication
 Test Site: 1#Shielding Room
 Operator: WADE
 Test Specification: N 120V/60Hz
 Comment: Mains port
 Start of Test: 1/14/2019 /

SCAN TABLE: "V 9K-30MHz fin"

Short Description: -SUB_STD_VTERM2 1.70
 Start Stop Step Detector Meas. IF Transducer
 Frequency Frequency Width Time Bandw.
 9.0 kHz 150.0 kHz 100.0 Hz QuasiPeak 1.0 s 200 Hz NSLK8126 2008
 Average
 150.0 kHz 30.0 MHz 5.0 kHz QuasiPeak 1.0 s 9 kHz NSLK8126 2008
 Average



MEASUREMENT RESULT: "TUV-0114-1_fin"

1/14/2019

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.155000	53.90	10.5	66	11.8	QP	N	GND
0.450000	35.70	10.7	57	21.2	QP	N	GND
3.810000	23.40	11.1	56	32.6	QP	N	GND
6.240000	28.10	11.2	60	31.9	QP	N	GND

MEASUREMENT RESULT: "TUV-0114-1_fin2"

1/14/2019

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.150000	36.30	10.5	56	19.7	AV	N	GND
0.450000	30.50	10.7	47	16.4	AV	N	GND
3.750000	17.60	11.1	46	28.4	AV	N	GND
6.510000	21.30	11.2	50	28.7	AV	N	GND


ACCURATE TECHNOLOGY CO., LTD

CONDUCTED EMISSION STANDARD FCC PART 15 C

EUT: FITNESS TRACKER M/N:ID107L
 Manufacturer: The StayWell Company, LLC
 Operating Condition: BT Communication
 Test Site: 1#Shielding Room
 Operator: WADE
 Test Specification: L 120V/60Hz
 Comment: Mains port
 Start of Test: 1/14/2019 /

SCAN TABLE: "V 9K-30MHz fin"

Start Frequency	Stop Frequency	Step Width	Detector	Meas.	IF	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	NSLK8126 2008
			Average			
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	NSLK8126 2008
			Average			



MEASUREMENT RESULT: "TUV-0114-2_fin"

1/14/2019

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	55.20	10.5	66	10.8	QP	L1	GND
0.455000	36.40	10.7	57	20.4	QP	L1	GND
1.325000	27.40	10.9	56	28.6	QP	L1	GND
5.600000	26.80	11.2	60	33.2	QP	L1	GND

MEASUREMENT RESULT: "TUV-0114-2_fin2"

1/14/2019

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.165000	36.20	10.5	55	19.0	AV	L1	GND
0.455000	29.20	10.7	47	17.6	AV	L1	GND
1.280000	25.20	10.9	46	20.8	AV	L1	GND
5.620000	20.20	11.2	50	29.8	AV	L1	GND

13. ANTENNA REQUIREMENT

13.1. The Requirement

According to FCC Section 15.203 and RSS-Gen Section 6.8, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

13.2. Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Antenna gain of EUT is -2.4dBi. Therefore, the equipment complies with the antenna requirement of FCC Section 15.203 and RSS-Gen Section 6.8.

***** End of Test Report *****