

## RF EXPOSURE REPORT

### FOR

<b>Applicant</b>	:	Shenzhen HOPE Microelectronics Co., Ltd.
<b>Address</b>	:	2/F Building 3, Pingshan Private Enterprise Science & Technology Park, Nanshan District, Shenzhen, China
<b>Equipment under Test</b>	:	WIFI Module
<b>Model No.</b>	:	HM-WF8266A, HM-WF8266C, HM-WF8266D, HM-WF8266E, HM-WF8266F
<b>Trade Mark</b>	:	HOPERF
<b>FCC ID</b>	:	2ASEO-HM-WF8266A
<b>Manufacturer</b>	:	Shenzhen HOPE Microelectronics Co., Ltd.
<b>Address</b>	:	2/F Building 3, Pingshan Private Enterprise Science & Technology Park, Nanshan District, Shenzhen, China

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan  
City, Guangdong Province, China, 523808

**Tel:** +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

**TABLE OF CONTENTS**

- Test report declares.....3
- 1. General information ..... 5
- 1.1. Description of Equipment..... 5
- 1.2. Assess laboratory..... 6
- 2. RF Exposure evaluation..... 6
- 2.1. Requirement..... 6
- 2.2. Calculation Method ..... 7
- 2.3. Estimation Result ..... 7

## TEST REPORT DECLARE

<b>Applicant</b>	:	Shenzhen HOPE Microelectronics Co., Ltd.
<b>Address</b>	:	2/F Building 3, Pingshan Private Enterprise Science & Technology Park, Nanshan District, Shenzhen, China
<b>Equipment under Test</b>	:	WIFI Module
<b>Model No.</b>	:	HM-WF8266A, HM-WF8266C, HM-WF8266D, HM-WF8266E, HM-WF8266F
<b>Trade mark</b>	:	HOPERF
<b>Manufacturer</b>	:	Shenzhen HOPE Microelectronics Co., Ltd.
<b>Address</b>	:	2/F Building 3, Pingshan Private Enterprise Science & Technology Park, Nanshan District, Shenzhen, China

**Standard Used:** KDB447498 D01 General RF Exposure Guidance v06

**We Declare:**

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

**After evaluation, our opinion is that the equipment In Accordance with above standard.**

<b>Report No:</b>	DDT-R19041806-1E5		
<b>Date of Receipt:</b>	Apr. 19, 2019	<b>Date of Test:</b>	Apr. 19, 2019~ Apr. 23, 2019

**Prepared By:**

*Ella Gong*

**Ella Gong/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Apr. 23, 2019	

## 1. General information

### 1.1. Description of Equipment

EUT* Name	: WIFI Module
Model Number	: HM-WF8266A, HM-WF8266C, HM-WF8266D, HM-WF8266E, HM-WF8266F
Difference of models	: Their electrical circuit design, layout, components used and internal wiring are identical, only the appearance is different, so choose HM-WF8266A for testing
EUT function description	: Please reference user manual of this device
Power supply	: DC 3.3V
Radio Specification	: IEEE 802.11b/g/n
Operation frequency	: IEEE 802.11b: 2412MHz-2462MHz : IEEE 802.11g: 2412MHz-2462MHz : IEEE 802.11n HT20: 2412MHz-2462MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) : IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) : IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Data rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps : IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps : IEEE 802.11n HT20: 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2 Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: 3 dBi
Sample Type	: Series production

## 1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

## 2. RF Exposure evaluation

### 2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

## 2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = Peak RF output power (mW)

**G** = EUT Antenna numeric gain (numeric)=

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained.

## 2.3. Estimation Result

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
2.4G WIFI Max power	19.20	83.18	3	2.00	0.003	1

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

**END OF REPORT**