

MPE CALCULATION

FCC ID: 2ASF5-JTR01

RF Exposure Requirements: 47 CFR §1.1307(b)

RF Radiation Exposure Limits: 47 CFR §1.1310

RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65

EUT Frequency Band: 902-928 MHz

Limits for General Population/Uncontrolled Exposure in the band of: 300 - 1500 MHz

Power Density Limit: f/1500 mW / cm²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

EUT: JETCO 915 RF Module, Model No. : JTR-01-R

Power = 15.77 dBm, Antenna Gain = -8.9 dBi, Power density = 0.000157 mW/ cm²

| CH Freq (MHz) | Conducted Power (dBm) | Antenna Gain (dBi) | Tune-Up Tolerance | Tolerance Max Power (dBm) | Measurement Distance (cm) | Calculated MPE (mW/cm ²) | MPE Limit (mW/cm ²) | Pass/Fail |
|---------------|-----------------------|--------------------|-------------------|---------------------------|---------------------------|--------------------------------------|---------------------------------|-----------|
| 915 | 15.77 | -8.9 | $\pm 1\text{dB}$ | 7.87 | 20 | 0.000157 | 0.61 | Pass |

The Above Result had shown that the Device complied with MPE requirement.



Completed By: Rachana Khanduri

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 02/02/2019