

RF Exposure evaluation

FCC ID: 2ASGG-CC-ASL-588

According to 447498 D01 General RF Exposure Guidance v06

4.3. General SAR test exclusion guidance

4.3.1. Standalone SAR test exclusion considerations

- a) For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where
 - $f(\text{GHz})$ is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation³¹
 - The result is rounded to one decimal place for comparison
 - The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

³⁰ This is equivalent to the formula written as: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (60 / \sqrt{f(\text{GHz})} \text{ mW})] \cdot [20 \text{ mm} / (\text{min. test separation distance, mm})] \leq 1.0$ for 1-g SAR; also see Appendix A for approximate exclusion threshold numerical values at selected frequencies and distances.

$$\text{eirp} = \text{pt} \times \text{gt} = (\text{Exd})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((\text{dBuV/m}) / 20) / 10^6$

d = measurement distance in meters (m)---3m

So $\text{pt} = (\text{Exd})^2 / 30 \times \text{gt}$

RF Exposure evaluation

Copied from the FCC test report: clause 9.4 Maximum Peak Output Power

Test Result:

For BLE:

| Test Mode | Frequency MHz | Reading dBm | Output Power mW | Limit mW |
|-----------|------------------|----------------|--------------------|-------------|
| GFSK(BLE) | 2402 | 0.60 | 1.15 | 1000 |
| | 2442 | 0.58 | 1.14 | 1000 |
| | 2480 | -3.04 | 0.50 | 1000 |

Note: the antenna gain of 0dB less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

Then we choose Normal mode channel as the worst case of Maximum Peak Output Power:

| Test Mode | Frequency MHz | Reading dBm | Output Power mW | Limit mW |
|-----------|------------------|----------------|--------------------|-------------|
| GFSK(BLE) | 2402 | 0.60 | 1.15 | 1000 |
| | 2442 | 0.58 | 1.14 | 1000 |
| | 2480 | -3.04 | 0.50 | 1000 |

EIRP/ dBm= Conducted Max Output Power/ dBm+ Antenna gain /dBi.

General RF Exposure:

$$(1.15\text{mW})/5.0\text{mm}) \times \sqrt{2.402 \text{ GHz}} = 0.36$$

$$(1.14\text{mW})/5.0\text{mm}) \times \sqrt{2.442 \text{ GHz}} = 0.36$$

$$(0.50\text{mW})/5.0\text{mm}) \times \sqrt{2.480 \text{ GHz}} = 0.16$$

SAR requirement: S=3.0

General RF Exposure < 3

Then SAR evaluation is not required