



FCC RF Exposure Report

1. Product information

FCC ID	2ASHC-AQUESTIA2X
Product	Electronic Hydraulic Controller Device
Model No.	Condor
Power supply	AC :115/110-240VAC Battery: 12/12-24VDC, via AC/DC adapter
Antenna type	PCB
Antenna gain	3.3 dBi (max.)
Assigned frequency range	2400.0-2483.5 MHz
Operating frequency range	2402.0-2480.0 MHz
Transmit power (conducted)	-14.9 dBm
Modulation bandwidth	2 MHz
Bit rate	1,2,3 (Mbit/s)
SAR exclusion considerations	A worst-case test separation distance of 20 cm

2. Evaluation Method and Limit

FCC, Part 1, Subpart I, Section 1.1310(e)(1), RSS 102, Issue 5, Section 2.5.2(table 4 requirements) KDB447498 D01 V06 (October 23, 2015)

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1, the standalone SAR test exclusion considerations are: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied.

The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1)."

For MPE evaluation we take the following E.U.T values:

1. Max. power (conducted)=-14.9 dBm = 0.03mW
 2. Antenna gain = 3.3 dBi = 2.2
 3. Minimum distance from human body: 20.0cm
 4. The power density was calculated using the following formula: $S = \frac{P_t G_t}{4\pi R^2}$
- S: Power density (mW/cm²)
P_t: Conducted Transmitted Power (mW)
G_t: Antenna Gain (numeric)
R: Distance from Transmitter (cm)

FCC Test Limit

Limits for General Population/Uncontrolled Exposure:

Frequency range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
1,500.0-100,000.0	1.0	< 30

3. Test Results

Frequency (MHz)	FCC calculation (mW/cm ²)	FCC limit (mW/cm ²)	Verdict
2440.0	$S = \frac{P_t G_t}{4\pi R^2} = (0.03 \cdot 2.2) / (4 \cdot 3.14 \cdot (20^2)) = 0.01$	<1.0	Pass

4. Conclusion

The measurement results comply with the Limit per FCC, Part 1, Subpart I, Section 1.1310(e)(1), KDB447498 D01 V06 (October 23, 2015)

End of Report