

RF Exposure Evaluation

FCC ID: 2ASHI-DT96

1. Client Information

Applicant	:	SHENZHEN XINKEYING DIGITAL CO.,LIMITED
Address	:	Room 17I, Block A, HuaQiang Square, HuaQiang North Road, Futian District, Shenzhen, China
Manufacturer	:	SHENZHEN XINKEYING DIGITAL CO.,LIMITED
Address	:	Room 17I, Block A, HuaQiang Square, HuaQiang North Road, Futian District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Smart Watch
Model(s) No.	:	DT96, DT95, DT86, DT66, DT56, DT52, DT97, DT92,DT59, DT40, DTX
Model Different	:	All these models are in the same PCB, layout and electrical circuit, the only difference is apperance size, It's all plastic
Product Description	Operation Frequency:	Bluetooth 5.0(BLE): 2402MHz~2480MHz
	Number of Channel:	Bluetooth 5.0(BLE): 40 channels
	RF Output Power:	3.565 dBm (Max)
	Antenna Gain:	2.71 dBi PIFA Antenna
	Modulation Type:	GFSK
	Bit Rate of Transmitter:	1Mbps&2Mbps
Power Rating	:	USB Input:DC 5V DC 3.7V by 230mAh Li-ion battery
Software Version	:	N/A
Hardware Version	:	Z23V2.0
Connecting I/O Port(S)	:	Please refer to the User's Manual
Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.		

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)]*[$\sqrt{f_{\text{(GHz)}}}$] ≤ 3.0 for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)]*[$\sqrt{f_{\text{(GHz)}}}$] $\leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
BLE Mode (1Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	2.823	3 ± 1	4	2.512	0.779	3.0
2.442	3.150	3 ± 1	4	2.512	0.785	3.0
2.480	3.206	3 ± 1	4	2.512	0.791	3.0
BLE Mode (2Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	3.492	3 ± 1	4	2.512	0.779	3.0
2.442	3.565	3 ± 1	4	2.512	0.785	3.0
2.480	3.412	3 ± 1	4	2.512	0.791	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----