

47 CFR PART 15 SUBPART C TEST REPORT

for

Fitness equipment(Rowing machine)

Model No.: SSR GO

FCC ID: 2ASJ3-SSRGO

of

Applicant: Aviron Interactive.

Address: 265 Bartley Drive. North York M4A2N7 Canada

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22402-23275-C-1

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com





TABLE OF CONTENTS

1	GENERAL INFORMATION.....	2
1.1	NOTES	2
1.2	TESTING LABORATORY	3
1.3	APPLICATION DETAILS.....	3
1.4	GENERAL INFORMATION OF TEST ITEM.....	4
1.5	DUTY CYCLE AND FACTOR.....	4
1.6	TEST STANDARDS	5
2	TEST CONFIGURATION	6
2.1	TEST ENVIRONMENT	6
2.2	MEASUREMENT UNCERTAINTY	6
2.3	TEST EQUIPMENT LIST.....	7
3	TEST RESULTS (ENCLOSURE)	8
3.1	PEAK OUTPUT POWER (TRANSMITTER).....	9
3.2	SPURIOUS EMISSIONS RADIATED – TRANSMITTER OPERATING	12
3.3	EMISSIONS IN NONRESTRICTED FREQUENCY BANDS.....	14
3.4	MINIMUM 6 DB BANDWIDTH	16
3.5	PEAK POWER SPECTRAL DENSITY	19
3.6	POWER LINE CONDUCTED EMISSION	22

Appendix: Diagrams



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

September 06, 2024

Brian Ng

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

September 06, 2024


Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)

Xizhi Lab

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited no.: ./.

Street: ./.


Town: ./.

Country: ./.

1.3 Application details

Approval holder

Name: Aviron Interactive.
Street: 265 Bartley Drive.
Town: North York M4A2N7
Country: Canada



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

Manufacturer: (if applicable)

Name: ./.

Street: ./.

Town: ./.

Country: ./.

Date of receipt of test item: March 21, 2024

Date of test: from March 22, 2024 to May 02, 2024

1.4 General information of Test item

Type of test item: Fitness equipment(Rowing machine)

Model no.: SSR GO

Multi-listing model no.: ./.

Brand name: Full rich

Power supply: 120Va.c.

Technical data

Mode	Channel	Conducted Power (dBm)
BLE	Ch 0: 2402 MHz	-3.41
	Ch 19: 2440 MHz	-2.96
	Ch 39: 2480 MHz	-2.44

Type of antenna: Chip Antenna

Antenna gain: 1.69 dBi

Operation modes: Duplex


Modulation type: GFSK

Sample no.: #01

1.5 Duty cycle and factor

The duty factor is computed as $[10 \log (1 / D)]$, where D is the duty cycle.



Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle(%)	1/T - VBW(kHz)
BLE	0.424	0.625	67.84%	2.36



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

Duty cycle plot



1.6 Test standards

47 CFR PART 15 SUBPART C § 15.247 (2021-10)



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

2 Test configuration

2.1 Test environment

Relative humidity content: 20 ... 75 %


Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

2.2 Measurement uncertainty

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 0.94 dB Voltage probe : 0.96 dB Include Pulse Limiter : 1.5 dB
Estimation Result of Uncertainty of Radiated Emission(3M-966A) (Spurious Emissions radiated – Transmitter operating)	Expanded Uncertainty : 0.009-30 MHz : 1.88 dB 30-1000 MHz : 3.20 dB 1-18 GHz : 3.56 dB 18-40 GHz : 2.94 dB
Estimation Result of Uncertainty of Bandwidth Measurement (Minimum 6 dB Bandwidth)	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.64 dB
Estimation Result of Uncertainty of Power Density Measurement (Peak Power Spectral Density)	Expanded Uncertainty : 1.64 dB
Estimation Result of Uncertainty of Band Edge Measurement (Emissions in nonrestricted frequency bands)	Expanded Uncertainty : 0.67 dBc

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

2.3 Test Equipment List

RF Output Power & 6DB Bandwidth & Bandedge & Power Density & Duty Cycle

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2024/2/16	2025/2/15
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2024/3/7	2025/3/6
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2024/2/16	2025/2/15
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2024/2/16	2025/2/15

Bandedge & Radiated Emission (966A)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2023/9/20	2024/9/19
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2024/4/10	2025/4/9
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2023/7/14	2024/7/13
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2024/3/4	2025/3/3
ETSTW-RE 178	Double Ridged Guide Horn Antenna	DRH18-E	210505A18ES	RFSPIN	2024/2/29	2025/2/28
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2023/7/14	2024/7/13
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2023/7/14	2024/7/13
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2023/7/14	2024/7/13
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	

AC Conducted

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2023/6/12	2024/6/11
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2023/10/26	2024/10/25
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-Cable 093	BNC Cable (3m)	EMCCFD-300 -BM-BM-3000	240109	EMCI	2024/1/10	2025/1/9
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)(3)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(d), 15.205, 15.209	☒	☒	☐
Emissions in nonrestricted frequency bands	15.247(d)	☒	☒	☐
Minimum 6 dB Bandwidth	15.247(a)(2)	☒	☒	☐
Peak Power Spectral Density	15.247(e)	☒	☒	☐
Power Line Conducted Emission	15.207(a)	☒	☒	☐

The following is intentionally left blank.



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.1 Peak Output Power (transmitter)

3.1.1 Applicable Standard

FCC Rule: 15.247(b)(3)


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.1.2 Test procedure

Following Subclause 11.9.1.1 of ANSI C63.10

1. Set the RBW $\geq$ DTS bandwidth , VBW $\geq$ $[3 \times \text{RBW}]$, span $\geq$ $[3 \times \text{RBW}]$.
2. Sweep time = auto couple , Detector = peak , Trace mode = max hold.
3. Allow trace to fully stabilize and determine the peak amplitude level.

3.1.3 Test Setup



3.1.4 Limits

Frequency (MHz)	Power (dBm)
902 - 928	30
2400 – 2483.5	30
5725 – 5850	30

In case of employing transmitter antennas having antenna gain > 6 dBi and using fixed point-to point operation consider §15.247 (b)(4)




Registration number: W6M22402-23275-C-1
FCC ID: 2ASJ3-SSRGO

3.1.5 Test Environmental Conditions


Test date: 2024-04-23 Temperature: 32.0°C Humidity: 60.0% Tester: Brian

3.1.6 Test results


Band	Mode	Channel	Power (dBm)	Limit (dBm)
2.4GHz	BLE 1M	Ch 0 : 2402 MHz	-3.41	30
		Ch 19 : 2440 MHz	-2.96	30
		Ch 39 : 2480 MHz	-2.44	30




MAX OUTPUT POWER BLE 1M CH00
Date: 23.APR.2024 16:23:42



Registration number: W6M22402-23275-C-1
FCC ID: 2ASJ3-SSRGO



MAX OUTPUT POWER BLE 1M CH19
Date: 23.APR.2024 16:22:24



MAX OUTPUT POWER BLE 1M CH39
Date: 23.APR.2024 16:23:09

Test equipment used: Please see test equipment utilized (RF Conducted).



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.2 Spurious Emissions radiated – Transmitter operating

3.2.1 Applicable Standard

FCC Rules: 15.247 (d), 15.205, 15.209

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

3.2.2 Test procedure

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m height to find out the highest emissions.
3. Receiver or Spectrum analyzer configuration
 - (a)120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
 - (b)RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
 - (c)RBW=1MHz, VBW=10Hz(1/T) and Peak detector is for average measured value of radiated emission above 1GHz.


3.2.3 Limits

Frequency (MHz)	Field strength (uV/m)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.2.4 Test Setup




Below 1 GHz



Above 1 GHz

3.2.5 Test results (With Environmental Conditions)

Explanation: See attached diagrams in Appendix.



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.3 Emissions in nonrestricted frequency bands

3.3.1 Applicable Standard

FCC Rules: 15.247(d)


In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.

In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

3.3.2 Test procedure

1. Set RBW = 100 kHz , VBW $\geq [3 \times \text{RBW}]$
2. Set Detector = peak , Sweep time = auto , Trace mode = max hold, and allow sweep to continue until the trace stabilizes
3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

3.3.3 Test setup




3.3.4 Limits

See 3.3.1

3.3.5 Test Environmental Conditions


Test date: 2024-04-23 Temperature: 32.0°C Humidity: 60.0% Tester: Brian




Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.3.6 Test results




BANDEGE BLE 1M CH00
Date: 23.APR.2024 16:30:01



BANDEGE BLE 1M CH39
Date: 23.APR.2024 16:29:15

Test equipment used: Please see test equipment utilized (RF Conducted).



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.4 Minimum 6 dB Bandwidth

3.4.1 Applicable Standard


FCC Rules: 15.247(a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.4.2 Test procedure

1. Set RBW = 100 kHz , Set the VBW $\geq [3 \times \text{RBW}]$.
2. Set Detector = peak , Trace mode = max hold , Sweep = auto couple and allow the trace to stabilize.
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.4.3 Test setup



3.4.4 Limits

Frequency Range (MHz)	Limits (kHz)
902-928	≥ 500
2400-2483.5	
5725-5850	


3.4.5 Test Environmental Conditions

Test date: 2024-04-23 Temperature: 32.0°C Humidity: 60.0% Tester: Brian


Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO


3.4.6 Test results




6DB BANDWIDTH BLE 1M CH00
Date: 23.APR.2024 16:25:46



6DB BANDWIDTH BLE 1M CH19
Date: 23.APR.2024 16:27:14



Registration number: W6M22402-23275-C-1
FCC ID: 2ASJ3-SSRGO



6DB BANDWIDTH BLE 1M CH39
Date: 23.APR.2024 16:27:58

Test equipment used: Please see test equipment utilized (RF Conducted).



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO

3.5 Peak Power Spectral Density

3.5.1 Applicable Standard


FCC Rules: 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 Test procedure

1. Set the RBW to $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$, the VBW $\geq [3 \times \text{RBW}]$.
2. Set Detector = peak, Sweep time = auto couple, Trace mode = max hold and allow trace to fully stabilize
3. Use the peak marker function to determine the maximum amplitude level within the RBW.

3.5.3 Test setup




3.5.4 Limits

Frequency Range (MHz)	Limits (dBm/3KHz)
902-928	8
2400-2483.5	
5725-5850	

3.5.5 Test Environmental Conditions


Test date: 2024-04-23 Temperature: 32.0°C Humidity: 60.0% Tester: Brian




Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO


3.5.6 Test results



POWER DENSITY BLE 1M CH00
Date: 23.APR.2024 16:32:04




POWER DENSITY BLE 1M CH19
Date: 23.APR.2024 16:32:43



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1
FCC ID: 2ASJ3-SSRGO



POWER DENSITY BLE 1M CH39
Date: 23.APR.2024 16:33:16

Test equipment used: Please see test equipment utilized (RF Conducted).

3.6 Power Line Conducted Emission

3.6.1 Applicable Standard


FCC Rules:15.207(a)

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

3.6.2 Test procedure

1. EUT is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. Connect EUT to a 50 μ H/50 ohms line impedance stabilization network (LISN). AC input is 120V/60Hz
3. This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

3.6.3 Test setup



3.6.4 Limits

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50



Registration number: W6M22402-23275-C-1

FCC ID: 2ASJ3-SSRGO


3.6.5 Test results (With Environmental Conditions)

Conducted Emission Measurement

Operator: Brian

Temperature: 24.0 °C

Humidity: 50 %



Site : Chamber_03

Condition : FCC Part 15 Class B Conduction (QP)

Phase: N

EUT : W6M22402-23275


Power : 120 V.a.c.

M/N:

Test Mode :

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1636	17.91	QP	9.64	27.55	65.28	-37.73	
	0.1636	-1.30	AVG	9.64	8.34	55.28	-46.94	
	0.1955	13.99	QP	9.64	23.63	63.80	-40.17	
	0.1955	-2.36	AVG	9.64	7.28	53.80	-46.52	
	0.2110	11.87	QP	9.64	21.51	63.17	-41.66	
	0.2110	-3.21	AVG	9.64	6.43	53.17	-46.74	
	0.4110	12.95	QP	9.66	22.61	57.63	-35.02	
	0.4110	0.98	AVG	9.66	10.64	47.63	-36.99	
	19.3375	21.21	QP	10.03	31.24	60.00	-28.76	
	19.3375	14.81	AVG	10.03	24.84	50.00	-25.16	
	24.0000	18.99	QP	10.08	29.07	60.00	-30.93	
*	24.0000	17.63	AVG	10.08	27.71	50.00	-22.29	




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22402-23275-C-1
FCC ID: 2ASJ3-SSRGO

Conducted Emission Measurement

Operator: Brian
Temperature: 24.0 °C
Humidity: 50 %



Site : Chamber_03

Condition : FCC Part 15 Class B Conduction (QP)

Phase: L1

EUT : W6M22402-23275

Power : 120 V.a.c.

M/N:


Test Mode :

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1520	19.73	QP	9.66	29.39	65.89	-36.50	
	0.1520	12.15	AVG	9.66	21.81	55.89	-34.08	
	0.1855	16.90	QP	9.65	26.55	64.24	-37.69	
	0.1855	12.55	AVG	9.65	22.20	54.24	-32.04	
	0.1925	14.50	QP	9.65	24.15	63.93	-39.78	
	0.1925	-3.81	AVG	9.65	5.84	53.93	-48.09	
	0.2110	11.73	QP	9.65	21.38	63.17	-41.79	
	0.2110	-5.23	AVG	9.65	4.42	53.17	-48.75	
	19.3375	22.85	QP	9.88	32.73	60.00	-27.27	
	19.3375	16.67	AVG	9.88	26.55	50.00	-23.45	
	24.5750	29.96	QP	9.90	39.86	60.00	-20.14	
*	24.5750	26.11	AVG	9.90	36.01	50.00	-13.99	

Explanation: ./.

Test equipment used: Please see test equipment utilized (AC Conducted).



Registration number: W6M22402-23275-C-1
FCC ID: 2ASJ3-SSRGO

Appendix

Measurement diagrams

Radiated Emission



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File: 1_BLE(1M)_TX 2402MHz Data: #1


Date: 2024/4/26

Temperature: 27.0 °C

80.0 dBuV/m

Time: 上午 03:15:14

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	148.8250	37.39	peak	-12.25	25.14	43.50	100	126	-18.36	
*	940.8300	34.28	peak	-0.72	33.56	46.00	100	337	-12.44	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File: 1_BLE(1M)_TX 2402MHz Data: #2


Date: 2024/4/26

Temperature: 27.0 °C

80.0 dBuV/m

Time: 上午 03:15:59

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_30-1000MHz

Polarization: **Vertical**

EUT : W6M22402-23275

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 2402MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	30.9700	49.49	peak	-14.75	34.74	40.00	100	181	-5.26	
*	38.2450	52.08	peak	-13.78	38.30	40.00	100	359	-1.70	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:08:16

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1535.500	56.89	peak	-8.41	48.48	74.00	150	63	-25.52	
*	1535.500	55.72	AVG	-8.41	47.31	54.00	150	63	-6.69	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:11:00

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1535.500	54.00	peak	-8.41	45.59	74.00	150	195	-28.41	
*	1535.500	52.97	AVG	-8.41	44.56	54.00	150	195	-9.44	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:08:59

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4804.000	37.45	peak	4.34	41.79	74.00	150	316	-32.21	
*	7206.000	33.53	peak	10.98	44.51	74.00	150	30	-29.49	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:11:43

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4804.000	42.10	peak	4.34	46.44	74.00	150	176	-27.56	
*	4804.000	33.16	AVG	4.34	37.50	54.00	150	176	-16.50	
	7206.000	34.02	peak	10.98	45.00	74.00	150	45	-29.00	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:09:48

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	33.34	peak	12.79	46.13	74.00	150	326	-27.87	
*	12010.000	33.49	peak	16.78	50.27	74.00	150	277	-23.73	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:12:25

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9608.000	33.55	peak	12.79	46.34	74.00	150	0	-27.66	
*	12010.000	33.73	peak	16.78	50.51	74.00	150	229	-23.49	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:10:04

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:12:41

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:10:15

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 05:12:52

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:53:34

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1535.500	57.54	peak	-8.41	49.13	74.00	150	163	-24.87	
*	1535.500	56.40	AVG	-8.41	47.99	54.00	150	163	-6.01	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:56:18

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1535.500	53.82	peak	-8.41	45.41	74.00	150	195	-28.59	
*	1535.500	52.81	AVG	-8.41	44.40	54.00	150	195	-9.60	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:54:17

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4880.000	37.66	peak	4.69	42.35	74.00	150	8	-31.65	
*	7320.000	34.32	peak	11.27	45.59	74.00	150	301	-28.41	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:57:01

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4880.000	42.57	peak	4.69	47.26	74.00	150	181	-26.74	
*	4880.000	33.99	AVG	4.69	38.68	54.00	150	181	-15.32	
	7320.000	35.92	peak	11.27	47.19	74.00	150	153	-26.81	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:55:06

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	32.46	peak	13.15	45.61	74.00	150	4	-28.39	
*	12200.000	33.41	peak	16.63	50.04	74.00	150	138	-23.96	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:57:43

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9760.000	33.03	peak	13.15	46.18	74.00	150	143	-27.82	
*	12200.000	33.39	peak	16.63	50.02	74.00	150	300	-23.98	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:55:23

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:58:00

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:55:33

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No.99, Sec.1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#10


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:58:10

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2440MHz

Note :

Polarization: *Vertical*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:29:23

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1535.500	58.91	peak	-8.41	50.50	74.00	150	300	-23.50	
*	1535.500	56.74	AVG	-8.41	48.33	54.00	150	300	-5.67	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:32:07

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	1535.500	55.56	peak	-8.41	47.15	74.00	150	59	-26.85	
*	1535.500	52.36	AVG	-8.41	43.95	54.00	150	59	-10.05	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:30:06

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	4960.000	40.07	peak	5.03	45.10	74.00	150	355	-28.90	
	7440.000	33.40	peak	10.97	44.37	74.00	150	230	-29.63	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:32:51

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4960.000	44.16	peak	5.03	49.19	74.00	150	90	-24.81	
*	4960.000	35.08	AVG	5.03	40.11	54.00	150	90	-13.89	
	7440.000	34.44	peak	10.97	45.41	74.00	150	2	-28.59	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:30:55

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	32.31	peak	13.40	45.71	74.00	150	119	-28.29	
*	12400.000	33.49	peak	17.05	50.54	74.00	150	70	-23.46	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:33:33

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	9920.000	32.54	peak	13.40	45.94	74.00	150	0	-28.06	
*	12400.000	34.88	peak	17.05	51.93	74.00	150	137	-22.07	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#4


Date: 2024/4/26

Temperature:27.0 °C

90.0 dBuV/m

Time: 上午 04:31:11

Humidity:51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:33:49

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:31:22

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2024/4/26

Temperature: 27.0 °C

90.0 dBuV/m

Time: 上午 04:33:59

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22402-23275

M/N:

Test Mode : TX 2480MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.


Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	49.46	peak	-4.97	44.49	74.00	150	347	-29.51	
*	2390.000	42.16	AVG	-4.97	37.19	54.00	150	347	-16.81	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : Bandedge

Data : #2


Date: 2024/4/26

Temperature: 27.0 °C

120.0 dBuV/m

Time: 上午 04:12:51

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

EUT : W6M22402-23275

M/N:

Test Mode : TX 2402MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2390.000	50.83	peak	-4.97	45.86	74.00	150	224	-28.14	
*	2390.000	42.88	AVG	-4.97	37.91	54.00	150	224	-16.09	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : Bandedge

Data : #1


Date: 2024/4/26

Temperature: 27.0 °C

120.0 dBuV/m

Time: 上午 04:20:07

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

Polarization: **Horizontal**

EUT : W6M22402-23275

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 2480MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	55.59	peak	-4.92	50.67	74.00	150	345	-23.33	
*	2483.500	43.83	AVG	-4.92	38.91	54.00	150	345	-15.09	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : Bandedge

Data : #2


Date: 2024/4/26

Temperature: 27.0 °C

120.0 dBuV/m

Time: 上午 04:25:18

Humidity: 51.1 %



Site : 966A Chamber

Condition : FCC 15.247 PK (Bandedge)

Polarization: Vertical

EUT : W6M22402-23275

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 2480MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2483.500	51.54	peak	-4.92	46.62	74.00	150	233	-27.38	
*	2483.500	43.66	AVG	-4.92	38.74	54.00	150	233	-15.26	

*:Maximum data x:Over limit !:over margin