

MPE REPORT

FCC ID: 2ASJX- LQ-C01

Date of issue: Feb. 28, 2019

Report Number: MTi190227E020

Sample Description: Multifunctional Wifi Smart Socket

Model(s): LQ-C01

Applicant: Shenzhen longquan technology co., LTD

Address: No.5, 3 / f, building 5, zhutouwo baoli industrial zone,
bantian street, longgang district, shenzhen

Date of Test: Feb. 16, 2019 - Feb. 28, 2019

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

TEST RESULT CERTIFICATION	
Applicant's name:	Shenzhen longquan technology co., LTD
Address:	No.5, 3 / f, building 5, zhutouwo baoli industrial zone, bantian street, longgang district, shenzhen
Manufacture's name:	Shenzhen longquan technology co., LTD
Address:	No.5, 3 / f, building 5, zhutouwo baoli industrial zone, bantian street, longgang district, shenzhen
Product name:	Multifunctional Wifi Smart Socket
Trademark:	N/A
Model name:	LQ-C01
Series model:	LQ-C02, LQ-C03, LQ-C05, LQ-C06, LQ-C07, LQ-C08, LQ-C09, LQ-C10, LQ-C11, LQ-C12
Difference in series models:	All the model are the same circuit and RF module, except the appearance.
RF Exposure Procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:



Orange Chen

Feb. 28, 2019

Reviewed by:



Blue Zheng

Feb. 28, 2019

Approved by:



Smith Chen

Feb. 28, 2019

1. RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi = 3.1415926$

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operation Frequency: WIFI 802.11b/g/n20:2412~2462MHz

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

Antenna gain: 3dBi

R=20cm

mW=10^(dBm/10)

Antenna gain Numeric=10^(dBi/10)= 10^(3/10)=2.0

2. SAR Test Exclusion Thresholds

Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power	Tune-up power	Max		Antenna	Evaluation result at 20cm	Power density Limits
		(dBm)	(dBm)	tune-up power	Gain			
				(dBm)	(mW)			
2412	802.11b	Ant A	Ant A	Ant A	Ant A	Ant A	Ant A	Ant A
		13.70	14±1	15	31.622777	2	0.01258	1
		14.37	14±1	15	31.622777	2	0.01258	1
2437	802.11g	13.73	14±1	15	31.622777	2	0.01258	1
2412		11.82	12.5±1	13.5	22.387211	2	0.00891	1
2437		12.70	12.5±1	13.5	22.387211	2	0.00891	1
2462	802.11n H20	13.22	12.5±1	13.5	22.387211	2	0.00891	1
2412		10.15	11±1	12	15.848932	2	0.00631	1
2437		11.14	11±1	12	15.848932	2	0.00631	1
2462		11.21	11±1	12	15.848932	2	0.00631	1

Conclusion:

For the max result: 0.01258 ≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----