



CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

PA1003 HD Streaming Video Drone

MODEL NUMBER: VL-6000/VL-6001/VL-6002

FCC ID: 2ASK3VL-6000R

REPORT NUMBER: 4789510507.1-2

ISSUE DATE: June 12, 2020

Prepared for

**AMAX INDUSTRIAL GROUP CHINA CO.,LTD
OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L TUNG CHOI STREET
MONGKOK KOWLOON HONG KONG**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	06/12/2020	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	20dB Bandwidth and 99% Occupied Bandwidth	CFR 47 FCC §15.215 (c)	Pass
2	Radiated Emission	CFR 47 FCC §15.249 (a)(d)(e) CFR 47 FCC §15.205 and §15.209	Pass
3	Conducted Emission Test For AC Power Port	FCC Part 15.207	Not Applicable
4	Antenna Requirement	CFR 47 FCC §15.203	Pass
Note: 1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C> when <Accuracy Method> decision rule is applied. 3. The EUT only employ battery power for operation and which do not operate from the AC power lines.			



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT.....	8
5.2. MAXIMUM FIELD STRENGTH	8
5.3. CHANNEL LIST.....	8
5.4. DESCRIPTION OF AVAILABLE ANTENNAS.....	8
5.5. TEST CHANNEL CONFIGURATION	8
5.6. THE WORSE CASE POWER SETTING PARAMETER.....	9
5.7. TEST ENVIRONMENT.....	9
5.8. DESCRIPTION OF TEST SETUP.....	10
5.9. MEASURING INSTRUMENT AND SOFTWARE USED	11
6. ANTENNA PORT TEST RESULTS	12
6.1. ON TIME AND DUTY CYCLE	12
6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	14
7. RADIATED TEST RESULTS	18
7.1. LIMITS AND PROCEDURE	18
7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS 24	
7.3. SPURIOUS EMISSIONS (1~3GHz)	30
7.4. SPURIOUS EMISSIONS (3~18GHz)	36
7.5. SPURIOUS EMISSIONS (18~26GHz)	42
7.6. SPURIOUS EMISSIONS BELOW 30MHz	44
7.7. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz	47
8. ANTENNA REQUIREMENTS	49



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

Manufacturer Information

Company Name: AMAX INDUSTRIAL GROUP CHINA CO.,LTD
Address: OFFICE NO.3 10/F WITTY COMMERCIAL BUILDING 1A-1L
TUNG CHOI STREET MONGKOK KOWLOON HONG KONG

EUT Description

EUT Name: PA1003 HD Streaming Video Drone
Model: VL-6000/VL-6001/VL-6002
Model Difference: All the same except for the model name and color.
Brand Name: /
Sample Status: Normal
Sample ID: 3106822
Sample Received Date: May 25, 2020
Date of Tested: May 25, 2020 ~ June 11, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS

Prepared By:

Mick Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 414788 D01 Radiated Test Site v01r01, FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011
---------------------------	--

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62dB
Radiation Emission test (include Fundamental emission) (9KHz-30MHz)	2.2dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	4.00dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	5.78dB (1GHz-18GHz)
	5.23dB (18GHz-26GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Equipment	PA1003 HD Streaming Video Drone
EUT Description	The EUT is a drone.
Model Name	VL-6000/VL-6001/VL-6002
Model difference	All the same except for the model name and color.
Operation frequency	2457 MHz ~ 2479 MHz
Modulation	GFSK
Battery	DC 7.4V

5.2. MAXIMUM FIELD STRENGTH

Frequency (MHz)	Channel Number	Max Peak field strength (dBμV/m)
2457	1[23]	94.22

5.3. CHANNEL LIST

EUT support channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2457	7	2463	13	2469	19	2475
2	2458	8	2464	14	2470	20	2476
3	2459	9	2465	15	2471	21	2477
4	2460	10	2466	16	2472	22	2478
5	2461	11	2467	17	2473	23	2479
6	2462	12	2468	18	2474	/	/

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency (MHz)	Antenna Type	Max Antenna Gain (dBi)
1	2457 ~ 2479	Whip Antenna	0

Test Mode	Transmit and Receive Mode	Description
GFSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5.5. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK	CH 1(Low Channel), CH 12(MID Channel), CH 23(High Channel)	2457MHz, 2468MHz, 2479MHz



5.6. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter under 2457 MHz ~ 2479 MHz Band				
Test Software Version		/		
Modulation Type	Transmit Antenna Number	Test Channel		
		CH1	CH12	CH23
GFSK	1	Default	Default	Default

5.7. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	22 ~ 28°C
Voltage:	VL	/
	VN	DC 7.4V
	VH	/

Note: VL= Lower Extreme Test Voltage
VN= Nominal Voltage
VH= Upper Extreme Test Voltage
TN= Normal Temperature



5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	P/N
/	/	/	/	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
/	/	/	/	/	/


ACCESSORY

Item	Equipment	Mfr/Brand	Model/Type No.	Specification	Series No.
/	/	/	/	/	/

TEST SETUP

The EUT have the engineer mode inside.

SETUP DIAGRAM FOR TEST



Note: New battery was used during all tests.

**5.9. MEASURING INSTRUMENT AND SOFTWARE USED**

Radiated Emissions						
Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec. 6, 2019	Dec. 6, 2020
☒	Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Sept.17, 2018	Sept.17,2021
☒	Preamplifier	HP	8447D	2944A09099	Dec. 5, 2019	Dec. 5, 2020
☒	EMI Measurement Receiver	R&S	ESR26	101377	Dec. 05, 2019	Dec.05, 2020
☒	Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept.17,2021
☒	Preamplifier	TDK	PA-02-0118	TRS-305-00067	Dec. 05, 2019	Dec.05, 2020
☒	Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17, 2022
☒	Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Dec. 05, 2019	Dec.05, 2020
☒	High Gain Horn Antenna	Schwarzbeck	BBHA-9170	691	Aug.11,2018	Aug.11,2021
☒	Preamplifier	TDK	PA-02-2	TRS-307-00003	Dec. 05, 2019	Dec.05, 2020
Software						
Used	Description		Manufacturer	Name		Version
☒	Test Software for Radiated disturbance		Farad	EZ-EMC		Ver. UL-3A1
Other instruments						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
☒	High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec. 05, 2019	Dec.05, 2020
☒	Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec. 05, 2019	Dec.05, 2020



6. ANTENNA PORT TEST RESULTS

6.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



TEST ENVIRONMENT


Temperature	23.2°C	Relative Humidity	55%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.4V

RESULTS


Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)
GFSK	49.78	100	0.4978	49.78	-6.06

Note: Duty Cycle Correction Factor=20log(x).
Where: x is Duty Cycle

ON TIME AND DUTY CYCLE MID CH PLOT



ON TIME AND DUTY CYCLE MID CH PLOT-2



Note: All the modes had been tested, but only the worst duty cycle recorded in the report.



6.2. 20 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.249) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.215 (c)	20dB Bandwidth	for reporting purposes only	2400-2483.5


TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	1% to 5% of the occupied bandwidth
VBW	approximately 3×RBW
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99% relative to the maximum level measured in the fundamental emission.



TEST SETUP




TEST ENVIRONMENT

Temperature	23.2°C	Relative Humidity	53%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.4V

RESULTS




20 dB BANDWIDTH LOW CH



Date: 29.MAY.2020 10:56:37

99% OCCUPIED BANDWIDTH LOW CH




Date: 29 MAY 2020 17:22:14




Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2468	0.5369	0.5874	PASS

20 dB BANDWIDTH MID CH



Date: 29.MAY.2020 10:58:55

99% OCCUPIED BANDWIDTH MID CH




Date: 29 MAY 2020 17:39:54




Frequency (MHz)	20dB bandwidth (MHz)	99% bandwidth (MHz)	Result
2479	0.5340	0.5904	PASS

20 dB BANDWIDTH HIG CH



Date: 29.MAY.2020 11:02:56

99% OCCUPIED BANDWIDTH HIG CH



Date: 29 MAY 2020 17:45:37



7. RADIATED TEST RESULTS

7.1. LIMITS AND PROCEDURE

LIMITS

CFR 47 FCC §15.205 and §15.209

CFR 47 FCC §15.249 (a)(d)(c)(e)

The field strength of emissions from intentional radiators operated within these frequency bands			
Frequency (MHz)	Field strength of Fundamental	Field strength of Harmonics	Distance (m)
902 - 928	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
2400 – 2483.5	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3
5725 – 5875	50 mV/m (94dBuV/m)	500 uV/m (54dBuV/m)	3

Emissions radiated outside of the specified frequency bands above 30MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30



FCC Restricted bands of operation:


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
VBW	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/ Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open field site. Therefore, the sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured

Above 1G




The setting of the spectrum analyser

RBW	1M
VBW	PEAK: 3M AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter or band reject filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements. Where necessary, average emission are determined by applying the Duty Cycle Correction Factor to the peak measurements. For the Duty Cycle and Correction Factor please refer to clause 6.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:




Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	59%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.4V


7.2. RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS

RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2360.995	15.90	32.85	48.75	74.00	-25.25	peak
2	2400.000	14.45	32.98	47.43	74.00	-26.57	peak
3	2457.250	60.83	33.39	94.22	114.00	-19.78	peak
4	2457.250	54.77	33.39	88.16	94.00	-5.84	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG Result=Peak Result + Duty Cycle Correction Factor.
5. For the Duty Cycle and Correction Factor, please refer to clause 6.1.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2391.220	15.26	32.95	48.21	74.00	-25.79	peak
2	2400.000	13.14	32.98	46.12	74.00	-27.88	peak
3	2457.250	59.56	33.39	92.95	114.00	-21.05	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2467.960	58.77	33.47	92.24	114.00	-21.76	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

FIELD STRENGTH OF INTENTIONAL EMISSIONS (MIDDLE CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2467.960	59.38	33.47	92.85	114.00	-21.15	peak

- Note:
1. Measurement = Reading Level + Correct Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Peak: Peak detector.
 4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2478.940	59.48	33.55	93.03	114.00	-20.97	peak
2	2483.500	15.31	33.58	48.89	74.00	-25.11	peak
3	2490.400	18.01	33.63	51.64	74.00	-22.36	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



RESTRICTED BANDEDGE AND FIELD STRENGTH OF INTENTIONAL EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.090	59.25	33.55	92.80	114.00	-21.20	peak
2	2483.500	14.54	33.58	48.12	74.00	-25.88	peak
3	2497.450	17.72	33.69	51.41	74.00	-22.59	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Only the worst emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

7.3. SPURIOUS EMISSIONS (1~3GHz)

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1246.000	45.24	-12.52	32.72	74.00	-41.28	peak
2	1536.000	45.06	-11.92	33.14	74.00	-40.86	peak
3	1858.000	44.86	-9.93	34.93	74.00	-39.07	peak
4	2080.000	44.70	-9.30	35.40	74.00	-38.60	peak
5	2457.000	47.22	-7.47	39.75	/	/	fundamental
6	2800.000	43.92	-6.06	37.86	74.00	-36.14	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1180.000	45.44	-12.85	32.59	74.00	-41.41	peak
2	1448.000	45.47	-12.30	33.17	74.00	-40.83	peak
3	1840.000	45.41	-9.93	35.48	74.00	-38.52	peak
4	2457.000	50.10	-7.47	42.63	/	/	fundamental
5	2526.000	46.19	-7.31	38.88	74.00	-35.12	peak
6	3000.000	43.31	-5.30	38.01	74.00	-35.99	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1260.000	45.45	-12.48	32.97	74.00	-41.03	peak
2	1950.000	45.43	-9.89	35.54	74.00	-38.46	peak
3	2146.000	45.60	-8.93	36.67	74.00	-37.33	peak
4	2468.000	44.68	-7.39	37.29	/	/	fundamental
5	2860.000	43.56	-5.73	37.83	74.00	-36.17	peak
6	2996.000	43.29	-5.30	37.99	74.00	-36.01	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1258.000	46.07	-12.49	33.58	74.00	-40.42	peak
2	1658.000	44.88	-11.11	33.77	74.00	-40.23	peak
3	1742.000	45.35	-10.49	34.86	74.00	-39.14	peak
4	1926.000	45.25	-9.92	35.33	74.00	-38.67	peak
5	2468.000	54.18	-7.39	46.79	/	/	fundamental
6	2844.000	43.25	-5.82	37.43	74.00	-36.57	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1358.000	45.49	-12.37	33.12	74.00	-40.88	peak
2	1548.000	46.17	-11.82	34.35	74.00	-39.65	peak
3	2026.000	45.94	-9.65	36.29	74.00	-37.71	peak
4	2479.000	45.69	-7.32	38.37	/	/	fundamental
5	2818.000	43.36	-5.97	37.39	74.00	-36.61	peak
6	2930.000	43.50	-5.46	38.04	74.00	-35.96	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1242.000	45.28	-12.53	32.75	74.00	-41.25	peak
2	1612.000	44.51	-11.33	33.18	74.00	-40.82	peak
3	1806.000	44.83	-9.92	34.91	74.00	-39.09	peak
4	2110.000	44.82	-9.10	35.72	74.00	-38.28	peak
5	2479.000	53.32	-7.32	46.00	/	/	fundamental
6	2962.000	43.15	-5.39	37.76	74.00	-36.24	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

7.4. SPURIOUS EMISSIONS (3~18GHz)

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	48.97	0.88	49.85	74.00	-24.15	peak
2	7035.000	40.42	5.81	46.23	74.00	-27.77	peak
3	11505.000	36.36	13.42	49.78	74.00	-24.22	peak
4	13800.000	33.24	17.10	50.34	74.00	-23.66	peak
5	16860.000	32.34	19.95	52.29	74.00	-21.71	peak
6	17715.000	30.31	22.56	52.87	74.00	-21.13	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. The High Pass filter loss factor already add into the correct factor.


5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4905.000	48.87	0.88	49.75	74.00	-24.25	peak
2	7905.000	39.80	7.21	47.01	74.00	-26.99	peak
3	11505.000	35.88	13.42	49.30	74.00	-24.70	peak
4	13785.000	33.28	16.91	50.19	74.00	-23.81	peak
5	16815.000	31.64	19.96	51.60	74.00	-22.40	peak
6	17865.000	29.87	23.33	53.20	74.00	-20.80	peak


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4935.000	49.37	1.05	50.42	74.00	-23.58	peak
2	7875.000	39.24	7.40	46.64	74.00	-27.36	peak
3	12570.000	35.80	14.17	49.97	74.00	-24.03	peak
4	13905.000	33.96	16.20	50.16	74.00	-23.84	peak
5	17220.000	31.41	21.08	52.49	74.00	-21.51	peak
6	17940.000	29.88	23.39	53.27	74.00	-20.73	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4935.000	49.10	1.05	50.15	74.00	-23.85	peak
2	7020.000	41.24	5.78	47.02	74.00	-26.98	peak
3	11520.000	36.03	13.38	49.41	74.00	-24.59	peak
4	13905.000	34.54	16.20	50.74	74.00	-23.26	peak
5	16815.000	32.14	19.96	52.10	74.00	-21.90	peak
6	17940.000	30.01	23.39	53.40	74.00	-20.60	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	49.60	1.13	50.73	74.00	-23.27	peak
2	7875.000	39.94	7.40	47.34	74.00	-26.66	peak
3	11535.000	36.83	13.33	50.16	74.00	-23.84	peak
4	13875.000	33.58	16.44	50.02	74.00	-23.98	peak
5	16755.000	31.81	19.94	51.75	74.00	-22.25	peak
6	17715.000	29.92	22.56	52.48	74.00	-21.52	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	48.44	1.13	49.57	74.00	-24.43	peak
2	7815.000	39.63	7.83	47.46	74.00	-26.54	peak
3	11430.000	37.26	12.85	50.11	74.00	-23.89	peak
4	13875.000	34.11	16.44	50.55	74.00	-23.45	peak
5	17340.000	31.06	21.61	52.67	74.00	-21.33	peak
6	17865.000	30.04	23.33	53.37	74.00	-20.63	peak

- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. The High Pass filter loss factor already add into the correct factor.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



7.5. SPURIOUS EMISSIONS (18~26GHz)

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19208.000	50.99	-5.02	45.97	74.00	-28.03	peak
2	19720.000	50.08	-4.39	45.69	74.00	-28.31	peak
3	21136.000	52.00	-5.41	46.59	74.00	-27.41	peak
4	22360.000	52.08	-5.95	46.13	74.00	-27.87	peak
5	23560.000	50.21	-4.72	45.49	74.00	-28.51	peak
6	25360.000	47.81	-1.46	46.35	74.00	-27.65	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.



HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18384.000	50.07	-4.37	45.70	74.00	-28.30	peak
2	18832.000	50.41	-4.85	45.56	74.00	-28.44	peak
3	20696.000	49.91	-5.08	44.83	74.00	-29.17	peak
4	21832.000	51.03	-5.92	45.11	74.00	-28.89	peak
5	23944.000	50.45	-4.14	46.31	74.00	-27.69	peak
6	25976.000	47.94	-2.35	45.59	74.00	-28.41	peak


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.

Note: All test modes had been tested, only the worst data record in the report.

7.6. SPURIOUS EMISSIONS BELOW 30MHz

SPURIOUS EMISSIONS (MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9kHz~ 150kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0091	76.08	-101.33	-25.25	48.28	-73.53	peak
2	0.0129	72.25	-101.38	-29.13	45.39	-74.52	peak
3	0.0206	68.42	-101.35	-32.93	41.32	-74.25	peak
4	0.0427	62.64	-101.45	-38.81	34.99	-73.80	peak
5	0.0675	58.14	-101.56	-43.42	31.02	-74.44	peak
6	0.0981	55.77	-101.78	-46.01	27.77	-73.78	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150kHz ~ 490kHz


No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1547	76.81	-101.65	-24.84	23.81	-48.65	peak
2	0.1731	73.46	-101.67	-28.21	22.84	-51.05	peak
3	0.2190	66.27	-101.75	-35.48	20.79	-56.27	peak
4	0.2605	62.64	-101.81	-39.17	19.28	-58.45	peak
5	0.3286	60.71	-101.88	-41.17	17.27	-58.44	peak
6	0.3800	58.02	-101.94	-43.92	16.01	-59.93	peak

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490kHz ~ 30MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6169	66.55	-62.08	4.47	31.80	-27.33	peak
2	1.0802	62.16	-62.23	-0.07	26.94	-27.01	peak
3	1.8180	57.03	-61.90	-4.87	29.54	-34.41	peak
4	4.2968	53.77	-61.38	-7.61	29.54	-37.15	peak
5	8.4870	52.10	-61.01	-8.91	29.54	-38.45	peak
6	16.4542	51.25	-60.96	-9.71	29.54	-39.25	peak

Note: 1. Measurement = Reading Level + Correct Factor.


2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All test modes had been tested, only the worst data record in the report.


7.7. SPURIOUS EMISSIONS BELOW 1GHz AND ABOVE 30MHz

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	31.9400	33.34	-17.05	16.29	40.00	-23.71	QP
2	177.4400	28.18	-16.71	11.47	43.50	-32.03	QP
3	250.1900	29.22	-16.34	12.88	46.00	-33.12	QP
4	426.7300	36.22	-12.21	24.01	46.00	-21.99	QP
5	467.4700	32.07	-11.52	20.55	46.00	-25.45	QP
6	903.9700	27.25	-4.19	23.06	46.00	-22.94	QP

- Note: 1. Result Level = Read Level + Correct Factor.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	35.17	-17.24	17.93	40.00	-22.07	QP
2	299.6600	29.74	-14.39	15.35	46.00	-30.65	QP
3	350.1000	30.22	-13.52	16.70	46.00	-29.30	QP
4	424.7900	31.95	-12.25	19.70	46.00	-26.30	QP
5	474.2600	31.17	-11.34	19.83	46.00	-26.17	QP
6	908.8200	28.12	-4.11	24.01	46.00	-21.99	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto

Note: All test modes had been tested, only the worst data record in the report.



8. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

END OF REPORT