



## MPE TEST REPORT

**Applicant** PHILLIPS CONNECT TECHNOLOGIES LLC  
**FCC ID** 2ASKH-MB01  
**Product** SolarNet  
**Brand** Phillips Connect  
**Model** 77-8000; 77-8001; 77-8002; 77-8003  
**Report No.** EFTA25022177-IE-03-M1V1  
**Issue Date** July 31, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

---

*Prepared by: Wei Fangying*

*Approved by: Xu Kai*

---

**Eurofins TA Technology (Shanghai) Co., Ltd.**

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China*

*TEL: +86-021-50791141/2/3*

*FAX: +86-021-50791141/2/3-8000*

## Table of Contents

1	Test Laboratory .....	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility.....	4
1.3	Testing Location.....	4
1.4	Laboratory Environment .....	4
2	Description of Equipment Under Test .....	5
3	Maximum Tune up and Antenna Gain .....	5
4	MPE Limit.....	7
5	RF Exposure Evaluation Result.....	9
	ANNEX A: The EUT Appearance .....	10

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	July 4, 2025
Rev.1	Update description.	July 31, 2025
Note: This revised report (Report No.: EFTA25022177-IE-03-M1V1) supersedes and replaces the previously issued report (Report No.: EFTA25022177-IE-03-M1). Please discard or destroy the previously issued report and dispose of it accordingly.		

## 1 Test Laboratory

### 1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2 Test Facility

#### FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

### 1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.  
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <https://www.eurofins.com/electrical-and-electronics>  
E-mail: Kain.Xu@cpt.eurofinscn.com

### 1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

## 2 Description of Equipment Under Test

### Client Information

<b>Applicant</b>	PHILLIPS CONNECT TECHNOLOGIES LLC
<b>Applicant address</b>	5231 California Avenue, Suite 110, Irvine, CA 92617
<b>Manufacturer</b>	PHILLIPS CONNECT TECHNOLOGIES LLC
<b>Manufacturer address</b>	5231 California Avenue, Suite 110, Irvine, CA 92617

### General Technologies

EUT Description			
Model	77-8000; 77-8001; 77-8002; 77-8003		
Lab internal SN	EFTA25022177-IE-01/S01		
HW Version	Megatron Board		
SW Version	Trailer 24A		
Frequency	Band	TX (MHz)	RX (MHz)
	WCDMA Band II	1850 ~ 1910	1930 ~ 1990
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 12	699 ~ 716	729 ~ 746
	Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5
Date of Testing	March 3, 2025 ~ March 13, 2025		
Date of Sample Received	February 24, 2025		
<p><b>Note:</b></p> <ol style="list-style-type: none"> <li>1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.</li> <li>2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.</li> </ol>			

Model	Separately	The others
77-8000	Base Model	
77-8001	Model with TPMS	
77-8002	Model with Camera	All the same
77-8003	Model with TPMS & Camera	

### 3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{\text{antenna gain}/10}$$

Band	Maximum Tune up Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
WCDMA Band II	25.70	371.54	4.72	2.96
WCDMA Band IV	25.70	371.54	4.00	2.51
WCDMA Band V	25.70	371.54	-3.00	0.50
LTE Band 2	25.70	371.54	4.72	2.96
LTE Band 4	25.70	371.54	4.00	2.51
LTE Band 12	25.70	371.54	0.19	1.04
Bluetooth LE	8.00	6.31	2.75	1.88

## 4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. \* = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is f/1500, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm <sup>2</sup> )
WCDMA Band II	1.000
WCDMA Band IV	1.000
WCDMA Band V	0.549
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 12	0.466
Bluetooth LE	1.000

## 5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm <sup>2</sup> )	Limit Value (mW/cm <sup>2</sup> )	The MPE Ratio
WCDMA Band II	25.70	4.72	30.42	1101.54	0.22	1.000	<b>0.219</b>
WCDMA Band IV	25.70	4.00	29.70	933.25	0.19	1.000	0.186
WCDMA Band V	25.70	-3.00	22.70	186.21	0.04	0.549	0.067
LTE Band 2	25.70	4.72	30.42	1101.54	0.22	1.000	0.219
LTE Band 4	25.70	4.00	29.70	933.25	0.19	1.000	0.186
LTE Band 12	25.70	0.19	25.89	388.15	0.08	0.466	0.166
Bluetooth LE	8.00	2.75	10.750	11.885	0.002	1.000	<b>0.002</b>

Note: R = 20cm  
 $\pi = 3.1416$   
 The MPE Ratio = Mac Result ÷ Limit Value

So the simultaneous transmitting antenna pairs as below:

TER = Bluetooth LE Antenna MPE ratio + WWAN Antenna MPE ratio = 0.219 + 0.002 = 0.221 < 1

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

## ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

\*\*\*\*\*END OF REPORT\*\*\*\*\*