

MPE TEST REPORT

Applicant Phillips Connect Technologies, LLC
FCC ID 2ASKH-S7PR1
Product Smart-7 Pro
Brand Phillips Connect
Model 77-6800 CAN
Report No. R2301A0045-M1V1
Issue Date June 26, 2023

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Wei Fangying

Prepared by: Wei Fangying

Fan Guangchang

Approved by: Fan Guangchang

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report	4
1.2	Test Facility	4
1.3	Testing Location.....	4
1.4	Laboratory Environment.....	4
2	Description of Equipment Under Test	5
3	Maximum Tune Up and Antenna Gain.....	6
4	Test Result	7
	ANNEX A: The EUT Appearance.....	10

Version	Revision description	Issue Date
Rev.0	Initial issue of report.	May 22, 2023
Rev.1	Update information and data.	June 26, 2023
Note: This revised report (Report No. R2301A0045-M1V1) supersedes and replaces the previously issued report (Report No. R2301A0045-M1). Please discard or destroy the previously issued report and dispose of it accordingly.		

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.

Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

City: Shanghai

Post code: 201201

Country: P. R. China

Contact: Fan Guangchang

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000

Website: <http://www.ta-shanghai.com>

E-mail: fanguangchang@ta-shanghai.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Phillips Connect Technologies, LLC
Applicant address	5231 California Avenue, Suite 110, Irvine, CA 92617, USA
Manufacturer	Phillips Connect Technologies, LLC
Manufacturer address	5231 California Avenue, Suite 110, Irvine, CA 92617, USA

General Technologies

Model	77-6800 CAN
IMEI	866961063364695
Hardware Version	Freight P6/Arrow-LA P3
Software Version	V6/V4
Date of Sample Received	January 10, 2023
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.	

3 Maximum Tune Up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{(\text{antenna gain}/10)}$$

Band	Maximum Tune Up Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
WCDMA Band II	25.700	371.535	1.000	1.259
WCDMA Band IV	25.700	371.535	1.000	1.259
WCDMA Band V	25.700	371.535	0.000	1.000
LTE Band 2	25.700	371.535	1.000	1.259
LTE Band 4	25.700	371.535	1.000	1.259
LTE Band 12	25.700	371.535	0.000	1.000
Bluetooth LE	8.000	6.310	0.350	1.084

4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
WCDMA Band II	1.000
WCDMA Band IV	1.000
WCDMA Band V	0.549
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 12	0.466
Bluetooth LE	1.000

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune Up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Test Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
WCDMA Band II	25.700	1.000	26.700	467.735	0.093	1.000	0.093
WCDMA Band IV	25.700	1.000	26.700	467.735	0.093	1.000	0.093
WCDMA Band V	25.700	0.000	25.700	371.535	0.074	0.549	0.135
LTE Band 2	25.700	1.000	26.700	467.735	0.093	1.000	0.093
LTE Band 4	25.700	1.000	26.700	467.735	0.093	1.000	0.093
LTE Band 12	25.700	0.000	25.700	371.535	0.074	0.466	0.159
Bluetooth LE	8.000	0.350	8.350	6.839	0.001	1.000	0.001
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Test Result ÷ Limit Value							

So the simultaneous transmitting antenna pairs as below:

$$\sum \text{of MPE Ratios} = \text{WWAN Antenna} + \text{Bluetooth LE} = 0.159 + 0.001 = 0.160 < 1$$

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

*****END OF REPORT *****

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.