

FCC Maximum Permissible RF Exposure (MPE) Estimation Report

In accordance with the requirements of
FCC 47 CFR Part 2(2.1091), ANSI/IEEE C95.1-1992 and
KDB 447498 D01

Product Name: Tail Auto-Director AI Camera

Trademark: OBSBOT

Model Name: Tail Auto-Director AI Camera

Family Model: Red OAR-1609, Black OAB-1609

Report No.: S18122902102003

FCC ID: 2ASMC-OBS-TAIL-01

Prepared for

Remo Tech Co.,Ltd

Room 220,Building 6,Qianhai Shenzhen-Hong Kong Youth Innovat and Entrepreneur
Hub,Shenzhen,China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District,
Shenzhen 518126 P.R.China.

Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name** : Remo Tech Co.,LtdAddress : Room 220,Building 6,Qianhai Shenzhen-Hong Kong Youth
Innovat and Entrepreneur Hub,Shenzhen,China**Manufacturer's Name** : Remo Tech Co.,LtdAddress : Room 220,Building 6,Qianhai Shenzhen-Hong Kong Youth
Innovat and Entrepreneur Hub,Shenzhen,China**Product description**

Product name : Tail Auto-Director AI Camera

Trademark : OBSBOT

Model and/or type reference : Tail Auto-Director AI Camera

Family Model : Red OAR-1609, Black OAB-1609

FCC 47 CFR Part 1(1.1310)

FCC 47 CFR Part 2(2.1091)

Standards : ANSI/IEEE C95.1-1992

KDB 447498 D01

This device described above has been tested by Shenzhen NTEK. Testing has shown that this device is capable of compliance with MPE specified in FCC 47 CFR Part 2(2.1091) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... : 18 Jan. 2019 ~ 05 Apr. 2019

Date of Issue : 05 May. 2019

Test Result : **Pass**

Prepared By : 
(Test Engineer) : _____
(Cheng Jiawen)

Approved By : 
(Lab Manager) : _____
(Sam Chen)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	May. 05, 2019	Cheng Jiawen

TABLE OF CONTENTS

1	General Information	5
1.1	RF Exposure Requirements.....	5
1.1.1	RF Exposure Limits	5
1.1.2	Additional Description.....	6
1.2	EUT Description	7
1.3	Test specification(s).....	7
1.4	Ambient Condition	7
2	RF Output Power	8
3	RF Exposure Evaluation	11
3.1	Operation in WLAN 2.4G	11
3.2	Operation in WLAN 5G	11
4	Exposure calculations for multiple sources.....	12
4.1	Estimation for WLAN2.4G MIMO	13
4.2	Estimation for WLAN5G MIMO	13

1 General Information

1.1 RF Exposure Requirements

1.1.1 RF Exposure Limits

Table - Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30
f = frequency in MHz * = Plane-wave equivalent power density				

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P_t * G_t}{4 * \pi * R^2}$$

Where:

S = Power density (mW/cm²)

P_t = Conducted output power (dBm)

G_t = numeric gain of the antenna in the direction of interest relative to an isotropic radiator (dBi)

R = distance to the centre of radiation of the antenna (cm)

EIRP = P_t * G_t

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

1.1.2 Additional Description

An estimation of MPE in this application for product is used to ensure if it complies to the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC's MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

1.2 EUT Description

Device Information			
Product Name	Tail Auto-Director AI Camera		
Trade Name	OBSBOT		
Model Name	Tail Auto-Director AI Camera		
Family Model	Red OAR-1609, Black OAB-1609		
FCC ID	2ASMC-OBS-TAIL-01		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna Type	Ant A: PCB Antenna Ant B: PCB Antenna		
Antenna Gain	Ant A: 2.79dBi for WLAN2.4G and 3.75dBi for WLAN5G Ant B: 2.79dBi for WLAN2.4G and 3.75dBi for WLAN5G		
Device Operating Configurations			
Supporting Mode(s)	WLAN 2.4G/5.2G/5.8G		
Test Modulation	WLAN(DSSS/OFDM)		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	

1.3 Test specification(s)

FCC 47 CFR Part 1(1.1310)
FCC 47 CFR Part 2(2.1091)
ANSI/IEEE C95.1-1992
KDB 447498 D01 General RF Exposure Guidance

1.4 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2 RF Output Power

Test Channel	Frequency (MHz)	Power Setting	Duty Cycle Factor (dB)	Peak Output Power(dBm)		Total		LIMIT (dBm)	Verdict
				ANT A	ANT B	(dBm)			
802.11b									
1	2412	Default	0	15.2	14.9	-	-	30	PASS
6	2437	Default	0	14.5	14.4	-	-	30	PASS
11	2462	Default	0	14.9	14.4	-	-	30	PASS
802.11g									
1	2412	Default	0	13.2	11.5	-	-	30	PASS
6	2437	Default	0	12.5	11.9	-	-	30	PASS
11	2462	Default	0	12.9	12.3	-	-	30	PASS
802.11n HT20									
1	2412	Default	0	12.5	12.3	15.41		30	PASS
6	2437	Default	0	11.6	10.7	14.18		30	PASS
11	2462	Default	0	12.3	11.7	15.02		30	PASS
802.11n HT40									
3	2422	Default	0	11.9	11.8	14.86		30	PASS
6	2437	Default	0	11.2	11.0	14.11		30	PASS
9	2452	Default	0	11.7	11.4	14.56		30	PASS

Test Channel	Frequency	Maximum output power. Antenna port		Total Power	LIMIT	Result
		(AV) (dBm)		(AV)		
	(MHz)	ANT A	ANT B	dBm	dBm	
TX 802.11a Mode						
CH36	5180	12.1	11.8	—	23.98	Pass
CH40	5200	12.2	12.1	—	23.98	Pass
CH48	5240	13.4	13.2	—	23.98	Pass
TX 802.11 n20M Mode						
CH36	5180	11.2	11.2	14.21	23.22	Pass
CH40	5200	11.4	11.1	14.26	23.22	Pass
CH48	5240	12.6	12.2	15.41	23.22	Pass
TX 802.11 n40M Mode						
CH38	5190	11.6	11.5	14.56	23.22	Pass
CH46	5230	12.7	12.5	15.61	23.22	Pass
TX 802.11 AC20M Mode						
CH36	5180	10.6	10.2	13.41	23.22	Pass
CH40	5200	10.9	10.5	13.71	23.22	Pass
CH48	5240	11.9	11.6	14.76	23.22	Pass
TX 802.11 AC40M Mode						
CH38	5190	10.8	10.5	13.66	23.22	Pass
CH46	5230	11.3	10.8	14.07	23.22	Pass
TX 802.11 AC80M Mode						
CH42	5210	11.1	10.8	13.96	23.22	Pass

Test Channel	Frequency	Maximum output power. Antenna port		Total Power	LIMIT	Result
		(AV) (dBm)		(AV)		
	(MHz)	ANT A	ANT B	dBm	dBm	
TX 802.11a Mode						
CH 149	5745	9.7	9.3	—	30	Pass
CH 157	5785	9.5	9.2	—	30	Pass
CH 165	5825	9.6	9.3	—	30	Pass
TX 802.11 n20M Mode						
CH 149	5745	10.6	10.1	13.37	29.24	Pass
CH 157	5785	10.5	10.4	13.46	29.24	Pass
CH 165	5825	10.3	10.3	13.31	29.24	Pass
TX 802.11 n40M Mode						
CH 151	5755	8.9	8.8	11.86	29.24	Pass
CH 159	5795	8.8	8.8	11.81	29.24	Pass
TX 802.11 ac20M Mode						
CH 149	5745	9.5	9.4	12.46	29.24	Pass
CH 157	5785	9.3	9.2	12.26	29.24	Pass
CH 165	5825	9.3	9.1	12.21	29.24	Pass
TX 802.11 ac40M Mode						
CH 151	5755	8.9	8.8	11.86	29.24	Pass
CH 159	5795	8.7	8.8	11.76	29.24	Pass
TX 802.11 ac80M Mode						
CH 155	5775	7.5	7.4	10.46	29.24	Pass

3 RF Exposure Evaluation

3.1 Operation in WLAN 2.4G

SISO

Antenna	Maximum output power (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
Ant A	15.2	2.79	17.99	62.95	20	0.0125	1	Pass
Ant B	14.9	2.79	17.69	58.75	20	0.0117	1	Pass

3.2 Operation in WLAN 5G

SISO

Antenna	Maximum output power (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
Ant A	13.4	3.75	17.15	51.88	20	0.0103	1	Pass
Ant B	13.2	3.75	16.95	49.55	20	0.0099	1	Pass

4 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table (A) and Table (B). To comply with the MPE, the fraction of the MPE in terms of E², H² (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^n \frac{S_i}{MPE_i}$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	WLAN 2.4G MIMO
2	WLAN 5.2G MIMO
3	WLAN 5.8G MIMO

4.1 Estimation for WLAN2.4G MIMO

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Calculation result	Conclusion
Ant A	12.5	2.79	15.29	33.81	20	0.0067	1	0.0131	Pass
Ant B	12.3	2.79	15.09	32.28	20	0.0064	1		

4.2 Estimation for WLAN5G MIMO

Antenna	Tune-up limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Calculation result	Conclusion
Ant A	12.7	3.75	16.45	44.16	20	0.0088	1	0.0172	Pass
Ant B	12.5	3.75	16.25	42.17	20	0.0084	1		

According to the Table above, we can conclude that the calculation results of all simultaneous transmission possibilities are less than 1, so it is into compliance.

Therefore the product also meets the requirements under multiple sources condition.

-----END-----