

FCC 47 CFR PART 15 SUBPART E 15.407
TEST REPORT
FOR
Wireless Solution

Model : AS-AP515914DPK-W, AS-AP515918DPK-W,
AS-AP515923DPK-W

Issued to
ANSER-NET CO ., LTD
3F., No.108, Shanghai Rd., Taoyuan Dist., Taoyuan City 330, Taiwan (R.O.C.)

Issued by
WH Technology Corp.



EMC Test Site	Xizhi Office and Lab	7F., No.262, Sec. 3, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)
Tel.: +886-2-7729-7707 Fax: +886-2- 8648-1311		

Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of WH Technology Corp. This document may be altered or revised by WH Technology Corp. Personnel only, and shall be noted in the revision section of the document.

Contents

PHOTOS OF EUT	1. General Information.....	3
2. Report of Measurements and Examinations.....		5
2.1	List of Measurements and Examinations	5
3. Test Configuration of Equipment under Test.....		6
3.1	Description of the tested samples	6
3.2	Carrier Frequency of Channels	7
3.3	Test Mode and Test Software	8
3.4	TEST Methodology & General Test Procedures	9
3.5	Measurement Uncertainty	10
3.6	Description of the Support Equipments	10
4. Test and measurement equipment.....		11
4.1	calibration	11
4.2	equipment	11
5. Antenna Requirements.....		14
5.1	Standard Applicable	14
5.2	Antenna Construction and Directional Gain.....	14
6. Test of Conducted Emission.....		15
6.1	Test Limit	15
6.2	Test Procedures	15
6.3	Typical Test Setup	16
6.4	Test Result and Data: N/A.....	17
7. Test of Radiated Emission		18
7.1	Test Limit	18
7.2	Test Procedures	18
7.3	Typical Test Setup	19
7.4	Test Result and Data (9kHz ~ 30MHz).....	20
7.5	Test Result and Data (30MHz ~ 1GHz, worst emissions found).....	20
7.6	Test Result and Data (Between 1~40 GHz).....	26
7.7	Restricted Bands Test Result and Data	44
8. 6dB Bandwidth Measurement Data.....		63
8.1	Test Result and Data.....	64
9. Output Power.....		73
9.1	Test Result and Data.....	74
10. Power Spectral Density		83
10.1	Test Result and Data.....	84
11. Band Edges Measurement.....		93
11.1	Test Result and Data.....	96
12. 26dB BANDWIDTH		103
12.1	Test procedure	103

12.2	Test setup.....	103
12.3	Test results	104
13.	Restricted Bands of Operation.....	113
13.1	Labeling Requirement.....	113

APPENDIX 1 PHOTOS OF TEST CONFIGURATION

PHOTOS OF EUT

1. General Information

Applicant : ANSER-NET CO ., LTD

Address : 3F., No.108, Shanghai Rd., Taoyuan Dist., Taoyuan City
330, Taiwan (R.O.C.)

Manufacturer : ANSER-NET CO ., LTD

Address : 3F., No.108, Shanghai Rd., Taoyuan Dist., Taoyuan City
330, Taiwan (R.O.C.)

EUT : Wireless Solution

Model Name : AS-AP515914DPK-W, AS-AP515918DPK-W,
AS-AP515923DPK-W

Model Differences : Size.

Is here with confirmed to comply with the requirements set out in the FCC Rules and Regulations Part 15 Subpart C and the measurement procedures were according to ANSI C63.4-2014. The said equipment in the configuration described in this report shows the maximum emission levels emanating

FCC part 15 subpart E

Receipt Date : 03/27/2019

Final Test Date : 04/24/2019

Tested By:

Reviewed by:



Apr. 24, 2019

Date

Bing Chang/ Engineer

Apr. 24, 2019

Date

Bell Wei / Manager

Designation Number: TW2954

2. Report of Measurements and Examinations

2.1 List of Measurements and Examinations

FCC Rule	Description of Test	Section	Result
15.203	Antenna requirement	5	Pass
15.207 15.407(b)(6)	Conducted Emission	6	N/A
15.205/15.209/ 15.407(b)(5), (6), (7)	Radiated Emission	7	Pass
15.407(e)	6dB Bandwidth	8	Pass
15.407(a)(3)	Maximum conducted output Power	9	Pass
15.407(a)(3)	Maximum Power Spectral Density	10	Pass
15.407(b)(4)	Band Edge	11	Pass
15.407(a)(5)	26dB Bandwidth	12	Pass

3. Test Configuration of Equipment under Test

3.1 Description of the tested samples

EUT Name : Wireless Solution

Model Number : AS-AP515914DPK-W, AS-AP515918DPK-W,
AS-AP515923DPK-W

FCC ID : 2ASNE102101420

Receipt Date : 03/27/2019

Power From : Inside Outside RJ45 port
 Adaptor Battery AC Power Source
 DC Power Source Support Unit PC or NB

Power Range : POE

Battery : N/A

Operate Frequency : WiFi:
802.11a, 802.11n HT20: 5745MHz ~ 5825MHz
802.11n HT40: 5755 MHz ~ 5795MHz

Modulation Technique : 802.11a, 802.11n HT20, 802.11n HT40: OFDM

Number of Channels : Refer to the channel list as described below

Antenna Type : Antenna R: Panel Antenna
Antenna L: Panel Antenna

Antenna gain : 23 dBi(for Model no.: AS-AP515923DPK-W)
18 dBi(for Model no.: AS-AP515918DPK-W)
14 dBi(for Model no.: AS-AP515914DPK-W)

3.2 Carrier Frequency of Channels

802.11a, 802.11n, HT20

Channel	Frequency(MHz)
149	5745
157	5785
165	5825

802.11n, HT40

Channel	Frequency(MHz)	Channel	Frequency(MHz)
151	5755	159	5795

3.3 Test Mode and Test Software

- a. EUT is power on and connected to PC via RJ45. Log in "10.10.10.10" on website and alter to "10.10.10.10/.rftest". Then we can choose frequency to make sure EUT is continuing transmitting.
- b. The following test modes were performed for test:
 - 802.11a, 802.11n, HT20: CH149: 5745MHz, CH157: 5785MHz, CH165: 5825MHz
 - 802.11n HT40: CH151: 5755MHz, CH159: 5795MHz

3.4 TEST Methodology & General Test Procedures

All testing as described bellowed were performed in accordance with ANSI C63.4:2014 and ANSI C63.10:2013.

Conducted Emissions

The EUT is placed on a wood table, which is at 0.8 m above ground plane acceding to clause 15.207 and requirements of ANSI C63.4:2014. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz are using CISPR Quasi-Peak / Average detectors.

Radiated Emissions

The EUT is a placed on a turn table, which is 0.8 m above ground plane. The turntable was rotated through 360 degrees to determine the position of maximum emission level. The EUT is placed at 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

- 1) Putting the EUT on the platform and turning on the EUT (on/off button on the bottom of the EUT).
- 2) Setting test channel described as “Channel setting and operating condition”, and testing channel by channel.
- 3) For the maximum output power measurement, we followed the method of measurement KDB 789033 D02.
- 4) For the spurious emission test based on ANSI(2014), at the frequency where below 1GHz used quasi-peak detector mode; where above 1GHz used the peak and average detector mode. IF the peak value may be under average limit, the average mode will not be performed.

3.5 Measurement Uncertainty

Measurement Item	Uncertainty
Peak Output Power(conducted)	±1.345dB
Power Spectral Density	±1.347dB
Radiated emission(1G-40GHz)	±5.00dB
Radiated emission(30M-1GHz)	±3.89dB
Conducted emission	±1.81dB

3.6 Description of the Support Equipments

Setup Diagram

See test photographs attached in appendix 1 for the actual connections between EUT and support equipment.

Support Equipment

Peripherals Devices:

OUTSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
	N/A	N/A	N/A	N/A	N/A	N/A	N/A
INSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Note: All the above equipment /cable were placed in worse case position to maximize emission signals during emission test

Grounding: Grounding was in accordance with the manufacturer's requirement and conditions for the intended use.

4. Test and measurement equipment

4.1 calibration

The measuring equipment utilized to perform the tests documented in the report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2 equipment

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and. Other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective.

TABLELIST OF TEST AND MEASUREMENT EQUIPMENT

Test Site	Instrument	Manufacturer	Model No.	S/N	Next Cal. Date
Conduction	Spectrum (9K--3GHz)	R&S	FSP3	833387/010	2019/09/20
	EMI Receiver	R&S	ESHS10	830223/008	2019/05/22
	LISN	Rolf Heine Hochfrequenztechnik	NNB-2/16z	98062	2019/05/25
	ISN	Schwarzbeck	8-Wire ISN CAT5	CAT5-8158-0094	2019/09/21
	RF Cable	N/A	N/A	EMI-3	2019/10/19
Radiation	Bilog antenna(30M -1G)	ETC	MCTD2786B	BLB16M04004/J B-5-004	2019/05/03
	Double Ridged Guide Horn antenna(1G- 18G)	ETC	MCTD 1209	DRH15N0 2009	2019/11/23
	Horn antenna (18G-26G)	com-power	AH-826	81000	2019/08/15
	LOOP Antenna (Below 30M)	com-power	AL-130	17117	2019/10/04
	Pre amplifier (30M-1G)	EMC INSTRUMENT	EMC9135	980334	2019/05/04
	Microwave Preamplifier (1G-18G)	EMC INSTRUMENT	EMC051845	980108&AT -18001	2019/10/23
	Pre amplifier (18G~26G)	MITEQ	JS4-18002600-3 0-5A	808329	2019/08/10
	EMI Test Receiver	R&S	ESVS30 (20M-1000MHz)	826006/002	2019/11/28
	RF Cable	EMCI	N male on end	30m	2019/10/19

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

	(open site)		of both sides (EMI4)		
	RF CABLE (1~26.5G)	HARBOUR INDUSTRIES	LL142MI(4M+4M)	NA	2020/03/08
	RF CABLE (1~26.5G)	HARBOUR INDUSTRIES	LL142MI(7M)	NA	2019/08/11
	Spectrum (9K--7GHz)	R&S	FSP7	830180/006	2020/03/25
	Spectrum (9K--40GHz)	AGILENT	8564EC	4046A0032	2020/03/01
--	Power Meter	R&S	NRVS	100696	2019/08/10
--	Power Sensor	R&S	URV5-Z4	0395.1619.05	2019/08/10

***CALIBRATION INTERVAL OF INSTRUMENTS LISTED ABOVE IS ONE YEAR**

5. Antenna Requirements

5.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.2 Antenna Construction and Directional Gain

Model no.: AS-AP515923DPK-W

Antenna Type: Panel Antenna

Antenna Gain: Gain: 23 dBi

Model no.: AS-AP515918DPK-W

Antenna Type: Panel Antenna

Antenna Gain: Gain: 18 dBi

Model no.: AS-AP515914DPK-W

Antenna Type: Panel Antenna

Antenna Gain: Gain: 14 dBi

6. Test of Conducted Emission

6.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 110 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2014 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

6.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

6.3 Typical Test Setup



6.4 Test Result and Data: N/A

EUT is powered by POE.

7. Test of Radiated Emission

7.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

7.2 Test Procedures


- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise,

the emissions will be measured in average mode again and reported.


- i. "Cone of radiation" has been considered to be 3dB bandwidth of the measurement antenna.

7.3 Typical Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].


7.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz - 30MHz spurious emission is under limit 20dB more.

7.5 Test Result and Data (30MHz ~ 1GHz, worst emissions found)

AS-AP515923DPK-W

Power	: POE	Pol/Phase	: HORIZONTAL
Test Mode	: TX 5825MHz(worst-case)	Temperature	: 30 °C
Humidity	: 65%		



Remarks : 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor


Freq	Read Level	Factor	Level	Limit	Over	Remark
				Line	Limit	
MHz	dB _{UV}	dB/m	dB _{UV} /m	dB _{UV} /m	dB	
1 @ 120.59	52.69	-15.21	37.48	43.50	-6.02	QP
2 147.70	47.83	-15.46	32.37	43.50	-11.13	QP
3 500.07	32.36	-8.91	23.45	46.00	-22.55	QP
4 549.80	36.47	-8.55	27.92	46.00	-18.08	QP
5 759.22	35.96	-5.52	30.44	46.00	-15.56	QP
6 935.07	38.68	-1.70	36.98	46.00	-9.02	QP

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	TX 5825MHz(worst-case)	Temperature	:	30 °C
Humidity	:	65%			



Remarks :
 : 1.Result=Read Value+Factor
 : 2.Factor=Antenna Factor-Cable loss-
 : Amplifier Factor

Freq	Read MHz	Read Level	Factor	Level	Limit Line	Over Limit	Over Limit Remark
		dB _{UV}	dB/m	dB _{UV} /m	dB _{UV} /m	dB	
1 @	70.46	53.72	-22.16	31.56	40.00	-8.44	QP
2	375.46	41.67	-11.44	30.23	46.00	-15.77	QP
3	500.01	38.36	-8.91	29.45	46.00	-16.55	QP
4	625.66	35.54	-7.96	27.58	46.00	-18.42	QP
5	756.90	40.09	-5.56	34.53	46.00	-11.47	QP
6	883.29	37.16	-3.56	33.60	46.00	-12.40	QP

Note:

All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.


WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

AS-AP515918DPK-W

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	TX 5825MHz(worst-case)	Temperature	:	30 °C
Humidity	:	65%			



Remarks : 1.Result=Read Value+Factor
 : 2.Factor=Antenna Factor-Cable loss-
 : Amplifier Factor


Freq	Read Level	Factor	Limit		Over Line	Over Limit	Remark
			Level	Level			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	70.18	49.42	-22.13	27.29	40.00	-12.71	QP
2 @	375.80	49.75	-11.43	38.32	46.00	-7.68	QP
3	500.59	41.35	-8.90	32.45	46.00	-13.55	QP
4	625.98	37.52	-7.94	29.58	46.00	-16.42	QP
5	752.31	41.29	-5.64	35.65	46.00	-10.35	QP
6	854.97	39.10	-3.60	35.50	46.00	-10.50	QP

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	TX 5825MHz(worst-case)	Temperature	:	30 °C
Humidity	:	65%			



Remarks :
 1.Result=Read Value+Factor
 2.Factor=Antenna Factor-Cable loss-
 Amplifier Factor


Freq	Read Level	Factor	Limit		Over Line	Over Limit	Remark
			Level	Line			
MHz	dB _{UV}	dB/m	dB _{UV} /m	dB _{UV} /m			dB
1 @ 121.84	51.63	-15.15	36.48	43.50	-7.02	QP	
2 224.13	48.28	-17.31	30.97	46.00	-15.03	QP	
3 375.54	43.75	-11.43	32.32	46.00	-13.68	QP	
4 501.26	42.44	-8.90	33.54	46.00	-12.46	QP	
5 704.31	36.93	-6.78	30.15	46.00	-15.85	QP	
6 857.32	36.00	-3.59	32.41	46.00	-13.59	QP	

Note:

All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.

AS-AP515914DPK-W

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	TX 5825MHz(worst-case)	Temperature	:	30 °C
Humidity	:	65%			



 Remarks :
 : 1.Result=Read Value+Factor
 : 2.Factor=Antenna Factor-Cable loss-
 : Amplifier Factor


Freq	Read			Limit	Over	Remark
	Level	Factor	Level			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	74.29	53.13	-22.60	30.53	40.00	-9.47 QP
2	288.35	48.66	-13.64	35.02	46.00	-10.98 QP
3 @	375.97	49.75	-11.43	38.32	46.00	-7.68 QP
4	675.79	44.26	-6.94	37.32	46.00	-8.68 QP
5	857.93	39.01	-3.60	35.41	46.00	-10.59 QP
6	880.84	38.25	-3.56	34.69	46.00	-11.31 QP

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	TX 5825MHz(worst-case)	Temperature	:	30 °C
Humidity	:	65%			



Remarks :
 1.Result=Read Value+Factor
 2.Factor=Antenna Factor-Cable loss-
 Amplifier Factor

Freq	Read		Limit Level	Line	Over Limit	Remark
	Level	Factor				
1 @ 118.61	50.89	-15.38	35.51	43.50	-7.99	QP
2 @ 289.70	49.43	-13.59	35.84	46.00	-10.16	QP
3 @ 375.46	40.76	-11.44	29.32	46.00	-16.68	QP
4 @ 501.84	35.92	-8.89	27.03	46.00	-18.97	QP
5 @ 696.44	38.28	-6.89	31.39	46.00	-14.61	QP
6 @ 879.20	38.28	-3.56	34.72	46.00	-11.28	QP

Note:


All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits

7.6 Test Result and Data (Between 1~40 GHz)

Above 1GHz:

AS-AP515923DPK-W

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11a Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			



Remarks :
1.Result=Read Value+Factor
2.Factor=Antenna Factor-Cable loss-
Amplifier Factor


Freq	Read Level	Factor	Level	Limit	Over	Remark
				Line	Limit	
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 @ 11490.00	35.52	8.39	43.91	54.00	-10.09	Average
2 11490.00	47.08	8.39	55.47	74.00	-18.53	Peak
3 11570.00	34.18	8.40	42.58	54.00	-11.42	Average
4 11570.00	45.51	8.40	53.91	74.00	-20.09	Peak
5 11650.00	34.64	8.51	43.15	54.00	-10.85	Average
6 11650.00	46.21	8.51	54.72	74.00	-19.28	Peak

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	802.11a Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			




Remarks :
: 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read Level	Factor	Level	Limit	Over	Remark
				Line	Line	
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 @ 11490.00	33.87	8.39	42.26	54.00	-11.74	Average
2 11490.00	46.10	8.39	54.49	74.00	-19.51	Peak
3 11570.00	44.48	8.40	52.88	74.00	-21.12	Peak
4 11650.00	33.24	8.51	41.75	54.00	-12.25	Average
5 11650.00	45.16	8.51	53.67	74.00	-20.33	Peak

Note:

All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11n HT 20 Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			



 Remarks : 1.Result=Read Value+Factor
 : 2.Factor=Antenna Factor-Cable loss-
 : Amplifier Factor


Freq	MHz	Read	Limit	Over	Remark
		Level	Factor	Level	
1	11490.00	37.22	8.39	45.61	54.00 -8.39 Average
2	11490.00	46.51	8.39	54.90	74.00 -19.10 Peak
3 @	11570.00	37.69	8.40	46.09	54.00 -7.91 Average
4	11570.00	47.08	8.40	55.48	74.00 -18.52 Peak
5	11650.00	36.64	8.51	45.15	54.00 -8.85 Average
6	11650.00	45.76	8.51	54.27	74.00 -19.73 Peak

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	802.11n HT 20 Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			



Remarks : 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read Level	Factor	Limit	Over	Remark
			Line	Limit	
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB
1 11490.00	36.20	8.39	44.59	54.00	-9.41 Average
2 11490.00	45.95	8.39	54.34	74.00	-19.66 Peak
3 @ 11570.00	36.52	8.40	44.92	54.00	-9.08 Average
4 11570.00	46.44	8.40	54.84	74.00	-19.16 Peak
5 11650.00	35.46	8.51	43.97	54.00	-10.03 Average
6 11650.00	45.29	8.51	53.80	74.00	-20.20 Peak

Note:


All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11n HT 40 Channel 151-159	Temperature	:	30 °C
Humidity	:	65%			



Remarks :
1.Result=Read Value+Factor
2.Factor=Antenna Factor-Cable loss-
3.Amplifier Factor


Freq	MHz	Read	Limit	Over	Remark
		Level	Factor	Level	
1	11510.00	35.21	8.40	43.61	54.00 -10.39 Average
2	11510.00	45.66	8.40	54.06	74.00 -19.94 Peak
3 @	11590.00	35.55	8.40	43.95	54.00 -10.05 Average
4	11590.00	45.93	8.40	54.33	74.00 -19.67 Peak

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	: POE	Pol/Phase	: VERTICAL
Test Mode	: 802.11n HT 40 Channel 151-159	Temperature	: 30 °C
Humidity	: 65%		



Remarks :
: 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read		Level1	Limit Line	Over Limit	Remark
	Freq	Level	Factor			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	11510.00	43.76	8.40	52.16	74.00	-21.84 Peak
2 @	11590.00	44.16	8.40	52.56	74.00	-21.44 Peak

Note:

All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.


WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

AS-AP515918DPK-W


Power	: POE	Pol/Phase	: HORIZONTAL
Test Mode	: 802.11a Channel 149-157-165	Temperature	: 30 °C
Humidity	: 65%		



Remarks :
: 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read Level	Factor	Limit	Over Line	Over Limit	Remark
			Level	dBuV/m	dBuV/m	
1 @ 11490.00	41.90	8.39	50.29	74.00	-23.71	Peak
2 11570.00	40.86	8.40	49.26	74.00	-24.74	Peak
3 11650.00	41.29	8.51	49.80	74.00	-24.20	Peak

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	802.11a Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			



Remarks :
: 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read		Level	Limit Line	Over Limit	Remark
	Level	Factor				
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 @ 11490.00	41.29	8.39	49.68	74.00	-24.32	Peak
2 11570.00	40.51	8.40	48.91	74.00	-25.09	Peak
3 11650.00	40.77	8.51	49.28	74.00	-24.72	Peak


Note:

All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.

WH Technology Corp.

Date of Issue: Apr. 24, 2019
Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11n HT 20 Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			



Remarks : 1.Result=Read Value+Factor
 : 2.Factor=Antenna Factor-Cable loss-
 : Amplifier Factor


Freq	Read Level	Factor	Level1	Limit	Over	Remark
				Line	Line	
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 11490.00	42.64	8.39	51.03	74.00	-22.97	Peak
2 11570.00	42.30	8.40	50.70	74.00	-23.30	Peak
3 @ 11650.00	42.98	8.51	51.49	74.00	-22.51	Peak

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	VERTICAL
Test Mode	:	802.11n HT 20 Channel 149-157-165	Temperature	:	30 °C
Humidity	:	65%			



Remarks : 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read Level	Limit		Over Line	Over Limit	Remark
		Factor	Level			
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 11490.00	42.44	8.39	50.83	74.00	-23.17	Peak
2 11570.00	42.01	8.40	50.41	74.00	-23.59	Peak
3 @ 11650.00	42.69	8.51	51.20	74.00	-22.80	Peak

Note:


All the modulation modes were tested, the data of the worst mode are recorded in the above pages and the others modulation methods do not exceed the limits.

WH Technology Corp.

Date of Issue: Apr. 24, 2019

Report No.: WH-FCC-R19032702

Power	:	POE	Pol/Phase	:	HORIZONTAL
Test Mode	:	802.11n HT 40 Channel 151-159	Temperature	:	30 °C
Humidity	:	65%			



Remarks : 1.Result=Read Value+Factor
: 2.Factor=Antenna Factor-Cable loss-
: Amplifier Factor

Freq	Read		Level	Limit	Over	Remark
	Level	Factor				
	MHz	dB _{UV}	dB/m	dB _{UV} /m	dB _{UV} /m	dB
1	11510.00	41.87	8.40	50.27	74.00	-23.73 Peak
2 @	11590.00	42.16	8.40	50.56	74.00	-23.44 Peak