

Transmitter Solutions
2480 South 3850 West, Suite B Salt Lake City UT 84120 United States

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: Remote Controller
Model No: XRE-100

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.


A safety statement concerning minimum separation distances from enclosure of the
Product : Remote Controller
will be integrated in the user's manual to provide end-users with transmitter operating
conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21806-18166-C-1
and the accompanying calculations.

Company: Transmitter Solutions
Address: 2480 South 3850 West, Suite B Salt Lake City UT 84120 United States

Date: 2019-03-22


Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21806-18166-C-1

FCC ID: 2ASPOXRE100A

3.2 RF Exposure Compliance Requirements

FCC Rule: 15.247(b)(3)

Test exclusion = max. conducted output power

Test exclusion = 26.63 dBm

Test equipment used: ETSTW-RE 055

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4\pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	460.2566	Peak value
D	dB		
AG	dBi	1.2	
G		1.32	Calculated Value
R	cm	20	Assumed value
S	mW/cm ²	0.12	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0