

XX/XX/XX

12-34-56-78
90-12-34-56

SYMMONS®
the smart choice™

Symmons Water Management

Sensor Model: WW-02326

IC: 248181-J/WW02326

FCC ID: 2A5CQP-WW02326

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:
(1) This device may not cause harmful interference,
(2) This device must accept any interference received,
including interference that may cause undesired operation.



TEMPERATURE SENSOR CONTROLS

ES061940

This device has been tested in accordance to UL 2043 and is safe to use in platinum and air handling spaces.

Normal Voltage: 3.7VDC

Operating Temperature Range: -30°C to 60°C

Lithium ion battery enclosed

R1

Symmons Industries Inc.

31 Brookes Drive

Burlington, MA 02194

symmons.com

Tel: 1-800-971-MACHINS, (603) 799-6667

Support: symmons.com/support

TURN DEVICE ON: HOLD BUTTON 30 SECONDS

TURN DEVICE OFF: HOLD BUTTON 20 SECONDS

RESET DEVICE: HOLD BUTTON 10 SECONDS

FLASH AUTO ONCE TO TEST DEVICE

DEVICE WILL BEEP 4 TIMES TO TEST THE FOLLOWING:

BEEP #1: BATTERY LEVEL

BEEP #2: SENSOR/PWIRE CONNECTED

BEEP #3: WIRELESS CONNECTION TO GATEWAY

BEEP #4: WIRELESS SIGNAL STRENGTH TO GATEWAY

4 BEEPS: SUCCESS, GREEN LED A SHORT BEEP

FLASHES: RED LED A LONG BEEP

⚠ CAUTION: - Temperature probes may be exposed to potentially hazardous temperatures.

⚠ ATTENTION: - La sonde de température peut être exposée à des températures potentiellement dangereuses.