



시험 성적서

TEST REPORT

페이지(page) : (1) / (총(Total) 33)

성적서 번호 Report No.		ICRT-TR-E190559-0A	
신청자 Client	기관명 Name	NEOPOP Inc.	
	주 소 Address	6-604, 229, Seokjeong-ro, Nam-gu, Incheon, Republic of Korea	
시험대상품목 Sample description		Pet Band	
모델명 Type designation		Pet Band 2.0	
정 격 Ratings		DC 3.7 V	
시험기간 Date of test			
시험방법/항목 Test Method/Item		FCC Part 15 Subpart C §15.247	
시험결과 Test Results		Refer to 3. Test Summary	
확 인 Affirmation	작성자 Tested by	기술책임자 Technical Manager	
	성 명 Name	성 명 Name	
	Hong-Kyu, Lee (Signature)	Jun-Hui, Lee (Signature)	
□ 위 성적서는 고객이 제공한 시료에 대한 시험결과 이며, 용도 이외의 사용은 금합니다. This is certified that the above mentioned products have been tested for the sample provided by customer and forbid the use except for original purpose. □ 위 성적서는 한국인정기구(KOLAS)인정과 관련이 없습니다. The above test report is not related to accreditation by Korea Laboratory Accreditation scheme. □ 위 성적서는 주식회사 아이씨알의 승인 없이는 복제 및 재발급이 금지됩니다. No part of this document may be duplicated or reproduced by any means without the express written permission of the ICR.			
2019. 04. 04 주식회사 아이씨알 대표이사 The head of INTERNATIONAL CERTIFICATION REGISTRAR 			

본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

경기도 김포시 양촌읍 황금3로7번길 112

112, Hwanggeum3-ro 7beon-gil, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea



Contents

1. Applicant & Manufacturer & Test Laboratory Information	4
1.1 Applicant information	4
1.2 Manufacturer Information	4
1.3 Test Laboratory Information	4
2. Equipment under Test(EUT) Information	5
2.1 General Information	5
2.2 Additional Information	5
2.3 Mode of operation during the test	5
2.4 Modifications of EUT	5
3. Test Summary	6
3.1 Test standards and results	6
3.2 Purpose of the test	6
3.3 Test Methodology	6
3.4 Configuration of Test System	6
3.5 Antenna requirement	7
4. Used equipment on test	8
5. 6 dB Bandwidth	9
5.1 Operating environment	9
5.2 Measurement method	9
5.3 Test setup	9
5.4 Test data	10
6. Maximum Conducted Output Power	12
6.1 Operating environment	12
6.2 Measurement method	12
6.3 Test setup	12
6.4 Test data	13
7. Power Spectral Density	15
7.1 Operating environment	15
7.2 Measurement method	15
7.3 Test setup	15
7.4 Test data	16
8. Conducted Spurious Emission	18
8.1 Operating environment	18
8.2 Measurement method	18
8.3 Test setup	18
8.4 Test data	19
9. Radiated Spurious Emission	24
9.1 Operating environment	24
9.2 Measurement method	24
9.3 Test setup	24
9.4 Test data	26
10. Power Line Conducted Emission	31



페이지(page) : (3)/(총(Total) 33)

10.1 Operating environment	31
10.2 Measurement method	31
10.3 Test setup	31
10.4 Test data	32

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E190559-0A	04-Apr-2019	Initial Issue	All



1. Applicant & Manufacturer & Test Laboratory Information

1.1 Applicant information

Applicant	NEOPOP Inc.
Address	6-604, 229, Seokjeong-ro, Nam-gu, Incheon, Republic of Korea
Contact Person	Kim, Sang Tae
Telephone No.	+82-32-867-6589
Fax No.	+82-32-831-6589
E-mail	gkstg@nate.com

1.2 Manufacturer Information

Manufacturer	MiraeSMT
Address	102-401~405,506,507 22, Samjak-ro, Bucheon-si, Gyeonggi-do, Republic of Korea

1.3 Test Laboratory Information

Conducted tests were performed at	
Laboratory	ICR Co., Ltd.
Address	112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
RRA No.	KR0165
KOLAS No.	KT652



2. Equipment under Test(EUT) Information

2.1 General Information

Product Name	NEOPOP Inc.
Brand Name	-
Model Name	Pet Band 2.0
Additional Model Name	-
FCC ID	2ASR5PETBAND2
Hardware Version	
Software Version	-
Power Supply	DC 3.7 V

2.2 Additional Information

Equipment Class	DTS-Digital Transmission System
Device Type	Stand-alone
Operating Frequency	2 402 MHz ~ 2 480 MHz
RF Output Power	-17.34 dBm
Number of Channel	40
Modulation Type	GFSK
Antenna Type	Chip Antenna
Antenna Gain	2.3 dBi
Antenna Operating Mode	Single Antenna Equipment with only one antenna
List of Each Oscillator or Crystal Frequency	16 MHz

2.3 Mode of operation during the test

- The EUT is continuous transmission mode during the test with set at Low Channel, Middle Channel, and High Channel. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, YZ, XZ planes.

2.4 Modifications of EUT

- None



3. Test Summary

3.1 Test standards and results

FCC Part 15 Subpart C			
Clause	Test items	Applied	Results
§15.247 (a) (1)	6 dB Bandwidth	☒	PASS
§15.247 (b) (3)	Maximum Conducted Output Power	☒	PASS
§15.247 (e)	Power Spectral Density	☒	PASS
§15.247 (d)	Conducted Spurious Emission	☒	PASS
§15.247 (d) & §15.209 & §15.205	Radiated Spurious Emission	☒	PASS
§15.207	Power Line Conducted Emission	☒	PASS
§15.203	Antenna Requirement	☒	PASS

3.2 Purpose of the test

- To determine whether the equipment under test fulfills the requirements of the standards stated in FCC Part 15 Subpart C Section 15.247

3.3 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013.

Radiated testing was performed at a distance of 3 m from EUT to the antenna.

3.4 Configuration of Test System

3.4.1 Radiated emission test

Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber. The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

3.4.2 AC powerline conducted emission test

The EUT was connected to LISN. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.



3.5 Antenna requirement

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.5.1 Result: Pass

The transmitter has a **Chip antenna**. The directional gain of the antenna is **2.3 dBi**.



4. Used equipment on test

	Description	Model Name	Serial Number	Manufacturer	Last Cal. (cycle)
☐	Spectrum analyzer	FSW85	100864	Rohde & Schwarz	2019. 03. 04 (1Y)
☒	Spectrum analyzer	FSV40	101455	Rohde & Schwarz	2018 .07. 10 (1Y)
☒	Signal Generator	SMB100A	180607	Rohde & Schwarz	2019. 03. 04 (1Y)
☐	Wideband Power Sensor	NRP-Z81	103673	Rohde & Schwarz	2019. 03. 05 (1Y)
☐	Open Switch and Control Platform	OSP150	101000	Rohde & Schwarz	2019. 03. 05 (1Y)
☐	Environmental Test Chamber	MHK-408NKDA	1060908	TERCHY	2019. 03. 04 (1Y)
☒	DC Power Supply	XDL 35-5P	J00385373	Sorensen	2019. 03. 05 (1Y)
☐	DC Power Supply	6603D	672483	Topward	2019. 03. 05 (1Y)
☒	Loop Antenna	HFH2-Z2	100506	Rohde & Schwarz	2017. 06. 19 (2Y)
☒	TRILOG BROADBAND ANTENNA	VULB9162	120	SCHWARZBECK	2018. 11. 23 (2Y)
☒	RF Pre Amplifier	SCU08	100747	Rohde & Schwarz	2018. 04. 17 (1Y)
☒	DOUBLE-RIDGE WAVEGUIDE HORN ANTENNA	HF907	102556	Rohde & Schwarz	2017. 07. 05 (2Y)
☒	RF Pre Amplifier	SCU18	102342	Rohde & Schwarz	2018. 04. 17 (1Y)
☒	Horn Antenna	LB-42-10-C-KF	J202024625	AINFO Inc.	2018. 04. 20 (2Y)
☒	RF Pre Amplifier	AMF-4F-18265-35-8P-1	771846	MITEQ	2019. 03. 04 (1Y)
☐	Horn Antenna	LB-28-10-C-KF	J202024627	AINFO Inc.	2018. 04. 20 (2Y)
☐	RF Pre Amplifier	AMF-4D-260400-45-6P	779919	MITEQ	2019. 03. 04 (1Y)
☒	EMI Test Receiver	ESR26	101461	Rohde & Schwarz	2018. 04. 17 (1Y)
☒	EMI Test Receiver	ESR3	102119	Rohde & Schwarz	2018. 04. 17 (1Y)
☒	LISN	ENV216	102194	Rohde & Schwarz	2018. 04. 16 (1Y)

※ All test equipment used is calibration on a regular basis.



5. 6 dB Bandwidth

5.1 Operating environment


Temperature : 22 °C
Relative humidity : 44 %

5.2 Measurement method

Standard : §15.247 (a) (2)

5.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz, and peak detection was used. The 6 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 6 dB.






5.4 Test data


Test date : 19. Feb. 2019
Operating mode : Transmit mode
Test Result : Pass

5.4.1 Measured Results


Modulation Type	Channel (Frequency)	Measured Value (kHz)	Limit (kHz)
Bluetooth LE	0 (2 402 MHz)	692.3	at least 500
	19 (2 440 MHz)	695.3	
	39 (2 480 MHz)	707.3	

5.4.2 Measured Graph





Mid CH



High CH



6. Maximum Conducted Output Power

6.1 Operating environment

Temperature : 22 °C


Relative humidity : 44 %

6.2 Measurement method

Standard : §15.247 (b) (3)

6.3 Test setup

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99 % bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.






6.4 Test data


Test date : 19. Feb. 2019
Operating mode : Transmit mode
Test Result : Pass

6.4.1 Measured Results


Modulation Type	Channel (Frequency)	Highest signal level (dBm)	Limit (dBm)
Bluetooth LE	0 (2 402 MHz)	-17.50	30 (1 Watt)
	19 (2 440 MHz)	-17.34	
	39 (2 480 MHz)	-17.99	

6.4.2 Measured Graph





Mid CH



High CH



7. Power Spectral Density

7.1 Operating environment


Temperature : 22 °C
Relative humidity : 44 %

7.2 Measurement method

Standard : §15.247 (e)

7.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 3 kHz, the video bandwidth is set to 3 times the resolution bandwidth.






7.4 Test data

Test date : 19. Feb. 2019
Operating mode : Transmit mode
Test Result : Pass

7.4.1 Measured Results


Modulation Type	Channel (Frequency)	Highest signal level (dBm)	Limit (dBm/3kHz)
Bluetooth LE	0 (2 402 MHz)	-29.73	8
	19 (2 440 MHz)	-29.21	
	39 (2 480 MHz)	-29.49	

7.4.2 Measured Graph






페이지(page) : (17) / (총(Total) 33)



Mid CH



High CH



8. Conducted Spurious Emission

8.1 Operating environment

Temperature : 22 °C


Relative humidity : 44 %

8.2 Measurement method

Standard : §15.247 (d)

8.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.







8.4 Test data

Test date : 19. Feb. 2019
Operating mode : Transmit mode
Test Result : Pass


8.4.1 Measured Results

8.4.1.1 Signal level (dB m)






Mid CH




High CH




8.4.1.2 Unwanted Emissions In Non-Restricted Frequency Bands







8.4.1.3 Band Edge



9. Radiated Spurious Emission

9.1 Operating environment

Temperature : 23 °C
Relative humidity : 41 %

9.2 Measurement method


Standard : §15.247 (d), §15.209, §15.205

9.3 Test setup


The radiated emissions measurements were performed on the 3 m, Semi-Anechoic Chamber. The EUT was placed on a non-conductive turntable above the ground plane.

The frequency spectrum from 9 kHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.


9.3.1 Below 30 MHz



9.3.2 30 MHz to 1 GHz



9.3.3 Above 1 GHz





9.4 Test data

Test date : 22. Feb. 2019 ~ 22. Feb. 2019
 Operating mode : Transmit mode
 Test Result : Pass

9.4.1 Test data for Restricted band

Frequency (MHz)	Reading (dBμV)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low CH							
2 332.23	59.81	Peak	V	-10.0	49.81	73.98	36.34
	40.65	Average	V		30.65	53.98	29.44
High CH							
2 483.50	56.09	Peak	H	-9.6	48.57	73.98	28.49
	34.06	Average	H		30.63	53.98	30.52

※ Ant. Pol. : Antenna Polarization

※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain

※ Result = Reading + Corr. Factor

※ Margin = Result - Limit

9.4.2 Test data for Spurious & Harmonic

9.4.2.1 Measurement Results for below 30 MHz

Frequency (MHz)	Reading (dB μ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
Low CH							
It was not found any emissions peaks found from the EUT.							
Mid CH							
It was not found any emissions peaks found from the EUT.							
High CH							
It was not found any emissions peaks found from the EUT.							

※ Ant. Pol. : Antenna Polarization


※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain

※ Result = Reading + Corr. Factor

※ Margin = Result - Limit




9.4.2.2 Measurement Results for below 1 GHz




Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
32.910000	27.41	40.00	12.59	200.3	H	164.0	-24.9
33.516250	27.61	40.00	12.39	99.7	V	77.0	-24.7
47.884375	37.57	40.00	2.43	99.7	V	77.0	-21.1
115.178125	22.86	43.50	20.64	200.1	V	357.0	-24.2
240.005000	29.98	46.00	16.02	99.8	H	46.0	-22.1
382.473750	32.12	46.00	13.88	99.8	H	355.0	-18.2

Low CH



Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
33.031250	26.51	40.00	13.49	99.8	V	86.0	-24.9
47.884375	37.71	40.00	2.29	99.8	V	112.0	-21.1
61.403750	23.64	40.00	16.36	99.8	V	112.0	-22.7
116.269375	24.29	43.50	19.21	99.8	V	13.0	-24.4
191.141250	26.67	43.50	16.83	99.8	H	27.0	-24.4
382.473750	33.05	46.00	12.95	99.8	H	0.0	-18.2

Mid CH



Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
38.911875	27.25	40.00	12.75	99.8	V	337.0	-22.5
48.005625	36.25	40.00	3.75	99.8	V	102.0	-21.1
60.555000	22.03	40.00	17.97	99.8	V	39.0	-22.5
86.926875	21.21	40.00	18.79	99.8	V	89.0	-26.0
115.905625	25.30	43.50	18.20	99.8	V	218.0	-24.4
648.071875	22.32	46.00	23.68	99.8	V	192.0	-13.5

High CH



9.4.2.3 Measurement Results for Above 1 GHz

Frequency (MHz)	Reading (dBμV)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low CH							
4 805.34	68.27	Peak	V	-2.2	66.07	73.98	7.91
	53.34	Average	V		51.14	53.98	2.84
Mid CH							
4 881.69	66.13	Peak	V	-1.9	64.23	73.98	9.75
	51.66	Average	V		49.76	53.98	4.22
High CH							
4 961.50	66.14	Peak	V	-1.7	64.44	73.98	9.54
	48.02	Average	V		46.32	53.98	7.66

※ Ant. Pol. : Antenna Polarization

※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain

※ Result = Reading + Corr. Factor

※ Margin = Result - Limit



10. Power Line Conducted Emission

10.1 Operating environment

Temperature : 23 °C


Relative humidity : 43 %

10.2 Measurement method

Standard : §15.207

10.3 Test setup

The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a $50\ \Omega$ / $50\ \mu\text{H}$ + $5\ \Omega$ Artificial Mains Network (AMN). The ground plane was electrically bonded to the reference ground system and all power lines were filtered from ambient.






10.4 Test data

Test date : 25. Feb. 2019
 Operating mode : Transmit mode
 Test Result : Pass

10.4.1 Measured Results & Graph

Live line




Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.183750	---	45.91	54.31	8.41	1000.0	9.000	L1	ON	9.9
0.183750	56.44	---	64.31	7.88	1000.0	9.000	L1	ON	9.9
0.483000	---	33.91	46.29	12.37	1000.0	9.000	L1	ON	9.9
0.483000	45.61	---	56.29	10.67	1000.0	9.000	L1	ON	9.9
1.567500	---	33.62	46.00	12.38	1000.0	9.000	L1	ON	9.7
1.567500	45.15	---	56.00	10.85	1000.0	9.000	L1	ON	9.7
3.921000	---	33.32	46.00	12.68	1000.0	9.000	L1	ON	9.8
3.921000	42.38	---	56.00	13.62	1000.0	9.000	L1	ON	9.8
12.455250	---	35.19	50.00	14.81	1000.0	9.000	L1	ON	10.0
12.455250	42.00	---	60.00	18.00	1000.0	9.000	L1	ON	10.0
21.111000	---	29.19	50.00	20.81	1000.0	9.000	L1	ON	10.0
21.111000	37.72	---	60.00	22.28	1000.0	9.000	L1	ON	10.0



Neutral line



Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.170250	---	39.36	54.95	15.59	1000.0	9.000	N	ON	10.0
0.170250	54.35	---	64.95	10.60	1000.0	9.000	N	ON	10.0
0.224250	---	24.16	52.66	28.50	1000.0	9.000	N	ON	9.7
0.224250	42.74	---	62.66	19.92	1000.0	9.000	N	ON	9.7
0.485250	---	34.80	46.25	11.45	1000.0	9.000	N	ON	9.9
0.485250	45.28	---	56.25	10.97	1000.0	9.000	N	ON	9.9
0.935250	---	31.48	46.00	14.52	1000.0	9.000	N	ON	9.8
0.935250	42.89	---	56.00	13.12	1000.0	9.000	N	ON	9.8
3.745500	---	33.76	46.00	12.24	1000.0	9.000	N	ON	9.8
3.745500	41.62	---	56.00	14.38	1000.0	9.000	N	ON	9.8
5.826750	---	35.71	50.00	14.29	1000.0	9.000	N	ON	9.8
5.826750	42.59	---	60.00	17.41	1000.0	9.000	N	ON	9.8