

FCC TEST REPORT

For

Electronic thermometer

**Model Number: RIT-P02-MED, RIT-P02-RR, RIT-P02-RS, RIT-P02-MM,
RIT-P02-R1**

FCC ID: 2ASVA-RIT-P02

Report Number : WT198001431

Test Laboratory : Shenzhen Academy of Metrology and Quality Inspection
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China
Tel : 0086-755-86928965
Fax : 0086-755-86009898-31396
Web : www.smq.com.cn
E-mail : emcrf@smq.com.cn

TEST REPORT DECLARATION

Applicant : Shenzhen Refresh Intelligent Technology Co., Ltd.
Address : 83D302A,3rd FL, Tianjing BLDG, TianAn CheGongMiao In dustrial Pk, XiangMiHu, Futian DIST., Shenzhen, China
Manufacturer : Shenzhen Refresh Intelligent Technology Co., Ltd.
Address : 83D302A,3rd FL, Tianjing BLDG, TianAn CheGongMiao In dustrial Pk, XiangMiHu, Futian DIST., Shenzhen, China
EUT Description : Electronic thermometer
Model No. : RIT-P02-MED, RIT-P02-RR, RIT-P02-RS, RIT-P02-MM, RIT-P02-R1
Trade mark : Ritsigns
Serial Number : /
FCC ID : 2ASVA-RIT-P02

Test Standards:

FCC Part 15 Subpart B 15.107, 15.109 (2018)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.


Project Engineer:		Date: Sep.19, 2019
	(Zhou Fangai 周芳媛)	
Checked by:		Date: Sep.19, 2019
	(Lin Yixiang 林奕翔)	
Approved by:		Date: Sep.19, 2019
	(Lin Bin 林斌)	

TABLE OF CONTENTS

TEST REPORT DECLARATION.....	2
1. TEST RESULTS SUMMARY.....	4
2. GENERAL INFORMATION.....	5
2.1. Report information.....	5
2.2. Laboratory Accreditation and Relationship to Customer	5
2.3. Measurement Uncertainty	5
3. PRODUCT DESCRIPTION.....	6
3.1. EUT Description	6
3.2. Block Diagram of EUT Configuration	6
3.3. Operating Condition of EUT	7
3.4. Support Equipment List.....	7
3.5. Test Conditions	7
3.6. Modifications	7
4. TEST EQUIPMENT USED.....	8
4.1. Test Equipment Used to Measure Radiated Emission.....	8
5. CONDUCTED EMISSION TEST.....	9
5.1. Test Standard and Limit	9
5.2. Test Procedure.....	9
5.3. Test Arrangement	9
5.4. Test Data.....	9
6. RADIATION EMISSION TEST.....	10
6.1. Test Standard and Limit	10
6.2. Test Procedure.....	10
6.3. Test Arrangement	10
6.4. Test Data.....	11

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
Conducted Emission	15.107	N/A
Radiation Emission	15.109	Pass

Remark: "N/A" means "Not applicable."

2. GENERAL INFORMATION

2.1. Report information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

2.3. Measurement Uncertainty

Conducted Emission
9 kHz~30MHz 2.9dB

Radiated Emission
30MHz~1000MHz 5.1dB
1GHz~6GHz 5.04dB
6GHz~18GHz 5.54dB

3. PRODUCT DESCRIPTION


3.1. EUT Description

Table 2 Specification of the Equipment under Test

Product Type:	Electronic thermometer
Hardware Version:	V2.0
Software Version :	V2.0
FCC-ID:	2ASVA-RIT-P02
Frequency:	Bluetooth:2402MHz~2480MHz
Type(s) of Modulation:	Bluetooth: GFSK
Antenna Type:	BT: Internal antenna 0dBi
Operating voltage:	Button cell:2.0V (Low)/3.0V (Nominal)/ 3.6V (Max)

Remark: All of the model's circuit theory, electrical design and the Critical Components are identical only except the color and appearance. The differences do not affect the EMC performance .Unless otherwise specified; the model RIT-P02-MED was chose to perform all the tests.

3.2. Block Diagram of EUT Configuration



Test mode 1

3.3. Operating Condition of EUT

Test mode 1: Connect Bluetooth to measure temperature through app

The test mode mentioned above is identified as worst case for this EUT and the test results for this mode are recorded in this report.

The Radiated emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane).

3.4. Support Equipment List

Table 3 Support Equipment List

Name	Model No	S/N	Manufacturer
Phone	Iphone 7Plus	--	Apple

3.5. Test Conditions

Date of test : Aug.23, 2019- Aug.27, 2019

Date of EUT Receive : Mar.18, 2019

Temperature: 21°C-24°C

Relative Humidity: 50%-52%

3.6. Modifications

No modification was made.

4. TEST EQUIPMENT USED

4.1. Test Equipment Used to Measure Radiated Emission

Table 4 Radiated Emission Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB3436	Test Receiver	R&S	ESI26	Nov.19,2018	1 Year
SB3955	Broadband Antenna	Schwarzbeck	VULB9163	May.31,2019	1 Year
SB84501/09	Test Receiver	R&S	ESU40	Mar.11,2019	1 Year
SB3435	Horn Antenna	R&S	HF906	Jan.01,2019	1 Year
SB8501/16	Pre-Amplifier	R&S	SCU 26	Feb.18,2019	1 Year
SB9058/03	Pre-Amplifier	R&S	SCU 18	Feb.18,2019	1 Year
SB9059	Pre-Amplifier	R&S	SCU 40	Aug.27,2019	1 Year
SB8501/11	Horn Antenna	R&S	3160-09	Mar.21,2017	3 Years
SB8501/12	Horn Antenna	R&S	3160-10	Mar.21,2017	3 Years

5. CONDUCTED EMISSION TEST

5.1. Test Standard and Limit

5.1.1. Test Standard

FCC Part 15: Section 15.107

5.1.2. Test Limit

Table 5 Conducted Emission Test Limit (Class B)

Frequency	Power Port limits (dB μ V)	
	Quasi-peak	Average
0.15MHz ~ 0.5MHz	66~56*	56~46*
0.5MHz ~ 5 MHz	56	46
5 MHz ~ 30MHz	60	50

* Decreasing linearly with logarithm of the frequency

5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver is used to test the emissions from both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

5.4. Test Data

The EUT is powered by button cell, so this item is not applicable.

6. RADIATION EMISSION TEST

6.1. Test Standard and Limit

6.1.1. Test Standard

FCC Part 15: Section 15.109

6.1.2. Test Limit

Table 6 Radiation Emission Test Limit for FCC (Class B) (9 kHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Table 7 Radiation Emission Test Limit for FCC (Class B) (Above 1G)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

* The lower limit shall apply at the transition frequency.

* The test distance is 3m.

6.2. Test Procedure

The EUT is placed on a turntable, which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set **3 meters** away from the receiving antenna, which is mounted on an antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test.

RBW = 100 kHz (less than or equal to 1 GHz); 1 MHz (above 1 GHz)

VBW \geq 3 x RBW

Detector = Peak & Quasi-Peak (frequency range 30 MHz to 1 GHz);

Peak & Average (frequency range above 1 GHz);

Changing VBW to 10 Hz for average measurement

The use of a higher-than-specified video bandwidth produces a conservative measurement result.

6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in

a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

6.4. Test Data

The emissions don't show in following result tables are more than 20dB below the limits, the test curves are shown in the next page.

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result

which was 20dB lower than the limit line per 15.31(o) was not reported.


Table 8 Radiated Emission Test Data

Model No.: RIT-P02-MED Test mode: 1								
Frequency (MHz)	Cable Loss +preamp (dB)	Antenna Factor (dB)	Reading (dB μ V/m)	Level (dB μ V/m)	Polarity (H/V)	Limit (dB μ V/m)	Margin (dB)	Note
32.767	0.7	12.3	-2.8	10.2	H	40	29.8	QP
37.621	0.6	12.3	-3.1	9.8	H	40	30.2	QP
45.205	0.8	13.6	-5.4	9.0	H	40	31.0	QP
60.537	1.0	12.7	-5.5	8.2	H	40	31.8	QP
100.523	1.1	13.2	-4.9	9.4	H	43.5	34.1	QP
585.674	3.0	16.6	-3.1	16.5	H	46	29.5	QP
31.625	0.6	12.3	-2.3	10.6	V	40	29.4	QP
36.097	0.6	12.3	-2.8	10.1	V	40	29.9	QP
41.515	0.7	13.6	-3.9	10.4	V	40	29.6	QP
56.754	0.8	13.0	-4.5	9.3	V	40	30.7	QP
99.975	1.1	12.8	-4.9	9.0	V	43.5	34.5	QP
617.757	3.1	18.5	-7.9	13.7	V	46	32.3	QP
17980.500	-32.8	43.3	50.2	60.7	V	74	13.3	PK
17898.000	-32.5	43.3	49.4	60.2	H	74	13.8	PK
17980.500	-32.8	43.3	36.4	46.9	V	54	7.1	AV
17898.000	-32.5	43.3	35.6	46.4	H	54	7.6	AV


Emission level (dB μ V)=Read Value(dB μ V/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)

Radiated Emission

EUT Name: RIT-P02-MED
Operating Condition: Test Mode 1
Test site: SMQ NETC EMC Lab.3m Chamber
Antenna Position: Horizontal & Vertical
Comment:




(Horizontal)




(Vertical)

Radiated Emission

EUT Name: RIT-P02-MED
Operating Condition: Test Mode 1
Test site: SMQ NETC EMC Lab.3m Chamber
Antenna Position: Vertical & Horizontal
Comment:



(Horizontal)



(Vertical)

-----End of Report-----