
FCC ID: 2ASWF-1689

Stand alone device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: PCB Antenna


Antenna Gain: -0.68 dBi

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-6.50	0.224	-7±1	-6.0	0.251	<5	0.07786	3.00	YES
	2.441	-6.80	0.209	-7±1	-6.0	0.251	<5	0.07849	3.00	YES
	2.480	-7.84	0.164	-7±1	-6.0	0.251	<5	0.07911	3.00	YES
$\pi/4$ -DQPSK	2.402	-5.36	0.291	-6±1	-5.0	0.316	<5	0.09802	3.00	YES
	2.441	-5.66	0.272	-6±1	-5.0	0.316	<5	0.09881	3.00	YES
	2.480	-6.72	0.213	-6±1	-5.0	0.316	<5	0.09960	3.00	YES

Conclusion:

For the max result: $0.09881 \leq 3.0$ for 1-g SAR, No SAR is required.

Signature:



Date: 2019/4/20

NAME AND TITLE (Please print or type): Murphy.Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China