



TEST REPORT

Report Reference No. : CHTEW19060148 Report verification: 

Project No. : SHT1905024403EW

FCC ID : 2ASWWCORN4

Applicant's name : XINCHUANGXIN INTERNATIONAL CO.,LTD

Address : ROOM 605 6/F, FA YUEN COMMERCIAL BUILDING, 75-77 FA YUEN STREET MONGKOK KL

Manufacturer : Shenzhen Chiteng Technology Co.,Ltd

Address : Second Floor, Area A, Building 4, Huiye Technology Workshop, Guangang Road, Tangjia Community, Gongming Street, Guangming New District, Shenzhen, Guangdong

Test item description : Smart phone

Trade Mark : CORN

Model/Type reference : C4

Listed Model(s) : -

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample : May 31, 2019

Date of testing : Jun 01, 2019- Jun 20, 2019

Date of issue : Jun 21, 2019

Result : PASS

Compiled by
(position+printedname+signature).... : File administrators Silvia Li

Supervised by
(position+printedname+signature).... : Project Engineer Aaron Fang

Approved by
(position+printedname+signature).... : RF Manager Hans Hu

Silvia Li

Aaron Fang

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	22
5.6.	Restricted band	28
5.7.	Band edge and Spurious Emissions (conducted)	33
5.8.	Spurious Emissions (radiated)	50
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>57</u>
<u>7.</u>	<u>EXTERANAL AND INTERNAL PHOTOS</u>	<u>58</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-06-21	Original

2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	PASS	JiongSheng.Feng
Line Conducted Emissions (AC Main)	15.207	PASS	Bruse.Li
Conducted Peak Output Power	15.247(b)(3)	PASS	JiongSheng.Feng
Power Spectral Density	15.247(e)	PASS	JiongSheng.Feng
6dB Bandwidth	15.247(a)(2)	PASS	JiongSheng.Feng
Restricted band	15.247(d)/15.205	PASS	JiongSheng.Feng
Spurious Emissions	15.247(d)/15.209	PASS	JiongSheng.Feng

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	XINCHUANGXIN INTERNATIONAL CO.,LTD
Address:	ROOM 605 6/F, FA YUEN COMMERCIAL BUILDING, 75-77 FA YUEN STREET MONGKOK KL
Manufacturer:	Shenzhen Chiteng Technology Co.,Ltd
Address:	Second Floor, Area A, Building 4, Huiye Technology Workshop, Guanguang Road, Tangjia Community, Gongming Street,Guangming New District, Shenzhen, Guangdong

3.2. Product Description

Name of EUT:	Smart phone
Trade Mark:	CORN
Model No.:	C4
Listed Model(s):	-
Power supply:	DC 3.7V
Adapter information:	Model:CS001 Input:100-240Va.c., 50/60Hz, 0.15A Output:5.0Vd.c., 1.0A
Hardware version:	D8085D2_MB_V1.0
Software version:	D8085D2_S40302_81_B25_V01
WIFI	
Supported type:	802.11b/802.11g/802.11n(HT20)/802.11n(HT40)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	PIFA Antenna
Antenna gain:	1.2 dBi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	-
02	2417	02	-
03	2422	03	2422
04	2427	04	2427
05	2432	05	2432
06	2437	06	2437
07	2442	07	2442
08	2447	08	2447
09	2452	09	2452
10	2457	10	-
11	2462	11	-

➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Manufacturer:	/
		Model No.:	/
○	/	Manufacturer:	/
		Model No.:	/

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.51 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.51 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.02 dB	(1)
Radiated Emissions below 1GHz	4.90 dB	(1)
Radiated Emissions above 1GHz	4.96 dB	(1)
Occupied Bandwidth	70 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

● Conducted Emission						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	ESCI	101247	2018/10/27	2019/10/26
●	Artificial Mains	SCHWARZBECK	NNLK 8121	573	2018/10/27	2019/10/26
●	Pulse Limiter	R&S	ESH3-Z2	100499	2018/10/27	2019/10/26
●	RF Connection Cable	HUBER+SUHNER	EF400	N/A	2018/11/15	2019/11/14
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
○	Single Balanced Telecom Pair ISN	FCC	FCC-TLISN-T2-02	20371	2018/10/28	2019/10/27
○	Two Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T4-02	20373	2018/10/28	2019/10/27
○	Four Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T8-02	20375	2018/10/28	2019/10/27
○	V-Network	R&S	ESH3-Z6	100211	2018/10/27	2019/10/26
○	V-Network	R&S	ESH3-Z6	100210	2018/10/27	2019/10/26
○	2-Line V-Network	R&S	ESH3-Z5	100049	2018/10/27	2019/10/26

● Radiated Emission-6th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-02	N/A	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	ESCI	100900	2018/10/28	2019/10/27
●	Loop Antenna	R&S	HFH2-Z2	100020	2017/11/20	2020/11/19
●	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	BBV 9742	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	N/A	N/A	2018/09/28	2019/09/27
●	RF Connection Cable	HUBER+SUHNER	SUCOFLEX104	501184/4	2018/09/28	2019/09/27
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

● Radiated emission-7th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-01	N/A	2018/09/30	2021/09/29
●	Spectrum Analyzer	R&S	FSP40	100597	2018/10/27	2019/10/26
●	Horn Antenna	SCHWARZBECK	9120D	1011	2017/03/27	2020/03/26
●	Pre-amplifier	BONN	BLWA0160-2M	1811887	2018/11/14	2019/11/13
●	Pre-amplifier	CD	PAP-0102	12004	2018/11/14	2019/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	2019/04/26	2020/04/25
●	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	2018/11/15	2019/11/14
●	Test Software	Audix	E3	N/A	N/A	N/A

●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

● **RF Conducted Method**

Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2018/10/28	2019/10/27
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2018/09/29	2019/09/28
●	OSP	R&S	OSP120	101317	N/A	N/A
○	Radio communication tester	R&S	CMW500	137688-Lv	2018/09/29	2019/09/28
○	Test software	Tonscend	JS1120-1(LTE)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-2(WIFI)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-3(WCDMA)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-4(GSM)	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

REQUIREMENT:

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L

**MEASUREMENT RESULT: "GM1906185063_fin"**

6/18/2019 9:03PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	52.80	9.9	66	13.2	QP	L1	GND
0.375000	42.00	9.9	58	16.4	QP	L1	GND
0.456000	47.00	9.9	57	9.8	QP	L1	GND
0.609000	45.80	9.9	56	10.2	QP	L1	GND
0.906000	42.70	9.9	56	13.3	QP	L1	GND
2.125500	42.10	9.9	56	13.9	QP	L1	GND


MEASUREMENT RESULT: "GM1906185063_fin2"

6/18/2019 9:03PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	43.20	9.9	56	12.8	AV	L1	GND
0.379500	38.00	9.9	48	10.3	AV	L1	GND
0.456000	41.00	9.9	47	5.8	AV	L1	GND
0.604500	39.40	9.9	46	6.6	AV	L1	GND
0.681000	40.70	9.9	46	5.3	AV	L1	GND
0.910500	38.60	9.9	46	7.4	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1906185064_fin"**

6/18/2019 9:05PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	51.90	9.9	66	14.1	QP	N	GND
0.226500	46.70	9.9	63	15.9	QP	N	GND
0.451500	43.60	9.9	57	13.2	QP	N	GND
1.059000	42.50	9.9	56	13.5	QP	N	GND
2.346000	34.30	10.0	56	21.7	QP	N	GND
5.379000	31.30	10.0	60	28.7	QP	N	GND

MEASUREMENT RESULT: "GM1906185064_fin2"

6/18/2019 9:05PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	41.80	9.9	56	14.2	AV	N	GND
0.681000	32.60	9.9	46	13.4	AV	N	GND
1.063500	27.90	9.9	46	18.1	AV	N	GND
2.193000	23.30	10.0	46	22.7	AV	N	GND
5.680500	19.20	10.0	50	30.8	AV	N	GND
20.809500	20.60	10.2	50	29.4	AV	N	GND

5.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


Type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
802.11b	01	19.29	16.61	≤30.00	Pass
	06	19.09	16.75		
	11	19.55	17.08		
802.11g	01	22.27	19.18	≤30.00	Pass
	06	21.72	18.57		
	11	22.07	18.88		
802.11n(HT20)	01	22.31	18.78	≤30.00	Pass
	06	22.25	18.61		
	11	22.79	19.48		
802.11n(HT40)	03	21.29	18.56	≤30.00	Pass
	06	21.87	18.20		
	09	21.53	18.35		

5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:


Please refer to the clause 3.3


TEST RESULTS


☒ Passed ☐ Not Applicable

Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	0.11	≤8.00	Pass
	06	0.41		
	11	0.88		
802.11g	01	-2.22	≤8.00	Pass
	06	-2.63		
	11	-1.87		
802.11n(HT20)	01	-2.54	≤8.00	Pass
	06	-1.16		
	11	-1.56		
802.11n(HT40)	03	-7.29	≤8.00	Pass
	06	-6.18		
	09	-6.76		

Test plot as follows:








5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span = 2 × DTS bandwidth
RBW = 100 kHz, VBW ≥ 3 × RBW
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:


Please refer to the clause 3.3


TEST RESULTS


☒ Passed ☐ Not Applicable


Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	9.18	≥500	Pass
	06	9.18		
	11	9.18		
802.11g	01	16.44	≥500	Pass
	06	16.41		
	11	16.41		
802.11n(HT20)	01	17.64	≥500	Pass
	06	17.64		
	11	17.64		
802.11n(HT40)	03	36.18	≥500	Pass
	06	36.24		
	09	36.48		

Test plot as follows:










5.6. Restricted band

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:
 RBW=1MHz, VBW=3MHz PEAK detector for Peak value.
 RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	13.86	28.05	7.73	0.00	49.64	74.00	-24.36	Vertical	Peak
2390.00	14.93	27.65	7.84	0.00	50.42	74.00	-23.58	Vertical	Peak
2310.00	13.78	28.05	7.73	0.00	49.56	74.00	-24.44	Horizontal	Peak
2390.00	13.23	27.65	7.84	0.00	48.72	74.00	-25.28	Horizontal	Peak
2310.00	10.81	28.05	7.73	0.00	46.59	54.00	-7.41	Vertical	Average
2390.00	10.72	27.65	7.84	0.00	46.21	54.00	-7.79	Vertical	Average
2310.00	10.85	28.05	7.73	0.00	46.63	54.00	-7.37	Horizontal	Average
2390.00	11.22	27.65	7.84	0.00	46.71	54.00	-7.29	Horizontal	Average

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	13.65	27.26	8.04	0.00	48.95	74.00	-25.05	Vertical	Peak
2500.00	13.75	27.20	8.08	0.00	49.03	74.00	-24.97	Vertical	Peak
2483.50	13.63	27.26	8.04	0.00	48.93	74.00	-25.07	Horizontal	Peak
2500.00	14.24	27.20	8.08	0.00	49.52	74.00	-24.48	Horizontal	Peak
2483.50	10.72	27.26	8.04	0.00	46.02	54.00	-7.98	Vertical	Average
2500.00	10.52	27.20	8.08	0.00	45.80	54.00	-8.20	Vertical	Average
2483.50	10.98	27.26	8.04	0.00	46.28	54.00	-7.72	Horizontal	Average
2500.00	10.55	27.20	8.08	0.00	45.83	54.00	-8.17	Horizontal	Average

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	13.63	28.05	7.73	0.00	49.41	74.00	-24.59	Vertical	Peak
2390.00	14.49	27.65	7.84	0.00	49.98	74.00	-24.02	Vertical	Peak
2310.00	14.77	28.05	7.73	0.00	50.55	74.00	-23.45	Horizontal	Peak
2390.00	15.08	27.65	7.84	0.00	50.57	74.00	-23.43	Horizontal	Peak
2310.00	10.89	28.05	7.73	0.00	46.67	54.00	-7.33	Vertical	Average
2390.00	11.63	27.65	7.84	0.00	47.12	54.00	-6.88	Vertical	Average
2310.00	10.87	28.05	7.73	0.00	46.65	54.00	-7.35	Horizontal	Average
2390.00	12.97	27.65	7.84	0.00	48.46	54.00	-5.54	Horizontal	Average

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	14.83	27.26	8.04	0.00	50.13	74.00	-23.87	Vertical	Peak
2500.00	14.40	27.20	8.08	0.00	49.68	74.00	-24.32	Vertical	Peak
2483.50	17.35	27.26	8.04	0.00	52.65	74.00	-21.35	Horizontal	Peak
2500.00	13.80	27.20	8.08	0.00	49.08	74.00	-24.92	Horizontal	Peak
2483.50	12.52	27.26	8.04	0.00	47.82	54.00	-6.18	Vertical	Average
2500.00	10.96	27.20	8.08	0.00	46.24	54.00	-7.76	Vertical	Average
2483.50	14.00	27.26	8.04	0.00	49.30	54.00	-4.70	Horizontal	Average
2500.00	11.21	27.20	8.08	0.00	46.49	54.00	-7.51	Horizontal	Average

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	13.50	28.05	7.73	0.00	49.28	74.00	-24.72	Vertical	Peak
2390.00	14.31	27.65	7.84	0.00	49.80	74.00	-24.20	Vertical	Peak
2310.00	14.16	28.05	7.73	0.00	49.94	74.00	-24.06	Horizontal	Peak
2390.00	14.82	27.65	7.84	0.00	50.31	74.00	-23.69	Horizontal	Peak
2310.00	10.89	28.05	7.73	0.00	46.67	54.00	-7.33	Vertical	Average
2390.00	11.60	27.65	7.84	0.00	47.09	54.00	-6.91	Vertical	Average
2310.00	10.89	28.05	7.73	0.00	46.67	54.00	-7.33	Horizontal	Average
2390.00	12.15	27.65	7.84	0.00	47.64	54.00	-6.36	Horizontal	Average

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	19.13	27.26	8.04	0.00	54.43	74.00	-19.57	Vertical	Peak
2500.00	14.25	27.20	8.08	0.00	49.53	74.00	-24.47	Vertical	Peak
2483.50	19.25	27.26	8.04	0.00	54.55	74.00	-19.45	Horizontal	Peak
2500.00	12.38	27.20	8.08	0.00	47.66	74.00	-26.34	Horizontal	Peak
2483.50	13.11	27.26	8.04	0.00	48.41	54.00	-5.59	Vertical	Average
2500.00	10.99	27.20	8.08	0.00	46.27	54.00	-7.73	Vertical	Average
2483.50	14.35	27.26	8.04	0.00	49.65	54.00	-4.35	Horizontal	Average
2500.00	11.57	27.20	8.08	0.00	46.85	54.00	-7.15	Horizontal	Average

802.11n(HT40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.26	28.05	7.73	0.00	50.04	74.00	-23.96	Vertical	Peak
2390.00	13.30	27.65	7.84	0.00	48.79	74.00	-25.21	Vertical	Peak
2310.00	12.00	28.05	7.73	0.00	47.78	74.00	-26.22	Horizontal	Peak
2390.00	13.18	27.65	7.84	0.00	48.67	74.00	-25.33	Horizontal	Peak
2310.00	10.95	28.05	7.73	0.00	46.73	54.00	-7.27	Vertical	Average
2390.00	10.96	27.65	7.84	0.00	46.45	54.00	-7.55	Vertical	Average
2310.00	10.94	28.05	7.73	0.00	46.72	54.00	-7.28	Horizontal	Average
2390.00	12.90	27.65	7.84	0.00	48.39	54.00	-5.61	Horizontal	Average

802.11n(HT40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	16.49	27.26	8.04	0.00	51.79	74.00	-22.21	Vertical	Peak
2500.00	15.06	27.20	8.08	0.00	50.34	74.00	-23.66	Vertical	Peak
2483.50	18.30	27.26	8.04	0.00	53.60	74.00	-20.40	Horizontal	Peak
2500.00	15.80	27.20	8.08	0.00	51.08	74.00	-22.92	Horizontal	Peak
2483.50	13.92	27.26	8.04	0.00	49.22	54.00	-4.78	Vertical	Average
2500.00	12.87	27.20	8.08	0.00	48.15	54.00	-5.85	Vertical	Average
2483.50	15.53	27.26	8.04	0.00	50.83	54.00	-3.17	Horizontal	Average
2500.00	14.55	27.20	8.08	0.00	49.83	54.00	-4.17	Horizontal	Average


5.7. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure
Center frequency=DTS channel center frequency
The span = 1.5 times the DTS bandwidth.
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum PSD level


Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement
Set the center frequency and span to encompass frequency range to be measured
RBW = 100 kHz, VBW $\geq 3 \times$ RBW
Detector = peak, Sweep time = auto couple, Trace mode = max hold
Allow trace to fully stabilize
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.


TEST MODE:



Please refer to the clause 3.3

TEST RESULTS




☒ Passed ☐ Not Applicable






Test Item:	Bandedge	Type:	802.11n(HT20)																																										
CH01	MultiViewSpectrum Ref Level 22.00 dBm Offset 1.00 dB RBW 100 kHz ATT 30 dB SWI 1.12 ms VBW 300 kHz Mode Auto Sweep Count 200/200 1 Frequency Sweep  2 Marker Table <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.40908 GHz</td><td>0.81 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-33.65 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-41.66 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-60.70 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.397024 GHz</td><td>-32.93 dBm</td><td></td><td></td></tr></tbody></table> Date: 14_JUN 2019 15:24:14			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.40908 GHz	0.81 dBm			M2	1		2.4 GHz	-33.65 dBm			M3	1		2.39 GHz	-41.66 dBm			M4	1		2.31 GHz	-60.70 dBm			M5	1		2.397024 GHz	-32.93 dBm		
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.40908 GHz	0.81 dBm																																									
M2	1		2.4 GHz	-33.65 dBm																																									
M3	1		2.39 GHz	-41.66 dBm																																									
M4	1		2.31 GHz	-60.70 dBm																																									
M5	1		2.397024 GHz	-32.93 dBm																																									
CH11	MultiViewSpectrum Ref Level 22.00 dBm Offset 1.00 dB RBW 100 kHz ATT 30 dB SWI 1.03 ms VBW 300 kHz Mode Auto Sweep Count 300/300 1 Frequency Sweep  2 Marker Table <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.461375 GHz</td><td>1.74 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-34.60 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-49.56 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.483584 GHz</td><td>-34.23 dBm</td><td></td><td></td></tr></tbody></table> Date: 14_JUN 2019 15:28:16			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.461375 GHz	1.74 dBm			M2	1		2.4835 GHz	-34.60 dBm			M3	1		2.5 GHz	-49.56 dBm			M4	1		2.483584 GHz	-34.23 dBm									
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.461375 GHz	1.74 dBm																																									
M2	1		2.4835 GHz	-34.60 dBm																																									
M3	1		2.5 GHz	-49.56 dBm																																									
M4	1		2.483584 GHz	-34.23 dBm																																									


Test Item:	Bandedge	Type:	802.11n(HT40)																																										
CH03	MultiView Spectrum Ref Level 22.00 dBm Offset 1.00 dB BW 100 kHz ATT 30 dB SWI 1.00 ms VBW 300 kHz Mode Auto Sweep Count 200/200 1 Frequency Sweep 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] -3.42 dBm M2[1] -42.05 dBm M1 -23.420 dBm 2.31 GHz 1001 pts 13.2 MHz/ 2.442 GHz 2 Marker Table <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.42413 GHz</td><td>-3.42 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-42.05 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-45.21 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-60.24 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399364 GHz</td><td>-40.26 dBm</td><td></td><td></td></tr></table> Date: 14_JUN 2019 15:29:37			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.42413 GHz	-3.42 dBm			M2	1		2.4 GHz	-42.05 dBm			M3	1		2.39 GHz	-45.21 dBm			M4	1		2.31 GHz	-60.24 dBm			M5	1		2.399364 GHz	-40.26 dBm		
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.42413 GHz	-3.42 dBm																																									
M2	1		2.4 GHz	-42.05 dBm																																									
M3	1		2.39 GHz	-45.21 dBm																																									
M4	1		2.31 GHz	-60.24 dBm																																									
M5	1		2.399364 GHz	-40.26 dBm																																									
CH09	MultiView Spectrum Ref Level 22.00 dBm Offset 1.00 dB BW 100 kHz ATT 30 dB SWI 1.1 ms VBW 300 kHz Mode Auto Sweep Count 300/300 1 Frequency Sweep 20 dBm 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] -3.03 dBm M2[1] -36.75 dBm M1 -23.030 dBm 2.432 GHz 1001 pts 6.8 MHz/ 2.5 GHz 2 Marker Table <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.455335 GHz</td><td>-3.03 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-36.75 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-39.83 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.48572 GHz</td><td>-35.91 dBm</td><td></td><td></td></tr></table> Date: 14_JUN 2019 15:36:37			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.455335 GHz	-3.03 dBm			M2	1		2.4835 GHz	-36.75 dBm			M3	1		2.5 GHz	-39.83 dBm			M4	1		2.48572 GHz	-35.91 dBm									
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.455335 GHz	-3.03 dBm																																									
M2	1		2.4835 GHz	-36.75 dBm																																									
M3	1		2.5 GHz	-39.83 dBm																																									
M4	1		2.48572 GHz	-35.91 dBm																																									

Test Item:	SE	Type:	802.11b
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference level






CH11
30MHz~1000MHz




CH11
1GHz~26GHz




Test Item:	SE	Type:	802.11g
CH01 Reference level	MultiviewSpectrum Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SW 1.04 ms VBW 300 kHz Mode Auto Sweep Count 100/100 1 Frequency Sweep MI[1] 1.00 dBm 2.4105010 GHz  CF 2.412 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 14 JUN 2019 16:41:49		
CH01 30MHz~1000MHz	MultiviewSpectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SW 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 1 Frequency Sweep MI[1] -60.46 dBm 462.2950 MHz  30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 14 JUN 2019 16:42:11		
CH01 1GHz~26GHz	MultiviewSpectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SW 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 1 Frequency Sweep MI[1] -51.16 dBm 25.992500 GHz  1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 14 JUN 2019 16:43:13		


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference level






CH11
30MHz~1000MHz




CH11
1GHz~26GHz




Test Item:	SE	Type:	802.11n(HT20)
CH01 Reference level	 Date: 14 JUN 2019 16:49:33		
CH01 30MHz~1000MHz	 Date: 14 JUN 2019 16:49:56		
CH01 1GHz~26GHz	 Date: 14 JUN 2019 16:50:19		


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH11
Reference level






CH11
30MHz~1000MHz




CH11
1GHz~26GHz




Test Item:	SE	Type:	802.11n(HT40)
CH03 Reference level	 Ref Level 30.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWI 1.07 ms VBW 300 kHz Mode Auto Sweep Count 100/100 M1[1] -3.06 dBm 2.4244580 GHz CF 2.422 GHz 1001 pts 6.0 MHz/ Span 60.0 MHz Date: 14 JUN 2019 16:55:40		
CH03 30MHz~1000MHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWI 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] -60.63 dBm 56.4680 MHz 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 14 JUN 2019 16:56:03		
CH03 1GHz~26GHz	 Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWI 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] -52.27 dBm 25.954167 GHz 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 14 JUN 2019 16:56:45		


CH06
Reference level




CH06
30MHz~1000MHz




CH06
1GHz~26GHz




CH09
Reference level



CH09
30MHz~1000MHz



CH09
1GHz~26GHz



5.8. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ 9kHz ~30MHz



➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note:

- 1) Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**

The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.


➤ **30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

➤ 30MHz ~ 1GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1906126057_red"**

6/12/2019 2:50PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	25.20	-9.4	40.0	14.8	QP	100.0	0.00	VERTICAL
66.860000	21.40	-8.1	40.0	18.6	QP	100.0	78.00	VERTICAL
156.100000	33.20	-9.8	43.5	10.3	QP	100.0	13.00	VERTICAL
179.380000	23.70	-8.5	43.5	19.8	QP	100.0	66.00	VERTICAL
536.340000	30.50	2.7	46.0	15.5	QP	100.0	0.00	VERTICAL
957.320000	38.90	10.9	46.0	7.1	QP	100.0	13.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1906126058_red"**

6/12/2019 2:53PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
49.400000	23.20	-4.8	40.0	16.8	QP	300.0	146.00	HORIZONTAL
57.160000	21.70	-5.5	40.0	18.3	QP	100.0	238.00	HORIZONTAL
158.040000	27.10	-9.7	43.5	16.4	QP	100.0	301.00	HORIZONTAL
173.560000	24.20	-9.0	43.5	19.3	QP	100.0	238.00	HORIZONTAL
315.180000	33.40	-3.1	46.0	12.6	QP	100.0	57.00	HORIZONTAL
904.940000	38.50	10.5	46.0	7.5	QP	100.0	6.00	HORIZONTAL

➤ 1 GHz ~ 25 GHz

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3616.45	42.38	29.30	10.00	37.87	43.81	74.00	-30.19	Vertical	Peak
4821.76	34.49	31.56	11.73	36.25	41.53	74.00	-32.47	Vertical	Peak
7245.81	34.24	36.25	14.53	34.76	50.26	74.00	-23.74	Vertical	Peak
8703.29	31.63	37.89	15.95	34.64	50.83	74.00	-23.17	Vertical	Peak
3616.45	42.20	29.30	10.00	37.87	43.63	74.00	-30.37	Horizontal	Peak
4821.76	34.89	31.56	11.73	36.25	41.93	74.00	-32.07	Horizontal	Peak
7245.81	32.90	36.25	14.53	34.76	48.92	74.00	-25.08	Horizontal	Peak
8462.98	32.39	36.79	15.89	34.28	50.79	74.00	-23.21	Horizontal	Peak

802.11b					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3653.46	41.17	29.30	9.99	37.93	42.53	74.00	-31.47	Vertical	Peak
4871.10	34.59	31.46	11.69	36.02	41.72	74.00	-32.28	Vertical	Peak
7319.96	33.17	36.30	14.58	34.77	49.28	74.00	-24.72	Vertical	Peak
8420.00	31.08	36.66	15.87	34.28	49.33	74.00	-24.67	Vertical	Peak
3653.46	41.58	29.30	9.99	37.93	42.94	74.00	-31.06	Horizontal	Peak
4871.10	36.42	31.46	11.69	36.02	43.55	74.00	-30.45	Horizontal	Peak
7319.96	33.40	36.30	14.58	34.77	49.51	74.00	-24.49	Horizontal	Peak
9088.19	31.72	38.16	16.00	35.47	50.41	74.00	-23.59	Horizontal	Peak

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3690.85	40.02	29.30	9.99	37.76	41.55	74.00	-32.45	Vertical	Peak
4920.96	34.64	31.42	11.72	35.82	41.96	74.00	-32.04	Vertical	Peak
8063.40	31.26	37.04	15.69	34.35	49.64	74.00	-24.36	Vertical	Peak
8747.72	31.57	37.80	15.97	34.72	50.62	74.00	-23.38	Vertical	Peak
3690.85	39.07	29.30	9.99	37.76	40.60	74.00	-33.40	Horizontal	Peak
4920.96	36.70	31.42	11.72	35.82	44.02	74.00	-29.98	Horizontal	Peak
7394.88	31.34	36.30	14.73	34.68	47.69	74.00	-26.31	Horizontal	Peak
8637.08	31.30	37.52	15.94	34.52	50.24	74.00	-23.76	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1732.97	37.23	25.27	6.61	37.91	31.20	74.00	-42.80	Vertical	Peak
3616.45	39.90	29.30	10.00	37.87	41.33	74.00	-32.67	Vertical	Peak
5271.06	31.74	31.36	12.25	35.00	40.35	74.00	-33.65	Vertical	Peak
10860.83	31.25	40.46	16.38	37.03	51.06	74.00	-22.94	Vertical	Peak
3616.45	41.51	29.30	10.00	37.87	42.94	74.00	-31.06	Horizontal	Peak
5230.96	31.28	31.44	12.14	34.77	40.09	74.00	-33.91	Horizontal	Peak
7245.81	30.88	36.25	14.53	34.76	46.90	74.00	-27.10	Horizontal	Peak
8615.13	31.63	37.39	15.93	34.48	50.47	74.00	-23.53	Horizontal	Peak

802.11g					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3653.46	39.78	29.30	9.99	37.93	41.14	74.00	-32.86	Vertical	Peak
5099.49	31.99	31.90	12.03	35.13	40.79	74.00	-33.21	Vertical	Peak
7045.74	30.89	35.44	14.50	34.65	46.18	74.00	-27.82	Vertical	Peak
8527.85	31.88	37.01	15.91	34.32	50.48	74.00	-23.52	Vertical	Peak
3216.84	34.76	28.70	9.48	37.38	35.56	74.00	-38.44	Horizontal	Peak
3653.46	40.21	29.30	9.99	37.93	41.57	74.00	-32.43	Horizontal	Peak
7227.39	31.00	36.23	14.53	34.75	47.01	74.00	-26.99	Horizontal	Peak
8104.56	31.41	36.99	15.67	34.33	49.74	74.00	-24.26	Horizontal	Peak

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3700.26	39.31	29.30	9.99	37.70	40.90	74.00	-33.10	Vertical	Peak
5086.52	31.67	31.85	12.03	35.19	40.36	74.00	-33.64	Vertical	Peak
8681.17	31.23	37.79	15.95	34.60	50.37	74.00	-23.63	Vertical	Peak
10888.51	30.92	40.56	16.37	37.03	50.82	74.00	-23.18	Vertical	Peak
2775.30	32.57	28.10	8.86	34.78	34.75	74.00	-39.25	Horizontal	Peak
3690.85	39.22	29.30	9.99	37.76	40.75	74.00	-33.25	Horizontal	Peak
5112.49	30.90	31.85	12.04	35.07	39.72	74.00	-34.28	Horizontal	Peak
8571.38	32.08	37.19	15.92	34.40	50.79	74.00	-23.21	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3208.66	35.46	28.75	9.46	37.34	36.33	74.00	-37.67	Vertical	Peak
3616.45	40.18	29.30	10.00	37.87	41.61	74.00	-32.39	Vertical	Peak
7245.81	32.20	36.25	14.53	34.76	48.22	74.00	-25.78	Vertical	Peak
10348.05	32.00	39.47	16.44	37.17	50.74	74.00	-23.26	Vertical	Peak
3200.50	34.54	28.80	9.44	37.40	35.38	74.00	-38.62	Horizontal	Peak
3616.45	40.42	29.30	10.00	37.87	41.85	74.00	-32.15	Horizontal	Peak
7245.81	32.37	36.25	14.53	34.76	48.39	74.00	-25.61	Horizontal	Peak
9909.80	32.26	39.10	16.37	37.19	50.54	74.00	-23.46	Horizontal	Peak

802.11n(HT20)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2846.85	34.65	28.29	8.90	36.09	35.75	74.00	-38.25	Vertical	Peak
3653.46	39.30	29.30	9.99	37.93	40.66	74.00	-33.34	Vertical	Peak
6833.77	31.50	34.24	13.96	34.78	44.92	74.00	-29.08	Vertical	Peak
9251.58	31.22	38.91	15.93	36.03	50.03	74.00	-23.97	Vertical	Peak
3653.46	40.13	29.30	9.99	37.93	41.49	74.00	-32.51	Horizontal	Peak
6094.14	31.82	32.50	13.48	35.28	42.52	74.00	-31.48	Horizontal	Peak
7190.69	30.91	36.14	14.52	34.73	46.84	74.00	-27.16	Horizontal	Peak
8615.13	31.89	37.39	15.93	34.48	50.73	74.00	-23.27	Horizontal	Peak

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3690.85	39.43	29.30	9.99	37.76	40.96	74.00	-33.04	Vertical	Peak
5112.49	31.61	31.85	12.04	35.07	40.43	74.00	-33.57	Vertical	Peak
7027.82	30.89	35.38	14.49	34.64	46.12	74.00	-27.88	Vertical	Peak
9784.47	32.02	39.10	16.21	37.09	50.24	74.00	-23.76	Vertical	Peak
3700.26	39.65	29.30	9.99	37.70	41.24	74.00	-32.76	Horizontal	Peak
7190.69	30.67	36.14	14.52	34.73	46.60	74.00	-27.40	Horizontal	Peak
8593.22	31.25	37.27	15.92	34.44	50.00	74.00	-24.00	Horizontal	Peak
10860.83	30.89	40.46	16.38	37.03	50.70	74.00	-23.30	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3184.25	36.00	28.80	9.39	37.50	36.69	74.00	-37.31	Vertical	Peak
3634.91	38.44	29.30	9.99	37.90	39.83	74.00	-34.17	Vertical	Peak
4617.55	33.94	30.95	11.41	36.49	39.81	74.00	-34.19	Vertical	Peak
8681.17	31.68	37.79	15.95	34.60	50.82	74.00	-23.18	Vertical	Peak
3625.67	38.93	29.30	9.99	37.88	40.34	74.00	-33.66	Horizontal	Peak
3883.62	36.77	29.68	10.35	37.45	39.35	74.00	-34.65	Horizontal	Peak
6628.18	31.17	34.20	14.10	35.06	44.41	74.00	-29.59	Horizontal	Peak
11399.03	30.50	40.30	16.59	36.43	50.96	74.00	-23.04	Horizontal	Peak

802.11n(HT40)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3644.18	38.12	29.30	9.99	37.91	39.50	74.00	-34.50	Vertical	Peak
4617.55	32.85	30.95	11.41	36.49	38.72	74.00	-35.28	Vertical	Peak
7117.84	31.07	35.71	14.51	34.69	46.60	74.00	-27.40	Vertical	Peak
8615.13	31.51	37.39	15.93	34.48	50.35	74.00	-23.65	Vertical	Peak
3192.37	35.23	28.80	9.41	37.45	35.99	74.00	-38.01	Horizontal	Peak
3644.18	37.99	29.30	9.99	37.91	39.37	74.00	-34.63	Horizontal	Peak
7045.74	30.67	35.44	14.50	34.65	45.96	74.00	-28.04	Horizontal	Peak
8615.13	31.23	37.39	15.93	34.48	50.07	74.00	-23.93	Horizontal	Peak

802.11n(HT40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3681.47	37.29	29.30	9.99	37.82	38.76	74.00	-35.24	Vertical	Peak
5164.81	31.60	31.64	12.05	34.79	40.50	74.00	-33.50	Vertical	Peak
6921.30	31.72	34.83	14.20	34.70	46.05	74.00	-27.95	Vertical	Peak
9065.08	32.22	38.10	16.00	35.40	50.92	74.00	-23.08	Vertical	Peak
3057.17	35.29	28.72	9.07	37.77	35.31	74.00	-38.69	Horizontal	Peak
3672.11	37.13	29.30	9.99	37.88	38.54	74.00	-35.46	Horizontal	Peak
5151.68	31.43	31.69	12.05	34.86	40.31	74.00	-33.69	Horizontal	Peak
8725.48	31.40	37.85	15.96	34.68	50.53	74.00	-23.47	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.


6. TEST SETUP PHOTOS

Conducted Emissions



Radiated Emissions





7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No.: CHTEW19060144

-----End of Report-----