



FCC RADIO TEST REPORT

FCC ID: 2ASYG518T-10W

Product : Wireless car charger

Trade Name : Brainiac

Model Name : 518T-10W

518A-10W, 518B-10W, 518C-S10W,

Serial Model : 518D-S10W, 518E-S10W, 518T-S10W,
518M-S10W, 518K-S10W, 518N-S10W

Report No. : UNIA19040207FR-01

Prepared for

ShenZhen Brainiac Technology Development Co., Ltd

2/F, Building B30, First Industrial Prak Of Fenghuang,
Fuyong St., Baoan District, Shen Zhen

Prepared by

Shenzhen United Testing Technology Co., Ltd.

2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang
Community, Xixiang Str, Bao'an District, Shenzhen, China

TEST RESULT CERTIFICATION

Applicant's name : **ShenZhen Brainiac Technology Development Co., Ltd**

Address : 2/F, Building B30, First Industrial Prak Of Fenghuang, Fuyong St., Baoan District, Shen Zhen

Manufacture's Name : **ShenZhen Brainiac Technology Development Co., Ltd**

Address : 2/F, Building B30, First Industrial Prak Of Fenghuang, Fuyong St., Baoan District, Shen Zhen

Product description

Product name : Wireless car charger

Trade Mark : Brainiac

Model and/or type reference : 518T-10W

Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.209
ANSI C63.10: 2013

This device described above has been tested by Shenzhen United Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of UNI, this document may be altered or revised by Shenzhen United Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

Date of Test :

Date (s) of performance of tests : Apr. 1~8, 2019

Date of Issue : Apr. 8, 2019

Test Result : Pass

Prepared by:

Reviewer:

Approved & Authorized Signer:



Liuze/Manager

Table of Contents	Page
1 TEST SUMMARY.....	4
2 GENERAL INFORMATION.....	5
2.1 GENERAL DESCRIPTION OF EUT.....	5
2.2 Operation of EUT during testing.....	5
2.3 DESCRIPTION OF TEST SETUP.....	5
2.4 MEASUREMENT INSTRUMENTS LIST.....	6
3 CONDUCTED EMISSION TEST.....	7
3.1 Conducted Power Line Emission Limit.....	7
3.2 Test Setup.....	7
3.3 Test Procedure.....	7
3.4 Test Result.....	7
4 RADIATED EMISSION TEST.....	10
4.1 Block Diagram of Test Setup.....	10
4.2 Rules and specifications.....	10
4.3 Test Procedure.....	11
4.4 Test Result.....	11
5 ANTENNA REQUIREMENT.....	14
6 PHOTOGRAPH OF TEST.....	15
6.1 Radiated Emission.....	15
6.2 Conducted Emission.....	16

1 TEST SUMMARY

TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSION TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

TEST FACILITY

Test Firm : Shenzhen United Testing Technology Co., Ltd.
Address : 2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L6494

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of testing Laboratories.

Designation Number: CN1227

Test Firm Registration Number: 674885

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files.

MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	= 2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.06dB, k=2

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless car charger
Trade Mark	Brainiac
Model Name	518T-10W
Serial No.	518A-10W, 518B-10W, 518C-S10W, 518D-S10W, 518E-S10W, 518T-S10W, 518M-S10W, 518K-S10W, 518N-S10W
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: 518T-10W
FCC ID	Wireless car charger
Antenna Type	Coil Antenna
Antenna Gain	0dBi
Operation frequency	110.0~205.0KHz
Battery	N/A
Power Source	Input: 5V/2A 9V1.67A
Adapter Model	M/N: P12USB020200 Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5V, 2.0A

2.2 Operation of EUT during testing

Operating Mode

The mode is used: Normal Working

2.3 DESCRIPTION OF TEST SETUP

Operation of EUT during testing:



Setup: Normal Working

Table for auxiliary equipment:

Equipment Description	Manufacturer	Model	Calibration Due Date
Mobile phone	Haixin	M30T	N/A
Adapter	XinShenHai	P12USB020200	N/A

2.4 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
CONDUCTED EMISSIONS TEST					
1	AMN	Schwarzbeck	NNLK8121	8121370	2019.9.9
2	AMN	ETS	3810/2	00020199	2019.9.9
3	EMI TEST RECEIVER	Rohde&Schwarz	ESCI	101210	2019.9.9
4	AAN	TESEQ	T8-Cat6	38888	2019.9.9
RADIATED EMISSION TEST					
1	Horn Antenna	Sunol	DRH-118	A101415	2019.9.29
2	BicoNILog Antenna	Sunol	JB1 Antenna	A090215	2019.9.29
3	PREAMP	HP	8449B	3008A00160	2019.9.9
4	PREAMP	HP	8447D	2944A07999	2019.9.9
5	EMI TEST RECEIVER	Rohde&Schwarz	ESR3	101891	2019.9.9
6	VECTOR Signal Generator	Rohde&Schwarz	SMU200A	101521	2019.9.28
7	Signal Generator	Agilent	E4421B	MY4335105	2019.9.28
8	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2019.9.28
9	MXA Signal Analyzer	Agilent	N9020A	MY51110104	2019.9.9
10	ANT Tower&Turn table Controller	Champro	EM 1000	60764	2019.9.28
11	Anechoic Chamber	Taihe Maorui	9m*6m*6m	966A0001	2019.9.9
12	Shielding Room	Taihe Maorui	6.4m*4m*3m	643A0001	2019.9.9
13	RF Power sensor	DARE	RPR3006W	15I00041SNO88	2019.9.9
14	RF Power sensor	DARE	RPR3006W	15I00041SNO89	2019.9.9
15	RF power divider	Anritsu	K241B	992289	2019.9.28
16	Wideband radio communication tester	Rohde&Schwarz	CMW500	154987	2019.9.28
17	Biconical antenna	Schwarzbeck	VHA 9103	91032360	2019.9.8
18	Biconical antenna	Schwarzbeck	VHA 9103	91032361	2019.9.8
19	Broadband Hybrid Antennas	Schwarzbeck	VULB9163	VULB9163#958	2019.9.8
20	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1680	2019.1.12
21	Active Receive Loop Antenna	Schwarzbeck	FMZB 1919B	00023	2019.9.8
22	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170651	2019.03.14
23	Microwave Broadband Preamplifier	Schwarzbeck	BBV 9721	100472	2019.9.8
24	Active Loop Antenna	Com-Power	AL-130R	10160009	2019.05.10
25	Power Meter	KEYSIGHT	N1911A	MY50520168	2019.05.10
26	Frequency Meter	VICTOR	VC2000	997406086	2019.05.10
27	DC Power Source	HYELEC	HY5020E	055161818	2019.05.10

3 CONDUCTED EMISSION TEST

3.1 Conducted Power Line Emission Limit


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

Frequency (MHz)	Maximum RF Line Voltage(dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15~0.50	79	66	66~56*	56~46*
0.50~5.00	73	60	56	46
5.00~30.0	73	60	60	50

Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure


- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. A wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer/Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

3.4 Test Result

PSSS


Remark: EUT was tested at AC 120V and 240V, only the worst result of AC 120V was reported.

Temperature:	26°C	Relative Humidity:	45%
Test Date:	Apr. 3, 2019	Pressure:	1010hPa
Test Voltage:	AC 120V, 60Hz	Phase:	Line
Test Mode:	Normal Working		



Freq	Level	Limit		Over	Remark
		Line	Limit		
MHz	dBuV	dBuV	dB		
1	0.154	46.71	55.78	-9.07	Average
2	0.154	62.40	65.78	-3.38	QP
3	0.193	42.22	53.89	-11.67	Average
4	0.193	58.60	63.89	-5.29	QP
5	0.233	38.59	52.35	-13.76	Average
6	0.233	55.30	62.35	-7.05	QP
7	0.282	36.64	50.76	-14.12	Average
8	0.282	51.10	60.76	-9.66	QP
9	0.426	37.93	47.33	-9.40	Average
10	0.426	48.80	57.33	-8.53	QP
11	0.469	39.63	46.54	-6.91	Average
12	0.469	48.10	56.54	-8.44	QP


Temperature:	26°C	Relative Humidity:	45%
Test Date:	Apr. 3, 2019	Pressure:	1010hPa
Test Voltage:	AC 120V, 60Hz	Phase:	Neutral
Test Mode:	Normal Working		



Freq	Level	Limit		Over Line Limit	Remark
		MHz	dBuV		
1	0.150	43.95	56.00	-12.05	Average
2	0.150	60.20	66.00	-5.80	QP
3	0.194	39.79	53.84	-14.05	Average
4	0.194	55.70	63.84	-8.14	QP
5	0.237	35.76	52.22	-16.46	Average
6	0.237	52.20	62.22	-10.02	QP
7	0.383	37.76	48.21	-10.45	Average
8	0.383	46.30	58.21	-11.91	QP
9	0.428	38.47	47.29	-8.82	Average
10	0.428	45.50	57.29	-11.79	QP
11	0.474	41.86	46.45	-4.59	Average
12	0.474	47.20	56.45	-9.25	QP

4 RADIATED EMISSION TEST

4.1 Block Diagram of Test Setup



4.2 Rules and specifications

CFR 47 Part 15, section 15.205

Only spurious emissions are permitted in any of the frequency bands listed the tables in these sections.

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

CFR 47 Part 15, section 15.209

The emissions from an intentional radiator shall not exceed the limits in the tables in these sections using an average detector

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(KHz)	300
0.490-1.705	24000/F(KHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

Limit calculation and transfer to 3m distance as showed in the following table:

Frequency (MHz)	Limit (dBuV/m)	Distance (m)
0.009-0.490	$20\log(2400/F(KHz))+40\log(300/3)$	3
0.490-1.705	$20\log(24000/F(KHz))+40\log(30/3)$	3
1.705-30.0	69.5	3
30-88	40.0	3
88-216	43.5	3
216-960	46.0	3
Above 960	54.0	3

CFR 47 Part 15, section 15.35

When average radiated emission measurements are specified, the limit on the peak level of the radio Frequency emission is 20dB above the maximum permitted average emission limit.

Transmitter Spurious Emissions 9KHz-30MHz			
	9-150KHz	150-490KHz	490KHz-30MHz
Resolution Bandwidth	200Hz	9KHz	9KHz
Video Bandwidth	2KHz	100KHz	100KHz
Detector	Peak	Peak	Peak
Trace Mode	Max Hold	Max Hold	Max Hold
Sweep Time	Auto	Auto	Auto

4.3 Test Procedure

Measurement distance is 3m.

For the measurement range up to 30MHz in the following plots the field strength result from 3m Distance measurement are extrapolated to 300m and 30m distance respectively, by 40dB/decade, According to part 15.31(f)(2), per antenna factor scaling.

Measurements below 1000MHz are performed with a peak detector and compared to average limits, Measurements with an average detector are not required.

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4 Test Result


PASS

For 9KHz-30MHz Test Results:

Freq. (MHz)	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limits 3m (dBuV/m)	Margin (dBuV/m)
1.92	Peak	42.51	15.48	57.99	69.5	-11.51
15.07	Peak	39.05	16.08	55.13	69.5	-14.37


For 30MHz-1GHz Test Results:

Temperature:	26°C	Relative Humidity:	45%
Test Date:	Apr. 3, 2019	Pressure:	1010hPa
Test Voltage:	AC 120V, 60Hz	Polarization:	Horizontal
Test Mode:	Normal Working		



Freq	ReadAntenna		Cable		Limit	Over	Over
	Level	Factor	Loss	Level			
	MHz	dB _{BuV}	dB/m	dB	dB _{BuV/m}	dB _{BuV/m}	dB
1	106.39	8.59	11.58	0.18	20.35	43.50	-23.15 QP
2	119.44	7.69	12.28	0.20	20.17	43.50	-23.33 QP
3	137.42	5.69	14.87	0.23	20.79	43.50	-22.71 QP
4	157.01	4.33	15.63	0.23	20.19	43.50	-23.31 QP
5	329.04	7.49	13.34	0.72	21.55	46.00	-24.45 QP
6	787.85	4.30	20.95	1.38	26.63	46.00	-19.37 QP

Temperature:	26°C	Relative Humidity:	45%
Test Date:	Apr. 3, 2019	Pressure:	1010hPa
Test Voltage:	AC 120V, 60Hz	Polarization:	Vertical
Test Mode:	Normal Working		



Freq	Read		Antenna		Cable		Limit	Over	Line	Limit	Remark
	Level	Factor	Loss	Level	dBuV/m	dBuV/m					
	MHz	dBuV	dB/m	dB							
1	30.00	5.69	14.80	0.34	20.83	40.00	-19.17	QP			
2	39.58	4.71	13.44	0.14	18.29	40.00	-21.71	QP			
3	107.13	12.41	11.62	0.18	24.21	43.50	-19.29	QP			
4	119.02	8.90	12.26	0.20	21.36	43.50	-22.14	QP			
5	136.94	4.86	14.80	0.23	19.89	43.50	-23.61	QP			
6	163.18	10.01	15.17	0.23	25.41	43.50	-18.09	QP			

Remark: Absolute Level= Reading Level+ Factor, Margin= Absolute Level – Limit

Factor=Ant. Factor + Cable Loss – Pre-amplifier

5 ANTENNA REQUIREMENT


Standard Applicable:

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Connected Construction


The antenna used in this product is a Coil Antenna, The directional gains of antenna used for transmitting is 0dBi.

ANTENNA:




6 PHOTOGRAPH OF TEST

6.1 Radiated Emission



6.2 Conducted Emission



End of Report