

MPE ESTIMATION

FCC ID: 2ASYM-FONEWE-B

1, In accordance with KDB447498D01V06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

2, Estimation Result

For BT:

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
BLE	1.15	1±1(2)	1.58	0	1	0.00032
$Pd = \frac{Pout * G}{4\pi r^2};$						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power.						
Conducted power see the test report HK2305312244-E , antenna gain=0dBi						

Per KDB 447498 D01 V06, when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00032mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----