



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT

Report Reference No.....: **GTS20190726008-1-5-2**

FCC ID.....: **2AT26CR928UBQA**

Compiled by

(position+printed name+signature)..**File administrators Jimmy Wang**

Supervised by

(position+printed name+signature)..**Test Engineer Aaron Tan**

Approved by

(position+printed name+signature)..**Manager Jason Hu**

Date of issue.....: **July 31, 2019**

Representative Laboratory Name : **Shenzhen Global Test Service Co., Ltd.**

Address.....: **No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong**

Applicant's name.....: **Dongguan Yihua Electrical Appliance Technology CO., LTD**

Address: **No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City, Guangdong Province, China**

Test specification

Standard: **FCC Rules and Regulations Part 15 Subpart C (Section 15.209), ANSI C63.10: 2013**

TRF Originator.....: **Shenzhen Global Test Service Co.,Ltd.**

Master TRF: **Dated 2014-12**

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: **WIRELESS QI CHARGING BLUETOOTH ALARM CLOCK**

Trade Mark: **SYLVANIA**

Manufacturer: **Dongguan Yihua Electrical Appliance Technology CO., LTD**

Model/Type reference.....: **CR928UBQA**

Listed Models: **SCR0932**

Modulation Type: **ASK**

Operation Frequency.....: **From 110KHz~205KHz**

Rating: **DC 3.0V from 2*AAA battery or DC 5V from adapter**

Result.....: **PASS**



TEST REPORT

Test Report No. :	GTS20190726008-1-5-2	July 31, 2019
		Date of issue

Equipment under Test : WIRELESS QI CHARGING BLUETOOTH ALARM CLOCK

Model /Type : CR928UBQA

Listed Models : SCR0932

Applicant : Dongguan Yihua Electrical Appliance Technology CO., LTD

Address : No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City, Guangdong Province, China

Manufacturer : Dongguan Yihua Electrical Appliance Technology CO., LTD

Address : No. 5, Nanyu Industrial Park, Nanchang Road, Wanglian Hamlet, Wangniudun Town, Dongguan City, Guangdong Province, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2</u>	<u>SUMMARY</u>	<u>5</u>
2.1	General Remarks	5
2.2	Product Description	5
2.3	Equipment under Test	5
2.4	Modifications	5
<u>3</u>	<u>TEST ENVIRONMENT</u>	<u>6</u>
3.1	Address of the test laboratory	6
3.2	Test Facility	6
3.3	Environmental conditions	6
3.4	Summary of measurement results	7
3.5	Statement of the measurement uncertainty	7
3.6	Equipments Used during the Test	7
<u>4</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>9</u>
4.1	AC Power Conducted Emission	9
4.2	Radiated Emission	12
4.3	Occupied Bandwidth	16
4.4	Antenna Requirement	17
<u>5</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>18</u>
<u>6</u>	<u>PHOTOS OF THE EUT</u>	<u>19</u>

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules and Regulations Part 15 Subpart C \(Section 15.207\)](#): Conducted limits.

[FCC Rules and Regulations Part 15 Subpart C \(Section 15.209\)](#): Radiated emission limits; general requirements.

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	July 22, 2019
Testing commenced on	:	July 23, 2019
Testing concluded on	:	July 31, 2019

2.2 Product Description

Product Name:	WIRELESS QI CHARGING BLUETOOTH ALARM CLOCK
Model/Type reference:	CR928UBQA
Power supply:	DC 3.0V from 2*AAA battery or DC 5V from adapter
Adapter Information:	Mode: GKYPK0200050US1 Input:100-240V~ 50/60Hz, 0.5A Output:DC 5V,2A
Wireless Charger	
Antenna Type	Coil Antenna
Antenna Gain	1.0dBi
Operation frequency	110KHz~205KHz
Modulation Type	ASK

2.3 Equipment under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/>	230V / 50 Hz	<input type="radio"/>	120V / 60Hz
		<input type="radio"/>	12 V DC	<input type="radio"/>	24 V DC
		<input checked="" type="radio"/>	Other (specified in blank below)		

DC 3.7V from battery

Description of the test mode

Operation Frequency each of channel	
Channel	Frequency
1	131KHz

Operating Mode

The mode is used: Transmitting mode

2.4 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Summary of measurement results

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSIONS TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2018/09/20	2019/09/19
LISN	R&S	ESH2-Z5	893606/008	2018/09/20	2019/09/19
Bilog Antenna	Schwarzbeck	VULB9163	976	2018/09/20	2019/09/19
EMI Test Receiver	R&S	ESCI7	101102	2018/09/20	2019/09/19
Spectrum Analyzer	Agilent	N9020A	MY48010425	2018/09/20	2019/09/19
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2018/09/20	2019/09/19
Active Loop Antenna	SCHWARZBEC K	FMZB1519	1519-037	2018/09/20	2019/09/19
Broadband Horn Antenna	SCHWARZBEC K	BBHA 9170	971	2018/09/20	2019/09/19
Amplifier	Schwarzbeck	BBV 9743	#202	2018/09/20	2019/09/19
Amplifier	EMCI	EMC051845B	980355	2018/09/20	2019/09/19
Temperature/Humidity Meter	Gangxing	CTH-608	02	2018/09/20	2019/09/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	KL142031	2018/09/20	2019/09/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	KL142032	2018/09/20	2019/09/19


RF Cable(below 1GHz)	HUBER+SUHNE R	RG214	RE01	2018/09/20	2019/09/19
RF Cable(above 1GHz)	HUBER+SUHNE R	RG214	RE02	2018/09/20	2019/09/19
Data acquisition card	Agilent	U2531A	TW53323507	2018/09/20	2019/09/19
Power Sensor	Agilent	U2021XA	MY5365004	2018/09/20	2019/09/19
EMI Test Software	R&S	ES-K1	V1.7.1	2018/09/20	2019/09/19
EMI Test Software	JS Tonscend	JS32-RE	2.0.1.5	2018/09/20	2019/09/19
EMI Test Software	Audix	E3	2..1.1	2018/09/20	2019/09/19

Note: The Cal.Interval was one year.

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

AC Power Conducted Emission Limit


For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

1. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below::

**MEASUREMENT RESULT: "GTS19073107_fin"**

7/31/2019 10:26AM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dBµV	dB	dBµV	dB			
	0.348000	50.60	9.9	59	8.4	QP	L1	GND
	0.649500	40.40	9.7	56	15.6	QP	L1	GND
	1.185000	39.10	9.6	56	16.9	QP	L1	GND
	2.440500	38.40	9.5	56	17.6	QP	L1	GND
	5.320500	29.60	9.3	60	30.4	QP	L1	GND
	19.554000	23.90	7.1	60	36.1	QP	L1	GND

MEASUREMENT RESULT: "GTS19073107_fin2"

7/31/2019 10:26AM	Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
	MHz	dBµV	dB	dBµV	dB			
	0.348000	44.10	9.9	49	4.9	AV	L1	GND
	0.672000	32.90	9.7	46	13.1	AV	L1	GND
	1.059000	29.20	9.6	46	16.8	AV	L1	GND
	2.463000	27.50	9.5	46	18.5	AV	L1	GND
	5.788500	20.00	9.2	50	30.0	AV	L1	GND
	13.771500	16.50	8.3	50	33.5	AV	L1	GND

Power supply:	DC 5V from Adapter AC 120V/60Hz	Polarization	N																																																								
SCAN TABLE: "Voltage (9K-30M) FIN"																																																											
Short Description: 150K-30M Voltage																																																											
MEASUREMENT RESULT: "GTS19073108_fin" 7/31/2019 10:29AM <table> <thead> <tr> <th>Frequency MHz</th> <th>Level dBμV</th> <th>Transd dB</th> <th>Limit dBμV</th> <th>Margin dB</th> <th>Detector</th> <th>Line</th> <th>PE</th> </tr> </thead> <tbody> <tr><td>0.343500</td><td>42.00</td><td>9.9</td><td>59</td><td>17.1</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>0.865500</td><td>36.10</td><td>9.6</td><td>56</td><td>19.9</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>0.946500</td><td>38.00</td><td>9.6</td><td>56</td><td>18.0</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>2.274000</td><td>32.90</td><td>9.5</td><td>56</td><td>23.1</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>6.733500</td><td>29.30</td><td>9.1</td><td>60</td><td>30.7</td><td>QP</td><td>N</td><td>GND</td></tr> <tr><td>13.272000</td><td>14.20</td><td>8.4</td><td>60</td><td>45.8</td><td>QP</td><td>N</td><td>GND</td></tr> </tbody> </table>				Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE	0.343500	42.00	9.9	59	17.1	QP	N	GND	0.865500	36.10	9.6	56	19.9	QP	N	GND	0.946500	38.00	9.6	56	18.0	QP	N	GND	2.274000	32.90	9.5	56	23.1	QP	N	GND	6.733500	29.30	9.1	60	30.7	QP	N	GND	13.272000	14.20	8.4	60	45.8	QP	N	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE																																																				
0.343500	42.00	9.9	59	17.1	QP	N	GND																																																				
0.865500	36.10	9.6	56	19.9	QP	N	GND																																																				
0.946500	38.00	9.6	56	18.0	QP	N	GND																																																				
2.274000	32.90	9.5	56	23.1	QP	N	GND																																																				
6.733500	29.30	9.1	60	30.7	QP	N	GND																																																				
13.272000	14.20	8.4	60	45.8	QP	N	GND																																																				
MEASUREMENT RESULT: "GTS19073108_fin2" 7/31/2019 10:29AM <table> <thead> <tr> <th>Frequency MHz</th> <th>Level dBμV</th> <th>Transd dB</th> <th>Limit dBμV</th> <th>Margin dB</th> <th>Detector</th> <th>Line</th> <th>PE</th> </tr> </thead> <tbody> <tr><td>0.343500</td><td>29.20</td><td>9.9</td><td>49</td><td>19.9</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>0.838500</td><td>27.00</td><td>9.6</td><td>46</td><td>19.0</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>1.000500</td><td>27.00</td><td>9.6</td><td>46</td><td>19.0</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>2.323500</td><td>22.00</td><td>9.5</td><td>46</td><td>24.0</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>5.617500</td><td>15.80</td><td>9.2</td><td>50</td><td>34.2</td><td>AV</td><td>N</td><td>GND</td></tr> <tr><td>13.528500</td><td>17.60</td><td>8.4</td><td>50</td><td>32.4</td><td>AV</td><td>N</td><td>GND</td></tr> </tbody> </table>				Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE	0.343500	29.20	9.9	49	19.9	AV	N	GND	0.838500	27.00	9.6	46	19.0	AV	N	GND	1.000500	27.00	9.6	46	19.0	AV	N	GND	2.323500	22.00	9.5	46	24.0	AV	N	GND	5.617500	15.80	9.2	50	34.2	AV	N	GND	13.528500	17.60	8.4	50	32.4	AV	N	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE																																																				
0.343500	29.20	9.9	49	19.9	AV	N	GND																																																				
0.838500	27.00	9.6	46	19.0	AV	N	GND																																																				
1.000500	27.00	9.6	46	19.0	AV	N	GND																																																				
2.323500	22.00	9.5	46	24.0	AV	N	GND																																																				
5.617500	15.80	9.2	50	34.2	AV	N	GND																																																				
13.528500	17.60	8.4	50	32.4	AV	N	GND																																																				

4.2 Radiated Emission

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION

1. Radiated Emission Test Set-Up, Frequency Below 30MHz



2. Radiated Emission Test Set-Up, Frequency below 1000MHz



Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 1000MHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP

TEST RESULTS**For 9 KHz-30MHz****WORST-CASE RADIATED EMISSION BELOW 30 MHz**

Frequency (MHz)	Reading (dB μ V/m)	Polar Loop	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Levels (dB μ V/m)	Limits at 3m (dB μ V/m)	Margin (dB)	Detector Mode
0.131(F)	54.91	Loop	23.64	0.01	78.56	103.91	25.35	PK
0.131(F)	45.90	Loop	23.64	0.01	69.55	83.91	14.36	AV
0.110	34.91	Loop	23.55	0.01	58.47	106.78	48.31	PK
0.110	26.09	Loop	23.55	0.01	49.65	86.78	37.13	AV
0.735	26.34	Loop	25.07	-0.17	51.24	70.28	19.04	QP
1.425	19.00	Loop	27.12	-0.25	45.87	64.53	18.66	QP
5.878	17.19	Loop	23.91	-0.24	40.86	69.54	28.68	QP
--	--	--	--	--	--	--	--	--

Remark:


1. Data of measurement within this frequency range shown “-- in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits and not recorded.
2. The test limit distance is 3m limit.
3. PK means Peak Value, QP means Quasi Peak Value, AV means Average Value.
4. F means Fundamental Frequency.
5. Emission level (dB μ V/m) =Reading + Antenna Factor + Cable Loss.
6. Margin value = Limit value- Emission level.

For 30MHz-1GHz

Horizontal


SWEET TABLE: "test (30M-1G)"

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz
				Transducer
				VULB9163

***MEASUREMENT RESULT: "GTS190731205_red"***

7/31/2019 3:22PM

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
55.220000	30.60	8.0	40.0	9.4	---	0.0	0.00	HORIZONTAL
95.960000	36.70	10.2	43.5	6.8	---	0.0	0.00	HORIZONTAL
97.900000	37.90	10.7	43.5	5.6	---	0.0	0.00	HORIZONTAL
121.180000	37.00	14.7	43.5	6.5	---	0.0	0.00	HORIZONTAL
148.340000	39.00	13.8	43.5	4.5	---	0.0	0.00	HORIZONTAL
202.660000	37.10	14.1	43.5	6.4	---	0.0	0.00	HORIZONTAL




MEASUREMENT RESULT: "GTS190731206_red"

7/31/2019 4:36PM

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	34.30	20.8	40.0	5.7	---	0.0	0.00	VERTICAL
94.020000	39.80	9.9	43.5	3.7	---	0.0	0.00	VERTICAL
117.300000	42.40	14.7	43.5	1.1	---	0.0	0.00	VERTICAL
144.460000	41.90	14.1	43.5	1.6	---	0.0	0.00	VERTICAL
210.420000	33.90	14.0	43.5	9.6	---	0.0	0.00	VERTICAL
955.380000	31.30	26.6	46.0	14.7	---	0.0	0.00	VERTICAL

4.3 Occupied Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment complies with the 20dB attenuation specification may base on measurement at the intentional radiator's antenna output terminal unless the intentional radiator uses a permanently attached antenna, in which case compliance shall be demonstrated by measuring the radiated emissions.

LIMIT

The 20dB bandwidth shall be less than 80% of the permitted frequency band.

TEST RESULTS

Mode	Freq (KHz)	20dB Bandwidth (KHz)	99% OBW (KHz)	Conclusion
Tx Mode	131	3.918	3.314	PASS



4.4 Antenna Requirement

Standard Applicable

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The antenna used in this product is a Coil Antenna, The directional gains of antenna used for transmitting is 1dBi.

5 Test Setup Photos of the EUT






6 PHOTOS OF THE EUT




External Photos of EUT












Internal Photos of EUT







***** End of Report *****