

Cala Health, Inc.

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Cala Base Station Model: TWO (Base Station)

REPORT NUMBER

103592127MPK-022A

ISSUE DATE

August 16, 2019

REVISED DATE

N/A

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 103592127MPK-022A

Project Number: G103592127

Report Issue Date: August 16, 2019

Product Designation: Cala Base Station

Model Tested: TWO (Base Station)

FCC ID: 2AT2D-BASE0017

to

**47CFR 2.1091
RSS-102 Issue 5**

for

Cala Health, Inc.


Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

Cala Health, Inc.
875 Mahler Road Suite 175
Burlingame, CA 94010 USA

Report prepared by:



Todd Moy / Project Engineer

Report reviewed by:



Krishna Vemuri / Engineering Team Lead

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 103592127MPK-022A	
Equipment Under Test:	Cala Base Station
Trade Name:	Cala Health, Inc.
Model(s) Tested:	TWO (Base Station)
Applicant:	Cala Health, Inc.
Contact:	Mark Shughart
Address:	Cala Health, Inc. 875 Mahler Road Suite 175 Burlingame, CA 94010
Country:	USA
Tel. Number:	(415) 890-3961
Email:	mark@calahealth.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

<i>Cala Health, Inc.</i>	1
1.0 RF Exposure Summary	5
2.0 RF Exposure Limits	5
3.0 Test Results (Mobile Configuration)	7
Appendix A: Power Density Calculation	9
4.0 Document History	10

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	$0.73/f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142/f^{0.3417}$	$0.008335/f^{0.3417}$	$0.02619/f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158/f^{0.5}$	$4.21 \times 10^{-4}/f^{0.5}$	$6.67 \times 10^{-5}/f$	$616000/f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Cala Base Station, Model: TWO (Base Station) consists of three radios: RFID, Bluetooth and Cellular.

3.3 Maximum RF Power

Frequency Range (MHz)	Peak FS @10m (dBμV/m)	Note
13.56	42.68	FS measurement was taken from Report # 103592127MPK-037

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
699-716	24.12	2.00	As declared by the client the EUT consists of an approved cellular radio module under FCC ID: XPY2AGQN4NNN.
1850-1910	30.71		
1710-1755	23.89		
2402-2480	-2.01	3.19	Conducted power measurements were taken from Report # 103592127MPK-022.

¹As declared by the manufacturer.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for RFID

Frequency Range (MHz)	Peak FS @10m (dBμV/m)	Peak FS @20 cm* (dBμV/m)	Peak FS @20 cm (V/m)	RSS Limit (V/m)	FCC Limit (V/m)	Results
13.56	42.68	110.64	0.34	27.46	60.77	Complies

* Distance Correction Factor was used.

3.4.2 RF Exposure calculation for Bluetooth & Cellular

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	MPE Ratio	Sum of MPE Ratios
1850-1910	32.71	1865.42	0.3711	1.27	0.2922	0.2948
2402-2480	1.18	1.31	0.0026	1	0.0026	

Note: Antenna gains below 0 are considered as 0dBi.

Frequency Range (MHz)	EIRP (dBm)	EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	MPE Ratio	Sum of MPE Ratios
1850-1910	32.71	1865.42	3.711	4.58	0.810	0.8147
2402-2480	1.18	1.31	0.026	5.47	0.0047	

Note: Antenna gains below 0 are considered as 0dBi.

The summation of the MPE ratio is less than 1, therefore, the EUT complies for the MPE requirement of simultaneous transmission.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
01/ G103592127	TM	KV	August 16, 2019	Original document