

TEST REPORT

Product Name : Portable general purpose luminaires
Model Number : DE25611H11
FCC ID : 2AT2H-DE25611H11

Prepared for : Ningbo Chinyo Lighting Appliance Co., Ltd
Address : No. 7, Ketai Road, Wangchun Industrial Zone Haishu
District, Ningbo, Zhejiang Provincce, China

Prepared by : EMTEK (NINGBO) CO., LTD.
Address : 1F Building 4, 1177#, Lingyun Road, Ningbo National
Hi-Tech Zone, Ningbo, Zhejiang, China.

Tel: +86-574-27907998
Fax: +86-574-27721538

Report Number : ENB2204150137W00102R
Date(s) of Tests : April 15, 2022 to May 09, 2022
Date of Issue : May 11, 2022

TABLE OF CONTENT

| Test Report Description | Page |
|---|----------|
| 1. SUMMARY OF TEST RESULT | 3 |
| 2. GENERAL INFORMATION | 5 |
| 2.1. DESCRIPTION OF DEVICE (EUT) | 5 |
| 2.2. DESCRIPTION OF TEST FACILITY | 5 |
| 2.3. MEASUREMENT UNCERTAINTY | 6 |
| 3. MEASURING DEVICE AND TEST EQUIPMENT | 7 |
| 3.1. FOR MPE MEASUREMENT | 7 |
| 4. RF EXPOSURE | 8 |
| 4.1. MEASURING STANDARD | 8 |
| 4.2. REQUIREMENTS | 8 |
| 4.3. TEST CONFIGURATION | 9 |
| 4.4. LIMITS | 10 |
| 4.5. MEASURING RESULTS | 11 |

TEST REPORT DESCRIPTION

Applicant : Ningbo Chinyo Lighting Appliance Co., Ltd
Address : No. 7, Ketai Road, Wangchun Industrial Zone Haishu District, Ningbo, Zhejiang Province, China
Manufacturer : Ningbo Chinyo Lighting Appliance Co., Ltd
Address : No. 7, Ketai Road, Wangchun Industrial Zone Haishu District, Ningbo, Zhejiang Province, China
EUT : Portable general purpose luminaires LED desk lamp
Model Name : DE25611H11
Trademark : N/A

Measurement Procedure Used:

FCC Part 1(1.1310) and Part 2(2.1091)

KDB 680106 D01 RF Exposure Portable general purpose luminaires LED desk lamp App v03

The device described above is tested by EMTEK (SHENZHEN) CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and EMTEK (SHENZHEN) CO., LTD. is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC requirements.


This report applies to above tested sample only and shall not be reproduced in part without written approval of EMTEK (SHENZHEN) CO., LTD.

Date of Test : April 15, 2022 to May 09, 2022



June Gao/Engineer

Prepared by : June Gao



Vinay/Supervisor

Reviewer : Vinay



TONY WE

Tony Wei/Manager

Approved & Authorized Signer : TONY WE

1. SUMMARY OF TEST RESULT

| EMISSION | | |
|--|--|---------|
| Description of Test Item | Standard & Limits | Results |
| MPE | FCC Part 1(1.1310) and Part 2(2.1091) KDB 680106 D01 RF Exposure Wireless Charging App v03 | Pass |
| Note: N/A is an abbreviation for Not Applicable. | | |



2. GENERAL INFORMATION

2.1. Description of Device (EUT)

| | |
|------------------------|---|
| Product: | Portable general purpose luminaires LED desk lamp |
| Model Number: | DE25611H11 |
| Sample Number: | 1# |
| Power Supply: | DC 12V from adapter |
| Wireless specification | 5W/7.5W |
| Modulation: | Ask |
| Maximum Power Rate: | 65.97 dBuV/m |
| Frequency Range: | 110 kHz~205 KHz |
| Antenna Type: | Integral Antenna(Induction coil) |
| Antenna Gain: | 0 dBi |
| Operating Temperature | 0°C ~ +50°C |
| Date of Received: | February 28, 2022 |

2.2. Description of Test Facility

Site Description

EMC Lab.

Accredited by CNAS

The Certificate Registration Number is L6666.

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1302

Test Firm Registration Number: 436491

Accredited by A2LA

The certificate is valid until May 31, 2023

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0114

Name of Firm

: EMTEK (NINGBO) CO., LTD.

Site Location

: 1F Building 4, 1177#, Lingyun Road, Ningbo National Hi-Tech Zone, Ningbo, Zhejiang, China.

2.3. Measurement Uncertainty

MPE

: $\pm 2\%$

3. MEASURING DEVICE AND TEST EQUIPMENT

3.1. For MPE Measurement

| Used | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|-------------------------------------|-----------------------------------|--------------|-----------|------------|---------------|---------------|
| <input checked="" type="checkbox"/> | E-Field Probe(100kHz-3GHz) | Narda | EF0391 | 2304/03 | July 08, 2021 | 1 Year |
| <input checked="" type="checkbox"/> | Broadband Field Meter | Narda | NBM-550 | 232421 | July 08, 2021 | 1 Year |
| <input checked="" type="checkbox"/> | Exposure Level Tester(1Hz-400KHz) | Narda | ELT-400 | C-0012 | July 08, 2021 | 1 Year |

4. RF EXPOSURE

4.1. Measuring Standard

FCC Part 1(1.1310) and Part 2(2.1091)

4.2. Requirements

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- o Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- o Mobile Devices: a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- o Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093). The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:
 - Occupational/Controlled Exposure: In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
 - General Population/Uncontrolled Exposure: The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

4.3. Test configuration

- 1, The field strength of both E-field and H-field was measured at 15cm(the 15 cm measured from the center of the probe(s) to the edge of the device) using the equipment list above for determining compliance with the MPE requirements of FCC Part 1.1310.
- 2, The RF power density was measured at 3 different charge conditions: min load, mid load, max load.
- 3, Maximum E-field and H-field measurements were made at 20cm from the top and 15cm from the edge of EUT. Along the side of the EUT and still 15cm away from the edge of the EUT, the field probes were positioned at the location where there is maximum field strength. The maximum E-field and H-field is reported below.
- 4, This device uses a wireless charging circuit for power transfer operating at the frequency of 110 – 205kHz. Thus, the 300kHz limits were used: E-field Limit = 614 (V/m); H-field limit = 1.63 (A/m).



4.4. Limits

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

| Test Mode | Description | Remark |
|--------------------------|-------------|---------------|
| Mode A Charging(7.5W) | 100% Load | With resistor |
| | 50% Load | With resistor |
| | 10% Load | With resistor |

4.5. Measuring Results

Test Mode: Mode A(100% Load)

| Electric Field Emissions | | |
|--------------------------|---------------------|------------|
| Test Position | Measure Value (V/m) | Limit(V/m) |
| Top | 8.76 | 614 |
| Left | 5.67 | 614 |
| Right | 4.98 | 614 |
| Rear | 5.12 | 614 |
| Front | 5.33 | 614 |
| Bottom | 4.97 | 614 |

| Magnetic Field Emissions | | |
|--------------------------|---------------------|------------|
| Test Position | Measure Value (A/m) | Limit(A/m) |
| Top | 0.275 | 1.63 |
| Left | 0.213 | 1.63 |
| Right | 0.205 | 1.63 |
| Rear | 0.212 | 1.63 |
| Front | 0.215 | 1.63 |
| Bottom | 0.232 | 1.63 |

Test Mode: Mode A(50% Load)

| Electric Field Emissions | | |
|--------------------------|---------------------|------------|
| Test Position | Measure Value (V/m) | Limit(V/m) |
| Top | 8.71 | 614 |
| Left | 5.63 | 614 |
| Right | 5.11 | 614 |
| Rear | 5.07 | 614 |
| Front | 5.15 | 614 |
| Bottom | 4.93 | 614 |

| Magnetic Field Emissions | | |
|--------------------------|---------------------|------------|
| Test Position | Measure Value (A/m) | Limit(A/m) |
| Top | 0.214 | 1.63 |
| Left | 0.203 | 1.63 |
| Right | 0.201 | 1.63 |
| Rear | 0.201 | 1.63 |
| Front | 0.204 | 1.63 |
| Bottom | 0.202 | 1.63 |

Test Mode: Mode A(10% Load)

| Electric Field Emissions | | |
|--------------------------|---------------------|------------|
| Test Position | Measure Value (V/m) | Limit(V/m) |
| Top | 8.33 | 614 |
| Left | 5.34 | 614 |
| Right | 5.03 | 614 |
| Rear | 5.01 | 614 |
| Front | 5.05 | 614 |
| Bottom | 4.91 | 614 |

| Magnetic Field Emissions | | |
|--------------------------|---------------------|------------|
| Test Position | Measure Value (A/m) | Limit(A/m) |
| Top | 0.209 | 1.63 |
| Left | 0.201 | 1.63 |
| Right | 0.201 | 1.63 |
| Rear | 0.204 | 1.63 |
| Front | 0.203 | 1.63 |
| Bottom | 0.201 | 1.63 |

Remark: The device meets the mobile RF exposure limit at 20cm from the top and 15cm from the edge of EUT separation distance as specified in §2.1091 of the FCC Rules. The maximum leakage fields at 20cm from the top and 15cm from the edge of EUT surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit.

Requirement for KDB Publication 680106 D01

| Condition Requirement | Answers |
|--|--|
| Power transfer frequency is less than 1 MHz. | The power transfer frequency is 110KHz-205KHz. |
| Output power from each primary coil is less than or equal to 15 watts. | The maximum output power is 7.5W |
| The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils. | The transfer system includes only single primary. |
| Client device is placed directly in contact with the transmitter. | Client device is placed directly in contact with the transmitter. |
| Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion). | Mobile exposure conditions only |
| The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. | Please refer to the result of Electric Field Emissions and Magnetic Field Emissions. |

*** End of Report ***

声 明 Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效；

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.