

FCC Part 15C Test Report

FCC ID: 2AT2O-GEEUR3500

Product Name:	UHF RFID Reader
Trademark:	N/A
Model Name :	GEE-UR-3500 GEE-UR-1000, GEE-UR-1100, GEE-UR-1200, GEE-UR-1400, GEE-UR-1600, GEE-UR-1800, GEE-UR-2000, GEE-UR-2100, GEE-UR-2200, GEE-UR-2400, GEE-UR-2500, GEE-UR-2600, GEE-UR-2800, GEE-UR-3000, GEE-UR-3200, GEE-UR-3300, GEE-UR-3600, GEE-UR-3800
Prepared For :	GEE NFC LIMITED
Address :	No. 13-5, Cuilong Road, Ping Shan District, Shenzhen, China
Prepared By :	Shenzhen BCTC Testing Co., Ltd.
Address :	BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Date:	Jun. 27, 2019 – Jul. 04, 2019
Date of Report :	Jul. 04, 2019
Report No.:	BCTC-FY190603228E

TEST RESULT CERTIFICATION

Applicant's name : GEE NFC LIMITED

Address : No. 13-5, Cuilong Road, Ping Shan District, Shenzhen, China

Manufacture's Name : GEE NFC LIMITED

Address : No. 13-5, Cuilong Road, Ping Shan District, Shenzhen, China

Product description

Product name : UHF RFID Reader

Trademark : N/A

Model and/or type reference : GEE-UR-3500

GEE-UR-1000, GEE-UR-1100, GEE-UR-1200, GEE-UR-1400,
GEE-UR-1600, GEE-UR-1800, GEE-UR-2000, GEE-UR-2100,
GEE-UR-2200, GEE-UR-2400, GEE-UR-2500, GEE-UR-2600,
GEE-UR-2800, GEE-UR-3000, GEE-UR-3200, GEE-UR-3300,
GEE-UR-3600, GEE-UR-3800

Standards : FCC Part15.247

ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Compiled by:

Willem Wang

Willem Wang

Reviewed by:

Zhil Yang

Eric Yang

Approved by:



倍测检测
BCTC
APPROVED
Zero Zhou/Manager
SHENZHEN BCTC TESTING CO., LTD.

This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen BCTC Technology Co., Ltd.

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	13
3.1.3 DEVIATION FROM TEST STANDARD	13
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION LIMITS	17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP	18
3.2.5 EUT OPERATING CONDITIONS	19
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	20
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	21
3.2.8 TEST RESULTS (1GHZ~11GHZ)	23
3.3 RADIATED BAND EMISSION MEASUREMENT	28
3.3.1 TEST REQUIREMENT:	28
3.3.2 TEST PROCEDURE	28
3.3.3 DEVIATION FROM TEST STANDARD	29
3.3.4 TEST SETUP	29
3.3.5 EUT OPERATING CONDITIONS	29
4 . BANDWIDTH TEST	37
4.1 APPLIED PROCEDURES / LIMIT	37
4.1.1 TEST PROCEDURE	37

Table of Contents

	Page
4.1.2 DEVIATION FROM STANDARD	37
4.1.3 TEST SETUP	37
4.1.4 EUT OPERATION CONDITIONS	37
4.1.5 TEST RESULTS	38
5 . NUMBER OF HOPPING CHANNEL	41
5.1 APPLIED PROCEDURES / LIMIT	41
5.1.1 TEST PROCEDURE	41
5.1.2 DEVIATION FROM STANDARD	41
5.1.3 TEST SETUP	41
5.1.4 EUT OPERATION CONDITIONS	41
5.1.5 TEST RESULTS	41
6 . AVERAGE TIME OF OCCUPANCY	43
6.1 APPLIED PROCEDURES / LIMIT	43
6.1.1 TEST PROCEDURE	43
6.1.2 DEVIATION FROM STANDARD	43
6.1.3 TEST SETUP	43
6.1.4 EUT OPERATION CONDITIONS	43
6.1.5 TEST RESULTS	44
7 . HOPPING CHANNEL SEPARATION MEASUREMENT	46
7.1 APPLIED PROCEDURES / LIMIT	46
7.1.1 TEST PROCEDURE	46
7.1.2 DEVIATION FROM STANDARD	46
7.1.3 TEST SETUP	46
7.1.4 EUT OPERATION CONDITIONS	46
7.1.5 TEST RESULTS	47
8 . PEAK OUTPUT POWER	49
8.1 APPLIED PROCEDURES / LIMIT	49
8.1.1 TEST PROCEDURE	49
8.1.2 DEVIATION FROM STANDARD	49
8.1.3 TEST SETUP	49
8.1.4 EUT OPERATION CONDITIONS	49
8.1.5 TEST RESULTS	49
9 . ANTENNA REQUIREMENT	51
9.1 STANDARD REQUIREMENT	51
9.2 EUT ANTENNA	51
10 . TEST SEUUP PHOTO	52

Table of Contents

	Page
11 . EUT PHOTO	54

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Testing Co., Ltd.

Add.: BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 712850

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**。

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	UHF RFID Reader										
Trade Name	N/A										
Model Name	GEE-UR-3500 GEE-UR-1000, GEE-UR-1100, GEE-UR-1200, GEE-UR-1400, GEE-UR-1600, GEE-UR-1800, GEE-UR-2000, GEE-UR-2100, GEE-UR-2200, GEE-UR-2400, GEE-UR-2500, GEE-UR-2600, GEE-UR-2800, GEE-UR-3000, GEE-UR-3200, GEE-UR-3300, GEE-UR-3600, GEE-UR-3800										
Model Difference	All the model are the same circuit and RF module, except model names .										
Product Description	<p>The EUT is a UHF RFID Reader</p> <table border="1"> <tr> <td>Operation Frequency:</td> <td>902.75-927.25MHz</td> </tr> <tr> <td>Modulation Type:</td> <td>FHSS(GFSK)</td> </tr> <tr> <td>Number Of Channel</td> <td>50CH</td> </tr> <tr> <td>Antenna type:</td> <td>External antenna</td> </tr> <tr> <td>Antenna Gain (dBi)</td> <td>0dBi</td> </tr> </table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>	Operation Frequency:	902.75-927.25MHz	Modulation Type:	FHSS(GFSK)	Number Of Channel	50CH	Antenna type:	External antenna	Antenna Gain (dBi)	0dBi
Operation Frequency:	902.75-927.25MHz										
Modulation Type:	FHSS(GFSK)										
Number Of Channel	50CH										
Antenna type:	External antenna										
Antenna Gain (dBi)	0dBi										
Channel List	Please refer to the Note 2.										
Power	DC 9V from adapter										
Adapter	Input: AC 100-240V 50/60Hz 1.5A Output: DC 9V 3A										
hardware version	--										
Software version	--										
Serial number	--										
Connecting I/O Port(s)	Please refer to the User's Manual										

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Channel List								
2.	CH	Center frequency (MHz)						
	1	902.75	14	909.25	27	915.75	39	921.75
	2	903.25	15	909.75	28	916.25	40	922.25
	3	903.75	16	910.25	29	916.75	41	922.75
	4	904.25	17	910.75	30	917.25	42	923.25
	5	904.75	18	911.25	31	917.75	43	923.75
	6	905.25	19	911.75	32	918.25	44	924.25
	7	905.75	20	912.25	33	918.75	45	924.75
	8	906.25	21	912.75	34	919.25	46	925.25
	9	906.75	22	913.25	35	919.75	47	925.75
	10	907.25	23	913.75	36	920.25	48	926.25
	11	907.75	24	914.25	37	920.75	49	926.75
	12	908.25	25	914.75	38	921.25	50	927.25
	13	908.75	26	915.25				

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


Pretest Mode	Description		
Mode 1	CH01	CH25	
Mode 2	CH25		
Mode 3	CH50		
Mode 4	Link Mode		
For Conducted & Radiated Emission			
Final Test Mode	Description		
Mode 1	CH01	CH25	
Mode 2	CH25		
Mode 3	CH50		
Mode 4	Link Mode		

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Directional Gain=0dBi+10log(4)=6.0dBi

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated & Conducted Spurious Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	UHF Card Reader	N/A	GEE-UR-3500	N/A	EUT
E-2	PC	ASUS	AWT8000	N/A	
E-2	Adapter	N/A	JYH3-0903000	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C1	No	No	1.5m	USB Line

Note:

- (1) For detachable type I/O cable should be specified the length in cm in «Length» column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation test, Band-edge test and 6db bandwidth test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45109572	Jun. 13, 2019	Jun. 12, 2020
2	Test Receiver (9kHz-7GHz)	R&S	ESR7	101154	Jun. 13, 2019	Jun. 12, 2020
3	Bilog Antenna (30MHz-3GHz)	SCHWARZBECK	VULB9163	VULB9163-942	Jun. 22, 2019	Jun. 21, 2020
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1541	Jun. 22, 2019	Jun. 21, 2020
5	Horn Antenna (18GHz-40GHz)	SCHWARZBECK	BBHA9170	822	Jun. 22, 2019	Jun. 21, 2020
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	Jun. 25, 2019	Jun. 24, 2020
7	Amplifier (0.5GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	Jun. 25, 2019	Jun. 24, 2020
8	Amplifier (18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	Jun. 17, 2019	Jun. 16, 2020
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	014	Jun. 25, 2019	Jun. 24, 2020
10	RF cables1 (9kHz-30MHz)	Huber+Suhnar	9kHz-30MHz	B1702988-0008	Jun. 25, 2019	Jun. 24, 2020
11	RF cables2 (30MHz-1GHz)	Huber+Suhnar	30MHz-1GHz	1486150	Jun. 25, 2019	Jun. 24, 2020
12	RF cables3 (1GHz-40GHz)	Huber+Suhnar	1GHz-40GHz	1607106	Jun. 25, 2019	Jun. 24, 2020
13	Power Meter	Keysight	E4419	\	Jun. 17, 2019	Jun. 16, 2020
14	Power Sensor (AV)	Keysight	E9 300A	\	Jun. 17, 2019	Jun. 16, 2020
15	Signal Analyzer 20kHz-26.5GHz	KEYSIGHT	N9020A	MY49100060	Jun. 13, 2019	Jun. 12, 2020
16	Spectrum Analyzer 9kHz-40GHz	Aglient	FSP40	100363	Jun. 13, 2019	Jun. 12, 2020
17	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
18	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESR3	102075	Jun. 13, 2019	Jun. 12, 2020
2	LISN	SCHWARZBEC K	NSLK8127	8127739	Jun. 13, 2019	Jun. 12, 2020
3	LISN	R&S	ENV216	101375	Jun. 13, 2019	Jun. 12, 2020
4	RF cables	Huber+Suhner	9kHz-30MHz	B1702988-00 08	Jun. 25, 2019	Jun. 24, 2020
5	Software	Frad	EZ-EMC	EMC-CON 3A1	\	\

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note:


1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 4


Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	0.4340	28.20	19.53	47.73	57.18	-9.45	QP	
2		0.4340	15.06	19.53	34.59	47.18	-12.59	AVG	
3		0.7740	21.71	19.63	41.34	56.00	-14.66	QP	
4		0.7740	12.06	19.63	31.69	46.00	-14.31	AVG	
5		1.0339	21.93	19.57	41.50	56.00	-14.50	QP	
6		1.0339	9.98	19.57	29.55	46.00	-16.45	AVG	
7		1.4140	20.12	19.58	39.70	56.00	-16.30	QP	
8		1.4140	9.41	19.58	28.99	46.00	-17.01	AVG	
9		1.6100	18.42	19.58	38.00	56.00	-18.00	QP	
10		1.6100	8.21	19.58	27.79	46.00	-18.21	AVG	
11		17.8419	25.66	19.75	45.41	60.00	-14.59	QP	
12		17.8419	15.27	19.75	35.02	50.00	-14.98	AVG	

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 4


Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1	*	0.4380	27.93	19.53	47.46	57.10	-9.64	QP	
2		0.4380	16.22	19.53	35.75	47.10	-11.35	AVG	
3		0.5140	22.27	19.65	41.92	56.00	-14.08	QP	
4		0.5140	11.33	19.65	30.98	46.00	-15.02	AVG	
5		0.7780	22.23	19.63	41.86	56.00	-14.14	QP	
6		0.7780	12.10	19.63	31.73	46.00	-14.27	AVG	
7		1.0940	20.18	19.57	39.75	56.00	-16.25	QP	
8		1.0940	9.33	19.57	28.90	46.00	-17.10	AVG	
9		1.7500	17.80	19.58	37.38	56.00	-18.62	QP	
10		1.7500	7.90	19.58	27.48	46.00	-18.52	AVG	
11		18.0419	26.14	19.75	45.89	60.00	-14.11	QP	
12		18.0419	15.25	19.75	35.00	50.00	-15.00	AVG	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Test Voltage :	DC 9V from adapter input AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	DC 9V from adapter input AC 120V/60Hz		
Test Mode :	Mode 4		




Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Over Detector
1		78.6888	50.00	-20.12	29.88	40.00	-10.12	QP
2	!	149.4857	59.36	-19.47	39.89	43.50	-3.61	QP
3	*	200.6879	56.53	-16.28	40.25	43.50	-3.25	QP
4		248.5517	53.54	-15.18	38.36	46.00	-7.64	QP
5	!	447.9821	51.48	-10.02	41.46	46.00	-4.54	QP
6	!	549.0193	48.44	-7.70	40.74	46.00	-5.26	QP

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Vertical
Test Voltage :	DC 9V from adapter input AC 120V/60Hz		
Test Mode :	Mode 4		


Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		77.3212	37.33	-19.82	17.51	40.00	-22.49	QP
2		149.4857	50.38	-19.47	30.91	43.50	-12.59	QP
3	!	194.4533	55.64	-16.65	38.99	43.50	-4.51	QP
4	!	248.5518	57.56	-15.18	42.38	46.00	-3.62	QP
5	*	447.9821	53.82	-10.02	43.80	46.00	-2.20	QP
6		549.0193	45.51	-7.70	37.81	46.00	-8.19	QP

3.2.8 TEST RESULTS (1GHZ~11GHZ)


Polar (H/V)	Frequency	Meter Reading	Pre- amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
operation frequency:902.75									
V	1805.50	51.69	33.75	5.38	20.46	43.78	74.00	-30.22	PK
V	1805.50	43.15	33.75	5.38	20.46	35.24	54.00	-18.76	AV
V	2708.25	51.14	34.45	6.61	21.57	44.87	74.00	-29.13	PK
V	2708.25	43.71	34.45	6.61	21.57	37.44	54.00	-16.56	AV
V	10308.00	51.70	36.29	9.16	24.57	49.14	74.00	-24.86	PK
H	1805.50	50.42	33.75	5.38	20.46	42.51	74.00	-31.49	PK
H	1805.50	43.19	33.75	5.38	20.46	35.28	54.00	-18.72	AV
H	2708.25	54.64	34.45	6.61	21.57	48.37	74.00	-25.63	PK
H	2708.25	43.33	34.45	6.61	21.57	37.06	54.00	-16.94	AV
H	10308.00	54.62	36.29	9.16	24.57	52.06	74.00	-21.94	PK
operation frequency:914.75									
V	1829.50	53.21	33.75	5.38	20.46	45.30	74.00	-28.70	PK
V	1829.50	43.74	33.75	5.38	20.46	35.83	54.00	-18.17	AV
V	2744.25	53.35	34.45	6.61	21.57	47.08	74.00	-26.92	PK
V	2744.25	43.76	34.45	6.61	21.57	37.49	54.00	-16.51	AV
V	10308.00	52.17	36.29	9.16	24.57	49.61	74.00	-24.39	PK
H	1829.50	51.94	33.75	5.38	20.46	44.03	74.00	-29.97	PK
H	1829.50	43.26	33.75	5.38	20.46	35.35	54.00	-18.65	AV
H	2744.25	54.96	34.45	6.61	21.57	48.69	74.00	-25.31	PK
H	2744.25	43.53	34.45	6.61	21.57	37.26	54.00	-16.74	AV
H	10308.00	52.25	36.29	9.16	24.57	49.69	74.00	-24.31	PK
operation frequency:927.25									
V	1854.50	52.09	33.75	5.38	20.46	44.18	74.00	-29.82	PK
V	1854.50	43.98	33.75	5.38	20.46	36.07	54.00	-17.93	AV
V	2781.75	53.12	34.45	6.61	21.57	46.85	74.00	-27.15	PK
V	2781.75	43.05	34.45	6.61	21.57	36.78	54.00	-17.22	AV
V	10308.00	51.84	36.29	9.16	24.57	49.28	74.00	-24.72	PK
H	1854.50	52.75	33.75	5.38	20.46	44.84	74.00	-29.16	PK
H	1854.50	43.12	33.75	5.38	20.46	35.21	54.00	-18.79	AV
H	2781.75	54.34	34.45	6.61	21.57	48.07	74.00	-25.93	PK
H	2781.75	43.55	34.45	6.61	21.57	37.28	54.00	-16.72	AV
H	10308.00	52.41	36.29	9.16	24.57	49.85	74.00	-24.15	PK

Remark:


1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For Conducted
Ant 1





Lowest channel



Middle channel




Highest channel

Ant 2

Lowest channel

Middle channel

Highest channel


Ant 3



Lowest channel



Middle channel



Highest channel


Ant 4



Lowest channel



Middle channel



Highest channel

3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz




3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	DC 9V from adapter input AC 120V/60Hz		
Test Mode :	Mode 1		


Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		901.9000	30.28	-1.49	28.79	46.00	-17.21	peak
2		902.0000	23.01	-1.48	21.53	46.00	-24.47	peak
3	*	902.7500	89.45	-1.48	87.97	46.00	41.97	peak


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Vertical
Test Voltage :	DC 9V from adapter input AC 120V/60Hz		
Test Mode :	Mode 1		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		901.9100	31.06	-1.49	29.57	46.00	-16.43	peak
2		902.0000	24.79	-1.48	23.31	46.00	-22.69	peak
3	*	902.7500	89.51	-1.48	88.03	46.00	42.03	peak


Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	DC 9V from adapter input AC 120V/60Hz		
Test Mode :	Mode 4		


Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dB	dBuV/m	dB/m	dB
1	*	927.2500	100.96	-1.29	99.67	46.00	53.67 peak
2		928.0000	36.52	-1.28	35.24	46.00	-10.76 peak
3		929.5900	28.56	-1.27	27.29	46.00	-18.71 peak

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Vertical
Test Voltage :	DC 9V from adapter input AC 120V/60Hz		
Test Mode :	Mode 4		


Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	927.2500	91.26	-1.29	89.97	46.00	43.97	peak
2		928.0000	25.20	-1.28	23.92	46.00	-22.08	peak
3		928.1000	31.60	-1.28	30.32	46.00	-15.68	peak


For Conducted Unhopping







Hopping Ant 3



Hopping Ant 4

4. BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

4.1.1 TEST PROCEDURE

1. Set RBW = 1%-5%OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

Temperature :	26°C	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 9V from adapter input AC 120V/60Hz
Test Mode :	TX Mode /CH01, CH25, CH50		

	Frequency (MHz)	20dB Bandwidth (kHz)	Result
Ant1	902.75	137.0	Pass
	914.75	136.0	Pass
	927.25	134.5	Pass
Ant2	902.75	134.2	Pass
	914.75	135.4	Pass
	927.25	134.2	Pass
Ant3	902.75	136.4	Pass
	914.75	135.3	Pass
	927.25	134.2	Pass
Ant4	902.75	136.6	Pass
	914.75	135.8	Pass
	927.25	134.4	Pass





5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥50	902-928	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW ≥ 1% of the span
VB	VBW ≥ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100KHz, VBW=3fere3rddrnryyt566tryiugmj00KHz, Sweep time = Auto.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP




5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	DC 9V from adapter input AC 120V/60Hz
Test Mode :	Hopping Mode		

Antenna	Number of Hopping Channel	Limit	Result
1	50	≥50	PASS
2	50	≥50	PASS
3	50	≥50	PASS
4	50	≥50	PASS



6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	902-928	PASS

6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 100KHz and VBW to 300KHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


6.1.5 TEST RESULTS

Frequency	Antenna	Dwell time(ms)	Limit(ms)	Result
914.75MHz	1	127.2	400	Pass
914.75MHz	2	128.0	400	Pass
914.75MHz	3	131.2	400	Pass
914.75MHz	4	128.8	400	Pass

Within 10 s period, the average time of occupancy = Time slot length (ms) * hops number / channel @ 10s

Within 20 s period, the average time of occupancy = Within 10 s period, the average time of occupancy*2





7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 902-928 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100 kHz (Channel Separation)
VB	300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP




7.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.1.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	DC 9V from adapter input AC 120V/60Hz
Test Mode :	Tx Mode		

Test Mode	Antenna	Ch. Separation (MHz)	Limit (MHz)	Result
TX	1	0.498	0.091	Complies
TX	2	0.498	0.091	Complies
TX	3	0.498	0.181	Complies
TX	4	0.498	0.181	Complies



8. PEAK OUTPUT POWER

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	30Bm or 20.96dBm	902-928	PASS

8.1.1 TEST PROCEDURE

- The EUT was directly connected to the Power meter

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	DC 9V from adapter input AC 120V/60Hz
Test Mode :	CH01/ CH25 /CH50		

Test Channel		Peak Output Power (dBm)	LIMIT (dBm)
CH00	Ant 1	14.35	30.00
	Ant 2	14.25	
	Ant 3	14.17	
	Ant 4	14.64	
CH25	Ant 1	14.52	30.00
	Ant 2	14.19	
	Ant 3	14.68	
	Ant 4	14.39	
CH78	Ant 1	14.51	30.00
	Ant 2	14.53	
	Ant 3	14.62	
	Ant 4	14.19	

9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is External antenna,. It comply with the standard requirement.

10. TEST SEUUP PHOTO

Radiated Measurement Photos



Conducted Measurement Photos



11. EUT PHOTO





***** END OF REPORT *****