

FRONT VIEW

3.3 HOW TO CONNECT THE APP TO THE RTUAL

1. CHARGE THE BATTERY
2. CONNECT THE RTUAL TO THE APP
3. CONNECT THE RTUAL TO THE APP

3.4 HOW TO CREATE A MESSAGE

1. CHARGE THE BATTERY
2. CONNECT THE RTUAL TO THE APP
3. CONNECT THE RTUAL TO THE APP

6. CUSTOMER SERVICE CONTACT

For more information, please contact info@martini.com

7. RTUAL WARNINGS

- Do not use the RTUAL in a wet or damp environment.
- Do not use the RTUAL in a hot or cold environment.
- Do not use the RTUAL in a high humidity environment.
- Do not use the RTUAL in a high temperature environment.
- Do not use the RTUAL in a high pressure environment.
- Do not use the RTUAL in a high vibration environment.
- Do not use the RTUAL in a high magnetic field environment.
- Do not use the RTUAL in a high electromagnetic interference environment.
- Do not use the RTUAL in a high radio frequency environment.
- Do not use the RTUAL in a high power environment.
- Do not use the RTUAL in a high speed environment.
- Do not use the RTUAL in a high acceleration environment.
- Do not use the RTUAL in a high deceleration environment.
- Do not use the RTUAL in a high shock environment.
- Do not use the RTUAL in a high impact environment.
- Do not use the RTUAL in a high pressure environment.
- Do not use the RTUAL in a high vibration environment.
- Do not use the RTUAL in a high magnetic field environment.
- Do not use the RTUAL in a high electromagnetic interference environment.
- Do not use the RTUAL in a high radio frequency environment.
- Do not use the RTUAL in a high power environment.
- Do not use the RTUAL in a high speed environment.
- Do not use the RTUAL in a high acceleration environment.
- Do not use the RTUAL in a high deceleration environment.
- Do not use the RTUAL in a high shock environment.
- Do not use the RTUAL in a high impact environment.

8. TECHNICAL DATA

- Battery: 3.7V 100mAh
- Charging time: 2 hours
- Operating time: 24 hours
- Operating temperature: -10°C to 40°C
- Storage temperature: -20°C to 60°C
- Humidity: 10% to 90%
- Pressure: 1013hPa
- Vibration: 0.1g
- Shock: 10g
- Impact: 10J
- Magnetic field: 10mT
- Electromagnetic interference: 10V/m
- Radio frequency: 10dBm
- Power: 10W
- Speed: 10km/h
- Acceleration: 10g
- Deceleration: 10g
- Shock: 10g
- Impact: 10J

4000314 RM RTUAL DE SERVICE A LA BOUTEILLE
(7875 dL - VSOP / 1738 / CLUB) - MODE D'EMPLOI

CONTENU COMPLET

- RTUAL
- Chargeur
- Câble USB
- Manuel d'emploi

RoHS CE

FCC Statement:
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
(1)Reorient or relocate the receiving antenna.
(2)Increase the separation between the equipment and receiver.
(3)Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
(4)Consult the dealer or an experienced radio/TV technician for help.
Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) The device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

CAUTION: RISK OF EXPLOSION IF BATTERY IS REPLACED BY AN INCORRECT TYPE. DISPOSE OF USED BATTERIES ACCORDING TO THE INSTRUCTIONS.

BACK VIEW

1. COMMENT CHARGER LE RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

2. COMMENT OUVRIR LE RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3. COMMENT PERSONNALISER LE RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3.1 HOW TO SWITCH ON/OFF

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3.2 LIGHTING

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

DIE CUT

FRONT VIEW

1. HOW TO CHARGE THE RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

2. HOW TO OPEN THE RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3. HOW TO PERSONNALISER LE RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3.1 COMMENT ALLUMER/ÉTEINDRE

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3.2 ÉCLAIRAGE

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

BACK VIEW

3.3 COMMENT CONNECTER L'APPLICATION AU RTUAL

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

3.4 COMMENT CHERCHER UN MESSAGE

1. CHARGEZ LA BATTERIE
2. CONNECTEZ LE RTUAL AU CHARGEUR
3. CONNECTEZ LE RTUAL AU CHARGEUR

6. CONTACT DU SERVICE CLIENT

For more information, please contact info@martini.com

7. AVERTISSEMENTS

- Do not use the RTUAL in a wet or damp environment.
- Do not use the RTUAL in a hot or cold environment.
- Do not use the RTUAL in a high humidity environment.
- Do not use the RTUAL in a high temperature environment.
- Do not use the RTUAL in a high pressure environment.
- Do not use the RTUAL in a high vibration environment.
- Do not use the RTUAL in a high magnetic field environment.
- Do not use the RTUAL in a high electromagnetic interference environment.
- Do not use the RTUAL in a high radio frequency environment.
- Do not use the RTUAL in a high power environment.
- Do not use the RTUAL in a high speed environment.
- Do not use the RTUAL in a high acceleration environment.
- Do not use the RTUAL in a high deceleration environment.
- Do not use the RTUAL in a high shock environment.
- Do not use the RTUAL in a high impact environment.

8. DONNÉES TECHNIQUES

- Batterie: 3.7V 100mAh
- Charging time: 2 hours
- Operating time: 24 hours
- Operating temperature: -10°C to 40°C
- Storage temperature: -20°C to 60°C
- Humidity: 10% to 90%
- Pressure: 1013hPa
- Vibration: 0.1g
- Shock: 10g
- Impact: 10J

4000314 RM BOUTEILLE SERVICE RTUAL (7875 dL - VSOP / 1738 / CLUB) - INSTRUCTION MANUAL

CONTENU COMPLET

- RTUAL
- Chargeur
- Câble USB
- Manuel d'emploi

RoHS CE

DIE CUT