

FCC Measurement/Technical Report on

In Cable Control and Protection Device Model IC-CPD

FCC ID: 2AT4E-ICCPDG2HIGH
IC: 25285-ICCPDG2HIGH

Test Report Reference: MDE_BEBRO_1501_FCCb_rev01

Test Laboratory:

7layers GmbH
Borsigstrasse 11
40880 Ratingen
Germany



Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7layers GmbH
Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350

Geschäftsführer/
Managing Directors:
Frank Spiller
Bernhard Retka
Alexandre Norré-Oudard

Registergericht/registered:
Düsseldorf HRB 75554
UST-Id.-Nr./VAT-No. DE203159652
Steuer-Nr./TAX-No. 147/5869/0385

*a Bureau Veritas
Group Company*
www.7layers.com

Table of content

1 Applied Standards and Test Summary	3
1.1 Applied Standards	3
1.2 FCC-IC Correlation Table	4
1.3 Measurement Summary / Signatures	5
2 Revision History	8
3 Administrative Data	9
3.1 Testing Laboratory	9
3.2 Project Data	9
3.3 Applicant Data	9
3.4 Manufacturer Data	9
4 Test object Data	10
4.1 General EUT Description	10
4.2 EUT Main components	12
4.3 Ancillary Equipment	13
4.4 Auxiliary Equipment	13
4.5 EUT Setups	13
4.6 Operating Modes	14
4.7 Product labelling	15
5 Test Results	16
5.1 Conducted Emissions at AC Mains	16
5.2 Occupied Bandwidth (6 dB)	19
5.3 Occupied Bandwidth (99%)	21
5.4 Peak Power Output	23
5.5 Spurious RF Conducted Emissions	25
5.6 Transmitter Spurious Radiated Emissions	28
5.7 Band Edge Compliance Conducted	35
5.8 Band Edge Compliance Radiated	38
5.9 Power Density	41
6 Test Equipment	44
7 Antenna Factors, Cable Loss and Sample Calculations	48
7.1 LISN R&S ESH3-Z5 (150 kHz – 30 MHz)	48
7.2 Antenna R&S HFH2-Z2 (9 kHz – 30 MHz)	49
7.3 Antenna R&S HL562 (30 MHz – 1 GHz)	50
7.4 Antenna R&S HF907 (1 GHz – 18 GHz)	51
7.5 Antenna EMCO 3160-09 (18 GHz – 26.5 GHz)	52
7.6 Antenna EMCO 3160-10 (26.5 GHz – 40 GHz)	53
8 Setup Drawings	54
9 Measurement Uncertainties	55
10 Photo Report	55

1 APPLIED STANDARDS AND TEST SUMMARY

1.1 APPLIED STANDARDS

Type of Authorization

Certification for an Intentional Radiator.

Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 and 15 (10-1-17 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz

Note:

The tests were selected and performed with reference to the FCC Public Notice "Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of the FCC Rules, 558074 D01 15.247 Meas Guidance v05r01, 2019-02-11". ANSI C63.10–2013 is applied.

Summary Test Results:

The EUT complied with all performed tests as listed in chapter 1.3 Measurement Summary / Signatures.

1.2 FCC-IC CORRELATION TABLE

**Correlation of measurement requirements for
DTS (e.g. WLAN 2.4 GHz, BT LE) equipment
from
FCC and IC**

DTS equipment

Measurement	FCC reference	IC reference
Conducted emissions on AC Mains	§ 15.207	RSS-Gen Issue 5: 8.8
Occupied bandwidth	§ 15.247 (a) (2)	RSS-247 Issue 2: 5.2 (a)
Peak conducted output power	§ 15.247 (b) (3), (4)	RSS-247 Issue 2: 5.4 (d)
Transmitter spurious RF conducted emissions	§ 15.247 (d)	RSS-Gen Issue 5: 6.13 / 8.9/8.10; RSS-247 Issue 2: 5.5
Transmitter spurious radiated emissions	§ 15.247 (d); § 15.209 (a)	RSS-Gen Issue 5: 6.13 / 8.9/8.10; RSS-247 Issue 2: 5.5
Band edge compliance	§ 15.247 (d)	RSS-247 Issue 2: 5.5
Power density	§ 15.247 (e)	RSS-247 Issue 2: 5.2 (b)
Antenna requirement	§ 15.203 / 15.204	RSS-Gen Issue 5: 8.3
Receiver spurious emissions	–	–

1.3 MEASUREMENT SUMMARY / SIGNATURES

47 CFR CHAPTER I FCC PART 15 **§ 15.207**
Subpart C §15.247

Conducted Emissions at AC Mains

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Operating mode, Connection to AC mains worst case, direct	S01_AI02	2019-03-07	Passed	Passed

47 CFR CHAPTER I FCC PART 15 **§ 15.247 (a) (2)**
Subpart C §15.247

Occupied Bandwidth (6 dB)

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency				
WLAN b, high	S01_AE01	2018-10-16	Passed	Passed
WLAN b, low	S01_AE01	2018-10-16	Passed	Passed
WLAN b, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN g, high	S01_AE01	2018-10-16	Passed	Passed
WLAN g, low	S01_AE01	2018-10-16	Passed	Passed
WLAN g, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, mid	S01_AE01	2018-10-16	Passed	Passed

47 CFR CHAPTER I FCC PART 15 **IC RSS-Gen & IC TRC-43; Ch. 6.7 & Ch. 8**
Subpart C §15.247

Occupied Bandwidth (99%)

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency				
WLAN b, high	S01_AE01	2018-09-25	N/A	Passed
WLAN b, low	S01_AE01	2018-09-25	N/A	Passed
WLAN b, mid	S01_AE01	2018-09-25	N/A	Passed
WLAN g, high	S01_AE01	2018-09-25	N/A	Passed
WLAN g, low	S01_AE01	2018-09-25	N/A	Passed
WLAN g, mid	S01_AE01	2018-09-25	N/A	Passed
WLAN n 20 MHz, high	S01_AE01	2018-09-25	N/A	Passed
WLAN n 20 MHz, low	S01_AE01	2018-09-25	N/A	Passed
WLAN n 20 MHz, mid	S01_AE01	2018-09-25	N/A	Passed
WLAN n 40 MHz, high	S01_AE01	2018-09-25	N/A	Passed
WLAN n 40 MHz, low	S01_AE01	2018-09-25	N/A	Passed
WLAN n 40 MHz, mid	S01_AE01	2018-09-25	N/A	Passed

47 CFR CHAPTER I FCC PART 15
Subpart C §15.247
§ 15.247 (b) (3)
Peak Power Output

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Measurement method				
WLAN b, high, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN b, low, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN b, mid, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN g, high, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN g, low, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN g, mid, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, high, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, low, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, mid, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, high, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, low, conducted	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, mid, conducted	S01_AE01	2018-10-16	Passed	Passed

47 CFR CHAPTER I FCC PART 15
Subpart C §15.247
§ 15.247 (d)
Spurious RF Conducted Emissions

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency				
WLAN b, high	S01_AE01	2018-10-16	Passed	Passed
WLAN b, low	S01_AE01	2018-10-16	Passed	Passed
WLAN b, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN g, high	S01_AE01	2018-10-16	Passed	Passed
WLAN g, low	S01_AE01	2018-10-16	Passed	Passed
WLAN g, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, mid	S01_AE01	2018-10-16	Passed	Passed

47 CFR CHAPTER I FCC PART 15
Subpart C §15.247
§ 15.247 (d)

Transmitter Spurious Radiated Emissions

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Measurement range				
WLAN b, high, 1 GHz - 26 GHz	S01_AA01	2018-11-03	Passed	Passed
WLAN b, high, 30 MHz - 1 GHz	S01_AA01	2018-10-29	Passed	Passed
WLAN b, low, 1 GHz - 26 GHz	S01_AA01	2018-11-03	Passed	Passed
WLAN b, low, 30 MHz - 1 GHz	S01_AA01	2018-10-29	Passed	Passed
WLAN b, mid, 1 GHz - 26 GHz	S01_AA01	2018-11-03	Passed	Passed
WLAN b, mid, 30 MHz - 1 GHz	S01_AA01	2018-10-29	Passed	Passed
WLAN b, mid, 9 kHz - 30 MHz	S01_AA01	2018-10-24	Passed	Passed
WLAN g, high, 1 GHz - 26 GHz	S01_AA01	2018-11-03	Passed	Passed
WLAN g, low, 1 GHz - 26 GHz	S01_AA01	2018-11-03	Passed	Passed
WLAN g, low, 1 GHz - 26 GHz	S01_AG02	2019-03-14	Passed	Passed
WLAN g, low, 30 MHz - 1 GHz	S01_AG02	2019-03-22	Passed	Passed
WLAN g, low, 9 kHz - 30 MHz	S01_AG02	2019-03-22	Passed	Passed
WLAN g, mid, 1 GHz - 26 GHz	S01_AA01	2018-11-03	Passed	Passed

47 CFR CHAPTER I FCC PART 15
§ 15.247 (d)
Subpart C §15.247

Band Edge Compliance Conducted

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Band Edge				
WLAN b, high, high	S01_AE01	2018-10-16	Passed	Passed
WLAN b, low, low	S01_AE01	2018-10-16	Passed	Passed
WLAN g, high, high	S01_AE01	2018-10-16	Passed	Passed
WLAN g, low, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, high, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, low, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, high, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, low, low	S01_AE01	2018-10-16	Passed	Passed

47 CFR CHAPTER I FCC PART 15
§ 15.247 (d)
Subpart C §15.247

Band Edge Compliance Radiated

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency, Band Edge				
WLAN b, high, high	S01_AA01	2018-11-03	Passed	Passed
WLAN g, high, high	S01_AA01	2018-11-03	Passed	Passed
WLAN n 20 MHz, high, high	S01_AA01	2018-11-13	Passed	Passed
WLAN n 40 MHz, high, high	S01_AA01	2018-11-13	Passed	Passed

47 CFR CHAPTER I FCC PART 15
Subpart C §15.247
§ 15.247 (e)
Power Density

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode	Setup	Date	FCC	IC
Radio Technology, Operating Frequency				
WLAN b, high	S01_AE01	2018-10-16	Passed	Passed
WLAN b, low	S01_AE01	2018-10-16	Passed	Passed
WLAN b, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN g, high	S01_AE01	2018-10-16	Passed	Passed
WLAN g, low	S01_AE01	2018-10-16	Passed	Passed
WLAN g, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 20 MHz, mid	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, high	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, low	S01_AE01	2018-10-16	Passed	Passed
WLAN n 40 MHz, mid	S01_AE01	2018-10-16	Passed	Passed

COMMENT:

The tests were repeated for the worst-case tests with new Sample with newer Hardware/Software.


 7 layers GmbH, Borsigstr. 11
 40880 Ratingen, Germany
 Phone +49 (0)2102 749 0

 (responsible for accreditation scope)
 Marco Kullik

 (responsible for testing and report)
 Wolfgang Richter

2 REVISION HISTORY

Report version control			
Version	Release date	Change Description	Version validity
initial	2019-03-29	--	invalid
rev01	2019-07-26	Frontpage: FCC ID and IC changed by applicant, detailed date of testing added in summary table	valid

3 ADMINISTRATIVE DATA

3.1 TESTING LABORATORY

Company Name: 7layers GmbH

Address: Borsigstr. 11
40880 Ratingen
Germany

The test facility is accredited by the following accreditation organisation:

Laboratory accreditation no: DAkkS D-PL-12140-01-00
FCC Designation Number: DE0015
FCC Test Firm Registration: 929146
ISED CAB Identifier DE0007; ISED#: 3699A

Responsible for accreditation scope: Marco Kullik

Report Template Version: 2019-02-12

3.2 PROJECT DATA

Responsible for testing and report: Wolfgang Richter

Employees who performed the tests: documented internally at 7Layers

Date of Report: 2019-07-26

Testing Period: 2018-09-25 to 2019-03-22

3.3 APPLICANT DATA

Company Name: eSystems MTG GmbH

Address: Bahnhofstraße 100
73240 Wendlingen
Germany

Contact Person: Frank Beger

3.4 MANUFACTURER DATA

Company Name: eSystems MTG GmbH

Address: Bahnhofstraße 100
73240 Wendlingen
Germany

Contact Person: Frank Beger

4 TEST OBJECT DATA

4.1 GENERAL EUT DESCRIPTION

Declared EUT data by the supplier	
Kind of Device product description	In Cable Control and Protection Device IEEE Std. 802.11™ a/b/g/n/ac WLAN/WIFI Device supporting 2.4 GHz band (Channel 1 to 11) and 5 GHz Sub band 1 (5150 – 5250 MHz) All variants of the EUT uses the identical (HW/SW) Wi-Fi-/WLAN-Module.
Product name	In Cable Control and Protection Device
Type	Model IC-CPD
Power Supply Type	AC mains
Nominal Voltage / Frequency	90 V - 240 V / 50 Hz, 60 Hz
Test Voltage / Frequency	tested with 120 V / 60 Hz
Highest internal frequency	5.3 GHz
Ports	Port Infrastructure, port Car
Special software used for testing	Original SW used
Antenna type / Gain	integral antenna / 2.4 dBi
Occupied Channel Bandwidth	WLAN b, g: 20 MHz WLAN n: 20 MHz, 40 MHz
Operating Modes, used Modulations, Data Rates and Settings for testing	WLAN 2.4 GHz band: Mode b: DSSS Modulation, 1 Mbps, power setting 13 dBm, Mode g: OFDM Modulation, 6 Mbps, power setting 14 dBm, Mode n: OFDM Modulation, MSC 0 (20 MHz), power setting 13 dBm, Mode n: OFDM Modulation, MSC 0 (40 MHz), power setting 13 dBm

Additional EUT data declared by manufacturer:	<p>OEM's trade names: Porsche Mobile Charger Connect Audi Charging System Connect Bentley Home Charging Unit</p> <p>Model: IC-CPD</p> <p>Variants:</p> <p>Porsche: 9Y0.971.675.BE = (7,2 kW) 9Y0.971.675.BG = (11 kW) 9Y0.971.675.BJ = (22 kW) 9Y0.971.675.BL = (9,6 kW) for UL-Region 9Y0.971.675.BM = (9,6 kW) for Japan</p> <p>Audi: 8V4.971.675.BE = (7,2 kW) 8V4.971.675.BG = (11 kW) 8V4.971.675.BJ = (22 kW) 8V4.971.675.BL = (9,6 kW) for UL-Region</p> <p>Bentley: 36A.971.675.F = (7,2 kW) 36A.971.675.G = (9,6 kW) for UL-Region 36A.971.675.J = (9,6 kW) for Japan</p>
---	--

The main components of the EUT are listed and described in chapter 3.2 EUT Main components.

4.2 EUT MAIN COMPONENTS

Sample Name	Sample Code	Description
EUT A	DE1321000aa01	Sample with integral antenna
Sample Parameter	Value	
Serial No.	0000680	
HW Version	09	
SW Version	SW_C: 2350, SW_P: 1830	
Comment	Radiated sample	
Variant	9Y0.971.675.BJ	

Sample Name	Sample Code	Description
EUT E	DE1321000ae01	Sample with temporary SMA antenna connector
Sample Parameter	Value	
Serial No.	0000673	
HW Version	09	
SW Version	SW_C: 2350, SW_P: 1830	
Comment	Conducted sample	
Variant	9Y0.971.675.BJ	

Sample Name	Sample Code	Description
EUT G	DE1321000ag02	Sample with integral antenna
Sample Parameter	Value	
Serial No.	0002136	
HW Version	13	
SW Version	SW_C: 2901, SW_P: 1900	
Comment	Radiated Sample with newer HW/SW	
Variant	9Y0.971.675.BL	

Sample Name	Sample Code	Description
EUT I	DE1321000ai02	Sample with integral antenna
Sample Parameter	Value	
Serial No.	0002123	
HW Version	13	
SW Version	SW_C: 2901, SW_P: 1900	
Comment	Radiated Sample with newer HW/SW	
Variant	9Y0.971.675.BL	

NOTE: The short description is used to simplify the identification of the EUT in this test report.

4.3 ANCILLARY EQUIPMENT

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless, Ancillary Equipment can influence the test results.

Device	Details (Manufacturer, Type Model, OUT Code)	Description
-	-	-

4.4 AUXILIARY EQUIPMENT

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless, Auxiliary Equipment can influence the test results.

Device	Details (Manufacturer, Type Model, HW, SW, S/N)	Description
ANC1	HARTING, 7PP.971.678.BH, -, -, -	Cable at Port Infrastructure
ANC2	HARTING, 7PP.971.676.BL, -, -, -	Cable at Port Car

4.5 EUT SETUPS

This chapter describes the combination of EUTs, and equipment used for testing. The rationale for selecting the EUTs, ancillary and auxiliary equipment and interconnecting cables, is to test a representative configuration meeting the requirements of the referenced standards.

Setup	Combination of EUTs	Description and Rationale
S01_AI02	EUT I, ANC1, ANC2,	Set-up used for radiated tests
S01_AA01	EUT A, ANC1, ANC2,	Set-up used for radiated tests
S01_AE01	EUT E, ANC1, ANC2,	Set-up used for conducted tests
S01_AG02	EUT G, ANC1, ANC2,	Set-up used for radiated tests

4.6 OPERATING MODES

This chapter describes the operating modes of the EUTs used for testing.

4.6.1 TEST CHANNELS

2.4 GHz ISM		
2400 - 2483.5 MHz		
low	mid	high
1	6	11
2412	2437	2462

40 MHz Test Channels:			
Channel:	low	mid	high
3	6	11	
2422	2437	2462	

4.6.2 USED SETTINGS AT EUT

IEEE 802.11 Mode	IEEE 802.11 channel	Centre frequency MHz	Position in Band (low/mid/high)	Input parameter (Channel) at EUT (red if different to IEEE 802.11)	Band	Band to be set at EUT	Bandwidth MHz	Data rate to be set at EUT	Power level to be set at EUT
	1	2412	low	1	2.4 GHz	2g	20	1 Mbps	13
b	6	2437	mid	6	2.4 GHz	2g	20	1 Mbps	13
	11	2462	high	11	2.4 GHz	2g	20	1 Mbps	13
	1	2412	low	1	2.4 GHz	2g	20	6 Mbps	14
g	6	2437	mid	6	2.4 GHz	2g	20	6 Mbps	14
	11	2462	high	11	2.4 GHz	2g	20	6 Mbps	14
	1	2412	low	1	2.4 GHz	2g	20	MCS0	13
n	6	2437	mid	6	2.4 GHz	2g	20	MCS0	13
	11	2462	high	11	2.4 GHz	2g	20	MCS0	13
	3	2422	low	1 (not 3!)	2.4 GHz	2g	40	MCS0	13
n	6	2437	mid	4 (not 6!)	2.4 GHz	2g	40	MCS0	13
	11	2462	high	13 (not 11!)	2.4 GHz	2g	40	MCS0	13

4.7 PRODUCT LABELLING

4.7.1 FCC ID LABEL

Please refer to the documentation of the applicant.

4.7.2 LOCATION OF THE LABEL ON THE EUT

Please refer to the documentation of the applicant.

5 TEST RESULTS

5.1 CONDUCTED EMISSIONS AT AC MAINS

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

5.1.1 TEST DESCRIPTION

The test set-up was made in accordance to the general provisions of ANSI C 63.10. The Equipment Under Test (EUT) was setup in a shielded room to perform the conducted emissions measurements in a typical installation configuration. The EUT was powered from 50 μ H || 50 Ohm Line Impedance Stabilization Network (LISN). The LISN's unused connections were terminated with 50 Ohm loads.

The measurement procedure consists of two steps. It is implemented into the EMI test software EMC-32 from R&S.

Step 1: Preliminary scan

Intention of this step is, to determine the conducted EMI-profile of the EUT.

EMI receiver settings:

- Detector: Peak – Maxhold & Average
- Frequency range: 150 kHz – 30 MHz
- Frequency steps: 2.5 kHz
- IF-Bandwidth: 9 kHz
- Measuring time / Frequency step: 100 ms (FFT-based)
- Measurement on phase + neutral lines of the power cords

On basis of this preliminary scan the highest amplitudes and the corresponding frequencies relative to the limit are identified. Emissions above the limit and emissions which are in the 10 dB range below the limit are considered.

Step 2: Final measurement

Intention of this step is, to determine the highest emissions with the settings defined in the test specification for the frequencies identified in step 1.

EMI receiver settings:

- Detector: Quasi-Peak
- IF Bandwidth: 9 kHz
- Measuring time: 1 s / frequency

At each frequency determined in step 1, four measurements are performed in the following combinations:

- 1) Neutral lead - reference ground (PE grounded)
- 2) Phase lead - reference ground (PE grounded)
- 3) Neutral lead - reference ground (PE floating)
- 4) Phase lead - reference ground (PE floating)

The highest value is reported.

5.1.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.207

Frequency (MHz)	QP Limits (dB μ V)	AV Limits (dB μ V)
0.15 – 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

Used conversion factor: Limit (dB μ V) = 20 log (Limit (μ V)/1 μ V).

5.1.3 TEST EQUIPMENT USED

- Conducted Emissions FCC

5.1.4 TEST PROTOCOL


Temperature: 25 °C
 Air Pressure: 1017 hPa
 Humidity: 35 %

Power line	PE	Frequency [MHz]	Measured value QP [dB μ V]	Measured value AV [dB μ V]	Limit [dB μ V]	Margin [dB]
please see table below diagram	-	-	-	-	-	-

Remark: Please see next sub-clause for the measurement plot.

5.1.5 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Test Description: Conducted Emissions
Test Standard: FCC §15.207, ANSI C63.10
EUT / Setup Code: DE1321000ai02
Operating Conditions: WLAN 2.4 GHz Traffic, no car connected, 120 V 60 Hz
Comment: No car connected
Legend: Trace: blue = PK, green = CISPR AV; Star: red or blue = critical frequency; Rhombus: blue = final QP, green = final CISPR AV
Tested Port / used LISN: AC mains => ESH3-Z5
Termination of other ports: Car port => no connection to GND



Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)
0.150000	---	48.00	56.00	8.00	1000.0	9.000	N	FLO	10.1
0.161250	---	46.90	55.40	8.50	1000.0	9.000	N	FLO	10.1
0.174750	---	45.57	54.73	9.16	1000.0	9.000	N	FLO	10.1
0.186000	---	44.02	54.21	10.19	1000.0	9.000	N	FLO	10.1
0.269250	---	39.31	51.14	11.84	1000.0	9.000	N	FLO	10.1
0.955500	---	37.89	46.00	8.11	1000.0	9.000	N	GND	10.1
1.074750	---	35.40	46.00	10.60	1000.0	9.000	N	GND	10.2
1.196250	---	39.99	46.00	6.01	1000.0	9.000	N	GND	10.2
1.434750	---	39.13	46.00	6.87	1000.0	9.000	N	GND	10.2
1.673250	---	35.30	46.00	10.70	1000.0	9.000	N	GND	10.2
2.442750	20.48	---	56.00	35.52	1000.0	9.000	L1	GND	10.3
3.187500	44.12	---	56.00	11.88	1000.0	9.000	L1	GND	10.3
4.200000	43.59	---	56.00	12.41	1000.0	9.000	L1	GND	10.4
4.983000	45.57	---	56.00	10.43	1000.0	9.000	L1	GND	10.4
5.937000	25.29	---	60.00	34.71	1000.0	9.000	L1	GND	10.5
7.593000	24.18	---	60.00	35.82	1000.0	9.000	N	GND	10.6
9.384000	45.55	---	60.00	14.45	1000.0	9.000	N	GND	10.6
10.554000	46.09	---	60.00	13.91	1000.0	9.000	N	GND	10.6
14.644500	48.73	---	60.00	11.27	1000.0	9.000	N	GND	10.9
15.236250	36.15	---	60.00	23.85	1000.0	9.000	N	GND	10.9

5.2 OCCUPIED BANDWIDTH (6 DB)

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

5.2.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.

The results recorded were measured with the modulation which produce the worst-case (smallest) emission bandwidth.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Span: 40 / 80 MHz (for 20 / 40 MHz nominal bandwidth)
- Trace: Maxhold
- Sweeps: 100
- Sweptime: Auto FFT
- Detector: Peak

5.2.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (a) (2)

Systems using digital modulation techniques may operate in the 902-928 MHz and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.2.3 TEST PROTOCOL

Ambient temperature: 25 °C
Air Pressure: 1010 hPa
Humidity: 40 %
WLAN b-Mode; 20 MHz; 1 Mbps

Band	Channel No.	Frequency [MHz]	6 dB Bandwidth [MHz]	Limit [MHz]	Margin to Limit [MHz]
2.4 GHz ISM	1	2412	8.3	0.5	7.8
	6	2437	9.2	0.5	8.7
	11	2462	9.2	0.5	8.7

WLAN g-Mode; 20 MHz; 6 Mbps

Band	Channel No.	Frequency [MHz]	6 dB Bandwidth [MHz]	Limit [MHz]	Margin to Limit [MHz]
2.4 GHz ISM	1	2412	16.5	0.5	16.0
	6	2437	16.5	0.5	16.0
	11	2462	16.5	0.5	16.0

WLAN n-Mode; 20 MHz; MCS 0

Band	Channel No.	Frequency [MHz]	6 dB Bandwidth [MHz]	Limit [MHz]	Margin to Limit [MHz]
2.4 GHz ISM	1	2412	16.3	0.5	15.8
	6	2437	16.3	0.5	15.8
	11	2462	16.3	0.5	15.8

WLAN n-Mode; 40 MHz; MCS 0


Band	Channel No.	Frequency [MHz]	6 dB Bandwidth [MHz]	Limit [MHz]	Margin to Limit [MHz]
2.4 GHz ISM	3	2412	36.2	0.5	35.7
	6	2437	35.7	0.5	35.2
	11	2462	36.2	0.5	35.7

Remark: Please see next sub-clause for the measurement plot.

5.2.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

6 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)	Result
2412.000000	8.300000	0.500000	---	2407.850000	2416.150000	6.9	PASS



5.2.5 TEST EQUIPMENT USED

- R&S TS8997

5.3 OCCUPIED BANDWIDTH (99%)

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10

5.3.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Resolution Bandwidth (RBW): 500 kHz / 1 MHz (for 20 / 40 MHz nominal bandwidth)
- Video Bandwidth (VBW): 2 MHz / 3 MHz (for 20 / 40 MHz nominal bandwidth)
- Span: 40 / 80 MHz (for 20 / 40 MHz nominal bandwidth)
- Trace: Maxhold
- Sweeps: 2000
- Sweptime: 20 ms
- Detector: Sample

The 99 % measurement function of the spectrum analyser function was used to determine the 99 % bandwidth.

5.3.2 TEST REQUIREMENTS / LIMITS

No applicable limit.

5.3.3 TEST PROTOCOL

Ambient temperature: 25 °C
Air Pressure: 1010 hPa
Humidity: 40 %
WLAN b-Mode; 20 MHz; 1 Mbps

Band	Channel No.	Frequency [MHz]	99 % Bandwidth [MHz]
2.4 GHz ISM	1	2412	11.6
	6	2437	11.7
	11	2462	11.7

WLAN g-Mode; 20 MHz; 6 Mbps

Band	Channel No.	Frequency [MHz]	99 % Bandwidth [MHz]
2.4 GHz ISM	1	2412	17.8
	6	2437	17.8
	11	2462	17.8

WLAN n-Mode; 20 MHz; MCS 0

Band	Channel No.	Frequency [MHz]	99 % Bandwidth [MHz]
2.4 GHz ISM	1	2412	18.8
	6	2437	18.7
	11	2462	18.7

WLAN n-Mode; 40 MHz; MCS 0

Band	Channel No.	Frequency [MHz]	99 % Bandwidth [MHz]
2.4 GHz ISM	1	2422	36.6
	6	2437	36.7
	11	2462	36.8

Remark: Please see next sub-clause for the measurement plot.

5.3.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")



5.3.5 TEST EQUIPMENT USED

- R&S TS8997

5.4 PEAK POWER OUTPUT

Standard **FCC Part 15 Subpart C**

The test was performed according to:
 ANSI C63.10

5.4.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the output power measurements. The results recorded were measured with the modulation which produces the worst-case (highest) output power. The EUT was connected to the gated RMS power meter via a short coax cable with a known loss.

5.4.2 TEST REQUIREMENTS / LIMITS

DTS devices:

FCC Part 15, Subpart C, §15.247 (b) (3)

For systems using digital modulation techniques in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands: 1 watt.

==> Maximum conducted peak output power: 30 dBm (excluding antenna gain, if antennas with directional gains that do not exceed 6 dBi are used).

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)

5.4.3 TEST PROTOCOL

Ambient temperature: 25 °C
 Air Pressure: 1010 hPa
 Humidity: 40 %
 WLAN b-Mode; 20 MHz; 1 Mbps

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]
2.4 GHz ISM	1	2412	15.7	30.0	14.3
	6	2437	15.8	30.0	14.2
	11	2462	16.0	30.0	14.0

WLAN g-Mode; 20 MHz; 6 Mbps

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]
2.4 GHz ISM	1	2412	13.3	30.0	16.7
	6	2437	13.6	30.0	16.4
	11	2462	13.7	30.0	16.3

WLAN n-Mode; 20 MHz; MCS 0

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]
2.4 GHz ISM	1	2412	12.5	30.0	17.5
	6	2437	12.7	30.0	17.3
	11	2462	13.0	30.0	17.0

WLAN n-Mode; 40 MHz; MCS 0

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]
2.4 GHz ISM	3	2412	13.3	30.0	16.7
	6	2437	13.4	30.0	16.6
	11	2462	13.6	30.0	16.4

Remark:


Please see next sub-clause for the measurement plot.

EIRP output power = Peak Power + Antenna Gain (here +2.4 dBi)

5.4.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Result

DUT Frequency (MHz)	Gated RMS (dBm)	Limit Max (dBm)	Gated EIRP (dBm)	DutyCycle (%)	Result
2462.000000	16.0	30.0	16.0	99.897	PASS



5.4.5 TEST EQUIPMENT USED

- R&S TS8997

5.5 SPURIOUS RF CONDUCTED EMISSIONS

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10

5.5.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the spurious emissions measurements. The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Frequency range: 30 – 25000 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Trace: Maxhold
- Sweeps: 2
- Sweep Time: 330 s
- Detector: Peak

The reference value for the measurement of the spurious RF conducted emissions is determined during the test "band edge compliance conducted". This value is used to calculate the 30 dBc limit.

5.5.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (c)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

5.5.3 TEST PROTOCOL

Ambient temperature: 25 °C
Air Pressure: 1010 hPa
Humidity: 40 %

WLAN b-Mode: 20 MHz; 1 Mbps

Channel No.	Channel Centre Freq. [MHz]	Spurious Freq. [MHz].	Spurious Level. [dBm]	Detector	RBW [kHz]	Ref. Level. [dBm]	Limit [dBc]	Margin to Limit [dB]
1	2412	-	-	PEAK	100	-	-30.0	> 6
6	2437	-	-	PEAK	100	-	-30.0	> 6
11	2462	-	-	PEAK	100	-	-30.0	> 6

WLAN g-Mode: 20 MHz; 6 Mbps

Channel No.	Channel Centre Freq. [MHz]	Spurious Freq. [MHz].	Spurious Level. [dBm]	Detector	RBW [kHz]	Ref. Level. [dBm]	Limit [dBc]	Margin to Limit [dB]
1	2412	-	-	PEAK	100	-	-30.0	> 6
6	2437	-	-	PEAK	100	-	-30.0	> 6
11	2462	-	-	PEAK	100	-	-30.0	> 6

WLAN n-Mode: 20 MHz; MCS 0

Channel No.	Channel Centre Freq. [MHz]	Spurious Freq. [MHz].	Spurious Level. [dBm]	Detector	RBW [kHz]	Ref. Level. [dBm]	Limit [dBc]	Margin to Limit [dB]
1	2412	-	-	PEAK	100	-	-30.0	> 6
6	2437	-	-	PEAK	100	-	-30.0	> 6
11	2462	-	-	PEAK	100	-	-30.0	> 6


WLAN n-Mode: 40 MHz; MCS 0

Channel No.	Channel Centre Freq. [MHz]	Spurious Freq. [MHz].	Spurious Level. [dBm]	Detector	RBW [kHz]	Ref. Level. [dBm]	Limit [dBc]	Margin to Limit [dB]
3	2412	-	-	PEAK	100	-	-30.0	> 6
6	2437	-	-	PEAK	100	-	-30.0	> 6
11	2462	-	-	PEAK	100	-	-30.0	> 6

Remark: Please see next sub-clause for the measurement plot.

5.5.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

WLAN n-Mode; 40 MHz; MCS 0; Ch. 1



Date: 16.OCT.2018 15:50:19

5.5.5 TEST EQUIPMENT USED

- R&S TS8997

5.6 TRANSMITTER SPURIOUS RADIATED EMISSIONS

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10

5.6.1 TEST DESCRIPTION

The test set-up was made in accordance to the general provisions of ANSI C63.10 in a typical installation configuration. The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m² in the semi-anechoic chamber. The influence of the EUT support table that is used between 30–1000 MHz was evaluated.

The measurement procedure is implemented into the EMI test software EMC32 from R&S. Exploratory tests are performed at 3 orthogonal axes to determine the worst-case orientation of a body-worn or handheld EUT. The final test on all kind of EUTs is also performed at 3 axes. A pre-check is performed while the EUT is powered from a DC power source.

1. Measurement up to 30 MHz

The Loop antenna HFH2-Z2 is used.

Step 1: pre measurement

- Anechoic chamber
- Antenna distance: 3 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 - 0.15 MHz and 0.15 – 30 MHz
- Frequency steps: 0.05 kHz and 2.25 kHz
- IF-Bandwidth: 0.2 kHz and 9 kHz
- Measuring time / Frequency step: 100 ms (FFT-based)

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 – 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 0.2 - 10 kHz
- Measuring time / Frequency step: 1 s

2. Measurement above 30 MHz and up to 1 GHz

Step 1: Preliminary scan

This is a preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Antenna distance: 3 m
- Detector: Peak-Maxhold / Quasipeak (FFT-based)
- Frequency range: 30 – 1000 MHz
- Frequency steps: 30 kHz
- IF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100 ms
- Turntable angle range: -180° to 90°
- Turntable step size: 90°

- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: Adjustment measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will slowly vary by $\pm 45^\circ$ around this value. During this action, the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position, the antenna height will also slowly vary by ± 100 cm around the antenna height determined. During this action, the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: $\pm 45^\circ$ around the determined value
- Height variation range: ± 100 cm around the determined value
- Antenna Polarisation: max. value determined in step 1

Step 3: Final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed:

EMI receiver settings for step 4:

- Detector: Quasi-Peak (< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

3. Measurement above 1 GHz

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:

Step 1:

The Equipment Under Test (EUT) was set up on a non-conductive support (tilt device) at 1.5 m height in the fully-anechoic chamber.

All steps were performed with one height (1.5 m) of the receiving antenna only.

The EUT is turned during the preliminary measurement across the elevation axis, with a step size of 90° .

The turn table step size (azimuth angle) for the preliminary measurement is 45° .

Step 2:

Due to the fact, that in this frequency range the test is performed in a fully anechoic room, the height scan of the receiving antenna in step 2 is omitted. Instead of this, a maximum search with a step size $\pm 45^\circ$ for the elevation axis is performed.

The turn table azimuth will slowly vary by $\pm 22.5^\circ$.

The elevation angle will slowly vary by $\pm 45^\circ$.

EMI receiver settings (for all steps):

- Detector: Peak, Average
- IF Bandwidth = 1 MHz

Step 3:

Spectrum analyser settings for step 3:

- Detector: Peak / Average

- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 1 MHz
- Measuring time: 1 s

5.6.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (μ V/m)	Measurement distance (m)	Limits (dB μ V/m)
0.009 – 0.49	2400/F(kHz)@300m	3	(48.5 – 13.8) @300m
0.49 – 1.705	24000/F(kHz)@30m	3	(33.8 – 23.0) @30m
1.705 – 30	30@30m	3	29.5@30m

The measured values are corrected with an inverse linear distance extrapolation factor (40 dB/decade) according FCC 15.31 (2).

Frequency in MHz	Limit (μ V/m)	Measurement distance (m)	Limits (dB μ V/m)
30 – 88	100@3m	3	40.0@3m
88 – 216	150@3m	3	43.5@3m
216 – 960	200@3m	3	46.0@3m
960 - 26000	500@3m	3	54.0@3m
26000 - 40000	500@3m	1	54.0@3m

The measured values above 26 GHz are corrected with an inverse linear distance extrapolation factor (20 dB/decade).

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dB μ V/m) = 20 log (Limit (μ V/m)/1 μ V/m)

5.6.3 TEST PROTOCOL

Temperature: 23 -25 °C
Air Pressure: 1010-1017 hPa
Humidity: 35-41 %

(S01_AA01)

WLAN b-Mode; 20 MHz; 1 Mbps

Applied duty cycle correction (AV): 0.0 dB

Ch. No.	Ch. Centre Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
1	2412	-	-	-	-	-	> 6	RB
6	2437	-	-	-	-	-	> 6	RB
11	2462	-	-	-	-	-	> 6	RB

(S01_AA01)

WLAN g-Mode; 20 MHz; 6 Mbps

Applied duty cycle correction (AV): 0.1 dB

Ch. No.	Ch. Centre Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
1	2412	2390.0	51.4	AV	1000	54.0	2.6	RB
1	2412	2390.0	65.3	PEAK	1000	74.0	8.7	RB
6	2437	-	-	-	-	-	> 6	RB
11	2462	2483.583	46.8	AV	1000	54.0	7.2	RB
11	2462	2483.748	62.2	PEAK	1000	74.0	11.8	RB

(S01_AG02)

WLAN g-Mode; 20 MHz; 6 Mbps


Applied duty cycle correction (AV): 0.1 dB

Ch. No.	Ch. Centre Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
1	2412	1187.0	33.4	AV	1000	54.0	20.6	RB
1	2412	1187.0	46.0	PEAK	1000	74.0	28.0	RB
1	2412	2389.8	42.2	AV	1000	54.0	11.8	RB
1	2412	2389.9	55.9	PEAK	1000	74.0	18.1	RB
1	2412	20829.7	54.9	PEAK	1000	74.0	19.1	RB
1	2412	20830.0	41.5	AV	1000	54.0	12.5	RB
1	2412	22170.2	42.5	AV	1000	54.0	11.5	RB
1	2412	22170.4	55.3	PEAK	1000	74.0	18.7	RB


Remark: Please see next sub-clause for the measurement plot.

5.6.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")


WLAN b-mode, Ch. 6, 20 MHz, 1 Mbps, (S01_AA01)




WLAN b-mode, Ch. 1, 20 MHz, 1 Mbps, (S01_AA01)




WLAN g-mode, Ch. 1, 20 MHz, 1 Mbps, (S01_AA01)




WLAN b-mode, Ch. 1, 20 MHz, 1 Mbps, (S01_AA01)




WLAN g-mode, Ch. 1, 20 MHz, 1 Mbps, (S01_AG01)



WLAN g-mode, Ch. 1, 20 MHz, 1 Mbps, (S01_AG01)



WLAN g-mode, Ch. 1, 20 MHz, 1 Mbps, (S01_AG01)



5.6.5 TEST EQUIPMENT USED

- Radiated Emissions

5.7 BAND EDGE COMPLIANCE CONDUCTED

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10

5.7.1 TEST DESCRIPTION

For the conducted measurement, the Equipment Under Test (EUT) is placed in a shielded room. The reference power was measured in the test case "Spurious RF Conducted Emissions". The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Span for Lower Band Edge: 2310.0 MHz to 2483.5 MHz
- Span for Upper Band Edge: 2400.0 MHz to 2500.0 MHz
- Detector: Peak
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Sweptime: Auto FFT
- Sweeps: 100
- Trace: Maxhold

5.7.2 TEST REQUIREMENTS / LIMITS

FCC Part 15.247 (d)

"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. ...

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the conducted measurement the RF power at the band edge shall be "at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power..."

5.7.3 TEST PROTOCOL

Temperature: 22 -25 °C
Air Pressure: 1009 - 1017 hPa
Humidity: 31 -40 %

(S01_AA01)

WLAN b-Mode; 20 MHz; 1 Mbps

Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
1	2412	2400.0	-33.4	PEAK	100	7.0	-23.0	10.4
11	2462	2483.5	-44.6	PEAK	100	7.7	-22.3	22.3

(S01_AA01)

WLAN g-Mode; 20 MHz; 6 Mbps

Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
1	2412	2400.0	-33.4	PEAK	100	7.0	-23.0	10.4
11	2462	2483.5	-44.6	PEAK	100	7.7	-22.3	22.3

(S01_AA01)

WLAN n-Mode; 20 MHz; MCS 0

Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
1	2412	2400.0	-40.7	PEAK	100	1.0	-29.0	11.7
11	2462	2483.5	-41.2	PEAK	100	1.6	-28.4	12.8

(S01_AA01)

WLAN n-Mode; 40 MHz; MCS 0


Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
3	2422	2400.0	-39.9	PEAK	100	-0.7	-30.7	9.2
11	2462	2483.5	-37.6	PEAK	100	-0.1	-30.1	7.5

Remark: Please see next sub-clause for the measurement plot.

5.7.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

WLAN n-Mode; Ch. 11, 40 MHz; MCS 0

Band Edge



5.7.5 TEST EQUIPMENT USED

- R&S TS8997

5.8 BAND EDGE COMPLIANCE RADIATED

Standard **FCC Part 15 Subpart C**

The test was performed according to:

ANSI C63.10

5.8.1 TEST DESCRIPTION

Please see test description for the test case "Spurious Radiated Emissions"

5.8.2 TEST REQUIREMENTS / LIMITS

For band edges connected to a restricted band, the limits are specified in Section 15.209(a)

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (μ V/m)	Measurement distance (m)	Limits (dB μ V/m)
0.009 – 0.49	2400/F(kHz)@300m	3	(48.5 – 13.8) @300m
0.49 – 1.705	24000/F(kHz)@30m	3	(33.8 – 23.0) @30m
1.705 – 30	30@30m	3	29.5@30m

The measured values are corrected with an inverse linear distance extrapolation factor (40 dB/decade) according FCC 15.31 (2).

Frequency in MHz	Limit (μ V/m)	Measurement distance (m)	Limits (dB μ V/m)
30 – 88	100@3m	3	40.0@3m
88 – 216	150@3m	3	43.5@3m
216 – 960	200@3m	3	46.0@3m
960 - 26000	500@3m	3	54.0@3m
26000 - 40000	500@3m	1	54.0@3m

The measured values above 26 GHz are corrected with an inverse linear distance extrapolation factor (20 dB/decade).

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit (dB μ V/m) = 20 log (Limit (μ V/m)/1 μ V/m)

5.8.3 TEST PROTOCOL

Temperature: 22 -25 °C
Air Pressure: 1009 - 1017 hPa
Humidity: 31 -40 %

(S01_AA01)

WLAN b-Mode; 20 MHz; 1 Mbps

Applied duty cycle correction (AV): 0 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
11	2462	2483.5	54.2	PEAK	1000	74.0	19.8	BE
11	2462	2483.5	38.4	AV	1000	54.0	15.6	BE

(S01_AA01)

WLAN g-Mode; 20 MHz; 6 Mbps

Applied duty cycle correction (AV): 0.1 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
11	2462	2483.5	62.0	PEAK	1000	74.0	12.0	BE
11	2462	2483.5	47.0	AV	1000	54.0	7.0	BE

(S01_AA01)

WLAN n-Mode; 20 MHz; MCS 0

Applied duty cycle correction (AV): 0.1 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
11	2462	2483.5	67.1	PEAK	1000	74.0	6.9	BE
11	2462	2483.5	49.6	AV	1000	54.0	4.4	BE

(S01_AA01)

WLAN n-Mode; 40 MHz; MCS 0

Applied duty cycle correction (AV): 0.1 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
11	2462	2483.5	68.1	PEAK	1000	74.0	5.9	BE
11	2462	2483.5	53.6	AV	1000	54.0	0.4	BE

(S01_AG02)

WLAN n-Mode; 40 MHz; MCS 0


Applied duty cycle correction (AV): 0.1 dB

Ch. No.	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dB μ V/m]	Detector	RBW [kHz]	Limit [dB μ V/m]	Margin to Limit [dB]	Limit Type
11	2462	2483.5	67.7	PEAK	1000	74.0	6.3	BE
11	2462	2483.5	51.9	AV	1000	54.0	2.1	BE


Remark: Please see next sub-clause for the measurement plot.

5.8.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

WLAN n-Mode; Ch.11, 40 MHz; MCS 0, (S01_AA01)



WLAN n-Mode; Ch.11, 40 MHz; MCS 0, (S01_AG02)



5.8.5 TEST EQUIPMENT USED

- Radiated Emissions

5.9 POWER DENSITY

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

5.9.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up in a shielded room to perform the Power Density measurements.

The results recorded were measured with the modulation which produces the worst-case (highest) power density.

The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Start and stop frequency adapted to TX channel

Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.39700 GHz	2.39700 GHz
Stop Frequency	2.42700 GHz	2.42700 GHz
Span	30.000 MHz	30.000 MHz
RBW	100.000 kHz	<= 100.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	600	~ 600
Sweeptime	3.000 s	3.000 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	10.000 dB	AUTO
Detector	RMS	RMS
SweepCount	1	1
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	7 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.35 dB	0.50 dB

5.9.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (e)

For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

...

The same method of determining the conducted output power shall be used to determine the power spectral density.

FCC Part 15, Subpart C, §15.247 (f)

(f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques.

...

The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

5.9.3 TEST PROTOCOL

Ambient temperature: 25 °C
 Air Pressure: 1010 hPa
 Humidity: 40 %

WLAN b-Mode; 20 MHz; 1 Mbps

Band	Channel No.	Frequency [MHz]	Power Density [dBm/3kHz]	Limit [dBm/3kHz]	Margin to Limit [dB]
2.4 GHz ISM	1	2412	-1.4	8.0	9.4
	6	2437	-1.4	8.0	9.4
	11	2462	-1.1	8.0	9.1

WLAN g-Mode; 20 MHz; 6 Mbps

Band	Channel No.	Frequency [MHz]	Power Density [dBm/3kHz]	Limit [dBm/3kHz]	Margin to Limit [dB]
2.4 GHz ISM	1	2412	-5.4	8.0	13.4
	6	2437	-5.3	8.0	13.3
	11	2462	-5.1	8.0	13.1

WLAN n-Mode; 20 MHz; MCS 0

Band	Channel No.	Frequency [MHz]	Power Density [dBm/3kHz]	Limit [dBm/3kHz]	Margin to Limit [dB]
2.4 GHz ISM	1	2412	-6.2	8.0	14.2
	6	2437	-5.9	8.0	13.9
	11	2462	-5.8	8.0	13.8

WLAN n-Mode; 40 MHz; MCS 0


Band	Channel No.	Frequency [MHz]	Power Density [dBm/3kHz]	Limit [dBm/3kHz]	Margin to Limit [dB]
2.4 GHz ISM	3	2412	-7.8	8.0	15.8
	6	2437	-7.4	8.0	15.4
	11	2462	-7.5	8.0	15.5

Remark: Please see next sub-clause for the measurement plot.

5.9.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

WLAN b-Mode; Ch. 11; 20 MHz; 1 Mbps

Power Spectral Density



5.9.5 TEST EQUIPMENT USED

- R&S TS8997

6 TEST EQUIPMENT

1 Conducted Emissions FCC
Conducted Emissions power line for FCC standards

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
1.1	Opus10 TPR (8253.00)	ThermoAirpressure Datalogger 13 (Environ)	Lufft Mess- und Regeltechnik GmbH	13936	2017-04	2019-04
1.2	ESW44	EMI Test Receiver	Rohde & Schwarz GmbH & Co. KG	101603	2018-05	2019-05
1.3	Fluke 177	Digital Multimeter 03 (Multimeter)	Fluke Europe B.V.	86670383	2018-04	2020-04
1.4	ESH3-Z5	Two-Line V-Network	Rohde & Schwarz	828304/029	2017-05	2019-05
1.5	EP 1200/B, NA/B1	Amplifier with integrated variable Oscillator	Spitzenberger & Spieß	B6278		
1.6	Chroma 6404	AC Power Source	Chroma ATE INC.	64040001304		
1.7	Shielded Room 02	Shielded Room for conducted testing, 12qm	Frankonia	-		
1.8	ESH3-Z5	Two-Line V-Network	Rohde & Schwarz	829996/002	2017-05	2019-05
1.9	ESR 7	EMI Receiver / Spectrum Analyzer	Rohde & Schwarz	101424	2017-01 2019-01	2019-01 2020-01
1.10	Opus10 THI (8152.00)	ThermoHygro Datalogger 02 (Environ)	Lufft Mess- und Regeltechnik GmbH	7489	2017-04	2019-04

2 R&S TS8997
EN300328/301893 Test Lab

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
2.1	SMB100A	Signal Generator 9 kHz - 6 GHz	Rohde & Schwarz	107695	2017-07	2020-07
2.2	MFS	Rubidium Frequency Standard	Datum-Beverly	5489/001	2018-07	2019-07
2.3	1515 / 93459	Broadband Power Divider SMA (Aux)	Weinschel Associates	LN673		
2.4	FSV30	Signal Analyzer 10 Hz - 30 GHz	Rohde & Schwarz	103005	2018-04	2020-04
2.5	Fluke 177	Digital Multimeter 03 (Multimeter)	Fluke Europe B.V.	86670383	2018-04	2020-04
2.6	VHF-3100+	High Pass Filter		-		
2.7	VT 4002	Temperature Chamber	Vötsch	58566002150010	2018-04	2020-04
2.8	A8455-4	4 Way Power Divider (SMA)		-		

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
2.9	Opus10 THI (8152.00)	ThermoHygro Datalogger 03 (Environ)	Lufft Mess- und Regeltechnik GmbH	7482	2017-03	2019-03
2.10	SMBV100A	Vector Signal Generator 9 kHz - 6 GHz	Rohde & Schwarz	259291	2016-10	2019-10
2.11	OSP120	Switching Unit with integrated power meter	Rohde & Schwarz	101158	2018-05	2021-05

3 Radiated Emissions
 Lab to perform radiated emission tests

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
3.1	NRV-Z1	Sensor Head A	Rohde & Schwarz GmbH & Co. KG	827753/005	2018-07	2019-07
3.2	MFS	Rubidium Frequency Normal MFS	Datum GmbH	002	2016-10 2018-10	2018-10 2020-10
3.3	Opus10 TPR (8253.00)	ThermoAirpressure Datalogger 13 (Environ)	Lufft Mess- und Regeltechnik GmbH	13936	2017-04	2019-04
3.4	ESW44	EMI Test Receiver	Rohde & Schwarz GmbH & Co. KG	101603	2018-05	2019-05
3.5	Anechoic Chamber	10.58 x 6.38 x 6.00 m ³	Frankonia	none	2018-06	2020-06
3.6	FS-Z60	Harmonic Mixer 40 - 60 GHz	Rohde & Schwarz Messgerätebau GmbH	100178	2016-12	2019-12
3.7	FS-Z220	Harmonic Mixer 140 - 220 GHz	Rohde & Schwarz Messgerätebau GmbH	101005	2017-03	2020-03
3.8	SGH-05	Standard Gain / Pyramidal Horn Antenna (140 - 220 GHz)	RPG-Radiometer Physics GmbH	075		
3.9	HL 562	Ultralog new biconicals	Rohde & Schwarz	830547/003	2018-07	2021-07
3.10	5HC2700/12750	High Pass -1.5-KK Filter	Trilithic	9942012		
3.11	ASP 1.2/1.8-10 kg	Antenna Mast	Maturo GmbH	-		
3.12	Fully Anechoic Room	8.80m x 4.60m x 4.05m (l x w x h)	Albatross Projects	P26971-647-001-PRB	2018-06	2020-06
3.13	Fluke 177	Digital Multimeter 03 (Multimeter)	Fluke Europe B.V.	86670383	2018-04	2020-04
3.14	NRVD	Power Meter	Rohde & Schwarz GmbH & Co. KG	828110/016	2018-07	2019-07
3.15	HF 906	Double-ridged horn	Rohde & Schwarz	357357/002	2018-09	2021-09
3.16	JS4-18002600-32-5P	Broadband Amplifier 18 GHz - 26 GHz	Miteq	849785		

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
3.17	FSW 43	Spectrum Analyzer	Rohde & Schwarz	103779	2017-02 2019-02	2019-02 2021-02
3.18	3160-09	Standard Gain / Pyramidal Horn Antenna 26.5 GHz	EMCO Elektronik GmbH	00083069		
3.19	SGH-19	Standard Gain / Pyramidal Horn Antenna (40 - 60 GHz)	RPG-Radiometer Physics GmbH	093		
3.20	WHKX 7.0/18G-8SS	High Pass Filter	Wainwright	09		
3.21	4HC1600/12750 -1.5-KK	High Pass Filter	Trilithic	9942011		
3.22	Chroma 6404	AC Power Source	Chroma ATE INC.	64040001304		
3.23	JS4-00102600-42-5A	Broadband Amplifier 30 MHz - 26 GHz	Miteq	619368		
3.24	TT 1.5 WI	Turn Table	Maturo GmbH	-		
3.25	HL 562 Ultralog	Log.-per. Antenna	Rohde & Schwarz	100609	2016-04	2019-04
3.26	HF 906	Double-ridged horn	Rohde & Schwarz	357357/001	2018-03	2021-03
3.27	FS-Z325	Harmonic Mixer 220 - 325 GHz	Rohde & Schwarz Messgerätebau GmbH	101006	2017-03	2020-03
3.28	3160-10	Standard Gain / Pyramidal Horn Antenna 40 GHz	EMCO Elektronik GmbH	00086675		
3.29	SGH-08	Standard Gain / Pyramidal Horn Antenna (90 - 140 GHz)	RPG-Radiometer Physics GmbH	064		
3.30	SGH-12	Standard Gain / Pyramidal HornAntenna (60 - 90 GHz)	RPG-Radiometer Physics GmbH	326		
3.31	5HC3500/18000 -1.2-KK	High Pass Filter	Trilithic	200035008		
3.32	FS-Z140	Harmonic Mixer 90 -140 GHz	Rohde & Schwarz Messgerätebau GmbH	101007	2017-02	2020-02
3.33	HFH2-Z2	Loop Antenna	Rohde & Schwarz	829324/006	2018-01	2021-01
3.34	Opus10 THI (8152.00)	ThermoHygro Datalogger 12 (Environ)	Lufft Mess- und Regeltechnik GmbH	12482	2017-03	2019-03
3.35	ESR 7	EMI Receiver / Spectrum Analyzer	Rohde & Schwarz	101424	2017-01 2019-01	2019-01 2020-01
3.36	JS4-00101800-35-5P	Broadband Amplifier 30 MHz - 18 GHz	Miteq	896037		
3.37	AS 620 P	Antenna mast	HD GmbH	620/37		
3.38	Tilt device Maturo (Rohacell)	Antrieb TD1.5-10kg	Maturo GmbH	TD1.5-10kg/024/37907 09		

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
3.39	SGH-03	Standard Gain / Pyramidal Horn Antenna (220 - 325 GHz)	RPG-Radiometer Physics GmbH	060		
3.40	FS-Z90	Harmonic Mixer 60 - 90 GHz	Rohde & Schwarz Messgerätebau GmbH	101686	2017-03	2020-03
3.41	ESIB 26	Spectrum Analyzer	Rohde & Schwarz	830482/004	2018-01	2020-01
3.42	PAS 2.5 - 10 kg	Antenna Mast	Maturo GmbH	-		
3.43	AFS42-00101800-25-S-42	Broadband Amplifier 25 MHz - 18 GHz	Miteq	2035324		
3.44	AM 4.0	Antenna mast	Maturo GmbH	AM4.0/180/1192 0513		
3.45	HF 907	Double-ridged horn	Rohde & Schwarz	102444	2018-07	2021-07

The calibration interval is the time interval between "Last Calibration" and "Calibration Due"

7 ANTENNA FACTORS, CABLE LOSS AND SAMPLE CALCULATIONS

This chapter contains the antenna factors with their corresponding path loss of the used measurement path for all antennas as well as the insertion loss of the LISN.

7.1 LISN R&S ESH3-Z5 (150 KHZ – 30 MHZ)

Frequency	Corr.	LISN insertion loss ESH3-Z5	cable loss (incl. 10 dB attenuator)
MHz	dB	dB	dB
0.15	10.1	0.1	10.0
5	10.3	0.1	10.2
7	10.5	0.2	10.3
10	10.5	0.2	10.3
12	10.7	0.3	10.4
14	10.7	0.3	10.4
16	10.8	0.4	10.4
18	10.9	0.4	10.5
20	10.9	0.4	10.5
22	11.1	0.5	10.6
24	11.1	0.5	10.6
26	11.2	0.5	10.7
28	11.2	0.5	10.7
30	11.3	0.5	10.8

Sample calculation

$$U_{\text{LISN}} (\text{dB } \mu\text{V}) = U (\text{dB } \mu\text{V}) + \text{Corr. (dB)}$$

U = Receiver reading

LISN Insertion loss = Voltage Division Factor of LISN

Corr. = sum of single correction factors of used LISN, cables, switch units (if used)

Linear interpolation will be used for frequencies in between the values in the table.

7.2 ANTENNA R&S HFH2-Z2 (9 KHZ – 30 MHZ)

Frequency	AF HFH-Z2)	Corr.	cable loss 1 (inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit)	cable loss 4 (to receiver)	distance corr. (-40 dB/ decade)	d _{Limit} (meas. distance (limit))	d _{used} (meas. distance (used))
			MHz	dB (1/m)	dB	dB	dB	m	m
0.009	20.50	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.01	20.45	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.015	20.37	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.02	20.36	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.025	20.38	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.03	20.32	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.05	20.35	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.08	20.30	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.1	20.20	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.2	20.17	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.3	20.14	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.49	20.12	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.490001	20.12	-39.6	0.1	0.1	0.1	0.1	-40	30	3
0.5	20.11	-39.6	0.1	0.1	0.1	0.1	-40	30	3
0.8	20.10	-39.6	0.1	0.1	0.1	0.1	-40	30	3
1	20.09	-39.6	0.1	0.1	0.1	0.1	-40	30	3
2	20.08	-39.6	0.1	0.1	0.1	0.1	-40	30	3
3	20.06	-39.6	0.1	0.1	0.1	0.1	-40	30	3
4	20.05	-39.5	0.2	0.1	0.1	0.1	-40	30	3
5	20.05	-39.5	0.2	0.1	0.1	0.1	-40	30	3
6	20.02	-39.5	0.2	0.1	0.1	0.1	-40	30	3
8	19.95	-39.5	0.2	0.1	0.1	0.1	-40	30	3
10	19.83	-39.4	0.2	0.1	0.2	0.1	-40	30	3
12	19.71	-39.4	0.2	0.1	0.2	0.1	-40	30	3
14	19.54	-39.4	0.2	0.1	0.2	0.1	-40	30	3
16	19.53	-39.3	0.3	0.1	0.2	0.1	-40	30	3
18	19.50	-39.3	0.3	0.1	0.2	0.1	-40	30	3
20	19.57	-39.3	0.3	0.1	0.2	0.1	-40	30	3
22	19.61	-39.3	0.3	0.1	0.2	0.1	-40	30	3
24	19.61	-39.3	0.3	0.1	0.2	0.1	-40	30	3
26	19.54	-39.3	0.3	0.1	0.2	0.1	-40	30	3
28	19.46	-39.2	0.3	0.1	0.3	0.1	-40	30	3
30	19.73	-39.1	0.4	0.1	0.3	0.1	-40	30	3

Sample calculation

$$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB } 1/\text{m)} + \text{Corr. (dB)}$$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

distance correction = $-40 * \log(d_{\text{Limit}} / d_{\text{used}})$

Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values

7.3 ANTENNA R&S HL562 (30 MHZ – 1 GHZ)

($d_{\text{Limit}} = 3 \text{ m}$)

Frequency	AF R&S HL562	Corr.
MHz	dB (1/m)	dB
30	18.6	0.6
50	6.0	0.9
100	9.7	1.2
150	7.9	1.6
200	7.6	1.9
250	9.5	2.1
300	11.0	2.3
350	12.4	2.6
400	13.6	2.9
450	14.7	3.1
500	15.6	3.2
550	16.3	3.5
600	17.2	3.5
650	18.1	3.6
700	18.5	3.6
750	19.1	4.1
800	19.6	4.1
850	20.1	4.4
900	20.8	4.7
950	21.1	4.8
1000	21.6	4.9

cable loss 1 (inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit)	cable loss 4 (to receiver)	distance corr. (-20 dB/ decade)	d_{Limit} (meas. distance (limit))	d_{used} (meas. distance (used))
dB	dB	dB	dB	dB	m	m
0.29	0.04	0.23	0.02	0.0	3	3
0.39	0.09	0.32	0.08	0.0	3	3
0.56	0.14	0.47	0.08	0.0	3	3
0.73	0.20	0.59	0.12	0.0	3	3
0.84	0.21	0.70	0.11	0.0	3	3
0.98	0.24	0.80	0.13	0.0	3	3
1.04	0.26	0.89	0.15	0.0	3	3
1.18	0.31	0.96	0.13	0.0	3	3
1.28	0.35	1.03	0.19	0.0	3	3
1.39	0.38	1.11	0.22	0.0	3	3
1.44	0.39	1.20	0.19	0.0	3	3
1.55	0.46	1.24	0.23	0.0	3	3
1.59	0.43	1.29	0.23	0.0	3	3
1.67	0.34	1.35	0.22	0.0	3	3
1.67	0.42	1.41	0.15	0.0	3	3
1.87	0.54	1.46	0.25	0.0	3	3
1.90	0.46	1.51	0.25	0.0	3	3
1.99	0.60	1.56	0.27	0.0	3	3
2.14	0.60	1.63	0.29	0.0	3	3
2.22	0.60	1.66	0.33	0.0	3	3
2.23	0.61	1.71	0.30	0.0	3	3

($d_{\text{Limit}} = 10 \text{ m}$)

30	18.6	-9.9
50	6.0	-9.6
100	9.7	-9.2
150	7.9	-8.8
200	7.6	-8.6
250	9.5	-8.3
300	11.0	-8.1
350	12.4	-7.9
400	13.6	-7.6
450	14.7	-7.4
500	15.6	-7.2
550	16.3	-7.0
600	17.2	-6.9
650	18.1	-6.9
700	18.5	-6.8
750	19.1	-6.3
800	19.6	-6.3
850	20.1	-6.0
900	20.8	-5.8
950	21.1	-5.6
1000	21.6	-5.6

0.29	0.04	0.23	0.02	-10.5	10	3
0.39	0.09	0.32	0.08	-10.5	10	3
0.56	0.14	0.47	0.08	-10.5	10	3
0.73	0.20	0.59	0.12	-10.5	10	3
0.84	0.21	0.70	0.11	-10.5	10	3
0.98	0.24	0.80	0.13	-10.5	10	3
1.04	0.26	0.89	0.15	-10.5	10	3
1.18	0.31	0.96	0.13	-10.5	10	3
1.28	0.35	1.03	0.19	-10.5	10	3
1.39	0.38	1.11	0.22	-10.5	10	3
1.44	0.39	1.20	0.19	-10.5	10	3
1.55	0.46	1.24	0.23	-10.5	10	3
1.59	0.43	1.29	0.23	-10.5	10	3
1.67	0.34	1.35	0.22	-10.5	10	3
1.67	0.42	1.41	0.15	-10.5	10	3
1.87	0.54	1.46	0.25	-10.5	10	3
1.90	0.46	1.51	0.25	-10.5	10	3
1.99	0.60	1.56	0.27	-10.5	10	3
2.14	0.60	1.63	0.29	-10.5	10	3
2.22	0.60	1.66	0.33	-10.5	10	3
2.23	0.61	1.71	0.30	-10.5	10	3

Sample calculation

$$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB } 1/\text{m)} + \text{Corr. (dB)}$$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)
 distance correction = $-20 * \text{LOG} \left(\frac{d_{\text{Limit}}}{d_{\text{used}}} \right)$

Linear interpolation will be used for frequencies in between the values in the table.

Tables show an extract of values.

7.4 ANTENNA R&S HF907 (1 GHZ – 18 GHZ)

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
1000	24.4	-19.4
2000	28.5	-17.4
3000	31.0	-16.1
4000	33.1	-14.7
5000	34.4	-13.7
6000	34.7	-12.7
7000	35.6	-11.0

cable loss 1 (relay + cable inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit, atten- uator & pre-amp)	cable loss 4 (to receiver)		
dB	dB	dB	dB		
0.99	0.31	-21.51	0.79		
1.44	0.44	-20.63	1.38		
1.87	0.53	-19.85	1.33		
2.41	0.67	-19.13	1.31		
2.78	0.86	-18.71	1.40		
2.74	0.90	-17.83	1.47		
2.82	0.86	-16.19	1.46		

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
3000	31.0	-23.4
4000	33.1	-23.3
5000	34.4	-21.7
6000	34.7	-21.2
7000	35.6	-19.8

cable loss 1 (relay inside chamber)	cable loss 2 (inside chamber)	cable loss 3 (outside chamber)	cable loss 4 (switch unit, atten- uator & pre-amp)	cable loss 5 (to receiver)	used for FCC 15.247
dB	dB	dB	dB	dB	
0.47	1.87	0.53	-27.58	1.33	
0.56	2.41	0.67	-28.23	1.31	
0.61	2.78	0.86	-27.35	1.40	
0.58	2.74	0.90	-26.89	1.47	
0.66	2.82	0.86	-25.58	1.46	

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
7000	35.6	-57.3
8000	36.3	-56.3
9000	37.1	-55.3
10000	37.5	-56.2
11000	37.5	-55.3
12000	37.6	-53.7
13000	38.2	-53.5
14000	39.9	-56.3
15000	40.9	-54.1
16000	41.3	-54.1
17000	42.8	-54.4
18000	44.2	-54.7

cable loss 1 (relay inside chamber)	cable loss 2 (High Pass)	cable loss 3 (pre- amp)	cable loss 4 (inside chamber)	cable loss 5 (outside chamber)	cable loss 6 (to receiver)
dB	dB	dB	dB	dB	dB
0.56	1.28	-62.72	2.66	0.94	1.46
0.69	0.71	-61.49	2.84	1.00	1.53
0.68	0.65	-60.80	3.06	1.09	1.60
0.70	0.54	-61.91	3.28	1.20	1.67
0.80	0.61	-61.40	3.43	1.27	1.70
0.84	0.42	-59.70	3.53	1.26	1.73
0.83	0.44	-59.81	3.75	1.32	1.83
0.91	0.53	-63.03	3.91	1.40	1.77
0.98	0.54	-61.05	4.02	1.44	1.83
1.23	0.49	-61.51	4.17	1.51	1.85
1.36	0.76	-62.36	4.34	1.53	2.00
1.70	0.53	-62.88	4.41	1.55	1.91

Sample calculation

$$E (\text{dB } \mu\text{V/m}) = U (\text{dB } \mu\text{V}) + AF (\text{dB } 1/\text{m}) + \text{Corr. (dB)}$$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

Linear interpolation will be used for frequencies in between the values in the table.

Tables show an extract of values.

7.5 ANTENNA EMCO 3160-09 (18 GHZ – 26.5 GHZ)

Frequency	AF EMCO 3160-09	Corr.	cable loss 1 (inside chamber)	cable loss 2 (pre- amp)	cable loss 3 (inside chamber)	cable loss 4 (switch unit)	cable loss 5 (to receiver)
			dB	dB	dB	dB	dB
18000	40.2	-23.5	0.72	-35.85	6.20	2.81	2.65
18500	40.2	-23.2	0.69	-35.71	6.46	2.76	2.59
19000	40.2	-22.0	0.76	-35.44	6.69	3.15	2.79
19500	40.3	-21.3	0.74	-35.07	7.04	3.11	2.91
20000	40.3	-20.3	0.72	-34.49	7.30	3.07	3.05
20500	40.3	-19.9	0.78	-34.46	7.48	3.12	3.15
21000	40.3	-19.1	0.87	-34.07	7.61	3.20	3.33
21500	40.3	-19.1	0.90	-33.96	7.47	3.28	3.19
22000	40.3	-18.7	0.89	-33.57	7.34	3.35	3.28
22500	40.4	-19.0	0.87	-33.66	7.06	3.75	2.94
23000	40.4	-19.5	0.88	-33.75	6.92	3.77	2.70
23500	40.4	-19.3	0.90	-33.35	6.99	3.52	2.66
24000	40.4	-19.8	0.88	-33.99	6.88	3.88	2.58
24500	40.4	-19.5	0.91	-33.89	7.01	3.93	2.51
25000	40.4	-19.3	0.88	-33.00	6.72	3.96	2.14
25500	40.5	-20.4	0.89	-34.07	6.90	3.66	2.22
26000	40.5	-21.3	0.86	-35.11	7.02	3.69	2.28
26500	40.5	-21.1	0.90	-35.20	7.15	3.91	2.36

Sample calculation

$$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB } 1/\text{m)} + \text{Corr. (dB)}$$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values.

7.6 ANTENNA EMCO 3160-10 (26.5 GHZ – 40 GHZ)

Frequency	AF EMCO 3160-10	Corr.
GHz	dB (1/m)	dB
26.5	43.4	-11.2
27.0	43.4	-11.2
28.0	43.4	-11.1
29.0	43.5	-11.0
30.0	43.5	-10.9
31.0	43.5	-10.8
32.0	43.5	-10.7
33.0	43.6	-10.7
34.0	43.6	-10.6
35.0	43.6	-10.5
36.0	43.6	-10.4
37.0	43.7	-10.3
38.0	43.7	-10.2
39.0	43.7	-10.2
40.0	43.8	-10.1

cable loss 1 (inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit)	cable loss 4 (to receiver)	distance corr. (-20 dB/ decade)	d _{limit} (meas. distance (limit))	d _{used} (meas. distance (used))
dB	dB	dB	dB	dB	m	m
4.4				-9.5	3	1.0
4.4				-9.5	3	1.0
4.5				-9.5	3	1.0
4.6				-9.5	3	1.0
4.7				-9.5	3	1.0
4.7				-9.5	3	1.0
4.8				-9.5	3	1.0
4.9				-9.5	3	1.0
5.0				-9.5	3	1.0
5.1				-9.5	3	1.0
5.1				-9.5	3	1.0
5.2				-9.5	3	1.0
5.3				-9.5	3	1.0
5.4				-9.5	3	1.0
5.5				-9.5	3	1.0

Sample calculation

$$E (\text{dB } \mu\text{V/m}) = U (\text{dB } \mu\text{V}) + AF (\text{dB } 1/\text{m}) + \text{Corr. (dB)}$$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)


Linear interpolation will be used for frequencies in between the values in the table.

distance correction = $-20 * \text{LOG} (d_{\text{limit}} / d_{\text{used}})$

Linear interpolation will be used for frequencies in between the values in the table.


Table shows an extract of values.

8 SETUP DRAWINGS



Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

Drawing 1: Setup in the Anechoic chamber. For measurements below 1 GHz the ground was replaced by a conducting groundplane.



Drawing 2: Setup for conducted radio tests.

9 MEASUREMENT UNCERTAINTIES

Test Case	Parameter	Uncertainty
AC Power Line	Power	± 3.4 dB
Field Strength of spurious radiation	Power	± 5.5 dB
6 dB / 26 dB / 99% Bandwidth	Power Frequency	± 2.9 dB ± 11.2 kHz
Conducted Output Power	Power	± 2.2 dB
Band Edge Compliance	Power Frequency	± 2.2 dB ± 11.2 kHz
Frequency Stability	Frequency	± 25 Hz
Power Spectral Density	Power	± 2.2 dB

10 PHOTO REPORT

Please see separate photo report.