



# TEST REPORT

Report No.: SHATBL2407020W07

**Applicant** : Shanghai AllyNav Technology Co.,Ltd.

**Product Name** : Orchard Sparying Robot

**Brand Name** : N/A

**Model Name** : Aries300N

**FCC ID** : 2AT4H-ARIES300N

**Test Standard** : 47 CFR 15.247

**Date of Test** : 2024.08.20-2024.08.28

**Report Prepared by** :

*Emily*

(Emily)

**Report Approved by** :

*Guozheng Li*

(Guozheng Li)

**Authorized Signatory** :

*Terry Yang*

(Terry Yang)



"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards, or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

Tel:+86(0)21-51298625

Web:www.atbl-lab.com

Email:atbl@atbl-lab.com

**TABLE OF CONTENTS**

TEST REPORT .....	1
TABLE OF CONTENTS .....	2
REVISION HISTORY .....	3
DECLARATION OF REPORT .....	4
SUMMARY OF TEST RESULT .....	5
1. GENERAL DESCRIPTION .....	6
1.1. Applicant .....	6
1.2. Manufacturer .....	6
1.3. Factory .....	6
1.4. General Information of EUT .....	7
1.5. Environmental conditions .....	8
1.6. Equipment Specification .....	8
1.7. Modification of EUT .....	9
1.8. Laboratory Information .....	9
1.9. Applicable Standards .....	9
2. TEST CONFIGURATION OF EUT .....	10
2.1. Carrier Frequency Channel .....	10
2.2. Test Modes .....	10
2.3. Block Diagram of Test System .....	11
2.4. Description of Support Units .....	11
2.5. Test Software and Power Level .....	11
2.6. EUT Operating Conditions .....	11
2.7. Equipment List .....	12
2.8. Measurement Uncertainty .....	13
3. TEST RESULT .....	14
3.1. Maximum Peak Conducted Output Power .....	14
3.2. Duty Cycle .....	16
3.3. 6dB Bandwidth and 99% Bandwidth .....	17
3.4. Power Spectral Density .....	19
3.5. Conducted Band Edge .....	20
3.6. Conducted Spurious Emission .....	21
3.7. Radiated Spurious Emission and Restricted Band .....	22
3.8. AC Power-Line Conducted Emission .....	25
3.9. Antenna Requirement .....	26
4. Test Setup Photographs .....	26
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....	26
Appendix A _ Conducted Test Data .....	27
Appendix B _ Radiated Test Data and AC Power-Line Conducted Emission Test Data .....	40

**REVISION HISTORY**

Rev.	Issue Date	Revisions	Revised by
00	2024.12.10	Initial Release	Guozheng Li

## DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR 15.247. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '□' indicates that EUT does not support content after '□', and '☒' indicates that it supports content after '☒'
6. Both the conducted and radiated tests are conducted using modules with a supply voltage of 12V

**SUMMARY OF TEST RESULT**

Report Section	Standard Section	Test Item	Judgment	Remark
3.1	47 CFR 15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	--
3.2	--	Duty Cycle	Report only	--
3.3	47 CFR 15.247(a)(2)	6dB Bandwidth	PASS	--
	--	99% Bandwidth	Report only	--
3.4	47 CFR 15.247(e)	Power Spectral Density	PASS	--
3.5	47 CFR 15.247(d)	Conducted Band Edge	PASS	--
3.6	47 CFR 15.247(d)	Conducted Spurious Emission	PASS	--
3.7	47 CFR 15.247(d)/15.209(a)/15.205(a)	Radiated Spurious Emission and Restricted Band	PASS	Note(1)
3.8	47 CFR 15.207(a)	AC Power-Line Conducted Emission	N/A	--
3.9	47 CFR 15.203	Antenna Requirements	PASS	--

Note:

(1)The data content is provided by Industrial Internet Innovation Center (Shanghai) Co.,Ltd.(A2LA number: #3682.01)

## 1. GENERAL DESCRIPTION

### 1.1. Applicant

Name : Shanghai AllyNav Technology Co.,Ltd.

Address : Room 201, Buliding 1, No 215, Gaoguang RD, Qingpu District, Shanghai, China

### 1.2. Manufacturer

Name : Shanghai AllyNav Technology Co.,Ltd.

Address : Room 201, Buliding 1, No 215, Gaoguang RD, Qingpu District, Shanghai, China

### 1.3. Factory

Name : Shanghai AllyNav Technology Co.,Ltd.

Address : Room 201, Buliding 1, No 215, Gaoguang RD, Qingpu District, Shanghai, China

**1.4. General Information of EUT**

General Information	
Equipment Name	Orchard Sparying Robot
Brand Name	N/A
Model Name	Aries300N
Series Model	Aries300N-1
Model Difference	The model is changed according to the difference of overseas customers, and its composition and key parts are exactly the same
Antenna Type	External antenna
Power Input	DC 48V
Adapter	N/A
Battery	Model: Lead acid battery Brand: TianNeng Capacity: 10-19AH
Hardware Version	Aries300N-1
Software Version	1.2.2.25RC
Connecting I/O Port(s)	Refer to the remark below.

Remark:

The above information of EUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.5. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature	Normal Temperature(TN):	25°C
	High Temperature(TH):	60°C
	Low Temperature(TL):	-20°C
Voltage	Normal Voltage(VN):	48V
	High Voltage(VH):	52.8V
	Low Voltage(VL):	45.6V
Other	Relative Humidity	52 %
	Air Pressure	101 kPa

### 1.6. Equipment Specification

Equipment Specification		
Frequency Range	2402 MHz - 2480 MHz	
Number of Channels	40	
Carrier Frequency of Each Channel	2402 + n*2 MHz; n = 0 ~ 39	
Maximum Output Power To Antenna	<input checked="" type="checkbox"/> Bluetooth LE(1Mbps):	-2.73dBm (0.000533W)
	<input checked="" type="checkbox"/> Bluetooth LE(2Mbps):	-2.67dBm (0.000541W)
Type of Modulation	Bluetooth LE:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	PCB antenna	
Antenna Gain	2.7 dBi	

### 1.7. Modification of EUT

No modifications are made to the EUT during all test items.

### 1.8. Laboratory Information

Company Name :	Shanghai ATBL Technology Co., Ltd.
Address :	5F., Unit 1, No.8, Free Trade One Life Science and Sci-Tech Industrial Park, No.160, Basheng Road, Pudong New District, Shanghai, China
Telephone :	+86(0)21-51298625

### 1.9. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

47 CFR Part 15 Subpart C §15.247

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. TEST CONFIGURATION OF EUT

### 2.1. Carrier Frequency Channel

Frequency Band	Channel	Frequency MHz	Channel	Frequency MHz	Channel	Frequency MHz
2400 - 2483.5 MHz	<b>00</b>	<b>2402</b>	14	2430	28	2458
	01	2404	15	2432	29	2460
	02	2406	16	2434	30	2462
	03	2408	17	2436	31	2464
	04	2410	18	2438	32	2466
	05	2412	<b>19</b>	<b>2440</b>	33	2468
	06	2414	20	2442	34	2470
	07	2416	21	2444	35	2472
	08	2418	22	2446	36	2474
	09	2420	23	2448	37	2476
	10	2422	24	2450	38	2478
	11	2424	25	2452	<b>39</b>	<b>2480</b>
	12	2426	26	2454	--	--
	13	2428	27	2456	--	--

Remark:

Low Channel: **CH 00\_2402 MHz**; Middle Channel: **CH 19\_2440 MHz**; High Channel: **CH 39\_2480 MHz**.


### 2.2. Test Modes

The table below is showing all test modes to demonstrate in compliance with the standard.

Summary Table of Test Modes		
Test Item	Data Rate / Modulation	
	<input checked="" type="checkbox"/> Bluetooth LE(1Mbps)	<input checked="" type="checkbox"/> Bluetooth LE(2Mbps)
For Conducted and Radiated Test	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz
	Mode 2: CH19_2440 MHz	Mode 5: CH19_2440 MHz
	Mode 3: CH39_2480 MHz	Mode 6: CH39_2480 MHz
For AC Power-line Conducted Emission	Mode 13: Keep Bluetooth link under the maximum output power	

## 2.3. Block Diagram of Test System

### 2.3.1. For AC Power-Line Conducted Emission



### 2.3.2. For Radiated Spurious Emission



### 2.3.3. For Conducted Test



## 2.4. Description of Support Units

NO.	Unit	Brand	Model	Description
1	Notebook	Lenovo	Air 14	/
2	USB Line	ZL	24AWG	/

## 2.5. Test Software and Power Level

During the test, the channel and power control software provided by the customer is used to control the operation channel and output power level.

## 2.6. EUT Operating Conditions

For AC power-line conducted emission, the EUT was connected under the large package sizes transmission.

For radiated spurious emission and conducted test, the engineering test program was provided and make the EUT to continuous transmit/receive.

## 2.7. Equipment List

### 2.7.1. For Conducted Test

Equipment Name	Manufacturer	Model	Serial No.	Calibration Until	Calibration DUE Until	Cal. Interval
Power meter	Anritsu	ML2496A	1935001	2024.07.18	2025.07.17	1 year
Power sensor	Anritsu	MA2411B	1911006	2024.07.18	2025.07.17	1 year
Power sensor	Keysight	U2021XA	MY59120004	2024.07.18	2025.07.17	1 year
Adjustable Attenuator	Agilent	8494B	MY42144015	2024.07.18	2025.07.17	1 year
Adjustable Attenuator	Agilent	8496B	MY42143776	2024.07.18	2025.07.17	1 year
Environmental Test Chamber	KSON	THS-B6C-150	9159K	2024.03.28	2025.03.27	1 year
Signal analyzer	Keysight	N9020A	MY50510136	2024.07.18	2025.07.17	1 year
Vector signal generator	Keysight	N5182B	MY57300196	2024.07.18	2025.07.17	1 year
Vector signal generator	Agilent	N5182A	MY50143555	2024.07.18	2025.07.17	1 year
Analog signal generator	Keysight	N5173B	MY60403026	2024.07.18	2025.07.17	1 year
Wideband radio communication tester	R&S	CMW500	101331	2024.07.18	2025.07.17	1 year
Spectrum analyzer	R&S	FSV40-N	101761	2024.07.18	2025.07.17	1 year
Switch Box	N/A	RFSW3003328	RFSW201019	N/A	N/A	1 year
Thermometer	DeLi	N/A	N/A	2024.07.18	2025.07.17	1 year
Test Software	FALA	LZ-RF	N/A	N/A	N/A	1 year
Test Software	Cesheng	WCS-WCN	N/A	N/A	N/A	N/A

### 2.7.2. For Radiated Spurious Emission

Equipment Name	Manufacturer	Model	Serial No.	Calibration Until	Calibration DUE Until	Cal. Interval
Universal Radio Communication Tester	R&S	CMW500	104178	2024.10.09	2025.10.08	1 year
Test Receiver	R&S	ESR7	102399	2024.06.07	2025.06.06	1 year
Test Receiver	R&S	FSW43	101943	2024.08.21	2025.08.20	1 year
Loop Antenna	COM-POWER	AL-130R	121083	2024.08.31	2025.08.30	1 year
Trilog Antenna	Schwarzbeck	VULB9162	00426	2024.08.02	2025.08.01	1 year
Double Ridged Guide Antenna	ETS	ETS-3117	00135885	2024.03.26	2025.03.25	1 year
Horn Antenna	R&S	QMS-00880	24715	2024.08.03	2025.08.02	1 year
EMI Test Software	R&S	EMC32 V10.60.20	N/A	N/A	N/A	N/A
Antenna Tower	Top Precision	TPMDC-LF	N/A	N/A	N/A	N/A
Antenna Tower	Top Precision	TPMDC-HF	N/A	N/A	N/A	N/A

## 2.8. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Output Power	1.266dB
2	Power spectral density	1.282dB
3	Conducted Frequency Stability	10.14Hz
4	Conducted spurious emissions	1.73dB
5	RF Cable Loss	1.22dB
6	Radiated Spurious Emission 9KHz-30MHz	2.35dB
7	Radiated Spurious Emission 30MHz-1GHz	3.60dB
8	Radiated Spurious Emission 1GHz-18GHz	5.40dB
9	Radiated Spurious Emission 18GHz - 40GHz	8.20dB

### 3. TEST RESULT

#### 3.1. Maximum Peak Conducted Output Power

##### 3.1.1. Limit

47 CFR 15.247(b)(3): For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

47 CFR 15.247(b)(4): If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

47 CFR 15.247(c)(1)(i): Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

##### 3.1.2. Test Procedure

ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter method: The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM: Method AVGPM is a measurement using an RF average power meter, as follows:

1. As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:

- ① The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
  - ② At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.


- ③ The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

2. If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in ANSI C63.10-2013 clause 11.6.

3. Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.

4. Adjust the measurement in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

### 3.1.3. Test Setup



### 3.1.4. Test Result of Maximum Peak Conducted Output Power

Please refer to the Appendix A1.

### 3.2. Duty Cycle

#### 3.2.1. Limit


There is no limit requirement for Duty Cycle.

#### 3.2.2. Test Procedure

*ANSI C63.10-2013 clause 11.6:* Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

1. A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
2. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
  - ① Set the center frequency of the instrument to the center frequency of the transmission.
  - ② Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
  - ③ Set  $VBW \geq RBW$ . Set detector = peak or average.
  - ④ The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

#### 3.2.3. Test Setup



#### 3.2.4. Test Result of Duty Cycle

Please refer to the Appendix A2.

### 3.3. 6dB Bandwidth and 99% Bandwidth

#### 3.3.1. Limit

47 CFR 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

There is no limit requirement for 99% Bandwidth.

#### 3.3.2. Test Procedure

1. The testing of 6dB Bandwidth follows ANSI C63.10-2013 clause 11.8.1: The steps for the first option are as follows:

- ① Set RBW = 100 kHz.
- ② Set the VBW  $\geq [3 \times \text{RBW}]$ .
- ③ Detector = peak.
- ④ Trace mode = max hold.
- ⑤ Sweep = auto couple.
- ⑥ Allow the trace to stabilize.
- ⑦ Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


2. The testing of 99% Bandwidth follows ANSI C63.10-2013 clause 6.9.3: The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- ① The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- ② The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- ③ Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level. Specific guidance is given in ANSI C63.10-2013 clause 4.1.5.2.
- ④ Step a) through step c) might require iteration to adjust within the specified range.
- ⑤ Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- ⑥ Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- ⑦ If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at

the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

⑧ The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

### **3.3.3. Test Setup**



### **3.3.4. Test Result of 6dB Bandwidth and 99% Bandwidth**

Please refer to the Appendix A3.

### 3.4. Power Spectral Density

#### 3.4.1. Limit


47 CFR 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 3.4.2. Test Procedure

ANSI C63.10-2013 clause 11.10.2: The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to 3 kHz.
4. Set the VBW  $\geq [3 \times \text{RBW}]$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.

#### 3.4.3. Test Setup



#### 3.4.4. Test Result of Power Spectral Density

Please refer to the Appendix A4.

### 3.5. Conducted Band Edge


#### 3.5.1. Limit

47 CFR 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### 3.5.2. Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Conducted Band Edge measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the 100 kHz bandwidth within the band that contains the highest level of the desired power when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.5.3. Test Setup



#### 3.5.4. Test Result of Conducted Band Edge

Please refer to the Appendix A5.

### 3.6. Conducted Spurious Emission


#### 3.6.1. Limit

47 CFR 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### 3.6.2. Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### 3.6.3. Test Setup



#### 3.6.4. Test Result of Conducted Spurious Emission

Please refer to the Appendix A5.

### 3.7. Radiated Spurious Emission and Restricted Band

#### 3.7.1. Limit

47 CFR 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

47 CFR 15.205(a): Only spurious emissions are permitted in any of the frequency bands listed below:

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)
0.090-0.110	12.29-12.293	149.9-150.05	1660-1710	8.025-8.5
0.495-0.505	12.51975-12.52025	156.52475-156.52525	1718.8-1722.2	9.0-9.2
2.1735-2.1905	12.57675-12.57725	156.7-156.9	2200-2300	9.3-9.5
4.125-4.128	13.36-13.41	162.0125-167.17	2310-2390	10.6-12.7
4.17725-4.17775	16.42-16.423	167.72-173.2	2483.5-2500	13.25-13.4
4.20725-4.20775	16.69475-16.69525	240-285	2690-2900	14.47-14.5
6.215-6.218	16.80425-16.80475	322-335.4	3260-3267	15.35-16.2
6.26775-6.26825	25.5-25.67	399.9-410	3332-3339	17.7-21.4
6.31175-6.31225	37.5-38.25	608-614	3345.8-3358	22.01-23.12
8.291-8.294	73-74.6	960-1240	3600-4400	23.6-24.0
8.362-8.366	74.8-75.2	1300-1427	4500-5150	31.2-31.8
8.37625-8.38675	108-121.94	1435-1626.5	5350-5460	36.43-36.5
8.41425-8.41475	123-138	1645.5-1646.5	7250-7750	Above 38.6

47 CFR 15.209(a): The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

### 3.7.2. Test Procedure


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.1 meter for frequency below 1GHz and 0.1 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Pre-amp Factor = Level.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - ① Span shall wide enough to fully capture the emission being measured;
  - ② When frequency  $< 1$  GHz:
    - Set RBW=100 kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - ③ When frequency  $\geq 1$  GHz:
    - Set RBW = 1 MHz; VBW = 3 MHz for peak measurement;
    - Set RBW = 1 MHz; VBW = 10 Hz, when duty cycle is no less than 98 percent or  $VBW \geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

### 3.7.3. Test Setup


#### 3.7.3.1. For radiated emissions below 30MHz



#### 3.7.3.2. For radiated emissions from 30MHz to 1GHz



#### 3.7.3.3. For radiated emissions above 1GHz



### 3.7.4. Test Result of Radiated Spurious Emission

Please refer to the Appendix B.

### 3.7.5. Test Result of Restricted Band

Please refer to the Appendix B.

### 3.8. AC Power-Line Conducted Emission

#### 3.8.1. Limit

47 CFR 15.207(a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table:


Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 3.8.2. Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 10 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

#### 3.8.3. Test Setup



#### 3.8.4. Test Result of AC Power-Line Conducted Emission

Please refer to the Appendix C.

### **3.9. Antenna Requirement**

#### **3.9.1. Standard Requirement**

According to 47 CFR 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### **3.9.2. EUT Antenna**

The antenna used for the EUT is PCB antenna, which meets the antenna requirements.

## **4. Test Setup Photographs**

Please refer to the Appendix D.

## **5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT**

External Photos Please refer to the Appendix D.

Internal Photos Please refer to the Appendix E.

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*


## **Appendix A \_ Conducted Test Data**

## Appendix A1. Conducted Output Power

Mode	Frequency (MHz)	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
BLE 1M	2402	0	-5.43	0.29	None	≤30	PASS
	2440	19	-6.47	0.23	None	≤30	PASS
	2480	39	-5.65	0.27	None	≤30	PASS
BLE 2M	2402	0	-5.37	0.29	None	≤30	PASS
	2440	19	-7.58	0.17	None	≤30	PASS
	2480	39	-8.46	0.14	None	≤30	PASS

Note: Average Conducted Output Power has considered the factor of the duty cycle

## Test Graphs







## Appendix A2. Duty Cycle

### Test Result


Mode	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)
BLE 1M	0	2.125	2.499	85.03	0.8503	0.7043
	19	2.126	2.499	85.08	0.8508	0.7017
	39	2.126	2.499	85.08	0.8508	0.7017
BLE 2M	0	1.070	1.874	57.11	0.5711	2.4329
	19	1.070	1.875	57.07	0.5707	2.4359
	39	1.070	1.874	57.11	0.5711	2.4329

### Test Graphs







### BLE 1M\_Channel 19




### BLE 1M\_Channel 39



### BLE 2M\_Channel 0



### BLE 2M\_Channel 19



## Appendix A3. 6dB Bandwidth and 99% Bandwidth

### 99% Bandwidth

#### Test Result

Mode	Channel	Center Frequency (MHz)	99% BW (MHz)
BLE 1M	0	2402	1.0402
	19	2440	1.0423
	39	2480	1.0428
BLE 2M	0	2402	2.0800
	19	2440	2.0752
	39	2480	2.0830

#### Test Graphs

