



MPE ESTIMATION

**Test report
On Behalf of
Hangzhou Dfire Technology Co., Ltd.
For
The Cash Register
Model No.: NOVO-01**

FCC ID: 2AT75-NOVO-01

Prepared for : Hangzhou Dfire Technology Co., Ltd.
Room 218, 2nd Floor, Building 10, Gongshu District, Hangzhou
City, Zhejiang Province, China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: July 08, 2019 ~ July 26, 2019
Date of Report: July 26, 2019
Report Number: HK1907261803-2E

**1, Limit for General Population/ Uncontrolled Exposures**

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result**2.4G WIFI**

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	13.79	13±1(14)	25.12	1	1.259	0.00629
11g	12.37	12±1(13)	19.95	1	1.259	0.00500
11n/HT20	11.96	11±1(12)	15.85	1	1.259	0.00397
11n/HT40	10.78	11±1(12)	15.85	1	1.259	0.00397

$$Pd = \frac{P_{out} * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1907261803-1E, antenna gain=1dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine SAR test exclusion. The test exclusion threshold is 0.00629mW/cm² which is < 1.0mW/cm², SAR testing is not required.

-----The End-----