



Maximum Permissible Exposure Evaluation

FCC ID: 2AT7C-MZ-622

Original Grant

Report No.	:	TBR-C-202504-0077-4	
Applicant	:	Shenzhen Innosystem Technology Co., Ltd	
Equipment Under Test (EUT)			
EUT Name	:	Bluetooth speaker	
Model No.	:	MZ-622	
Series Model No.	:	MZ-650, MZ-660	
Brand Name	:	INWA	
Sample ID	:	HC-C-202504-0077-01-07#& HC-C-202504-0077-01-08#	
Receipt Date	:	2025-04-22	
Test Date	:	2025-04-22 to 2025-06-12	
Issue Date	:	2025-06-12	
Standards	:	FCC Part 2.1091	
Test Method	:	KDB 447498 D01 General RF Exposure Guidance v06	
Conclusions	:	PASS	
		In the configuration tested, the EUT complied with the standards specified above.	
Test By	:	Lily.zhang	Lily Zhang
Reviewed By	:	Camille li	Camille Li
Approved By	:	Ivan Su	Ivan Su

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

CONTENTS

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Antenna Gain.....	4
2. MEASUREMENT UNCERTAINTY.....	5
3. TEST FACILITY.....	6
4. METHOD OF MEASUREMENT FOR FCC.....	7
5. TEST RESULT.....	8



Revision History



1. General Information about EUT

1.1 Client Information

Applicant	:	Shenzhen Innosystem Technology Co., Ltd
Address	:	201, Building 3, Shenzhen Software Park, Technology Middle 2Rd, Hi-Tech Park, ShenZhen, China
Manufacturer	:	Shenzhen Innosystem Technology Co., Ltd
Address	:	201, Building 3, Shenzhen Software Park, Technology Middle 2Rd, Hi-Tech Park, ShenZhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Bluetooth speaker
Models No.	:	MZ-622, MZ-650, MZ-660
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is appearance color.
Product Description	:	Operation Frequency: Bluetooth: 2402MHz~2480MHz
Power Rating	:	Adapter Model: J652-1903780EX Input: 100-240V~ 50/60Hz 1.7A Output: 19.0V--3.7A
Software Version	:	CS:BD0F1099
Hardware Version	:	----

Remark: The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

1.3 Antenna Gain

Band	Antenna Type	Antenna Gain(dBi)
Bluetooth	PCB	1.2



2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (ULab)
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB
Temperature	/	± 0.6 °C
Humidity	/	± 4 %
Supply voltages	/	± 2 %
Time	/	± 4 %



3. Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



4. Method of Measurement for FCC

4.1 EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4.3 Simultaneous transmission MPE Considerations

According to KDB447498 D01 v06: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . This means that:

$$\sum \text{ of MPE ratios} \leq 1.0$$



5. Test Result

MPE Result									
Mode	N _{TX}	Freq. (MHz)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]	limit (mW/cm ²)
GFSK (1Mbps)	1	2402	2.79	3±1	4	1.2	20	0.0007	1
		2441	3.676	4±1	5	1.2	20	0.0008	1
		2480	3.852	4±1	5	1.2	20	0.0008	1
Pi/4-DQPSK (2Mbps)	1	2402	3.112	3±1	4	1.2	20	0.0007	1
		2441	3.778	4±1	5	1.2	20	0.0008	1
		2480	3.947	4±1	5	1.2	20	0.0008	1
8-DPSK (3Mbps)	1	2402	3.227	3±1	4	1.2	20	0.0007	1
		2441	3.844	4±1	5	1.2	20	0.0008	1
		2480	3.99	4±1	5	1.2	20	0.0008	1

Note:
N_{TX}= Number of Transmit Antennas
RF Output power specifies that Maximum Conducted Peak Output Power.

Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/cm ²)
300-1,500	F/1500
1,500-100,000	1.0

MPE limit S: 1mW/ cm²

The MPE is calculated as 0.0008 mW / cm² < limit 1mW / cm².

So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b). The RF Exposure Information page from the manual is included here for reference.

-----END OF THE REPORT-----

