

SKU	G50 & G100 迈默 (带磁盖不开光) 说明书 Oplus
型号/产品名称/文件名称	展开尺寸: 770 X 130mm 折尺寸: 110 X 130mm
尺寸长x宽xmm	105G50磁盖 白色后盖 正反面通晒 风车折
材质	P55 G50/L100 L201
料号	
版本号	Z01

包装	测试	电子	结构	确认人	审核人
林科斌					
日期: 2023.4.20	日期:	日期:	日期:	日期:	日期:

Olafus®



LED FLOOD LIGHT

Product Manual

MODEL □ LA6202 □ LA6500 □ LA6100

LARISSE

- 1. 100% light source
- 2. 100% light source
- 3. 100% light source
- 4. 100% light source

LARISSE

- 1. 100% light source
- 2. 100% light source
- 3. 100% light source
- 4. 100% light source

LARISSE

- 1. 100% light source
- 2. 100% light source
- 3. 100% light source
- 4. 100% light source

SPECIFICATIONS			
LED Flood Light			
Model	LA512	LA512S	LA505SD
Wattage	100W	50W	50W
Beam Spread	50°/60°	50°/60°	1,17°
Rated Current	2000W	1000W	1000W
Rated Voltage	175VAC	200VAC	200VAC
Rated Power	100W	50W	50W
Color	COB	RGB	RGB
Power Factor	0.95	0.95	0.95
Life Span	50,000 hrs	50,000 hrs	50,000 hrs
Dimensions (mm)	400x200x120 (HxWxD)		
LED Flood Light Locations			
Applications			
Model	LA512S	LA505SD	LA505SD
Dimensions (mm)	400x200x120 (HxWxD)	400x200x120 (HxWxD)	400x200x120 (HxWxD)
Weight	1.5kg	1.5kg	1.5kg
			

[illegible][illegible]

Figure 4: How to pair the LED Light

1. Tap on the LED Light icon to pair the LED Light.
2. Tap on the LED Light icon to pair the LED Light.
3. Tap on the LED Light icon to pair the LED Light.
4. Tap on the LED Light icon to pair the LED Light.
5. Tap on the LED Light icon to pair the LED Light.

APP OPERATING INSTRUCTIONS

The figure shows two screenshots of the HP Color LaserJet printer's control panel. The top screenshot shows the 'Color' menu with options: 'Print', 'Copy', 'Scan', 'Fax', 'Color', 'Black', 'Red', 'Green', 'Blue', 'Magenta', 'Yellow', 'Cyan', 'Black', 'White', 'Gray', 'Color', 'Black', 'Red', 'Green', 'Blue', 'Magenta', 'Yellow', 'Cyan', 'Black', 'White', 'Gray'. The bottom screenshot shows the 'Color' menu with options: 'Print', 'Copy', 'Scan', 'Fax', 'Color', 'Black', 'Red', 'Green', 'Blue', 'Magenta', 'Yellow', 'Cyan', 'Black', 'White', 'Gray', 'Color', 'Black', 'Red', 'Green', 'Blue', 'Magenta', 'Yellow', 'Cyan', 'Black', 'White', 'Gray'.

[illegible]

PREPARATION

CAUTION:
PLEASE MAKE SURE YOUR WALL SWITCH AND POWER AT MAIN CIRCUIT BREAKER BOTH ARE OFF.

IF IN DOUBT ABOUT ELECTRICAL INSTALLATION, CONSULT A QUALIFIED ELECTRICIAN.

WARNING: INSTALLING THIS LIGHT IN AN UNGROUNDING CIRCUIT MAY CAUSE THE LIGHT TO OVERHEAT. ALWAYS USE THE WIRE GAUGE SPECIFIED IN THE INSTRUCTIONS. OVERHEATING OF THE WIRE COULD CAUSE THE WIRE TO MELT, SHORTING THE CIRCUIT, OR DAMAGE THE WIRE, CAUSING ELECTRICAL CONNECTIONS TO BE DAMAGED OR LOOSE IN THIS CASE, WHICH COULD CAUSE A SHORT CIRCUIT, FIRE, OR ELECTRICAL SHOCK, RESULTING IN INJURY OR DEATH.

BEFORE INSTALLING THE LIGHT, CHECK THE ELECTRICAL INSULATION, COVERING, AND CONDITION OF ALL WIRE. DO NOT LET THE WIRES TOUCH ANY SHARP EDGES.

WARNING:
THE PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL LOCAL CODES. FOLLOW THE INSTRUCTIONS AND THE INSTRUCTIONS OF THE MANUFACTURER OF THE CIRCUIT BREAKER AND THE MAIN SERVICE BUS.

[illegible]