



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20221202165E-02

Applicant: SHENZHEN CLOBOT INTELLIGENT TECHNOLOGY CO., LTD.

Address of Applicant: Area A&B, 7/F, Building 1, SZZT Industrial Park, No.3 Tongguan Road, Yutang Street, Guangming New District, Shenzhen, Guangdong, China

Equipment Under Test (EUT):

EUT Name: Robotic Vacuum Cleaner

Model No.: MT-210, MT-200, MT-220, MT-230, MT-240, MT-250, MT-260, MT-270, MT-280, MT-290, R20, R21, R22

Test Model No.: MT-210

Brand Name: N/A

FCC ID: 2AT9W-MT210

Standards: 47 CFR Part 1.1307

47 CFR Part 1.1310

447498 D04 Interim General RF Exposure Guidance v01

Date of Receipt: 2022-12-14

Date of Test: 2022-12-14 to 2023-01-03

Date of Issue: 2023-02-09

Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: lewis zhou

(Lewis Zhou)

Reviewed By: Timo Lei

(Timo Lei)

Approved By: Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20221202165E-02	Rev.01	Initial report	2023-02-09

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.1.3 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	SHENZHEN CLOBOT INTELLIGENT TECHNOLOGY CO., LTD.
Address of Applicant:	Area A&B, 7/F, Building 1, SZZT Industrial Park, No.3 Tongguan Road, Yutang Street, Guangming New District, Shenzhen, Guangdong, China
Manufacturer:	SHENZHEN CLOBOT INTELLIGENT TECHNOLOGY CO., LTD.
Address of Manufacturer:	Area A&B, 7/F, Building 1, SZZT Industrial Park, No.3 Tongguan Road, Yutang Street, Guangming New District, Shenzhen, Guangdong, China
Factory:	SHENZHEN CLOBOT INTELLIGENT TECHNOLOGY CO., LTD.
Address of Factory:	Area A&B, 7/F, Building 1, SZZT Industrial Park, No.3 Tongguan Road, Yutang Street, Guangming New District, Shenzhen, Guangdong, China

3.2 General Description of EUT

Product Name:	Robotic Vacuum Cleaner
Model No.:	MT-210, MT-200, MT-220, MT-230, MT-240, MT-250, MT-260, MT-270, MT-280, MT-290, R20, R21, R22
Test Model No.:	MT-210
Trade Mark:	N/A
Software Version:	V28.2.4
Hardware Version:	M210_V2.0
EUT Power Supply:	1# Li-ion battery: DC 14.8V 2600mAh, Charge by DC 19V for Charging Base 2# Li-ion battery: DC 12.8V 1800mAh, Charge by DC 19V for Charging Base Charging Base: Output: 19V 0.6A Dust collecting bucket: Power AC 120V~ 60Hz

3.3 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable
Antenna Type:	PCB antenna
Antenna Gain:	2.5dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda /2 \pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda /4$ or if the antenna gain is less than that of a half-wave Dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For 2.4G WIFI Classic

Measurement Data

11B mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	11.48	9.33	9.5±1	10.5	11.22
Middle(2437MHz)	12.1	9.95	10.0±1	11.0	12.59
Highest(2462MHz)	11.06	8.91	9.0±1	10.0	10.00
11G mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	9.17	7.02	7.0±1	8.0	6.31
Middle(2437MHz)	9.96	7.81	8.0±1	9.0	7.94
Highest(2462MHz)	9.07	6.92	7.0±1	8.0	6.31
11N20 mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2412MHz)	8.45	6.3	6.5±1	7.5	5.62
Middle(2437MHz)	9.31	7.16	7.0±1	8.0	6.31
Highest(2462MHz)	8.21	6.06	6.0±1	7.0	5.01

Note: 1) Refer to report No. CQASZ20221202165E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

*** END OF REPORT ***