

# FCC TEST REPORT

**Product Name:** NuStar 65 Portable Data Collector

**Trade Mark:**  **3nStar**

**Model No.:** Nustar65

**Report Number:** 24081713266EMC-1

**Test Standards:** FCC 47 CFR Part 15 Subpart B

**FCC ID:** 2ATAN-NUSTAR65

**Test Result:** PASS

**Date of Issue:** October 23, 2024

Prepared for:

**3nStar, Inc.**

**10813 NW 30th, Street, STE#110, Doral FL, 33172, USA**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F, Block A, Building 6th, Baoneng Science and Technology Park,**  
**Longhua Street, Longhua District, Shenzhen, China**

**TEL: +86-755-2823 0888**

**FAX: +86-755-2823 0886**

Prepared by:

*David Chen*

David Chen  
Senior Project Engineer

Reviewed by:

*Henry Lu*

Henry Lu  
Team Leader

Approved by:

*Robben Chen*

Robben Chen  
Assistant Manager

Date:

October 23, 2024

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.1

Version

| Version No. | Date             | Description |
|-------------|------------------|-------------|
| V1.0        | October 23, 2024 | Original    |



## CONTENTS

|                                                        |           |
|--------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION</b>                          | <b>4</b>  |
| 1.1 CLIENT INFORMATION                                 | 4         |
| 1.2 EUT INFORMATION                                    | 4         |
| 1.2.1 GENERAL DESCRIPTION OF EUT                       | 4         |
| 1.2.2 DESCRIPTION OF ACCESSORIES                       | 5         |
| 1.3 DESCRIPTION OF SUPPORT UNITS                       | 6         |
| 1.4 TEST LOCATION                                      | 6         |
| 1.5 TEST FACILITY                                      | 6         |
| 1.6 DEVIATION FROM STANDARDS                           | 6         |
| 1.7 ABNORMALITIES FROM STANDARD CONDITIONS             | 7         |
| 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER        | 7         |
| 1.9 MEASUREMENT UNCERTAINTY                            | 7         |
| <b>2. TEST SUMMARY</b>                                 | <b>8</b>  |
| <b>3. EQUIPMENT LIST</b>                               | <b>9</b>  |
| <b>4. TEST CONFIGURATION</b>                           | <b>10</b> |
| 4.1 ENVIRONMENTAL CONDITIONS FOR TESTING               | 10        |
| 4.1.1 NORMAL OR EXTREME TEST CONDITIONS                | 10        |
| 4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE     | 10        |
| 4.2 TEST MODES                                         | 10        |
| 4.3 TEST SETUP                                         | 11        |
| 4.3.1 FOR RADIATED EMISSIONS TEST SETUP                | 11        |
| 4.3.2 FOR CONDUCTED EMISSIONS TEST SETUP               | 12        |
| 4.4 SYSTEM TEST CONFIGURATION                          | 12        |
| <b>5. REFERENCE DOCUMENTS FOR TESTING</b>              | <b>13</b> |
| <b>6. EMC REQUIREMENTS SPECIFICATION</b>               | <b>13</b> |
| 6.1 RADIATED EMISSION                                  | 13        |
| 6.2 CONDUCTED EMISSION                                 | 18        |
| <b>APPENDIX 1 PHOTOS OF TEST SETUP</b>                 | <b>21</b> |
| <b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b> | <b>21</b> |


## 1. GENERAL INFORMATION

### 1.1 CLIENT INFORMATION

|                                 |                                                      |
|---------------------------------|------------------------------------------------------|
| <b>Applicant:</b>               | 3nStar, Inc.                                         |
| <b>Address of Applicant:</b>    | 10813 NW 30th, Street, STE#110, Doral FL, 33172, USA |
| <b>Manufacturer:</b>            | 3nStar, Inc.                                         |
| <b>Address of Manufacturer:</b> | 10813 NW 30th, Street, STE#110, Doral FL, 33172, USA |

### 1.2 EUT INFORMATION

#### 1.2.1 General Description of EUT

|                                           |                                                                                                                                          |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name:</b>                      | NuStar 65 Portable Data Collector                                                                                                        |
| <b>Model No.:</b>                         | Nustar65                                                                                                                                 |
| <b>Trade Mark:</b>                        |                                                         |
| <b>DUT Stage:</b>                         | Identical Prototype                                                                                                                      |
| <b>Rated Voltage:</b>                     | <input checked="" type="checkbox"/> Powered by Cradle                                                                                    |
|                                           | <input checked="" type="checkbox"/> Powered by USB port                                                                                  |
|                                           | <input checked="" type="checkbox"/> Powered by 3.87Vdc (1x3.87V Lithium-ion Battery)                                                     |
|                                           | <input checked="" type="checkbox"/> Powered by AC/DC adapter<br>Input: 100-240V~50/60Hz, 0.5A<br>Output: 5.0 V $\Rightarrow$ 2.0 A       |
| <b>Classification of digital devices:</b> | Class B                                                                                                                                  |
| <b>Highest Internal Frequency:</b>        | 5825 MHz                                                                                                                                 |
| <b>Software Version:</b>                  | S651-G1-SC6101-NU419-V3.01.240830 (Provided by the customer)                                                                             |
| <b>Hardware Version:</b>                  | S651_MA_B08D_V1.0 (Provided by the customer)                                                                                             |
| <b>Sample Received Date:</b>              | August 16, 2024                                                                                                                          |
| <b>Sample Tested Date:</b>                | August 19, 2024 to August 27, 2024                                                                                                       |
| <b>Remark:</b>                            | The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description. |

## 1.2.2 Description of Accessories

| Adapter    |                         |
|------------|-------------------------|
| Model No.: | BI12T-050200-BdVU       |
| Input:     | 100-240 V~50/60 Hz 0.5A |
| Output:    | 5.0 V $\equiv$ 2.0A     |

| Battery                 |                             |
|-------------------------|-----------------------------|
| Model No.:              | BAT-655001                  |
| Battery Type:           | Rechargeable Li-ion Battery |
| Rated Voltage:          | 3.87 Vdc                    |
| Limited Charge Voltage: | 4.45 Vdc                    |
| Rated Capacity:         | 5050 mAh                    |

| Cable        |                                    |
|--------------|------------------------------------|
| Description: | USB Type-C to USB 3.0 Type A Cable |
| Connector:   | USB Type-C / USB 3.0 Type A        |
| Cable Type:  | Shielded without ferrite           |
| Length:      | 1 Meter                            |

| Adapter (Desktop Cradle) |                         |
|--------------------------|-------------------------|
| Model No.:               | BI24G-120200-AdU        |
| Input:                   | 100-240 V~50/60 Hz 0.8A |
| Output:                  | 12 V $\equiv$ 2.0A      |

| Desktop Cradle |                                                     |
|----------------|-----------------------------------------------------|
| Model No.:     | S65-HB                                              |
| Input:         | Input: 12.0 V $\equiv$ 2.0A                         |
| Output:        | Output: 5.0 V $\equiv$ 3.0A and 4.4 V $\equiv$ 1.7A |

### 1.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

| Description | Manufacturer | Model No.     | Serial Number     | Supplied by |
|-------------|--------------|---------------|-------------------|-------------|
| Notebook    | DELL         | Inspiron 5593 | N/A               | UnionTrust  |
| Notebook    | DELL         | Latitude 3400 | 16238087894       | UnionTrust  |
| Mouse       | Lenovo       | MOGOUO        | 8S0A36101NWTZ1549 | UnionTrust  |
| Earphone    | HUAWEI       | N/A           | N/A               | UnionTrust  |

2) Support Cable

| Cable No. | Description | Connector | Length | Supplied by |
|-----------|-------------|-----------|--------|-------------|
| --        | --          | --        | --     | --          |

### 1.4 TEST LOCATION

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

### 1.5 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

**CNAS-Lab Code: L9069**

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

**A2LA-Lab Certificate No.: 4312.01**

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**ISED Wireless Device Testing Laboratories**

CAB identifier: CN0032

**FCC Accredited Lab.**

Designation Number: CN1194

Test Firm Registration Number: 259480

### 1.6 DEVIATION FROM STANDARDS

None.

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.1

## 1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

## 1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

## 1.9 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

| No. | Item                            | Measurement Uncertainty |
|-----|---------------------------------|-------------------------|
| 1   | Conducted emission 9kHz-150kHz  | $\pm 3.2$ dB            |
| 2   | Conducted emission 150kHz-30MHz | $\pm 2.7$ dB            |
| 3   | Radiated emission 9kHz-30MHz    | $\pm 4.7$ dB            |
| 4   | Radiated emission 30MHz-1GHz    | $\pm 4.6$ dB            |
| 5   | Radiated emission 1GHz-18GHz    | $\pm 4.4$ dB            |
| 6   | Radiated emission 18GHz-40GHz   | $\pm 4.6$ dB            |

## 2. TEST SUMMARY

| FCC 47 CFR Part 15 Subpart B Test Cases |                        |                 |        |
|-----------------------------------------|------------------------|-----------------|--------|
| Test Item                               | Test Requirement       | Test Method     | Result |
| Conducted Emission                      | FCC 47 CFR Part 15.107 | ANSI C63.4-2014 | PASS   |
| Radiated Emission                       | FCC 47 CFR Part 15.109 | ANSI C63.4-2014 | PASS   |



### 3. EQUIPMENT LIST

| Radiated Emission Test Equipment List |                                                      |              |            |                            |             |               |
|---------------------------------------|------------------------------------------------------|--------------|------------|----------------------------|-------------|---------------|
| Used                                  | Equipment                                            | Manufacturer | Model No.  | Serial Number              | Cal. date   | Cal. Due date |
| <input checked="" type="checkbox"/>   | 3m SAC                                               | ETS-LINDGREN | 3M         | Euroshiedpn-CT001270-1317  | 11-Nov-2023 | 10-Nov-2026   |
| <input checked="" type="checkbox"/>   | Receiver                                             | R&S          | ESIB26     | 100114                     | 27-Oct-2023 | 26-Oct-2024   |
| <input type="checkbox"/>              | Loop Antenna                                         | ETS-LINDGREN | 6502       | 00202525                   | 30-Oct-2023 | 29-Oct-2024   |
| <input checked="" type="checkbox"/>   | Broadband Antenna                                    | ETS-LINDGREN | 3142E      | 00201566                   | 30-Oct-2023 | 29-Oct-2024   |
| <input checked="" type="checkbox"/>   | 6dB Attenuator                                       | Talent       | RA6A5-N-18 | 18103001                   | 30-Oct-2023 | 29-Oct-2024   |
| <input checked="" type="checkbox"/>   | Preamplifier                                         | HP           | 8447F      | 2805A02960                 | 31-Oct-2023 | 30-Oct-2024   |
| <input checked="" type="checkbox"/>   | Double-Ridged Waveguide Horn Antenna (Pre-amplifier) | ETS-LINDGREN | 3117-PA    | 00201541                   | 01-Apr-2024 | 31-Mar-2025   |
| <input checked="" type="checkbox"/>   | Pre-amplifier                                        | ETS-LINDGREN | 00118385   | 00201874                   | 31-Oct-2023 | 30-Oct-2024   |
| <input checked="" type="checkbox"/>   | Double-Ridged Waveguide Horn Antenna (Pre-amplifier) | ETS-LINDGREN | 3116C-PA   | 00202652                   | 30-Oct-2023 | 29-Oct-2024   |
| <input checked="" type="checkbox"/>   | Pre-amplifier                                        | ETS-LINDGREN | 00118384   | 00202652                   | 30-Oct-2023 | 29-Oct-2024   |
| <input checked="" type="checkbox"/>   | Multi device Controller                              | ETS-LINDGREN | 7006-001   | 00160105                   | N/A         | N/A           |
| <input checked="" type="checkbox"/>   | Test Software                                        | Audix        | e3         | Software Version: 9.160323 |             |               |

| Conducted Emission Test Equipment List |               |              |           |                                 |             |               |
|----------------------------------------|---------------|--------------|-----------|---------------------------------|-------------|---------------|
| Used                                   | Equipment     | Manufacturer | Model No. | Serial Number                   | Cal. date   | Cal. Due date |
| <input checked="" type="checkbox"/>    | Receiver      | R&S          | ESR7      | 101181                          | 27-Oct-2023 | 26-Oct-2024   |
| <input checked="" type="checkbox"/>    | Pulse Limiter | R&S          | ESH3-Z2   | 0357.8810.54                    | 27-Oct-2023 | 26-Oct-2024   |
| <input checked="" type="checkbox"/>    | LISN          | R&S          | ESH2-Z5   | 860014/024                      | 27-Oct-2023 | 26-Oct-2024   |
| <input type="checkbox"/>               | LISN          | ETS-Lindgren | 3816/2SH  | 00201088                        | 27-Oct-2023 | 26-Oct-2024   |
| <input checked="" type="checkbox"/>    | Test Software | EZ-EMC       | EZ-CON    | Software Version: EMC-CON 3A1.1 |             |               |

## 4. TEST CONFIGURATION

### 4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

#### 4.1.1 Normal or Extreme Test Conditions

| Environment Parameter                                           | Selected Values During Tests |                                                                        |                       |
|-----------------------------------------------------------------|------------------------------|------------------------------------------------------------------------|-----------------------|
| Test Condition                                                  | Ambient                      |                                                                        |                       |
|                                                                 | Temperature (°C)             | Voltage                                                                | Relative Humidity (%) |
| NT/NV                                                           | +15 to +35                   | 1. 120V~60Hz and/or 3.87V Battery<br>2. 240V~50Hz and/or 3.87V Battery | 20 to 75              |
| <b>Remark:</b><br>1) NV: Normal Voltage; NT: Normal Temperature |                              |                                                                        |                       |

#### 4.1.2 Record of Normal Environment and Test Sample

| Test Item          | Temp. (°C) | Relative Humidity (%) | Pressure (kPa) | Sample No.             | Tested by  |
|--------------------|------------|-----------------------|----------------|------------------------|------------|
| Radiated Emission  | 25.3       | 54.2                  | 100.0          | S2202408164150-ZJA03/7 | Jackson Wu |
| Conducted Emission | 23.7       | 57.3                  | 99.9           |                        | Linson Xie |

### 4.2 TEST MODES

| Test Item                                                                                                              | EMI Test Modes                                                                                                                                          |
|------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Radiated Emission                                                                                                      | <b>Test Mode 1:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>MP4 playing</b> + GSM 850 idle + Wi-Fi idle + BT idle + GNSS + NFC            |
|                                                                                                                        | <b>Test Mode 2:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>Camera (Front)</b> + WCDMA Band V idle + Wi-Fi idle + BT idle + GNSS + NFC    |
|                                                                                                                        | <b>Test Mode 3:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>Camera (Back)</b> + LTE Band 5 idle + Wi-Fi idle + BT idle + GNSS + NFC       |
|                                                                                                                        | <b>Test Mode 4:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>Scan+ Camera (Top)</b> + LTE Band 26 idle + Wi-Fi idle + BT idle + GNSS + NFC |
|                                                                                                                        | <b>Test Mode 5:</b> Charging from Adapter (with 240 Vac) + <b>Worse from test mode 1~4</b> + GSM 1900 + Wi-Fi idle + BT idle + GNSS + NFC               |
|                                                                                                                        | <b>Test Mode 6:</b> Charging from <b>Cradle</b> + <b>Worse from test mode 1~4</b> + LTE Band 7 idle + Wi-Fi idle + BT idle + GNSS + NFC                 |
|                                                                                                                        | <b>Test Mode 7:</b> Airplane mode + <b>Worse from test mode 1~4</b> + Earphone (Type-C)                                                                 |
|                                                                                                                        | <b>Test Mode 8:</b> Data transfer with notebook + USB Cable + <b>LTE Band 38 idle + Wi-Fi idle + BT idle + GNSS + NFC</b>                               |
| Conducted Emission                                                                                                     | <b>Test Mode 1:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>MP4 playing</b> + GSM 850 idle + Wi-Fi idle + BT idle + GNSS + NFC            |
|                                                                                                                        | <b>Test Mode 2:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>Camera (Front)</b> + WCDMA Band V idle + Wi-Fi idle + BT idle + GNSS + NFC    |
|                                                                                                                        | <b>Test Mode 3:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>Camera (Back)</b> + LTE Band 5 idle + Wi-Fi idle + BT idle + GNSS + NFC       |
|                                                                                                                        | <b>Test Mode 4:</b> Charging from Adapter (with 120 Vac) + USB Cable + <b>Scan+ Camera (Top)</b> + LTE Band 26 idle + Wi-Fi idle + BT idle + GNSS + NFC |
|                                                                                                                        | <b>Test Mode 5:</b> Charging from Adapter (with 240 Vac) + <b>Worse from test mode 1~4</b> + GSM 1900 + Wi-Fi idle + BT idle + GNSS + NFC               |
|                                                                                                                        | <b>Test Mode 6:</b> Charging from <b>Cradle</b> + <b>Worse from test mode 1~4</b> + LTE Band 7 idle + Wi-Fi idle + BT idle + GNSS + NFC                 |
|                                                                                                                        | <b>Test Mode 7:</b> Data transfer with notebook + USB Cable + <b>LTE Band 38 idle + Wi-Fi idle + BT idle + GNSS + NFC</b>                               |
| <b>Remark:</b> The above test modes in boldface were the worst cases, only the test data of these modes were reported. |                                                                                                                                                         |

### 4.3 TEST SETUP

#### 4.3.1 For Radiated Emissions test setup

Figure 1. 30MHz to 1GHz





Figure 2. Above 1GHz





## 5. REFERENCE DOCUMENTS FOR TESTING

| No. | Identity                                 | Document Title                                                                                                                                                      |
|-----|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | FCC 47 CFR Part15 Subpart B              | Unintentional Radiators                                                                                                                                             |
| 2   | ANSI C63.4-2014                          | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |
| 3   | KDB 174176 D01 Line Conducted FAQ v01r01 | AC power-line conducted emission frequency asked questions                                                                                                          |
| 4   | KDB 896810 D02 SDoC FAQ v01r02           | Supplier's Declaration of Conformity frequency asked questions                                                                                                      |

## 6. EMC REQUIREMENTS SPECIFICATION

### 6.1 RADIATED EMISSION

**Test Requirement:** FCC 47 CFR Part 15.109

**Test Method:** ANSI C63.4-2014

**Receiver Setup:**

| Frequency: (f)<br>(MHz) | Detector type | Measurement receiver bandwidth |         |
|-------------------------|---------------|--------------------------------|---------|
|                         |               | RBW                            | VBW     |
| $30 \leq f \leq 1\,000$ | Quasi Peak    | 120 kHz                        | 300 kHz |
| $f \geq 1000$           | Peak          | 1 MHz                          | 3 MHz   |
|                         | Average       | 1 MHz                          | 3 MHz   |

**Measured frequency range**

| Highest frequency generated or used in the device or on which the device operates or tunes (MHz) | Upper frequency of measurement range (MHz)                           |
|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| Below 1.705                                                                                      | 30.                                                                  |
| 1.705-108                                                                                        | 1000.                                                                |
| 108-500                                                                                          | 2000.                                                                |
| 500-1000                                                                                         | 5000.                                                                |
| Above 1000                                                                                       | 5th harmonic of the highest frequency or 40 GHz, whichever is lower. |

**Limits:**

Limits for Class B devices

| Frequency (MHz) | limits at 3m (dB $\mu$ V/m) |             |             |
|-----------------|-----------------------------|-------------|-------------|
|                 | QP Detector                 | PK Detector | AV Detector |
| 30-88           | 40.0                        | --          | --          |
| 88-216          | 43.5                        | --          | --          |
| 216-960         | 46.0                        | --          | --          |
| 960 to 1000     | 54.0                        | --          | --          |
| Above 1000      | --                          | 74.0        | 54.0        |

**Remark:**

- The lower limit shall apply at the transition frequencies.
- Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).
- For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

**Test Setup:** Refer to section 4.3.1 for details.

**Test Procedures:**

- From 30 MHz to 1GHz test procedure as below:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.1

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 120 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP value: vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

2. Above 1GHz test procedure as below:

- 1) The Product was placed on the non-conductive turntable 0.8 m above the ground at a chamber.
- 2) Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- 3) For each frequency whose maximum record was higher or close to limit, measure its AV value: rotate the turntable from 0 to 360 degrees to find the degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to AV value and specified bandwidth with Maximum Hold Mode, and record the maximum value.

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass

**The worst measurement data as follows:**

**Below 1GHz (Quasi Peak):**


**Test Mode 1**

**Horizontal**



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|--------------------------|-----------------|----------------|-------------|----------|
| 1   | 32.049          | 33.74          | -6.14                    | 27.60           | 40.00          | -12.40      | QP       |
| 2   | 51.675          | 36.77          | -14.30                   | 22.47           | 40.00          | -17.53      | QP       |
| 3   | 88.109          | 39.88          | -16.32                   | 23.56           | 43.50          | -19.94      | QP       |
| 4   | 196.670         | 41.31          | -11.18                   | 30.13           | 43.50          | -13.37      | QP       |
| 5   | 583.513         | 27.05          | -1.17                    | 25.88           | 46.00          | -20.12      | QP       |
| 6   | 950.450         | 23.46          | 5.23                     | 28.69           | 46.00          | -17.31      | QP       |

# Vertical



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|--------------------------|-----------------|----------------|-------------|----------|
| 1   | 30.306          | 40.44          | -4.65                    | 35.79           | 40.00          | -4.21       | QP       |
| 2   | 35.658          | 41.20          | -6.73                    | 34.47           | 40.00          | -5.53       | QP       |
| 3   | 83.319          | 54.28          | -17.58                   | 36.70           | 40.00          | -3.30       | QP       |
| 4   | 194.681         | 45.83          | -11.14                   | 34.69           | 43.50          | -8.81       | QP       |
| 5   | 548.992         | 26.22          | -1.66                    | 24.56           | 46.00          | -21.44      | QP       |
| 6   | 854.242         | 24.16          | 4.04                     | 28.20           | 46.00          | -17.80      | QP       |

## Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.1

Above 1GHz (Peak & Average)  
Test Mode 8  
Horizontal



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|--------------------------|-----------------|----------------|-------------|----------|
| 1   | 1003.400        | 38.83          | -12.92                   | 25.91           | 54.00          | -28.09      | Average  |
| 2   | 1003.400        | 50.95          | -12.92                   | 38.03           | 74.00          | -35.97      | Peak     |
| 3   | 3035.104        | 34.90          | -6.01                    | 28.89           | 54.00          | -25.11      | Average  |
| 4   | 3035.104        | 47.03          | -6.01                    | 41.02           | 74.00          | -32.98      | Peak     |
| 5   | 4876.388        | 33.94          | -2.05                    | 31.89           | 54.00          | -22.11      | Average  |
| 6   | 4876.388        | 48.09          | -2.05                    | 46.04           | 74.00          | -27.96      | Peak     |
| 7   | 6415.042        | 34.51          | 1.08                     | 35.59           | 54.00          | -18.41      | Average  |
| 8   | 6415.042        | 46.63          | 1.08                     | 47.71           | 74.00          | -26.29      | Peak     |
| 9   | 7256.625        | 37.78          | 1.30                     | 39.08           | 54.00          | -14.92      | Average  |
| 10  | 7256.625        | 49.91          | 1.30                     | 51.21           | 74.00          | -22.79      | Peak     |
| 11  | 9230.523        | 37.61          | 2.90                     | 40.51           | 54.00          | -13.49      | Average  |
| 12  | 9230.523        | 49.74          | 2.90                     | 52.64           | 74.00          | -21.36      | Peak     |

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: [info@uttlab.com](mailto:info@uttlab.com)

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.1

# Vertical



## Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. All possible modes of operation were investigated, and testing at two nominal voltages of 240V~50Hz and 120V~60Hz, only the worst case emissions reported.
5. For Radiated Emission above 18GHz, there was not any unwanted emission detected.

## Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-EMC-FCCPART15B-V1.1

## 6.2 CONDUCTED EMISSION

**Test Requirement:** FCC 47 CFR Part 15.107

**Test Method:** ANSI C63.4-2014

**Limits:**

Limits for Class B devices

| Frequency range<br>(MHz) | Limits (dB(μV)) |          |
|--------------------------|-----------------|----------|
|                          | Quasi-peak      | Average  |
| 0,15 to 0,50             | 66 to 56        | 56 to 46 |
| 0,50 to 5                | 56              | 46       |
| 5 to 30                  | 60              | 50       |

**Remark:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

**Test Setup:** Refer to section 4.3.2 for details.

**Test Procedures:**

- 1) The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- 2) The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- 3) For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass

The worst measurement data as follows:

Quasi Peak and Average:


Test Mode 6

Live Line



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|------------------------|---------------|--------------|-------------|----------|
| 1   | 0.1541          | 46.66          | 10.20                  | 56.86         | 65.78        | -8.92       | QP       |
| 2   | 0.1541          | 24.95          | 10.20                  | 35.15         | 55.78        | -20.63      | AVG      |
| 3   | 0.1963          | 41.48          | 10.16                  | 51.64         | 63.77        | -12.13      | QP       |
| 4   | 0.1963          | 20.31          | 10.16                  | 30.47         | 53.77        | -23.30      | AVG      |
| 5   | 0.2893          | 41.76          | 10.21                  | 51.97         | 60.54        | -8.57       | QP       |
| 6   | 0.2893          | 17.87          | 10.21                  | 28.08         | 50.54        | -22.46      | AVG      |
| 7   | 0.5460          | 41.55          | 10.19                  | 51.74         | 56.00        | -4.26       | QP       |
| 8   | 0.5460          | 26.86          | 10.19                  | 37.05         | 46.00        | -8.95       | AVG      |
| 9   | 1.0950          | 30.11          | 10.33                  | 40.44         | 56.00        | -15.56      | QP       |
| 10  | 1.0950          | 13.98          | 10.33                  | 24.31         | 46.00        | -21.69      | AVG      |
| 11  | 13.6272         | 35.29          | 10.50                  | 45.79         | 60.00        | -14.21      | QP       |
| 12  | 13.6272         | 23.72          | 10.50                  | 34.22         | 50.00        | -15.78      | AVG      |

## Neutral Line



| No. | Frequency (MHz) | Reading (dBuV) | Correction factor (dB) | Result (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|------------------------|---------------|--------------|-------------|----------|
| 1   | 0.1661          | 46.08          | 10.15                  | 56.23         | 65.15        | -8.92       | QP       |
| 2   | 0.1661          | 25.35          | 10.15                  | 35.50         | 55.15        | -19.65      | AVG      |
| 3   | 0.2115          | 41.03          | 10.05                  | 51.08         | 63.15        | -12.07      | QP       |
| 4   | 0.2115          | 20.15          | 10.05                  | 30.20         | 53.15        | -22.95      | AVG      |
| 5   | 0.2478          | 36.55          | 10.08                  | 46.63         | 61.83        | -15.20      | QP       |
| 6   | 0.2478          | 16.66          | 10.08                  | 26.74         | 51.83        | -25.09      | AVG      |
| 7   | 0.2805          | 34.11          | 10.09                  | 44.20         | 60.80        | -16.60      | QP       |
| 8   | 0.2805          | 11.55          | 10.09                  | 21.64         | 50.80        | -29.16      | AVG      |
| 9   | 0.3614          | 42.83          | 10.15                  | 52.98         | 58.70        | -5.72       | QP       |
| 10  | 0.3614          | 12.52          | 10.15                  | 22.67         | 48.70        | -26.03      | AVG      |
| 11  | 13.6320         | 35.19          | 10.58                  | 45.77         | 60.00        | -14.23      | QP       |
| 12  | 13.6320         | 23.48          | 10.58                  | 34.06         | 50.00        | -15.94      | AVG      |

## Remark:

1. Correct Factor = LISN Factor + Cable Loss + Pulse Limiter Factor, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit
4. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.
5. All possible modes of operation were investigated, and testing at two nominal voltages of 240V~50Hz and 120V~60Hz, only the worst case emissions reported.

## APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

---

\*\*\*\*\* End of Report \*\*\*\*\*

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---