

MPE Analysis Report

The Equipment-Under-Test (EUT) aspara is a hydroponic smart grower that helps you grow fresh and healthy-to-eat vegetables and herbs right on your kitchen countertop. It has a microcontroller with integrated wifi, which control the water circulation and lighting of the device, and communicate with the server. The EUT is powered by a 24V AC AC/DC adaptor.

WiFi Module

Antenna Type: Internal, Integral

Antenna Gain: 2 dBi

Operating mode	Range of Peak Conducted Power	Modulation Type
<u>WLAN portion</u>		
802.11b	15dBm to 20dBm	DSSS
802.11g	10dBm to 15dBm	OFDM
802.11n (HT20)	10dBm to 15dBm	MCSn (n=0 to 7)
802.11n (HT40)	10dBm to 15dBm	MCSn (n=0 to 7)

For Maximum Permissible Exposure (MPE) evaluation of the unit, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65 and meet the requirement listed in KDB447498.

For the WiFi portion of the unit, the measured powers among all the measured channels were within its production tolerance. The antenna gain is 2 dBi = 1.58 (num gain) and its maximum source-based time-averaging duty factor is 100%. From these data and its operating configuration, the exposed power density at a distance (R) of **Error! Reference source not found.**cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

The EIRP radiated power
 = conducted power (with maximum tolerance) + antenna gain
 = 20 dBm + 2 dBi
 = 22 dBm (158.5 mW)

The radiated (EIRP) source-based time-averaging output power
 = (158.5 * 1) mW
 = 158.5 mW

The power density at 20 cm from the antenna
 = EIRP / $4\pi R^2$
 = 0.0315 mW cm⁻²

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm⁻² for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons.

The following RF exposure statement is proposed to be included in the user manual:

“ FCC RF Radiation Exposure Statement

Caution: To maintain compliance with the FCC's RF exposure guidelines, place the unit at least 20cm from nearby persons.”