

Ingersoll-Rand Industrial U.S., Inc.

RF TEST REPORT

Report Type:

FCC Part 15.247 & ISSED RSS-247 RF report

Model:

RTS025PQ4, RTS060PS6, RTS060PH6, RTS060PS8,
RTS060PH8, RTS140PS8, RTS140PH8, RTS225PS8,
RTS225PH8

REPORT NUMBER:

2311A1829SHA-002

ISSUE DATE:

Jun 5, 2024

DOCUMENT CONTROL NUMBER:

TTRF15.247-02_V1 © 2018 Intertek



Applicant: Ingersoll-Rand Industrial U.S., Inc.
525 Harbour Place Drive Davidson NC 28036 United States Of America

Manufacturer: Ingersoll-Rand Industrial U.S., Inc.
525 Harbour Place Drive Davidson NC 28036 United States Of America

FCC ID: 2ATB3-RTSSTM55WB

IC: 25117-RTSSTM55WB

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2023): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 3 (August 2023): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 (April 2018)+A1(March 2019)+A2(February 2021): General Requirements for Compliance of Radio Apparatus

PREPARED BY:

REVIEWED BY:



Project Engineer
Teddy Yin

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	5
MEASUREMENT RESULT SUMMARY	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION	8
1.3 DESCRIPTION OF TEST FACILITY	9
2 TEST SPECIFICATIONS.....	10
2.1 STANDARDS OR SPECIFICATION	10
2.2 MODE OF OPERATION DURING THE TEST.....	10
2.3 TEST SOFTWARE LIST	11
2.4 TEST PERIPHERALS LIST	11
2.5 TEST ENVIRONMENT CONDITION:.....	11
2.6 INSTRUMENT LIST	12
2.7 MEASUREMENT UNCERTAINTY	13
3 MINIMUM 6DB BANDWIDTH.....	14
3.1 LIMIT	14
3.2 MEASUREMENT PROCEDURE	14
3.3 TEST CONFIGURATION	14
3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH	14
4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.....	15
4.1 LIMIT	15
4.2 MEASUREMENT PROCEDURE	15
4.3 TEST CONFIGURATION	15
4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER.....	15
5 POWER SPECTRUM DENSITY	16
5.1 LIMIT	16
5.2 MEASUREMENT PROCEDURE	16
5.3 TEST CONFIGURATION	16
5.4 TEST RESULTS OF POWER SPECTRUM DENSITY	16
6 EMISSION OUTSIDE THE FREQUENCY BAND	17
6.1 LIMIT	17
6.2 MEASUREMENT PROCEDURE	17
6.3 TEST CONFIGURATION	18
6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND.....	18
7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS.....	19
7.1 LIMIT	19
7.2 MEASUREMENT PROCEDURE	19
7.3 TEST CONFIGURATION	21
7.4 TEST RESULTS OF RADIATED EMISSIONS	23
8 POWER LINE CONDUCTED EMISSION.....	26
8.1 LIMIT	26

TEST REPORT

8.2	TEST CONFIGURATION	26
8.3	MEASUREMENT PROCEDURE	27
8.4	TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	28
9	OCCUPIED BANDWIDTH	29
9.1	LIMIT	29
9.2	MEASUREMENT PROCEDURE	29
9.3	TEST CONFIGURATION	29
9.4	THE RESULTS OF OCCUPIED BANDWIDTH	29
10	ANTENNA REQUIREMENT	30
	APPENDIX A: TEST RESULTS	31

Revision History

Report No.	Version	Description	Issued Date
2311A1829SHA-002	Rev. 01	Initial issue of report	Jun 5, 2024

Measurement result summary

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	RSS-247 Issue 3 Clause 5.2	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	RSS-247 Issue 3 Clause 5.4	Pass
Power spectrum density	15.247(e)	RSS-247 Issue 3 Clause 5.2	Pass
Emission outside the frequency band	15.247(d)	RSS-247 Issue 3 Clause 5.5	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Power line conducted emission	15.207(a)	RSS-Gen Issue 5 Clause 8.8	NA
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.7	Tested
Antenna requirement	15.203	-	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Mechanical Pulse Wrench
Type/Model/PMN/HVIN:	RTS025PQ4, RTS060PS6, RTS060PH6, RTS060PS8, RTS060PH8, RTS140PS8, RTS140PH8, RTS225PS8, RTS225PH8
Description of EUT:	The EUT is Mechanical pulse wrench with WIFI 2.4G/ 5G, Zigbee and BLE functions. All models are fully same except for the head part's shape and size. The details are in the following table. RTS060PS6 was tested as representative. This report is for Zigbee function.
Rating:	DC 20V
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample No.:	A240305-21-001
Sample received date:	Jan 31, 2024
Date of test:	Jan 31~Apr 3, 2024

Model	Output shaft					Impact hammer & Spring			
	1/4" Hex	3/8" Ring with Hole	3/8" Pin	1/2" Ring with Hole	1/2" Pin	A	B	C	D
RTS025PQ4	■					■			
RTS060PS6			■				■		
RTS060PH6		■					■		
RTS060PS8					■		■		
RTS060PH8				■			■		
RTS140PS8					■			■	
RTS140PH8				■				■	
RTS225PS8					■				■
RTS225PH8				■					■

TEST REPORT

Impact hammer & Spring : Model A, B, C, D



1.2 Technical Specification

Frequency Range:	2405-2480MHz
Support Standards:	Zigbee
Type of Modulation:	O-QPSK
Channel Number:	16
Data Rate:	250kbps

TEST REPORT

Channel Separation:	5MHz
Antenna Information:	2.03dBi, Chip antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2023)

ANSI C63.10 (2013)

KDB 558074 D01(v05r02)

RSS-247 Issue 3 (August 2023)

RSS-Gen Issue 5 (April 2018)+A1(March 2019) +A2(February 2021)

2.2 Mode of operation during the test

The lowest, middle and highest channel were tested as representatives.

Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2405 MHz	6	2435 MHz	12	2465 MHz
1	2410 MHz	7	2440 MHz	13	2470 MHz
2	2415 MHz	8	2445 MHz	14	2475 MHz
3	2420 MHz	9	2450 MHz	15	2480 MHz
4	2425 MHz	10	2455 MHz	-	-
5	2430 MHz	11	2460 MHz	-	-

Data rate VS Power:

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

Test software and Power Setting parameter			
Test Software	STM32CubeMonitor-RF		
Working Mode	Zigbee		
Test Channel	2405MHz	2440MHz	2480MHz
Power Setting	default	default	default

TEST REPORT

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

Radiated test mode: EUT transmitted signal with zigbee antenna;

Conducted test mode: EUT transmitted signal from zigbee RF port connected to SPA directly;

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
1	Laptop computer	DELL 5480	/
2			

2.5 Test environment condition:

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	22°C	55% RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	22°C	55% RH
Power line conducted emission	/	/

2.6 Instrument list

Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2024-08-24
☒	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2024-09-12
☒	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC 5262	2024-06-15
☒	Horn antenna	ETS	3117	EC 4792-1	2024-09-15
☒	Horn antenna	ETS	3116c	EC 5955	2024-07-22
☒	Semi-anechoic chamber	Albatross	-	EC 3048	2024-07-08
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2025-03-07
☒	Coaxial cable	ETS	/	/	2024-06-15
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	Testo	175h1	EC 6640	2024-08-28
☒	Therom-Hygrograph	Testo	175h1	EC 6641	2024-08-28

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 Minimum 6dB bandwidth

Test result: Pass


3.1 Limit

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2 Measurement Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3 Test Configuration



3.4 Test Results of Minimum 6dB bandwidth

Please refer to Appendix A

4 Maximum conducted output power and e.i.r.p.

Test result: Pass

4.1 Limit


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands:
1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

4.2 Measurement Procedure

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

4.3 Test Configuration



4.4 Test Results of Maximum conducted output power

Please refer to Appendix A

5 Power spectrum density

Test result: Pass

5.1 Limit


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and $8 + (6 - \text{antenna gain} - \text{beam forming gain})$.

5.2 Measurement Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Test Configuration



5.4 Test Results of Power spectrum density

Please refer to Appendix A

6 Emission outside the frequency band

Test result: Pass

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

6.2 Measurement Procedure

Reference level measurement

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

6.3 Test Configuration



6.4 The results of Emission outside the frequency band

Please refer to Appendix A

7 Radiated Emissions in restricted frequency bands

Test result: Pass

7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

7.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters (0.1 meters for floor-standing device) above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, the lowest height of the magnetic antenna was 1 m above the ground.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) or 0.1 meters (for floor-standing device) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or $3 \times \text{RBW}$ (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported

7.3 Test Configuration


For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:



For Radiated emission above 1GHz:



7.4 Test Results of Radiated Emissions


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

The worst waveform from 30MHz to 1000MHz is listed as below:

Horizontal



Vertical



TEST REPORT

Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	59.16	19.10	14.20	40.00	20.90	PK
H	164.13	25.40	14.50	43.50	18.10	PK
H	214.67	26.40	12.00	43.50	17.10	PK
H	436.27	27.00	18.50	46.00	19.00	PK
H	692.87	29.90	23.40	46.00	16.10	PK
H	953.35	34.10	26.80	46.00	11.90	PK
V	43.61	24.90	14.10	40.00	15.10	PK
V	162.18	30.10	14.70	43.50	13.40	PK
V	263.27	29.20	13.90	46.00	16.80	PK
V	426.55	29.40	18.30	46.00	16.60	PK
V	683.15	29.70	23.30	46.00	16.30	PK
V	941.68	34.60	26.70	46.00	11.40	PK

Test result above 1GHz:

The emission was conducted from 1GHz to 25GHz

CH	Antenna	Frequency (MHz)	Correct Factor (dB/m)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H/V	2390.00	31.20	54.03	74.00	19.97	PK
	H/V	2390.00	31.20	39.96	54.00	14.04	AV
	H/V	4810.00	3.00	49.40	74.00	24.60	PK
	H/V	7215.00	7.70	43.80	74.00	30.20	PK
	H/V	12025.00	14.20	50.10	74.00	23.90	PK
M	H/V	4880.00	3.10	46.50	74.00	27.50	PK
	H/V	7320.00	8.10	45.10	74.00	28.90	PK
	H/V	12200.00	13.90	48.10	74.00	25.90	PK
H	H/V	2483.50	31.19	63.43	74.00	10.57	PK
	H/V	2483.50	31.19	52.26	54.00	1.74	AV
	H/V	4960.00	3.30	46.20	74.00	27.80	PK
	H/V	7440.00	8.50	43.10	74.00	30.90	PK
	H/V	12400.00	13.70	48.20	74.00	25.80	PK

TEST REPORT

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$;
Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;
Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.

8 Power line conducted emission


Test result: NA

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

8.2 Test Configuration



8.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

8.4 Test Results of Power line conducted emission

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Delta = Level- Limit

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

9 Occupied Bandwidth

Test result: Tested

9.1 Limit


None

9.2 Measurement Procedure

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

9.3 Test Configuration



9.4 The results of Occupied Bandwidth

Please refer to Appendix A

10 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses a dedicated chip antenna to the intentional radiator, so it can comply with the provisions of this section.


TEST REPORT


Appendix A: Test results

1. RF Output Power

1.1 Test Result and Data

TestMode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
ZIGB	Ant1	2405	-0.36	≤30	1.67	≤36	PASS
ZIGB	Ant1	2440	-0.49	≤30	1.54	≤36	PASS
ZIGB	Ant1	2480	-0.74	≤30	1.29	≤36	PASS







2. Power Spectral Density

2.1 Test Result and Data

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
ZIGB	Ant1	2405	-16.09	≤8.00	PASS
ZIGB	Ant1	2440	-16.47	≤8.00	PASS
ZIGB	Ant1	2480	-16.06	≤8.00	PASS






3. 6dB BandWidth

3.1 Test Result and Data

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
ZIGB	Ant1	2405	1.510	2404.280	2405.790	0.5	PASS
ZIGB	Ant1	2440	1.420	2439.300	2440.720	0.5	PASS
ZIGB	Ant1	2480	1.360	2479.370	2480.730	0.5	PASS




TEST REPORT

4. 99% BandWidth

4.1 Test Result and Data

TestMode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
ZIGB	Ant1	2405	2.5132	2403.8132	2406.3264	---	PASS
ZIGB	Ant1	2440	2.6511	2438.7530	2441.4041	---	PASS
ZIGB	Ant1	2480	2.5016	2478.8198	2481.3214	---	PASS







5.Transmitter Spurious Emission and Band Edge

5.1 Test Result and Data


TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
ZIGB	Ant1	Low	2405	-4.06	-45.58	≤-24.06	PASS
ZIGB	Ant1	High	2480	-5.82	-41.18	≤-25.82	PASS







TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
ZIGB	Ant1	2405	0~Reference	-5.30	-5.30	---	PASS
ZIGB	Ant1	2405	30~1000	-5.30	-61.54	≤-25.3	PASS
ZIGB	Ant1	2405	1000~26500	-5.30	-46.47	≤-25.3	PASS
ZIGB	Ant1	2440	0~Reference	-5.42	-5.42	---	PASS
ZIGB	Ant1	2440	30~1000	-5.42	-58.4	≤-25.42	PASS
ZIGB	Ant1	2440	1000~26500	-5.42	-52.22	≤-25.42	PASS
ZIGB	Ant1	2480	0~Reference	-5.91	-5.91	---	PASS
ZIGB	Ant1	2480	30~1000	-5.91	-60.9	≤-25.91	PASS
ZIGB	Ant1	2480	1000~26500	-5.91	-52.44	≤-25.91	PASS









***** END *****