



FCC TEST REPORT

FCC ID: 2ATCG-BB810QI4A

On Behalf of
Shanghai Ibeelink technology Co.,LTD
2.4G Bluetooth Module
Model No.: BB810-QI4A

Prepared for : Shanghai Ibeelink technology Co.,LTD
Address : Rm 3900, Building No.2, No.1,Haikun Road, Fengxian District, Shanghai, P.R. China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen, Guangdong, China

Report Number : A1906098-C01-R02
Date of Receipt : June 19, 2019
Date of Test : June 19-July 5, 2019
Date of Report : July 5, 2019
Version Number : V0

TABLE OF CONTENTS

<u>Description</u>	<u>Page</u>
1. Summary of Standards And Results-----	6
1.1. Description of Standards and Results -----	6
2. General Information-----	7
2.1. Description of Device (EUT)-----	7
2.2. Accessories of Device (EUT) -----	8
2.3. Tested Supporting System Details -----	8
2.4. Block Diagram of connection between EUT and simulators -----	8
2.5. Test Mode Description -----	8
2.6. Test Conditions -----	8
2.7. Test Facility -----	9
2.8. Measurement Uncertainty -----	9
2.9. Test Equipment List -----	10
3. Spurious Emission-----	11
3.1. Test Limits -----	11
3.2. Test Procedure -----	11
3.3. Test Setup -----	12
3.4. Test Results -----	13
4. Power Line Conducted Emission-----	17
4.1. Test Limits -----	17
4.2. Test Procedure -----	17
4.3. Test Setup -----	17
4.4. Test Results -----	18
5. Conducted Maximum Output Power -----	20
5.1. Test limits -----	20
5.2. Test Procedure -----	20
5.3. Test Setup -----	20
5.4. Test Results -----	20
6. Peak Power Spectral Density-----	21
6.1. Test limits -----	21
6.2. Test Procedure -----	21
6.3. Test Setup -----	21
6.4. Test Results -----	21
7. Bandwidth-----	24
7.1. Test limits -----	24
7.2. Test Procedure -----	24
7.3. Test Setup -----	24
7.4. Test Results -----	24
8. Band Edge Check-----	27
8.1. Test limits -----	27
8.2. Test Procedure -----	27
8.3. Test Setup -----	27
8.4. Test Results -----	27
9. Antenna Requirement -----	32
9.1. Standard Requirement -----	32
9.2. Antenna Connected Construction-----	32

9.3. Results -----	32
10. Test setup photo-----	33
10.1. Photos of Radiated emission -----	33
10.2. Photos of Conducted Emission test-----	34
11. EUT photo-----	35

TEST REPORT DECLARATION

Applicant : Shanghai Ibeelink technology Co.,LTD
Address : Rm 3900, Building No.2, No.1,Haikun Road, Fengxian District, Shanghai, P.R. China
Manufacturer : Shanghai Ibeelink technology Co.,LTD
Address : Rm 3900, Building No.2, No.1,Haikun Road, Fengxian District, Shanghai, P.R. China
EUT Description : 2.4G Bluetooth Module
(A) Model No. : BB810-QI4A
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:

Lucas Pang
Project Engineer



Approved by (name + signature).....:

Simple Guan
Project Manager



Date of issue..... : July 5, 2019

Revision History

Revision	Issue Date	Revisions	Revised By
V0	July 5, 2019	Initial released Issue	Simple Guan

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Test Requirement	Standards Paragraph	Result
Conducted Emission	FCC PART 15	15.207	P
6dB Bandwidth	FCC PART 15	15.247 (a)(2)	P
Output Power	FCC PART 15	15.247 (b)(3)	P
Radiated Spurious Emission	FCC PART 15	15.247 (c)	P
Conducted Spurious & Band Edge Emission	FCC PART 15	15.247 (d)	P
Power Spectral Density	FCC PART 15	15.247 (e)	P
Radiated Band Edge Emission	FCC PART 15	15.205	P
Antenna Requirement	FCC PART 15	15.203	P
Note:		1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT Name : 2.4G Bluetooth Module

Trade Name : N/A

Model No. : BB810-QI4A

DIFF : N/A

Power supply : DC 3.3V

Radio Technology : Bluetooth V5.0 BLE

Operation frequency : 2402 MHz -2480 MHz

Modulation : GFSK

Modulation rate : 1Mbps, 2Mbps

Antenna Type : PCB Antenna, Maximum Gain is 2dBi

Software : BB810-QI4A v1.0

Hardware : BB810-QI4A v1.12

Intend use environment : Residential, commercial and light industrial environment


2.2. Accessories of Device (EUT)

Accessories1 : /
 Manufacturer : /
 Model : /
 Ratings : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or DOC
1	Notebook PC	ACER	ASPIRE M1830	PTSF90C00305005C AC3000	DOC

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK (1M)	Low :CH1	2402
	Middle: CH20	2440
	High: CH40	2480
GFSK (2M)	Low :CH1	2402
	Middle: CH20	2440
	High: CH40	2480

2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	24°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
 Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
 Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
 Registration Number: 293961

July 25, 2017 Certificated by IC
 Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.42dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.54dB(Polarize: V)
	4.1dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	2.08dB(Polarize: H)
	2.56dB(Polarize: V)
Uncertainty for radio frequency	1×10^{-9}
Uncertainty for conducted RF Power	0.65dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9. Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	2018.09.21	1 Year
Spectrum analyzer	Agilent	E4407B	MY46185649	2018.09.21	1 Year
Receiver	R&S	ESCI	1166.5950K03-1011	2018.09.21	1 Year
Receiver	R&S	ESCI	101202	2018.09.21	1 Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2018.04.13	2 Year
Horn Antenna	EMCO	3115	640201028-06	2018.04.13	2 Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2018.04.13	2 Year
Cable	Resenberger	N/A	No.1	2018.09.21	1 Year
Cable	SCHWARZBEC K	N/A	No.2	2018.09.21	1 Year
Cable	SCHWARZBEC K	N/A	No.3	2018.09.21	1 Year
Pre-amplifier	Schwarzbeck	BBV9743	9743-019	2018.09.21	1 Year
Pre-amplifier	R&S	AFS33-18002650- 30-8P-44	SEL0080	2018.09.21	1 Year
Temperature controller	Terchy	MHQ	120	2018.09.21	1 Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2018.09.21	1 Year
L.I.S.N.#2	ROHDE&SCHW ARZ	ENV216	101043	2018.09.21	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2018.09.21	1 Year
Horn Antenna	SCHWARZBEC K	BBHA 9170	BBHA 9170294	2018.04.13	2 Year
Power Meter	Anritsu	ML2487A	6K00001491	2018.09.21	1 Year

3. SPURIOUS EMISSION

3.1. Test Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

NOTE:

- a) The tighter limit applies at the band edges.
- b) Emission Level(dB uV/m)=20log Emission Level(uV/m)

3.2. Test Procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GH and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation



The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured


If Peak value comply with QP limit Below 1GHz.The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.

3.3. Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the 10th harmonic from 9 kHz to the EUT.


Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS


Note: 1.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2.Only show the test data of the worst Channel in this report.

H



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
			Level							Degree
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		50.7636	7.85	13.65	21.50	40.00	-18.50	peak		
2		168.4137	11.29	13.90	25.19	43.50	-18.31	peak		
3		216.0240	22.18	11.06	33.24	46.00	-12.76	peak		
4		240.8303	21.83	11.99	33.82	46.00	-12.18	peak		
5	*	293.0842	26.15	13.24	39.39	46.00	-6.61	peak		
6		731.9202	11.14	21.37	32.51	46.00	-13.49	peak		



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table		
			Level								
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		36.0007	10.30	13.50	23.80	40.00	-16.20	peak			
2		78.1389	17.76	9.84	27.60	40.00	-12.40	peak			
3		80.9275	17.14	9.49	26.63	40.00	-13.37	peak			
4		216.0240	18.09	11.06	29.15	46.00	-16.85	peak			
5		240.8304	19.36	11.99	31.35	46.00	-14.65	peak			
6	*	280.0237	21.78	12.97	34.75	46.00	-11.25	peak			

Notes: Above is below 1GHz test data. This report only shall the worst case mode for TX 2402MHz.

From 1G-25GHz

4. POWER LINE CONDUCTED EMISSION

4.1. Test Limits

Frequency	Limits dB(μ V)	
MHz	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50


Notes: 1. *Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.
 3. The limit decreases in line with the logarithm of the frequency in range of 0.15 to 0.50 MHz.

4.2. Test Procedure


The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.


4.3. Test Setup



4.4. Test Results



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV	dB	Detector	
1	*	0.1559	54.88	0.10	54.98	65.68	-10.70	peak
2		0.1859	50.65	0.10	50.75	64.22	-13.47	peak
3		0.2129	47.65	0.10	47.75	63.09	-15.34	peak
4		0.4020	37.10	0.10	37.20	57.81	-20.61	peak
5		1.7069	29.79	0.10	29.89	56.00	-26.11	peak
6		5.6878	44.16	0.14	44.30	60.00	-15.70	peak



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV	dB	Detector	
1	*	0.1500	54.60	0.10	54.70	66.00	-11.30	peak
2		0.1920	48.92	0.10	49.02	63.95	-14.93	peak
3		0.2790	38.66	0.10	38.76	60.85	-22.09	peak
4		0.4889	33.78	0.10	33.88	56.19	-22.31	peak
5		4.9408	41.94	0.13	42.07	56.00	-13.93	peak
6		23.7777	34.03	0.44	34.47	60.00	-25.53	peak

Note: All modes and channels have been tested and only the TX 2402MHz mode with the worst data is listed.

5. CONDUCTED MAXIMUM OUTPUT POWER

5.1. Test limits

Please refer section RSS-247 & 15.247.

5.2. Test Procedure


Details see the KDB 558074 D01 15.247 Meas Guidance v05r01

5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.3. Test Setup



5.4. Test Results

GFSK(1M)

Channel	Frequency (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
CH1	2402	3.200	2.089	30	Pass
CH20	2440	3.339	2.157	30	Pass
CH40	2480	3.458	2.217	30	Pass

GFSK(2M)

Channel	Frequency (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
CH1	2402	3.475	2.226	30	Pass
CH20	2440	3.357	2.166	30	Pass
CH40	2480	3.218	2.098	30	Pass

6. PEAK POWER SPECTRAL DENSITY

6.1. Test limits

6.1.1 Please refer section RSS-247 & 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

6.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r01

6.2.1 Place the EUT on the table and set it in transmitting mode.


6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as $RBW = 3\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$),
 $VBW = 10\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), span= $1.5 \times DTS$ bandwidth., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

6.3. Test Setup



6.4. Test Results

GFSK(1M)

Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE	2402	Ant 1	-15.447	8	Pass
BLE	2440	Ant 1	-16.467	8	Pass
BLE	2480	Ant 1	-15.249	8	Pass

PSD NVLT BLE 2402MHz Ant1



PSD NVLT BLE 2440MHz Ant1




PSD NVLT BLE 2480MHz Ant1




GFSK(2M)

Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
BLE	2402	Ant 1	-17.243	8	Pass
BLE	2440	Ant 1	-18.325	8	Pass
BLE	2480	Ant 1	-16.994	8	Pass

PSD NVLT BLE 2402MHz Ant1



PSD NVLT BLE 2440MHz Ant1



PSD NVLT BLE 2480MHz Ant1



7. BANDWIDTH

7.1. Test limits

Please refer section RSS-247 & 15.247


For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r01

- a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set RBW = 100kHz, VBW $\geq 3 \times \text{RBW}$ = 300kHz, Sweep time set auto, detail see the test plot.

7.3. Test Setup




7.4. Test Results


GFSK(1M)

Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE	2402	Ant 1	1.0748	0.5164	0.5	Pass
BLE	2440	Ant 1	1.0779	0.5162	0.5	Pass
BLE	2480	Ant 1	1.0774	0.5593	0.5	Pass


OBW NVLT BLE 2402MHz Ant1



OBW NVLT BLE 2440MHz Ant1




OBW NVLT BLE 2480MHz Ant1



GFSK(2M)

Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE	2402	Ant 1	2.0792	0.8313	0.5	Pass
BLE	2440	Ant 1	2.0805	0.8329	0.5	Pass
BLE	2480	Ant 1	2.0850	0.8285	0.5	Pass

OBW NVLT BLE 2402MHz Ant1



8. BAND EDGE CHECK

8.1. Test limits

Please refer section RSS-GEN&15.247.

8.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r01

8.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured
rotating the EUT to 360 degrees, Find the maximum Emission

8.2.2 Check the spurious emissions out of band.

8.2.3 RBW 1MHz ,VBW 3MHz ,peak detector for peak value , RBW 1MHz ,VBW 3MHz ,RMS
detector for AV value.


8.3. Test Setup

Same as 5.2.2.


8.4. Test Results

GFSK (1M)

Band Edge NVLT BLE 2402MHz Ant1




Band Edge NVLT BLE 2480MHz Ant1




GFSK (2M)

Band Edge NVLT BLE 2402MHz Ant1




Band Edge NVLT BLE 2480MHz Ant1




Radiated Method: GFSK(1M)

Test Mode: Low

Polarization: Vertical




Polarization: Horizontal




Test Mode: High

Polarization: Vertical




Polarization: Horizontal




Radiated Method: GFSK(2M)

Test Mode: Low

Polarization: Vertical




Polarization: Horizontal




Test Mode: High

Polarization: Vertical



Polarization: Horizontal



9. ANTENNA REQUIREMENT

9.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2. Antenna Connected Construction


The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.

9.3. Results

The EUT antenna is PCB Antenna. It complies with the standard requirement.

10. TEST SETUP PHOTO



10.1. Photos of Radiated emission





10.2.Photos of Conducted Emission test



11. EUT PHOTO





-----THE END OF REPORT-----