

Test Report

FCC ID: 2ATDP-PSW-15W-BK

Date of issue: July 25, 2019

Report Number: MTi190513E066

Sample Description: IMPEREA Wireless Charging Pad - Single Station - 15 W - Black

Model(s): PSW1-15W-BK

Applicant: Power MP Electronics Co., Ltd.

Address: Unit 04, 7/F, Bright Way Tower, No. 33 Mong KOK Road, Kowlong, HongKong

Date of Test: May 08, 2019 – July 25, 2019

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>

Table of Contents

1	GENERAL INFORMATION	4
1.1	FEATURE OF EQUIPMENT UNDER TEST (EUT).....	4
1.2	TEST MODE.....	4
1.3	EUT TEST SETUP	5
1.4	ANCILLARY EQUIPMENT	5
1.5	MEASUREMENT UNCERTAINTY	5
2	SUMMARY OF TEST RESULT	6
2.1	OPERATION CHANNEL LIST	6
2.2	TEST CHANNEL	6
3	TEST FACILITIES AND ACCREDITATIONS	7
3.1	TEST LABORATORY	7
3.2	ENVIRONMENTAL CONDITIONS	7
3.3	MEASUREMENT UNCERTAINTY	7
3.4	TEST SOFTWARE	7
4	LIST OF TEST EQUIPMENT.....	8
5	TEST RESULTS	9
5.1	ANTENNA REQUIREMENT.....	9
5.1.1	<i>Standard requirement</i>	9
5.1.2	<i>EUT Antenna</i>	9
5.2	CONDUCTED EMISSION	10
5.2.1	<i>Limits</i>	10
5.2.2	<i>Test Procedures</i>	10
5.2.3	<i>Test Setup</i>	10
5.2.4	<i>Test Result</i>	10
5.3	RADIATED EMISSION	15
5.3.1	<i>Limits</i>	15
5.3.2	<i>Test Procedures</i>	16
5.3.3	<i>Test Setup</i>	17
5.3.4	<i>Test Result</i>	17
5.4	OCCUPIED BANDWIDTH.....	21
5.4.1	<i>Test method</i>	21
5.4.2	<i>Test result</i>	21
	PHOTOGRAPHS OF THE TEST SETUP	22
	PHOTOGRAPHS OF THE EUT	24

Test Result Certification

Applicant's name: Power MP Electronics Co., Ltd.

Address: Unit 04, 7/F, Bright Way Tower, No. 33 Mong KOK Road, Kowlong, HongKong

Manufacture's name: Power MP(Changping) Electronics Co., Ltd.

Address: Second Industrial Zone, Changping Park, Eastern Industrial Park, Changping Town, Dongguan City, Guangdong Province, China

Product name: IMPEREA Wireless Charging Pad - Single Station - 15 W - Black

Trademark: Infinite Peripherals

Model name: PSW1-15W-BK

Standards: FCC Part 15C

Test Procedure: ANSI C63.10-2013

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:



Jone Lee

July 25, 2019

Reviewed by:



Blue Zheng

July 25, 2019

Approved by:



Smith Chen

July 25, 2019

1 GENERAL INFORMATION

1.1 Feature of equipment under test (EUT)

Product name:	IMPEREA Wireless Charging Pad - Single Station - 15 W - Black
Model name:	PSW1-15W-BK
Operation frequency:	115–205 kHz
Modulation type:	Load modulation
Antenna type:	Coil Antenna
Power supply:	DC 5V/9V/12V from adapter
Battery:	N/A
Adapter information:	N/A
Model difference:	N/A

1.2 Test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test mode	Description
Mode 1	Wireless charging

Note1: The test modes were carried out for all operation modes. The final test mode of the EUT was the worst test mode for EMI, and its test data was showed.

Note2: EUT is tested under full load and belongs to the worst mode.

1.3 EUT test setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary equipment

Equipment	Model	S/N	Manufacturer
Adapter	HA832	/	ZIMI
Load	/	/	/

1.5 Measurement Uncertainty

Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$

Conducted emission(150kHz~30MHz)	± 2.5 dB
Radiated emission(30MHz~1GHz)	± 4.2 dB
Radiated emission (above 1GHz)	± 4.3 dB
Temperature	± 1 degree
Humidity	± 5 %

2 SUMMARY OF TEST RESULT

Item	FCC Part No.	Description of Test	Result
1	FCC PART 15.203	Antenna requirement	Pass
2	FCC PART 15.207	Conducted emission	Pass
3	FCC PART 15.209	Radiated emission	Pass
4	FCC Part 15.215	20dB bandwidth	Pass

2.1 Operation channel list

Channel List

Channel	Frequency (kHz)
Low	115
Middle	145
High	205

2.2 Test channel

Channel	Frequency (kHz)
Middle	145

3 TEST FACILITIES AND ACCREDITATIONS

3.1 Test laboratory

Test Laboratory	Shenzhen Microtest Co., Ltd
Location	No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China
FCC Registration No.:	448573

3.2 Environmental conditions

Temperature:	15°C~35°C
Humidity	20%~75%
Atmospheric pressure	98kPa~101kPa

3.3 Measurement uncertainty

Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$

RF frequency	1×10^{-7}
RF power, conducted	± 1 dB
Conducted emission(150kHz~30MHz)	± 2.5 dB
Radiated emission(30MHz~1GHz)	± 4.2 dB
Radiated emission (above 1GHz)	± 4.3 dB
Temperature	± 1 degree
Humidity	± 5 %

3.4 Test software

Software Name	Manufacturer	Model	Version
RF Test System	Farad	LZ-RF	Lz_Rf 3A3

4 LIST OF TEST EQUIPMENT

Equipment No.	Equipment Name	Manufacturer	Model	Serial No.	Calibration date	Due date
MTI-E001	Spectrum Analyzer	Agilent	E4407B	MY41441082	2018/09/18	2019/09/17
MTI-E004	EMI Test Receiver	Rohde&schwarz	ESPI	1000314	2018/09/18	2019/09/17
MTI-E006	Broadband antenna	schwarabeck	VULB9163	872	2018/09/18	2019/09/17
MTI-E007	Horn antenna	schwarabeck	BBHA9120D	1201	2018/09/18	2019/09/17
MTI-E014	amplifier	America	8447D	3113A06150	2018/09/18	2019/09/17
MTI-E015	Conduction Immunity Signal Generator	Schloder	CDG6000	126A1343/2015	2018/09/18	2019/09/17
MTI-E016	Coupled decoupling network	Schloder	CND M2/M3	A2210332/2015	2018/09/18	2019/09/17
MTI-E034	amplifier	Agilent	8449B	3008A02400	2018/09/18	2019/09/17
MTI-E037	Artificial power network	Schwarzbeck	NSLK8127	#841	2018/09/18	2019/09/17
MTI-E040	Spectrum analyzer	Agilent	N9020A	MY49100060	2018/09/18	2019/09/17
MTI-E041	Signal generator	Agilent	N5182A	MY49060455	2018/09/18	2019/09/17
MTI-E042	Analog signal generator	Agilent	E4421B	GB40051240	2018/09/18	2019/09/17
MTI-E043	Power probe	Dare Instruments	RPR3006W	16I00054SN016	2018/09/18	2019/09/17
MTI-E047	10dB attenuator	Mini-Circuits	UNAT-10+	15542	2018/09/18	2019/09/17
MTI-E049	spectrum analyzer	Rohde&schwarz	FSP-38	100019	2018/09/18	2019/09/17
MTI-E050	PSG Signal generator	Agilent	E8257D	MY46520873	2018/09/18	2019/09/17
MTI-E061	Active Loop Antenna 9kHz - 30MHz	Schwarzbeek	FMZB 1519 B	00044	2018/09/18	2019/09/17
MTI-E052	18-40GHz amplifier	Chengdu step Micro Technology	ZLNA-18-40G-21	1608001	2018/09/18	2019/09/17
MTI-E053	15-40G Antenna	Schwarzbeek	BBHA9170	BBHA9170582	2018/09/18	2019/09/17
MTI-E058	Artificial power network	Schwarzbeck	NSLK8127	#841	2018/09/18	2019/09/17
Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).						

5 TEST RESULTS

5.1 Antenna requirement

5.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 EUT Antenna

The EUT antenna is Coil Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted emission

5.2.1 Limits

For the following equipment, when designed to be connected to the public utility (AC) power line the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.5 -5	56	46
5 -30	60	50

Note : the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.2.2 Test Procedures

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.


Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN is at least 80 cm from nearest part of EUT chassis.


For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test Setup




5.2.4 Test Result

Temperature:	25.1℃	Relative Humidity:	68%
Pressure:	101kPa	Phase:	L
Test voltage:	DC 12V from adapter AC 120V/60Hz	Test mode:	Mode 1




No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1		0.1695	46.05	9.73	55.78	64.98	-9.20	QP	
2		0.1695	35.83	9.73	45.56	54.98	-9.42	AVG	
3	*	0.1891	47.69	9.73	57.42	64.08	-6.66	QP	
4		0.1891	32.58	9.73	42.31	54.08	-11.77	AVG	
5		0.2398	38.27	9.73	48.00	62.10	-14.10	QP	
6		0.2398	23.73	9.73	33.46	52.10	-18.64	AVG	
7		0.6031	19.71	9.89	29.60	56.00	-26.40	QP	
8		0.6031	17.57	9.89	27.46	46.00	-18.54	AVG	
9		1.0875	19.30	9.95	29.25	56.00	-26.75	QP	
10		1.0875	16.01	9.95	25.96	46.00	-20.04	AVG	
11		4.3922	24.12	10.04	34.16	56.00	-21.84	QP	
12		4.3922	17.52	10.04	27.56	46.00	-18.44	AVG	

Temperature:	25.1℃	Relative Humidity:	68%
Pressure:	101kPa	Phase:	N
Test voltage:	DC 12V from adapter AC 120V/60Hz	Test mode:	Mode 1




No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1	*	0.1539	49.37	9.73	59.10	65.79	-6.69	QP	
2		0.1539	35.09	9.73	44.82	55.79	-10.97	AVG	
3		0.1734	46.41	9.73	56.14	64.80	-8.66	QP	
4		0.1734	36.42	9.73	46.15	54.80	-8.65	AVG	
5		0.2047	44.73	9.73	54.46	63.42	-8.96	QP	
6		0.2047	31.08	9.73	40.81	53.42	-12.61	AVG	
7		0.6031	20.81	9.89	30.70	56.00	-25.30	QP	
8		0.6031	17.76	9.89	27.65	46.00	-18.35	AVG	
9		1.0836	21.66	9.95	31.61	56.00	-24.39	QP	
10		1.0836	16.40	9.95	26.35	46.00	-19.65	AVG	
11		4.4078	26.40	10.04	36.44	56.00	-19.56	QP	
12		4.4078	15.57	10.04	25.61	46.00	-20.39	AVG	

Temperature:	25.1℃	Relative Humidity:	68%
Pressure:	101kPa	Phase:	L
Test voltage:	DC 12V from adapter AC 240V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1	*	0.1578	42.30	9.73	52.03	65.58	-13.55	QP	
2		0.1578	17.41	9.73	27.14	55.58	-28.44	AVG	
3		0.1773	38.94	9.73	48.67	64.61	-15.94	QP	
4		0.1773	25.56	9.73	35.29	54.61	-19.32	AVG	
5		0.2359	33.17	9.73	42.90	62.24	-19.34	QP	
6		0.2359	23.04	9.73	32.77	52.24	-19.47	AVG	
7		0.3608	27.78	9.79	37.57	58.71	-21.14	QP	
8		0.3608	21.28	9.79	31.07	48.71	-17.64	AVG	
9		0.5992	20.05	9.89	29.94	56.00	-26.06	QP	
10		0.5992	15.19	9.89	25.08	46.00	-20.92	AVG	
11		4.4508	24.72	10.04	34.76	56.00	-21.24	QP	
12		4.4508	19.49	10.04	29.53	46.00	-16.47	AVG	

Temperature:	25.1℃	Relative Humidity:	68%
Pressure:	101kPa	Phase:	N
Test voltage:	DC 12V from adapter AC 240V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBpW	Correct Factor dB	Measure- ment dBpW	Limit dBpW	Over dB	Detector	Comment
1		0.1655	41.02	9.73	50.75	65.18	-14.43	QP	
2		0.1655	27.64	9.73	37.37	55.18	-17.81	AVG	
3		0.2281	34.41	9.73	44.14	62.52	-18.38	QP	
4		0.2281	23.96	9.73	33.69	52.52	-18.83	AVG	
5		0.2906	33.14	9.75	42.89	60.51	-17.62	QP	
6		0.2906	27.15	9.75	36.90	50.51	-13.61	AVG	
7		0.4352	28.40	9.84	38.24	57.15	-18.91	QP	
8	*	0.4352	25.68	9.84	35.52	47.15	-11.63	AVG	
9		1.0172	24.06	9.95	34.01	56.00	-21.99	QP	
10		1.0172	20.22	9.95	30.17	46.00	-15.83	AVG	
11		3.9195	25.17	10.03	35.20	56.00	-20.80	QP	
12		3.9195	23.94	10.03	33.97	46.00	-12.03	AVG	

Note: The 5V, 9V and 12V operating voltages have been tested and the results show that the 12V operating voltage data is the worst, and the report only shows the worst mode.

5.3 Radiated emission

5.3.1 Limits

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)*	Measurement distance (m)**	Field strength (dBμV/m) @3m**	Detector
0.009-0.49	2400/F(kHz)	48.5-13.8	300	128.5-93.8	QP***
0.49-1.705	24000/F(kHz)	33.8-23	30	73.8-63	QP
1.705-30	30	29.5	30	69.5	QP
30-88	100	40	3	40	QP
88-216	150	43.5	3	43.5	QP
216-960	200	46	3	46	QP
960-1000	500	54	3	54	QP
above 1000	500	54	3	54	AV
above 1000	5000	74	3	74	PK

*: $\text{dB}\mu\text{V/m} = 20 \cdot \log(\mu\text{V/m})$
 **: Limit 3m ($\text{dB}\mu\text{V/m}$) = limit(distance) + $40 \cdot \log(\text{distance}/3\text{m})$ (blew 30MHz)
 ***: in 9-90kHz, 110-490KHz bands employing an AV detector

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP


5.3.2 Test Procedures

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
- h. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.


Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

5.3.3 Test Setup

Radiated Emission Test-Up Frequency Below 30MHz



Radiated Emission Test-Up Frequency 30MHz~1GHz



5.3.4 Test Result


Frequency range (9kHz – 30MHz)

Temperature:	23.5℃	Relative Humidity:	66%
Pressure:	101kPa	Test mode:	Mode 1
Test voltage:	DC 12V from adapter AC 120V/60Hz		

Frequency	Read Level	Correct Factor	Measurement	Limits	Over	Detector
(MHz)	(dBμV)	(dBuV/m)	(dBμV/m)	(dBμV/m)	(dB)	
0.0281	62.33	20.34	82.67	118.56	-35.89	QP
0.1454	77.43	19.85	97.28	104.32	-7.04	QP
0.2902	59.23	19.75	78.98	98.34	-19.36	QP
0.4361	58.43	20.04	78.47	94.81	-16.34	QP


Frequency range (30MHz – 1GHz)

Temperature:	25.2°C	Relative Humidity:	69%
Pressure:	101kPa	Polarization:	Vertical
Test voltage:	DC 12V from adapter AC 120V/60Hz	Test mode:	Mode 1



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dBuV/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		45.2165	38.41	-12.58	25.83	40.00	-14.17	QP
2	*	82.6482	52.60	-17.30	35.30	40.00	-4.70	QP
3		166.6512	44.40	-15.74	28.66	43.50	-14.84	QP
4		203.5228	41.84	-13.03	28.81	43.50	-14.69	QP
5		302.4812	39.94	-10.81	29.13	46.00	-16.87	QP
6		338.4001	39.49	-10.22	29.27	46.00	-16.73	QP

Temperature:	25.2°C	Relative Humidity:	69%
Pressure:	101kPa	Polarization:	Horizontal
Test voltage:	DC 12V from adapter AC 120V/60Hz	Test mode:	Mode 1



Note: The 5V, 9V and 12V operating voltages have been tested and the results show that the 12V operating voltage data is the worst, and the report only shows the worst mode.

5.4 Occupied bandwidth

5.4.1 Test method

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq 1\%$ of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak


Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth and 99% occupied bandwidth of the emission.

5.4.2 Test result



Frequency (kHz)	20dB emission bandwidth (kHz)	99% occupied bandwidth (kHz)
145	8.147	6.977

Test plots as below



Photographs of the Test Setup

Radiated emission



Conducted emission



Photographs of the EUT

See the APPENDIX 1: EUT PHOTO in the report No.: MTi190513E066-1.

----END OF REPORT----