



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190500379E-02

Applicant: Open Appliances Pvt Ltd.

Address of Applicant: No. 1, Srichakra, 18th Main Road, Sector 3, HSR Layout, Bangalore - Karnataka, India-560102

Manufacturer: Open Appliances Pvt Ltd.

Address of Manufacturer: No. 1, Srichakra, 18th Main Road, Sector 3, HSR Layout, Bangalore - Karnataka, India-560102

Equipment Under Test (EUT):

Product: Bluetooth Padlock

All Model No.: SPLAL197, LT01B, UL01B, CL01B, LK01B

Test Model No.: SPLAL197

Brand Name: OPEN

FCC ID: 2ATE2OPEN

Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2019-05-28 to 2019-06-11

Date of Issue: 2019-06-11

Test Result : PASS*

Tested By:

Daisy Qin

(Daisy Qin)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190500379E-02	Rev.01	Initial report	2019-06-11

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 RF EXPOSURE EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Limits.....	5
4.1.2 Test Procedure	5
4.2 1.1.3 EUT RF EXPOSURE EVALUATION	6

3 General Information

3.1 Client Information

Applicant:	Open Appliances Pvt Ltd.
Address of Applicant:	No. 1, Srichakra, 18th Main Road, Sector 3, HSR Layout, Bangalore - Karnataka, India-560102
Manufacturer:	Open Appliances Pvt Ltd.
Address of Manufacturer:	No. 1, Srichakra, 18th Main Road, Sector 3, HSR Layout, Bangalore - Karnataka, India-560102

3.2 General Description of EUT

Product Name:	Bluetooth Padlock
All Model No.:	SPLAL197, LT01B, UL01B, CL01B, LK01B
Test Model No.:	SPLAL197
Trade Mark:	OPEN
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	☒ Mobile ☐ Portable ☐ Fix Location
Test Software of EUT:	nRFgo Studio (manufacturer declare)
Antenna Type:	Ceramic antenna
Antenna Gain:	0dBi
EUT Power Supply:	lithium battery:DC3V

Note:

All model: SPLAL197, LT01B, UL01B, CL01B, LK01B

Only the model SPLAL197 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For BLE

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-9.79	-9±1	-8	0.158
Middle(2440MHz)	-9.85	-9±1	-8	0.158
Highest(2480MHz)	-9.55	-9±1	-8	0.158

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
0.158	0	0.000032	1.0	PASS

Note: 1) Refer to report No. CQASZ20190500379E-01 for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (0.158 \cdot 1) / (4 \cdot 3.1416 \cdot 20^2) = 0.000032$