



MPE ESTIMATION

**Test report
On Behalf of
Linsun Smart Technology Co.,LTD
For
Smart pet dispenser
Model No.: D01, T980, V36, V3309, V86, W86, V96, W96, W66,
V66, W3309**

FCC ID: 2ATE8D01

Prepared for : Linsun Smart Technology Co.,LTD
3/F,Block A, No.48, First Ring Rd,Guangming community,Dongcheng District, Dongguan city, Guangdong, China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

Date of Test: April 26, 2019 ~ May 15, 2019
Date of Report: May 16, 2019
Report Number: HK1904230907-2E

**1, Limit for General Population/ Uncontrolled Exposures**

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result**2.4G WIFI**

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	13.06	12.5±1(13.5)	22.39	1	1.2589	0.00561
11g	11.14	11±1(12)	15.85	1	1.2589	0.00397
11n/HT20	10.86	10±1(11)	12.59	1	1.2589	0.00315
11n/HT40	9.67	9±1(10)	10.00	1	1.2589	0.00251

$$Pd = \frac{P_{out} * G}{4\pi r^2}$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1904230907-1E, antenna gain=1dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine SAR test exclusion. The test exclusion threshold is 0.00561mW/cm² which is< 1.0mW/cm², SAR testing is not required.

-----The End-----