



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No......: **GTS20200109007-1-11-2**

FCC ID.....: **2ATEXBIRDYSL2**

Compiled by
(position+printed name+signature)...: File administrators Jimmy Wang

Supervised by
(position+printed name+signature)...: Test Engineer Aaron Tan

Approved by
(position+printed name+signature)...: Manager Jason Hu

Date of issue.....: Jan. 04, 2020

Representative Laboratory Name .: **Shenzhen Global Test Service Co., Ltd.**

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name.....: **TPL SYSTEMES**

Address: ZAE du Perigord Noir SARLAT 24200 FRANCE

Test specification

Standard: **FCC Part 15.247**

TRF Originator: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Pager

Trade Mark: TPL

Manufacturer: **TPL SYSTEMES**

Model/Type reference.....: Birdy Slim IoT

Listed Models: Birdy Slim IoT Pager, Safety IoT Pager, CR68 IoT Pager, Epoc-S IoT Pager

Modulation Type: Lora

Operation Frequency.....: From 903MHz~914.2MHz

Hardware version: BIRDY_SLIM_IOT_V6

Software version.....: BirdyIOT-1.00.1-03

Rating: DC 3.7V from battery charged by AC/DC adapter

Result.....: **PASS**

Jimmy Wang



Jason Hu

TEST REPORT

Test Report No. : GTS20200109007-1-11-2	Jan. 04, 2020 Date of issue
--	--------------------------------

Equipment under Test : Pager

Model /Type : Birdy Slim IoT

Listed Models : Birdy Slim IoT Pager, Safety IoT Pager, CR68 IoT Pager, Epoc-S IoT Pager

Applicant : **TPL SYSTEMES**

Address : ZAE du Perigord Noir SARLAT 24200 FRANCE

Manufacturer : **TPL SYSTEMES**

Address : ZAE du Perigord Noir SARLAT 24200 FRANCE

Factory : **Shenzhen Wex Technology Co. Ltd.**

Address : 5th Floor, 501, Makin FuyongInteligent Manufacturing Port, Huai De Yin Shan Building, Fuyong Town, Baoan District, Shenzhen, China, 518103

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2</u>	<u>SUMMARY</u>	<u>5</u>
2.1	General Remarks	5
2.2	Product Description	5
2.3	Equipment Under Test	5
2.4	Short description of the Equipment under Test (EUT)	5
2.5	EUT operation mode	6
2.6	Related Submittal(s) / Grant (s)	6
2.7	Modifications	6
<u>3</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Environmental conditions	7
3.4	Summary of measurement results	8
3.5	Statement of the measurement uncertainty	9
3.6	Equipments Used during the Test	9
<u>4</u>	<u>TEST CONDITIONS AND RESULTS.....</u>	<u>11</u>
4.1	AC Power Conducted Emission	11
4.2	Radiated Emissions and Band Edge	14
4.3	Maximum Conducted Output Power	20
4.4	Power Spectral Density	21
4.5	6dB Bandwidth	23
4.6	Out-of-band Emissions	25
4.7	Antenna Requirement	28
<u>5</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>29</u>
<u>6</u>	<u>PHOTOS OF THE EUT</u>	<u>29</u>

1 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 v05r02](#): Guidance for Compliance Measurements on Digital Transmission Systems (DTS) ,Frequency Hopping Spread Spectrum System(HFSS), and Hybrid System Devices Operating Under §15.247 of The FCC rules.

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Dec. 21, 2019
Testing commenced on	:	Dec. 22, 2019
Testing concluded on	:	Jan. 03, 2019

2.2 Product Description

Product Name:	Pager
Model/Type reference:	Birdy Slim IoT
Power supply:	DC 3.7V from battery
Adapter information :	Model: K06S050100U Input: 100-240V~, 50/60Hz, 0.3A Output: 5.0V---1.0A
Lora 500KHz(DTS):	
Operation frequency:	903MHz~914.2MHz
Modulation:	LoRa
Channel number:	8
Channel separation:	1.6MHz
Antenna type:	PIFA antenna
Antenna gain:	2.0 dBi

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC3.70V from battery

2.4 Short description of the Equipment under Test (EUT)

This is a Pager.

For more details, refer to the user's manual of the EUT.

2.5 EUT operation mode

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 8 channels provided to the EUT and Channel 64/68/71 were selected to test.

Operation Frequency:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
64	903.00	68	909.40
65	904.60	69	911.00
66	906.20	70	912.60
67	907.80	71	914.20

2.6 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.7 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Test result
§15.247(b)(4)	Antenna gain	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Pass
§15.247(e)	Power spectral density	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Pass
§15.247(a)(2)	Spectrum bandwidth – 6 dB bandwidth	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Pass
§15.247(b)(1)	Maximum output power	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Pass
§15.247(d)	Band edge compliance conducted	Lora DR4	☒ Lowest ☒ Highest	Lora DR4	☒ Lowest ☒ Highest	Pass
§15.205	Band edge compliance radiated	Lora DR4	☒ Lowest ☒ Highest	Lora DR4	☒ Lowest ☒ Highest	Pass
§15.247(d)	TX spurious emissions conducted	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Pass
§15.247(d)	TX spurious emissions Radiated Above 1GHz	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Pass
§15.209(a)	TX spurious Emissions radiated Below 1GHz	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Middle	Pass
§15.107(a) §15.207	Conducted Emissions 9KHz-30 MHz	Lora DR4	☒ Lowest ☒ Middle ☒ Highest	Lora DR4	☒ Middle	Pass

Note: DR means DataRate refer to LoRaWAN Specification as below:

DataRate	Configuration	Indicative physical bit rate [bit/sec]
0	LoRa: SF10 / 125 kHz	980
1	LoRa: SF9 / 125 kHz	1760
2	LoRa: SF8 / 125 kHz	3125
3	LoRa: SF7 / 125 kHz	5470
4	LoRa: SF8 / 500 kHz	12500

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2019/09/20	2020/09/19
LISN	R&S	ESH2-Z5	893606/008	2019/09/20	2020/09/19
EMI Test Receiver	R&S	ESPI 3	101841-cd	2019/09/20	2020/09/19
EMI Test Receiver	R&S	ESCI7	101102	2019/09/20	2020/09/19
Spectrum Analyzer	Agilent	N9020A	MY48010425	2019/09/20	2020/09/19
Spectrum Analyzer	R&S	FSV40	100019	2019/09/20	2020/09/19
Controller	EM Electronics	Controller EM 1000	N/A	2019/09/21	2020/09/20
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	15006	2019/10/12	2020/10/11
By-log Antenna	SCHWARZBECK	VULB9163	000976	2019/05/26	2020/05/25
Double Ridged Horn Antenna (1~18GHz)	SCHWARZBECK	BBHA 9120D	01622	2019/09/23	2020/09/22
Horn Antenna (18GHz~40GHz)	Schwarzbeck	BBHA9170	791	2019/09/20	2020/09/19
Amplifier (30MHz~1GHz)	Schwarzbeck	BBV 9743	#202	2019/09/20	2020/09/19
Amplifier (1GHz~18GHz)	Taiwan Chengyi	EMC051845B	980355	2019/09/20	2020/09/19
Amplifier (26.5GHz~40GHz)	Schwarzbeck	BBV9179	9719-025	2019/09/20	2020/09/19
Temperature/Humidity Meter	Gangxing	CTH-608	02	2019/09/20	2020/09/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2019/09/20	2020/09/19


High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2019/09/20	2020/09/19
Data acquisition card	Agilent	U2531A	TW53323507	2019/09/20	2020/09/19
Power Sensor	Agilent	U2021XA	MY5365004	2019/09/20	2020/09/19
RF Cable	HUBER+SUHNER	RG214	N/A	2019/09/20	2020/09/19
Conducted Emission	JS32-CE	V2.5	N/A	N/A	N/A
Radiated Emission	JS32-RE	Ver 2.5.1.8	N/A	N/A	N/A

Note: The Cal.Interval was one year.

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

Remark:

1. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply(charge from adapter)have been tested, only the worst result of 120 VAC, 60 Hz with middle channel was reported as below:


Power supply:

DC 5V from Adapter
AC 120V/60Hz

Polarization

L

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	Result [dBμV]	Limit [dBμV]	Margin [dB]	Detector	Line	Remark
1	0.2130	41.03	10.14	51.17	63.09	11.92	PK	L1	PASS
2	0.2130	28.25	10.14	38.39	53.09	14.70	AV	L1	PASS
3	0.3570	35.07	10.14	45.21	58.80	13.59	PK	L1	PASS
4	0.3570	26.53	10.14	36.67	48.80	12.13	AV	L1	PASS
5	0.4965	31.37	10.25	41.62	46.06	4.44	AV	L1	PASS
6	0.4965	38.60	10.25	48.85	56.06	7.21	PK	L1	PASS
7	1.0680	35.62	10.20	45.82	56.00	10.18	PK	L1	PASS
8	1.0680	26.55	10.20	36.75	46.00	9.25	AV	L1	PASS
9	2.1975	25.05	10.28	35.33	46.00	10.67	AV	L1	PASS
10	2.2695	34.03	10.29	44.32	56.00	11.68	PK	L1	PASS
11	3.6195	34.80	10.36	45.16	56.00	10.84	PK	L1	PASS
12	3.6195	22.65	10.36	33.01	46.00	12.99	AV	L1	PASS

Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


Power supply:

DC 5V from Adapter
AC 120V/60Hz

Polarization

N

Test Graph



Suspected List

NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	Result [dBμV]	Limit [dBμV]	Margin [dB]	Detector	Line	Remark
1	0.2220	35.65	10.14	45.79	62.74	16.95	PK	N	PASS
2	0.2220	22.77	10.14	32.91	52.74	19.83	AV	N	PASS
3	0.5055	26.76	10.25	37.01	46.00	8.99	AV	N	PASS
4	0.5055	34.39	10.25	44.64	56.00	11.36	PK	N	PASS
5	1.3740	26.21	10.23	36.44	46.00	9.56	AV	N	PASS
6	1.3965	42.74	10.23	52.97	56.00	3.03	PK	N	PASS
7	3.4440	31.14	10.35	41.49	56.00	14.51	PK	N	PASS
8	3.4485	18.36	10.35	28.71	46.00	17.29	AV	N	PASS
9	4.5375	15.56	10.36	25.92	46.00	20.08	AV	N	PASS
10	4.5420	30.78	10.36	41.14	56.00	14.86	PK	N	PASS
11	7.2330	28.14	10.52	38.66	60.00	21.34	PK	N	PASS
12	7.3860	14.34	10.53	24.87	50.00	25.13	AV	N	PASS


Note:1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


4.2 Radiated Emissions and Band Edge

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.


The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+ 40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+ 40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. For below 1GHz testing recorded worst mode at middle channel.
2. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz



For 1GHz to 25GHz

Frequency(MHz):			903.00		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1806.00	58.59	PK	74.00	15.41	62.85	27.17	4.02	35.45	-4.26
1806.00	49.02	AV	54.00	4.98	53.28	27.17	4.02	35.45	-4.26
2709.50	54.56	PK	74.00	19.44	55.70	29.34	4.94	35.43	-1.14
2709.50	46.32	AV	54.00	7.68	47.46	29.34	4.94	35.43	-1.14
3612.00	43.05	PK	74.00	30.95	40.63	32.09	5.95	35.62	2.42
3612.00	--	AV	54.00	--	--	--	--	--	--

Frequency(MHz):			903.00		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1806.00	59.11	PK	74.00	14.89	63.37	27.17	4.02	35.45	-4.26
1806.00	50.24	AV	54.00	3.76	54.50	27.17	4.02	35.45	-4.26
2709.50	55.69	PK	74.00	18.31	56.83	29.34	4.94	35.43	-1.14
2709.50	47.58	AV	54.00	6.42	48.72	29.34	4.94	35.43	-1.14
3612.00	45.11	PK	74.00	28.89	42.69	32.09	5.95	35.62	2.42
3612.00	--	AV	54.00	--	--	--	--	--	--

Frequency(MHz):			909.40		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1818.50	57.59	PK	74.00	16.41	61.76	27.24	4.03	35.44	-4.17
1818.50	48.26	AV	54.00	5.74	52.43	27.24	4.03	35.44	-4.17
2728.00	54.05	PK	74.00	19.95	55.11	29.41	4.96	35.43	-1.06
2728.00	45.26	AV	54.00	8.74	46.32	29.41	4.96	35.43	-1.06
3637.50	44.79	PK	74.00	29.21	42.18	32.25	5.99	35.63	2.61
3637.50	--	AV	54.00	--	--	--	--	--	--

Frequency(MHz):			909.40		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1818.50	58.97	PK	74.00	15.03	63.14	27.24	4.03	35.44	-4.17
1818.50	49.12	AV	54.00	4.88	53.29	27.24	4.03	35.44	-4.17
2728.00	55.75	PK	74.00	18.25	56.81	29.41	4.96	35.43	-1.06
2728.00	46.25	AV	54.00	7.75	47.31	29.41	4.96	35.43	-1.06
3637.50	45.17	PK	74.00	28.83	42.56	32.25	5.99	35.63	2.61
3637.50	--	AV	54.00	--	--	--	--	--	--

Frequency(MHz):			914.20		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1828.00	59.25	PK	74.00	14.75	63.35	27.29	4.04	35.43	-4.10
1828.00	50.24	AV	54.00	3.76	54.34	27.29	4.04	35.43	-4.10
2742.50	55.12	PK	74.00	18.88	56.11	29.46	4.98	35.43	-0.99
2742.50	47.41	AV	54.00	6.59	48.40	29.46	4.98	35.43	-0.99
3655.50	45.02	PK	74.00	28.98	42.28	32.36	6.01	35.63	2.74
3655.50	--	AV	54.00	--	--	--	--	--	--

Frequency(MHz):			914.20		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1828.00	60.22	PK	74.00	13.78	64.32	27.29	4.04	35.43	-4.10
1828.00	51.25	AV	54.00	2.75	55.35	27.29	4.04	35.43	-4.10
2742.50	56.28	PK	74.00	17.72	57.27	29.46	4.98	35.43	-0.99
2742.50	47.89	AV	54.00	6.11	48.88	29.46	4.98	35.43	-0.99
3655.50	46.28	PK	74.00	27.72	43.54	32.36	6.01	35.63	2.74
3655.50	--	AV	54.00	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

4.3 Maximum Conducted Output Power


Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

Type	Channel	Output power (dBm)	Limit (dBm)	Result
Lora	64	18.879	30.00	Pass
	68	18.925		
	71	19.024		

4.4 Power Spectral Density


Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration




Test Results


Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
Lora	64	4.684	8.00	Pass
	68	4.806		
	71	4.825		

Test plot as follows:

CH64



CH68



CH71

4.5 6dB Bandwidth


Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.


Test Configuration




Test Results

Type	Channel	6dB Bandwidth (MHz)	99% OBW (MHz)	Limit (KHz)	Result
Lora	64	0.7739	0.8093	≥500	Pass
	68	0.7800	0.8030		
	71	0.7676	0.7989		


Test plot as follows:



CH64



CH68



CH71

4.6 Out-of-band Emissions


Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

Test Configuration




Test Results


Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test plot as follows:


Lora



CH64




CH68



CH71

Band-edge Measurements for RF Conducted Emissions:



4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Antenna Connected Construction

The maximum gain of antenna was 2.0dBi.

5 Test Setup Photos of the EUT

Please refer to separated files for Test Setup Photos of the EUT.

6 Photos of the EUT

External Photos of EUT

Please refer to separated files for External Photos of the EUT.

Internal Photos of EUT

Please refer to separated files for Internal Photos of the EUT.

***** End of Report *****