



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190400299E-02

Applicant: SHENZHEN YIJIELIAN TECHNOLOGY CO.,LTD.

Address of Applicant: 513, Building 49, No. 3, Queshan Yunfeng Road, Dalang Street, Longhua District, Shenzhen, China

Manufacturer: SHENZHEN YIJIELIAN TECHNOLOGY CO.,LTD.

Address of Manufacturer: 513, Building 49, No. 3, Queshan Yunfeng Road, Dalang Street, Longhua District, Shenzhen, China

Equipment Under Test (EUT):

Product: Wireless WIFI SMART SWITCHES

Model No.: X801S, X801T, X801K, X802K, X803K, X805S, X806, TS01, TS01Q, TS02, TS03, TC01, TD01, WS2, WS3, ED, EL, EW, WM1, WM2

Test Model No.: X801S

Brand Name: EJLINK

FCC ID: 2ATGX-X801S

Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2019-04-30 to 2019-05-08

Date of Issue: 2019-05-08

Test Result : PASS*

Tested By:

Daisy Qin

(Daisy Qin)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190400299E-02	Rev.01	Initial report	2019-05-08

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF WIFI.....	4
4 RF EXPOSURE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure.....	6
4.2 1.1.3 EUT RF EXPOSURE EVALUATION	7

3 General Information

3.1 Client Information

Applicant:	SHENZHEN YIJIELIAN TECHNOLOGY CO.,LTD.
Address of Applicant:	513, Building 49, No. 3, Queshan Yunfeng Road, Dalang Street, Longhua District, Shenzhen, China
Manufacturer:	SHENZHEN YIJIELIAN TECHNOLOGY CO.,LTD.
Address of Manufacturer:	513, Building 49, No. 3, Queshan Yunfeng Road, Dalang Street, Longhua District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Wireless WIFI SMART SWITCHES
All Model No.:	X801S, X801T, X801K, X802K, X803K, X805S, X806, TS01, TS01Q, TS02, TS03, TC01, TD01, WS2, WS3, ED, EL, EW, WM1, WM2
Test Model No.:	X801S
Trade Mark:	EJLINK
Hardware Version:	V1.0
Software Version:	V1.0
Sample Type:	☐ Mobile ☐ Portable ☒ Fix Location
Power Supply:	AC120V 60Hz

3.3 General Description of WIFI

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20/40): OFDM (64QAM, 16QAM,QPSK,BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Test Software of EUT:	SecureCRT(manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi

Note:

1. All model: X801S, X801T, X801K, X802K, X803K, X805S, X806, TS01, TS01Q, TS02, TS03, TC01, TD01, WS2, WS3, ED, EL, EW, WM1, WM2

2. Only the model X801S, was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For BT

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

802.11b mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	7.6	7.5±1	8.5	7.079
Middle(2437MHz)	7.83	7.5±1	8.5	7.079
Highest(2462MHz)	8.02	7.5±1	8.5	7.079
802.11g mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	6.22	6.5±1	7.5	5.623
Middle(2437MHz)	6.8	6.5±1	7.5	5.623
Highest(2462MHz)	6.93	6.5±1	7.5	5.623
802.11n(HT20)mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	6.04	6.5±1	7.5	5.623
Middle(2437MHz)	6.77	6.5±1	7.5	5.623
Highest(2462MHz)	7.03	6.5±1	7.5	5.623
802.11n(HT40)mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2422MHz)	6.07	6.5±1	7.5	5.623
Middle(2437MHz)	6.49	6.5±1	7.5	5.623
Highest(2452MHz)	6	6.5±1	7.5	5.623

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
7.079	0	0.0014	1.0	PASS

Note: 1) The Max Conducted Average Output Power data refer to report Report No.: CQASZ20190400299E-01

2) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (7.079 * 1.0) / (4 * 3.1416 * 20^2) = 0.0014$