



FCC RF EXPOSURE REPORT

For

Wireless Charging Pad

MODEL NUMBER: AWC1043, AWC1043AW, AWC1043SG, AWC1043XX
(X would be any Arabian number or English letter or blank)

FCC ID: 2ATGY-AWC1043

REPORT NUMBER: 4789000048.4-4

ISSUE DATE: June 14, 2019

Prepared for

**Ubio Labs, Inc.
2821 Northup Way, Suite 250, Bellevue, WA 98004, USA**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	06/14/2019	Initial Issue	

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. REQUIREMENT	6

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Ubio Labs, Inc.
Address: 2821 Northup Way, Suite 250, Bellevue, WA 98004, USA

Manufacturer Information


Company Name: Shenzhen PYS Industrial Co., LTD
Address: Floor 3,8,12 , Bldg 9#, Lianhua Industrial Zone, Loangyuan Road, Longhua Street, Longhua District, Shenzhen

EUT Description

EUT Name: Wireless Charging Pad
Model: AWC1043, AWC1043AW, AWC1043SG, AWC1043XX
(X would be any Arabian number or English letter or blank)
Model Difference: All the same except for the model number and color.
Brand Name: /
Sample Status: Normal
Sample ID: 2289514
Sample Received Date: May 15, 2019
Date of Tested: June 3, 2019 ~ June 14, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§1.1307	PASS
FCC 47CFR§1.1310	PASS
FCC 47CFR§2.1093	PASS
FCC 47CFR§2.1091	PASS

Tested By:



Denny Huang
Project Engineer
Approved By:



Stephen Guo
Laboratory Manager

Checked By:



Shawn Wen
Laboratory Leader

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC 47CFR§1.1307(b)(1), FCC 47CFR§1.1310, FCC 47CFR§2.1093, 680106 D01 RF Exposure wireless charging apps v03.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>IC (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.</p> <p>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</p> <p>Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p>
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

4. REQUIREMENT


RF EXPOSURE LIMIT

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (Minutes)
0.3 -- 1.34	614	1.63	(100)*	30
1.34 -- 30	824/f	2.19/f	(180/f ²)*	30
30 -- 300	27.5	0.073	0.2	30
300 -- 1500	--	--	f/1500	30
1500 -- 100,000	--	--	1.0	30

METHOD OF MEASUREMENT

- The RF exposure test was performed in shielded chamber.
- The measurement probe was placed at test distance (15cm) which is between the edge of the charger and the geometric centre of probe.
- The measurement probe used to search of highest strength.
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- The EUT were measured according to the dictates of KDB 680106D01v03.

BLOCK DIAGRAM OF TEST SETUP



Note: As bottom point is not required to test for desktop devices, so we scanning all the surfaces and recorded the worst level in F.

EQUIPMENT APPROVAL CONSIDERATIONS

The EUT does comply with KDB 680106D01v03.

- 1) Power transfer frequency is less than 1 MHz.
Yes; the device operate in the frequency range from 127.5kHz.
- 2) Output power from each primary coil is less than or equal to 15 watts.
Yes; the maximum output power of the each primary coil is 10 watts.
- 3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
Yes; the transfer system includes only single primary and secondary coils.
- 4) Client device is placed directly in contact with the transmitter.
Yes; Client device is placed directly in contact with the transmitter.
- e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
Yes; The EUT is a mobile devices.
- f) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
Yes; The EUT field strength levels are less than 50% of the MPE limit.

MEASURING INSTRUMENT USED

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Electric and Magnetic Field Analyzer	Narda	EHP-200A	170WX90204	April 21, 2019	April 21, 2020

H FIELD STRENGTH

Test mode for wireless charger:

Config	Test Mode	Description
Mode 1	Standby	EUT alone powered by AC/DC adapter
Mode 2	Operating	EUT and iPhone powered by AC/DC adapter
Mode 3	Operating	EUT and 10W load powered by AC/DC adapter
Mode 4	Operating	EUT and 5W load powered by AC/DC adapter

H-Filed Strength at 15 cm from the edges surrounding the EUT and 20cm above the top surface of the EUT (A/m)

Test Position	H-Filed Strength Measure Result		Limits (A/m)	
	Mode 1			
	A/m			
A	0.0312		1.63	
B	0.0346		1.63	
C	0.0322		1.63	
D	0.5323		1.63	
E	0.6122		1.63	
F	0.5433		1.63	

Test Position	H-Filed Strength Measure Result		Limits (A/m)	
	Mode 3			
	A/m			
A	0.0866		1.63	
B	0.0934		1.63	
C	0.0940		1.63	
D	0.1143		1.63	
E	0.1301		1.63	
F	0.1268		1.63	

Test Position	H-Filed Strength Measure Result		Limits (A/m)	
	Mode 4			
	A/m			
A	0.0532		1.63	
B	0.0501		1.63	
C	0.0503		1.63	
D	0.6321		1.63	
E	0.8432		1.63	
F	0.7542		1.63	

E-Filed Strength at 15 cm from the edges surrounding the EUT (V/m)

Test Position	E-Filed Strength Measure Result		Limits (V/m)	
	Mode 1			
	V/m			
A	0.2342		614	
B	0.2456		614	
C	0.3212		614	
D	0.3765		614	
E	0.4567		614	
F	0.3478		614	

Test Position	E-Filed Strength Measure Result		Limits (V/m)	
	Mode 3			
	V/m			
A	0.7541		614	
B	0.7658		614	
C	1.2105		614	
D	1.2066		614	
E	1.3569		614	
F	1.2674		614	

Test Position	E-Filed Strength Measure Result		Limits (V/m)	
	Mode 4			
	V/m			
A	0.4212		614	
B	0.4322		614	
C	0.7564		614	
D	0.7732		614	
E	0.8354		614	
F	0.7613		614	

Note 1: $f = 127.5\text{kHz}$

Note 2: All the modes had been tested, but only the worst data recorded in the report.

END OF REPORT