

FCC MPE TEST REPORT

FCC ID: 2ATGY-PWB1119

Product: POWER BANK

Trade Name: **ubiolabs**

Model Name: PWB1119

PWB1119SG, PWB1119PG, PWB1119XX

Serial Model: (where X should be any Arabian or English
later or blank)

Report No.: UNIA19090213FR-02

Prepared for

Ubio Labs, Inc.

2821 Northup Way, Suite 250, Bellevue, WA 98004, USA

Prepared by

Shenzhen United Testing Technology Co., Ltd.

2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang
Community, Xixiang Str, Bao'an District, Shenzhen, China

TEST RESULT CERTIFICATION

Applicant's name : Ubio Labs, Inc.

Address : 2821 Northup Way, Suite 250, Bellevue, WA 98004, USA

Manufacture's Name : Shenzhen PYS Industrial Co., LTD

Address : 101-1201 (Floor 1 to Floor12), Block.9 Lianhua Industry Zone,
Longyuan Road, Longhua Street, Longhua District, Shenzhen,
China

Product description

Product name : POWER BANK

Trade Mark : **ubiolabs**

Model and/or type reference : PWB1119, PWB1119SG, PWB1119PG, PWB1119XX (where X
should be any Arabian or English later or blank)

Standards : FCC KDB 680106 D01 RF Exposure Wireless Charging
Apps v03

This device described above has been tested by Shenzhen United Testing Technology
Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance
with the FCC requirements. And it is applicable only to the tested sample identified in the
report.

This report shall not be reproduced except in full, without the written approval of UNI, this
document may be altered or revised by Shenzhen United Testing Technology Co., Ltd.,
personnel only, and shall be noted in the revision of the document.

Date of Test.....:

Date (s) of performance of tests.....: Aug. 28, 2019 ~ Sep. 10, 2019

Date of Issue : Sep. 10, 2019

Test Result : Pass

Prepared by:

Bob liao

Bob liao/Editor



Reviewer:

Kahn yang/Supervisor

Approved & Authorized Signer:

Liuze/Manager

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Channel List			
Channel	Frequency(KHz)	Channel	Frequency(MHz)
01	125		

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.

1. SUMMARY OF TEST RESULTS

1.1 Test procedures according to the technical standards:

FCC KDB 680106 D01 RF Exposure Wireless Charging Apps v03

FCC CFR 47			
Standard Section	Test Item	Judgment	Remark
FCC CFR 47 part1, 1.1310 KDB680106 D01 v03(3)(3)	Electric Field Strength (E) (V/m)	PASS	
	Magnetic Field Strength (H) (A/m)	PASS	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	All emissions, radiated(<30M)(9KHz-30MHz)	$\pm 2.45\text{dB}$
2	Temperature	$\pm 0.5^\circ\text{C}$
3	Humidity	$\pm 2\%$

1.3 Test Instruments

Description	Brand	Model No.	Frequency Range	Calibrated Until
Broadband Field Meter	NARDA	NBM-550	—	Jan. 01, 2020
Magnetic Field Meter	NARDA	ELT-400	1–400kHz	Jan. 01, 2020
Magnetic Probe	NARDA	HF-3061	300kHz–30MHz	Jan. 01, 2020
Magnetic Probe	NARDA	HF-0191	27–1000MHz	Jan. 01, 2020
Broadband Field Meter	NARDA	NBM-550	—	Jan. 01, 2020
Electric Field Meter	COMBINOVA	EFM 200	5Hz–400kHz	Jan. 01, 2020
E-Field Probe	NARDA	EF-0391	100kHz–3GHz	Jan. 01, 2020
E-Field Probe	NARDA	EF-6091	100MHz–60GHz	Jan. 01, 2020

NOTE: The calibration interval of the above test instruments is 12 months.

2. MAXIMUM PERMISSIBLE EXPOSURE

2.1 MAXIMUM PERMISSIBLE EXPOSURE

Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density.


2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03.

3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.


3. TEST PROCEDURE

For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be at 15 cm surrounding the device and 20 cm above the top surface. E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair at 15 cm surrounding the device and 20 cm above the top surface.

4.1 TEST SETUP



4.2 TEST PHOTO



4.3 RESULT OF MAXIMUM PERMISSIBLE EXPOSURE

For Full load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.125	1.19	1.18	1.20	1.16	1.15	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.125	0.16	0.17	0.17	0.20	0.20	0.815	1.63

For Half Load for wrist band mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.125	1.16	1.18	1.18	1.19	1.19	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.125	0.16	0.16	0.18	0.20	0.20	0.815	1.63

For Half Load for shopped mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.125	1.16	1.16	1.16	1.18	1.17	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.125	0.17	0.17	0.16	0.16	0.18	0.815	1.63

For No load mode:

E-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (V/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (V/m)	Limits Test (V/m)
0.125	1.18	1.16	1.18	1.20	1.18	307	614

H-Filed Strength at 15 cm surrounding the device and 20 cm above the top surface (A/m)

Frequency Range (MHz)	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Reference Limit (A/m)	Limits Test (A/m)
0.125	0.18	0.17	0.17	0.18	0.20	0.815	1.63

※※※※※ THE END ※※※※※