

FCC REPORT

Applicant: Ubio Labs, Inc.

Address of Applicant: 2821 Northup Way, Suite 250 Bellevue, WA 98004 USA

Equipment Under Test (EUT)

Product Name: Wireless Speaker & Charging Hub

Model No.: WSP1000

Trade mark: ubiolabs

FCC ID: 2ATGY-WSP1000

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.209

Date of sample receipt: 24 Jun., 2020

Date of Test: 24 Jun., to 14 Jul., 2020

Date of report issue: 03 Aug., 2020

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	15 Jul., 2020	Original
01	03 Aug., 2020	Update page 5, 10, 11, 12

Tested By:

Mike Ou

Test Engineer

Date:

03 Aug., 2020

Reviewed By:

Winner Zhang

Project Engineer

Date:

03 Aug., 2020

3 Contents

Page

1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE	5
5.4 DESCRIPTION OF SUPPORT UNITS.....	5
5.5 MEASUREMENT UNCERTAINTY.....	5
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	6
5.7 LABORATORY FACILITY.....	6
5.8 LABORATORY LOCATION	6
5.9 TEST INSTRUMENTSLIST.....	6
6 TEST RESULTS AND MEASUREMENT DATA	7
6.1 ANTENNA REQUIREMENT	7
6.2 RADIATED EMISSION	8
6.3 CONDUCTED EMISSION	14
6.4 20dB BANDWIDTH	17
7 TEST SETUP PHOTOS.....	20
8 EUT CONSTRUCTIONAL PHOTOS.....	22

4 Test Summary

Test Item	Section in CFR 47	Result
Spurious emissions	15.209	Pass
20dB Bandwidth	15.215(c)	Pass
Conducted Emission	15.207	Pass
Remark: <i>1. Pass: The EUT complies with the essential requirements in the standard.</i> <i>2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer).</i>		
Test Method:	ANSI C63.4-2014 ANSI C63.10-2013	

5 General Information

5.1 Client Information

Applicant:	Ubio Labs, Inc.
Address:	2821 Northup Way, Suite 250 Bellevue, WA 98004 USA
Factory:	SHENZHEN JUNLAN ELECTRONIC LTD.
Address:	No.277 PingKui Road, Shijing Community, Pingshan Street, Pingshan New District, Shenzhen, China.

5.2 General Description of E.U.T.

Product Name:	Wireless Speaker & Charging Hub
Model No.:	WSP1000
Operation Frequency:	114.0kHz~205.0kHz
Modulation type:	ASK
Antenna Type:	Coil Antenna
Input:	DC 9.0V, 3000mA
Output (Wireless)	5W, 7.5W, 10W • 10W Qi certified fast charging for Samsung Galaxy S6 and later, Samsung Note5 and later, Motorola, LG • 7.5W wireless charging for iPhone 8 and later • 5W wireless charging for compatible devices
AC adapter:	Model: CHG1085 Input: AC110-240V, 50/60Hz, 0.7A Output: DC 9.0V, 3000mA
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test mode

TX 1 mode:	Keep the EUT in transmitting(Output 10W (Wireless)) mode with modulation
TX 2 mode:	Keep the EUT in transmitting(Output 7.5W (Wireless)) mode with modulation
TX 3 mode:	Keep the EUT in transmitting(Output 5W (Wireless)) mode with modulation
Remark	The EUT 5W, 7.5W, 10W output (Wireless) are all tested, found 10W output (Wireless) was worse case mode, the report only reflects the worst mode.

5.4 Description of Support Units

Manufacturer	Description	Model	S/N	FCC ID/DoC
Skytek	Wireless charging match load	N/A	N/A	N/A
Apple	Mobile phone	iPhone 11 Pro	MWDE2CH/A	Doc

5.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB
Radiated Emission (18GHz ~ 26.5GHz)	±3.20 dB

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5.9 Test Instrumentslist

Radiated Emission:


Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00044	03-07-2020	03-06-2021
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Simulated Station	Anritsu	MT8820C	6201026545	03-07-2020	03-06-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021

Conducted Emission:


Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-05-2020	03-04-2021
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	1447	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
Cable	HP	10503A	N/A	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A


6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
	

6.2 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209				
Test Frequency Range:	9kHz to 1000MHz				
Test site:	Measurement Distance: 3m(Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	600Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency (MHz)		Limit (uV/m @3m)		Distance (m)
	0.009-0.490		2400/F(kHz)		300
	0.490-1.705		24000/F(kHz)		30
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 1GHz		500		3
Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test setup:	9kHz-30MHz  30MHz-1GHz				


	 The diagram illustrates the test setup. An EUT (Equipment Under Test) is placed on a Turn Table at a height of 0.8m from the Ground Plane. A Search Antenna is mounted on an Antenna Tower at a height of 1m from the Ground Plane. The horizontal distance between the EUT and the Search Antenna is 3m. The vertical distance between the EUT and the Search Antenna is 4m. An RF Test Receiver is connected to the Search Antenna.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass
Remark:	The emission levels of above 1 GHz are very lower than the limit and not show in test report.

Measurement Data:

b) Radiated spurious:

Below 1GHz:

Product Name:	Wireless Speaker & Charging Hub	Product Model:	WSP1000
Test By:	Mike	Test mode:	TX1 mode
Test Frequency:	9kHz~30MHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	0.016	38.23	20.38	0.01	0.00	0.00	58.62	143.71	-85.09 Peak
2	0.031	31.93	20.24	0.02	0.00	0.00	52.19	137.65	-85.46 Peak
3	0.045	28.23	20.52	0.02	0.00	0.00	48.77	134.48	-85.71 Peak
4	0.174	48.97	20.27	0.04	0.00	0.00	69.28	122.82	-53.54 Peak
5	0.524	27.58	20.78	0.09	0.00	0.00	48.45	73.22	-24.77 Peak
6	0.873	19.01	20.56	0.10	0.00	0.00	39.67	68.80	-29.13 Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Wireless Speaker & Charging Hub	Product Model:	WSP1000
Test By:	Mike	Test mode:	TX1 mode
Test Frequency:	9kHz~30MHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	ReadAntenna	Cable	Aux	Preamp	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	Factor	Factor	Line	Limit	
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	0.016	36.83	20.38	0.01	0.00	0.00	57.22	143.71	-86.49 Peak
2	0.031	30.85	20.24	0.02	0.00	0.00	51.11	137.65	-86.54 Peak
3	0.099	23.30	20.51	0.02	0.00	0.00	43.83	107.67	-63.84 Peak
4	0.174	54.68	20.27	0.04	0.00	0.00	74.99	122.82	-47.83 Peak
5	0.524	32.04	20.78	0.09	0.00	0.00	52.91	73.22	-20.31 Peak
6	0.873	22.70	20.56	0.10	0.00	0.00	43.36	68.80	-25.44 Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Wireless Speaker & Charging Hub	Product Model:	WSP1000
Test By:	Mike	Test mode:	TX1 mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24°C Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	30.317	55.81	11.85	0.40	0.00	29.98	38.08	40.00	-1.92	QP
2	40.276	52.11	12.81	0.35	0.00	29.90	35.37	40.00	-4.63	QP
3	44.431	53.25	12.89	0.38	0.00	29.86	36.66	40.00	-3.34	QP
4	151.067	49.03	14.32	0.62	0.00	29.21	34.76	43.50	-8.74	QP
5	219.075	46.77	18.38	0.74	0.00	28.71	37.18	46.00	-8.82	QP
6	322.189	45.00	18.75	0.89	0.00	28.50	36.14	46.00	-9.86	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Wireless Speaker & Charging Hub	Product Model:	WSP1000
Test By:	Mike	Test mode:	TX1 mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Environment:	Temp: 24℃ Humi: 57%




	Freq	Read Level	Antenna Factor	Cable Loss	Aux Factor	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	164.330	37.82	15.59	0.64	0.00	29.10	24.95	43.50	-18.55	QP
2	223.733	44.06	18.40	0.74	0.00	28.69	34.51	46.00	-11.49	QP
3	229.293	50.93	18.42	0.75	0.00	28.65	41.45	46.00	-4.55	QP
4	269.428	41.59	18.58	0.82	0.00	28.50	32.49	46.00	-13.51	QP
5	311.087	48.58	18.72	0.88	0.00	28.48	39.70	46.00	-6.30	QP
6	334.859	42.78	18.77	0.91	0.00	28.53	33.93	46.00	-12.07	QP

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.3 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.207				
Test Frequency Range:	150kHz to 30MHz				
Class / Severity:	Class B				
Receiver setup:	RBW=9kHz, VBW=30kHz				
Limit:	Frequency range (MHz)	Limit (dB μ V)			
		Quasi-peak		Average	
		0.15-0.5		66 to 56*	56 to 46*
		0.5-5		56	46
	0.5-30		60	50	
* Decreases with the logarithm of the frequency.					
Test setup:	Reference Plane  Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m				
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.				
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.: 101kPa
Test Instruments:	Refer to section 5.9 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Pass				

Measurement data:

Product name:	Wireless Speaker & Charging Hub	Product Model:	WSP1000
Test by:	Mike	Test mode:	TX1 mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




Trace: 23

	Freq	Read Level	LISN Factor	Cable Loss	Aux Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.222	25.73	-0.58	10.76	-0.19	35.72	62.74	-27.02	QP
2	0.222	20.54	-0.58	10.76	-0.19	30.53	52.74	-22.21	Average
3	0.354	32.54	-0.51	10.73	0.14	42.90	58.87	-15.97	QP
4	0.402	22.21	-0.48	10.72	0.42	32.87	47.81	-14.94	Average
5	0.442	23.78	-0.46	10.74	0.08	34.14	47.02	-12.88	Average
6	0.447	34.89	-0.46	10.74	0.05	45.22	56.93	-11.71	QP
7	0.510	24.20	-0.44	10.76	-0.35	34.17	46.00	-11.83	Average
8	0.535	30.66	-0.45	10.76	-0.36	40.61	56.00	-15.39	QP
9	1.021	28.83	-0.62	10.87	0.44	39.52	56.00	-16.48	QP
10	1.535	24.60	-0.55	10.93	-0.03	34.95	46.00	-11.05	Average
11	12.784	27.82	-0.71	10.92	2.95	40.98	60.00	-19.02	QP
12	13.057	24.99	-0.70	10.91	3.01	38.21	50.00	-11.79	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	Wireless Speaker & Charging Hub	Product Model:	WSP1000
Test by:	Mike	Test mode:	TX1 mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Cable Loss	Aux Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.253	24.60	-0.67	10.75	0.01	34.69	51.64	-16.95	Average
2	0.354	32.54	-0.65	10.73	-0.03	42.59	58.87	-16.28	QP
3	0.447	27.67	-0.64	10.74	-0.02	37.75	46.93	-9.18	Average
4	0.449	36.74	-0.64	10.74	-0.01	46.83	56.89	-10.06	QP
5	0.510	26.62	-0.65	10.76	0.03	36.76	46.00	-9.24	Average
6	0.535	32.60	-0.65	10.76	0.03	42.74	56.00	-13.26	QP
7	0.894	25.94	-0.67	10.84	0.07	36.18	46.00	-9.82	Average
8	1.662	30.38	-0.70	10.94	0.15	40.77	56.00	-15.23	QP
9	2.554	24.71	-0.67	10.94	0.25	35.23	46.00	-10.77	Average
10	3.700	30.12	-0.65	10.90	0.46	40.83	56.00	-15.17	QP
11	13.127	28.41	-0.80	10.91	2.54	41.06	60.00	-18.94	QP
12	13.127	26.62	-0.80	10.91	2.54	39.27	50.00	-10.73	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.


6.4 20dB Bandwidth

Test Requirement:	FCC Part15 C Section 15.215 (c)
Receiver setup:	RBW=1 kHz, VBW=3 kHz, detector: Peak
Limit:	The fundamentelemission be kept within atleast the central 80% of the permittedband
Test Procedure:	1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data


20dB bandwidth (kHz)		99% bandwidth (kHz)		Limits
Lowest channel	Highest channel	Lowest channel	Highest channel	N/A
8.30	8.10	7.10	6.90	
Remark: For report purpose only.				

Test plot as follows:




99% bandwidth

Lowest channel



Date: 28.JUN.2020 15:03:31

Highest channel



Date: 28.JUN.2020 14:56:46