

TEST REPORT

Product Name : SMART FOUR CONNECTED
Brand Mark : GiiKER
Model No. : JKSZQ001
FCC ID : 2ATHZ-SMARTFOUR
Report Number : BLA-EMC-202009-A3901
Date of Sample Receipt : 2020/9/8
Date of Test : 2020/9/8 to 2020/9/18
Date of Issue : 2020/9/22
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

FS GIIKER TECHNOLOGY CO.,LTD.

**Room 602,East Building,GIDC Square,No.1 Sanle Road North,Beijiao,Shunde,
Foshan 528311,Guangdong,China.**

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

IOT Test Centre of BlueAsia

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen,China

TEL: +86-755-23059481

Compiled by:

Jozu.

Approved by:

Tamen Li

Review by:

Sweet. Liang

Date:

2020/9/22



REPORT REVISE RECORD

Version No.	Date	Description
00	2020/9/22	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	6
2	GENERAL INFORMATION	7
3	GENERAL DESCRIPTION OF E.U.T.	7
4	TEST ENVIRONMENT	8
5	TEST MODE	8
6	MEASUREMENT UNCERTAINTY	8
7	DESCRIPTION OF SUPPORT UNIT.....	9
8	LABORATORY LOCATION.....	9
9	TEST INSTRUMENTS LIST	10
	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	13
	LIMITS.....	13
	BLOCK DIAGRAM OF TEST SETUP.....	13
	PROCEDURE	13
	TEST DATA	15
	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	17
	LIMITS.....	17
	BLOCK DIAGRAM OF TEST SETUP.....	17
	PROCEDURE	17
	TEST DATA	19
	RADIATED SPURIOUS EMISSIONS	21
	LIMITS.....	21
	BLOCK DIAGRAM OF TEST SETUP.....	22
	PROCEDURE	22
	TEST DATA	24
	CONDUCTED BAND EDGES MEASUREMENT	32
	LIMITS.....	32
	BLOCK DIAGRAM OF TEST SETUP.....	32
	TEST DATA	33
	ANTENNA REQUIREMENT.....	34
	CONCLUSION.....	34

MINIMUM 6DB BANDWIDTH	35
LIMITS.....	35
BLOCK DIAGRAM OF TEST SETUP	35
TEST DATA	35
RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	36
LIMITS.....	36
BLOCK DIAGRAM OF TEST SETUP	37
PROCEDURE	37
TEST DATA	39
CONDUCTED SPURIOUS EMISSIONS.....	43
LIMITS.....	43
BLOCK DIAGRAM OF TEST SETUP	43
TEST DATA	44
POWER SPECTRUM DENSITY	45
LIMITS.....	45
BLOCK DIAGRAM OF TEST SETUP	45
TEST DATA	45
CONDUCTED PEAK OUTPUT POWER	46
LIMITS.....	46
BLOCK DIAGRAM OF TEST SETUP	46
TEST DATA	47
10 APPENDIX.....	48
10.1 APPENDIX: DTS BANDWIDTH.....	48
Test Result.....	48
Test Graphs.....	49
10.2 APPENDIX: OCCUPIED CHANNEL BANDWIDTH	50
Test Result.....	50
Test Graphs.....	51
10.3 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER	52
Test Result.....	52
Test Graphs.....	53
10.4 APPENDIX: MAXIMUM POWER SPECTRAL DENSITY	55
Test Result.....	55

	<i>Test Graphs</i>	56
10.5	APPENDIX: BAND EDGE MEASUREMENTS	58
	<i>Test Result</i>	58
	<i>Test Graphs</i>	59
10.6	APPENDIX: CONDUCTED SPURIOUS EMISSION	60
	<i>Test Result</i>	60
	<i>Test Graphs</i>	61
APPENDIX A: PHOTOGRAPHS OF TEST SETUP		64
APPENDIX B: PHOTOGRAPHS OF EUT		67

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart B	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass

2 GENERAL INFORMATION

Applicant	FS GIIKER TECHNOLOGY CO.,LTD.
Address	Room 602,East Building,GIDC Square,No.1 Sanle Road North,Beijiao,Shunde,Foshan 528311,Guangdong,China.
Manufacturer	FS GIIKER TECHNOLOGY CO.,LTD.
Address	Room 602,East Building,GIDC Square,No.1 Sanle Road North,Beijiao,Shunde,Foshan 528311,Guangdong,China.
Factory	FS GIIKER TECHNOLOGY CO.,LTD.
Address	2nd Floor,Building-8,No.6 Weiye West Road,Beijiao,Shunde, Foshan, Guangdong 528311, China.
Product Name	SMART FOUR CONNECTED
Test Model No.	JKSZQ001

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	GMF 3.2(PRO) 2020.8.27
Software Version	V2
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	0.5dBi (Provided by the customer)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode
Remark: Only the data of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission	±4.34dB
Radiated Emission	±4.24dB
Radiated Emission	±4.68dB
AC Power Line Conducted Emission	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
IOT Test Centre of BlueAsia
No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
Tests were sub-contracted:
Radiation test is conducted by Global United Technology Services Co., Ltd.
No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, sBaoan District, Shenzhen, Guangdong, China 518102
FCC —Registration No.: 381383
Job No.: GTS202009000096

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	6/10/2018	6/9/2021
Receiver	R&S	ESPI3	101082	4/20/2020	4/19/2021
LISN	R&S	ENV216	3560.6550.15	7/1/2020	6/30/2021
LISN	AT	AT166-2	AKK1806000003	12/17/2019	12/16/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 02 2020	July. 01 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 25 2020	June. 24 2021
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 25 2020	June. 24 2021
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 25 2020	June. 24 2021
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 25 2020	June. 24 2021
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 25 2020	June. 24 2021
9	Coaxial Cable	GTS	N/A	GTS211	June. 25 2020	June. 24 2021
10	Coaxial cable	GTS	N/A	GTS210	June. 25 2020	June. 24 2021
11	Coaxial Cable	GTS	N/A	GTS212	June. 25 2020	June. 24 2021
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 25 2020	June. 24 2021
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 25 2020	June. 24 2021
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 25 2020	June. 24 2021
15	Band filter	Amindeon	82346	GTS219	June. 25 2020	June. 24 2021
16	Power Meter	Anritsu	ML2495A	GTS540	June. 25 2020	June. 24 2021
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 25 2020	June. 24 2021
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 25 2020	June. 24 2021
19	Splitter	Agilent	11636B	GTS237	June. 25 2020	June. 24 2021
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 25 2020	June. 24 2021
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 25 2020	June. 24 2021

Test Equipment Of Conducted Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Power Spectrum Density					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Conducted Peak Output Power					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/1/2020	6/30/2021
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

BLOCK DIAGRAM OF TEST SETUP



Remark
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50?H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as

the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,

4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.


5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $LISN = Read\ Level + Cable\ Loss + LISN\ Factor$

TEST DATA

[Test Mode: TX]; [Line: Neutral]

Conducted Emission Measurement



Site: Phase: **N** Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V 60Hz Humidity: 60 %
EUT: SMART FOUR
M/N: JKSZQ001
Mode: BT mode
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1940	23.47	9.89	33.36	63.86	-30.50	QP	
2		0.1940	16.18	9.89	26.07	53.86	-27.79	AVG	
3		0.5780	20.01	9.74	29.75	56.00	-26.25	QP	
4	*	0.5780	14.88	9.74	24.62	46.00	-21.38	AVG	
5		1.9820	18.35	9.86	28.21	56.00	-27.79	QP	
6		1.9820	9.63	9.86	19.49	46.00	-26.51	AVG	
7		4.3460	19.86	9.85	29.71	56.00	-26.29	QP	
8		4.3460	9.98	9.85	19.83	46.00	-26.17	AVG	
9		7.9740	24.09	9.87	33.96	60.00	-26.04	QP	
10		7.9740	13.30	9.87	23.17	50.00	-26.83	AVG	
11		19.4220	21.31	10.08	31.39	60.00	-28.61	QP	
12		19.4220	6.62	10.08	16.70	50.00	-33.30	AVG	


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode: TX]; [Line: Line]

Conducted Emission Measurement



Site: Phase: **L1** Temperature: 26
Limit: FCC Class B Conduction(QP) Power: AC 120V 60Hz Humidity: 60 %
EUT: SMART FOUR
M/N: JKSZQ001
Mode: BT mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	29.57	9.88	39.45	66.00	-26.55	QP	
2		0.1500	17.91	9.88	27.79	56.00	-28.21	AVG	
3		0.5780	24.46	9.74	34.20	56.00	-21.80	QP	
4	*	0.5780	19.59	9.74	29.33	46.00	-16.67	AVG	
5		2.1900	21.22	9.82	31.04	56.00	-24.96	QP	
6		2.1900	11.95	9.82	21.77	46.00	-24.23	AVG	
7		4.7660	18.46	9.87	28.33	56.00	-27.67	QP	
8		4.7660	8.22	9.87	18.09	46.00	-27.91	AVG	
9		7.8780	25.44	9.87	35.31	60.00	-24.69	QP	
10		7.8780	14.48	9.87	24.35	50.00	-25.65	AVG	
11		20.4340	26.02	10.03	36.05	60.00	-23.95	QP	
12		20.4340	9.68	10.03	19.71	50.00	-30.29	AVG	

*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX mode (SE) below 1G;TX mode (SE) Above 1G
Test Mode (Final Test)	TX mode (SE) below 1G;TX mode (SE) Above 1G
Tester	Jozu
Temperature	23℃
Humidity	48%

LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BLOCK DIAGRAM OF TEST SETUP



PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

TEST DATA

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]

Power:AC120V/60Hz




	Freq	ReadLevel	AntennaFactor	PreampFactor	CableLoss	Level	LimitLine	OverLimit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	41.422	35.95	12.22	35.75	0.68	13.10	40.00	-26.90	QP
2	49.533	36.74	12.30	36.16	0.77	13.65	40.00	-26.35	QP
3	146.888	56.95	7.54	37.06	1.55	28.98	43.50	-14.52	QP
4	225.308	50.06	11.35	37.36	1.99	26.04	46.00	-19.96	QP
5	251.180	55.91	12.18	37.38	2.13	32.84	46.00	-13.16	QP
6	292.058	51.75	13.38	37.41	2.32	30.04	46.00	-15.96	QP

Test Result: Pass

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]

Power:AC120V/60Hz




	Freq	ReadAntenna	Preamp	Cable	Level	Limit	Over	Remark
	MHz	Level	Factor	Loss	dBuV/m	Line	Limit	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	
1	30.000	38.07	11.20	35.00	0.55	14.82	40.00	-25.18 QP
2	40.559	37.26	12.21	35.70	0.67	14.44	40.00	-25.56 QP
3	47.326	37.57	12.28	36.05	0.74	14.54	40.00	-25.46 QP
4	61.562	39.87	10.72	36.34	0.87	15.12	40.00	-24.88 QP
5	95.762	39.63	11.59	36.69	1.16	15.69	43.50	-27.81 QP
6	146.888	45.06	7.54	37.06	1.55	17.09	43.50	-26.41 QP

Test Result: Pass


[TestMode: GFSK]

Test channel:lowest



Condition : FCC PART 15 (PK) 3m HORIZONTAL
Job.No : GTS202009000096
Test Mode : TX2402
Test Engineer: hans
Remark :


	Freq	Read	Antenna	Preamp	Cable	Limit	Over	
	MHz	Level	Factor	Factor	Loss	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	4804.000	30.02	31.20	37.73	4.61	28.10	54.00	-25.90 Average
2	4804.000	40.10	31.20	37.73	4.61	38.18	74.00	-35.82 Peak
3	7206.000	21.06	36.16	35.63	6.48	28.07	54.00	-25.93 Average
4	7206.000	31.16	36.16	35.63	6.48	38.17	74.00	-35.83 Peak
5	9608.000	21.32	37.93	34.94	7.97	32.28	54.00	-21.72 Average
6	9608.000	31.62	37.93	34.94	7.97	42.58	74.00	-31.42 Peak



Condition : FCC PART 15 (PK) 3m VERTICAL
 Job.No : GTS202009000096
 Test Mode : TX2402
 Test Engineer: hans
 Remark :


		Read	Antenna	Preamp	Cable		Limit	Over	
	Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4804.000	26.30	31.20	37.73	4.61	24.38	54.00	-29.62	Average
2	4804.000	35.69	31.20	37.73	4.61	33.77	74.00	-40.23	Peak
3	7206.000	21.03	36.16	35.63	6.48	28.04	54.00	-25.96	Average
4	7206.000	31.24	36.16	35.63	6.48	38.25	74.00	-35.75	Peak
5	9608.000	20.64	37.93	34.94	7.97	31.60	54.00	-22.40	Average
6	9608.000	30.60	37.93	34.94	7.97	41.56	74.00	-32.44	Peak

Test channel: Middle



Condition : FCC PART 15 (PK) 3m VERTICAL
 Job.No : GTS202009000096
 Test Mode : TX2440
 Test Engineer: hans
 Remark :


	Freq	ReadAntenna	Preamp	Cable	Limit	Over	
	Level	Factor	Factor	Loss	Level	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	4880.000	26.34	31.31	37.75	4.69	24.59	54.00 -29.41 Average
2	4880.000	35.79	31.31	37.75	4.69	34.04	74.00 -39.96 Peak
3	7320.000	21.93	36.43	35.60	6.63	29.39	54.00 -24.61 Average
4	7320.000	31.74	36.43	35.60	6.63	39.20	74.00 -34.80 Peak
5	9760.000	21.09	38.10	35.03	8.03	32.19	54.00 -21.81 Average
6	9760.000	30.86	38.10	35.03	8.03	41.96	74.00 -32.04 Peak



Condition : FCC PART 15 (PK) 3m HORIZONTAL
Job.No : GTS2020090000096
Test Mode : TX2440
Test Engineer: hans
Remark :


	Freq	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	4880.000	32.60	31.31	37.75	4.69	30.85	54.00	-23.15	Average
2	4880.000	42.13	31.31	37.75	4.69	40.38	74.00	-33.62	Peak
3	7320.000	21.68	36.43	35.60	6.63	29.14	54.00	-24.86	Average
4	7320.000	31.82	36.43	35.60	6.63	39.28	74.00	-34.72	Peak
5	9760.000	20.36	38.10	35.03	8.03	31.46	54.00	-22.54	Average
6	9760.000	30.78	38.10	35.03	8.03	41.88	74.00	-32.12	Peak

Test channel: Highest



Condition : FCC PART 15 (PK) 3m HORIZONTAL
 Job.No : GTS2020090000096
 Test Mode : TX2480
 Test Engineer: hans
 Remark :

	Freq	ReadAntenna	Preamp	Cable	Limit	Over		
	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	4960.000	30.35	31.44	37.78	4.79	28.80	54.00	-25.20 Average
2	4960.000	40.29	31.44	37.78	4.79	38.74	74.00	-35.26 Peak
3	7440.000	22.69	36.66	35.56	6.77	30.56	54.00	-23.44 Average
4	7440.000	32.59	36.66	35.56	6.77	40.46	74.00	-33.54 Peak
5	9920.000	21.98	38.30	35.14	8.09	33.23	54.00	-20.77 Average
6	9920.000	31.82	38.30	35.14	8.09	43.07	74.00	-30.93 Peak



Condition : FCC PART 15 (PK) 3m VERTICAL
 Job.No : GTS202009000096
 Test Mode : TX2480
 Test Engineer: hans
 Remark :

	Freq	ReadAntenna	Preampl	Cable	Limit	Over	
	Level	Factor	Factor	Loss	Level	Limit	Remark
-----	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	4960.000	26.64	31.44	37.78	4.79	25.09	54.00 -28.91 Average
2	4960.000	36.36	31.44	37.78	4.79	34.81	74.00 -39.19 Peak
3	7440.000	22.98	36.66	35.56	6.77	30.85	54.00 -23.15 Average
4	7440.000	32.25	36.66	35.56	6.77	40.12	74.00 -33.88 Peak
5	9920.000	24.03	38.30	35.14	8.09	35.28	54.00 -18.72 Average
6	9920.000	31.76	38.30	35.14	8.09	43.01	74.00 -30.99 Peak

Test Result: Pass


CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA**Pass: Please Refer To Appendix: Appendix1 For Details**

BlueAsia

ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0.5dBi.




MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	24°C
Humidity	53%

LIMITS

Limit:	≥ 500 kHz
--------	----------------

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BLOCK DIAGRAM OF TEST SETUP



PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamplifier Factor}$


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

TEST DATA

[TestMode: TX mode (SE) Above 1G];

Test channel:lowest

Horizontal



	Freq	ReadAntenna	Preamp	Cable		Limit	Over	
	Level	Factor	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2310.000	35.03	27.14	30.43	2.81	34.55	54.00	-19.45 Average
2	2310.000	44.40	27.14	30.43	2.81	43.92	74.00	-30.08 Peak
3	2390.000	35.06	27.37	30.24	2.91	35.10	54.00	-18.90 Average
4	2390.000	44.53	27.37	30.24	2.91	44.57	74.00	-29.43 Peak
5	2400.000	44.68	27.41	30.26	2.91	44.74	54.00	-9.26 Average
6	2400.000	54.48	27.41	30.26	2.91	54.54	74.00	-19.46 Peak