

FCC TEST REPORT

Product Name: AIR COUTURE EARBUDS BUNDLE
Trade Mark: AIRBUDS
Model No.: 14816
Add. Model No.: 14811, 14813, 14814, 14815, 14772,
14771, 14362, 14361, 14365, 14366 ,
14367, 10612
Report Number: 24042411021RFC-1
Test Standards: FCC 47 CFR Part 15 Subpart C
FCC ID: 2ATOM-14816
Test Result: PASS
Date of Issue: September 3, 2024

Prepared for:

AFH Industries Inc.
7FL,110 West 34th street New York United states

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China**

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen
Senior Project Engineer

Reviewed by:

Henry Lu

Henry Lu
Team Leader

Approved by:

Robben chen

Robben Chen
Assistant Manager

Date: September 3, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

Version

Version No.	Date	Description
V1.0	September 3, 2024	Original



CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.2.1 GENERAL DESCRIPTION OF EUT	4
1.2.2 DESCRIPTION OF ACCESSORIES	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
1.4 OTHER INFORMATION	5
1.5 DESCRIPTION OF SUPPORT UNITS	5
1.6 TEST LOCATION	6
1.7 TEST FACILITY	6
1.8 DEVIATION FROM STANDARDS	6
1.9 ABNORMALITIES FROM STANDARD CONDITIONS	6
1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
1.11 MEASUREMENT UNCERTAINTY	7
2. TEST SUMMARY	8
3. EQUIPMENT LIST	9
4. TEST CONFIGURATION	10
4.1 ENVIRONMENTAL CONDITIONS FOR TESTING	10
4.1.1 NORMAL OR EXTREME TEST CONDITIONS	10
4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE	10
4.2 TEST CHANNELS	10
4.3 EUT TEST STATUS	10
4.4 PRE-SCAN	11
4.4.1 PRE-SCAN UNDER ALL PACKETS AT MIDDLE CHANNEL	11
4.4.2 WORST-CASE DATA PACKETS	11
4.4.3 TESTED CHANNEL DETAIL	11
4.5 TEST SETUP	12
4.5.1 FOR RADIATED EMISSIONS TEST SETUP	12
4.5.2 FOR CONDUCTED RF TEST SETUP	13
4.6 SYSTEM TEST CONFIGURATION	14
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION	15
5.1 REFERENCE DOCUMENTS FOR TESTING	15
5.2 ANTENNA REQUIREMENT	15
5.3 CONDUCTED PEAK OUTPUT POWER	16
5.4 20 dB BANDWIDTH	17
5.5 CARRIER FREQUENCIES SEPARATION	18
5.6 NUMBER OF HOPPING CHANNEL	19
5.7 DWELL TIME	20
5.8 CONDUCTED OUT OF BAND EMISSION	21
5.9 RADIATED SPURIOUS EMISSIONS	22
5.10 BAND EDGE MEASUREMENTS (RADIATED)	29
APPENDIX A RF TEST DATA	34
A.1 20dB BANDWIDTH	34
A.2 CARRIER FREQUENCIES SEPARATION	35
A.3 CONDUCTED OUT OF BAND EMISSION	36
A.4 DUTY CYCLE	39
A.5 DWELL TIME	43
A.6 NUMBER OF HOPPING CHANNEL	47
APPENDIX 1 PHOTOS OF TEST SETUP	48
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	48

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	AFH Industries Inc.
Address of Applicant:	7FL,110 West 34th street New York United states
Manufacturer:	AFH Industries Inc.
Address of Manufacturer:	7FL,110 West 34th street New York United states

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	AIR COUTURE EARBUDS BUNDLE	
Model No.:	14816	
Add. Model No.:	14811, 14813, 14814, 14815, 14772, 14771, 14362, 14361, 14365, 14366 , 14367, 10612	
Trade Mark:	AIRBUDS	
DUT Stage:	Identical Prototype	
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	Bluetooth 5.3
Sample Received Date:	April 24, 2024	
Sample Tested Date:	June 19, 2024 to August 14, 2024	

Remark:

The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

Charging Case	
Battery (Charging Case)	
Model No.:	601230
Battery Type:	Lithium-ion Rechargeable Battery
Rated Voltage:	3.7 Vdc
Rated Capacity:	180 mAh

Battery(earbuds)	
Model No.:	PL401012
Battery Type:	Lithium-ion Rechargeable Battery
Rated Voltage:	3.7 Vdc
Rated Capacity:	35 mAh

Cable	
Connector:	USB Cable
Cable Type:	Unshielded without ferrite
Length:	0.2 Meter

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation:	GFSK, $\pi/4$ DQPSK
Number of Channels:	79
Channel Separation:	1 MHz
Hopping Channel Type:	Adaptive Frequency Hopping Systems
Antenna Type: (Provided by the customer)	Chip Antenna
Antenna Gain: (Provided by the customer)	3.59 dBi
Maximum Peak Power:	-2.087 dBm
Normal Test Voltage:	3.7 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
$f = 2402 + k \text{ MHz}, k = 0, \dots, 78$	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	1-DH1	4	27
	1-DH3	11	183
	1-DH5	15	339
$\pi/4$ DQPSK	2-DH1	20	54
	2-DH3	26	367
	2-DH5	30	679

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1 Meter	Applicant

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 x 10 ⁻⁸
12	Transmission Time	± 0.19 %

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (b)	N/A	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013 Section 6.2	N/A ^(Note)
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(1)	ANSI C63.10-2013 Section 7.8.5	PASS
20 dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 6.9.2	PASS
Carrier Frequencies Separation	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 7.8.2	PASS
Number of Hopping Channel	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)(iii)	ANSI C63.10-2013 Section 7.8.3	PASS
Dwell Time	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 7.8.4	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8	PASS
Radiated Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6	PASS
Band Edge Measurement	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Section 6.10.5	PASS
Note: Place earbuds into the charging case, they will turn off automatically, and the Bluetooth does not work.			
Disclaimer and Explanations: The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.			

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	27-Oct-2023	26-Oct-2024
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	30-Oct-2023	29-Oct-2024
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	30-Oct-2023	29-Oct-2024
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	30-Oct-2023	29-Oct-2024
☒	Preamplifier	HP	8447F	2805A02960	31-Oct-2023	30-Oct-2024
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	1-Apr-2024	31-Mar-2025
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	1-Apr-2024	31-Mar-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	30-Oct-2023	29-Oct-2024
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	30-Oct-2023	29-Oct-2024
☒	Band Reject Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	27-Oct-2023	26-Oct-2024
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

RF Conducted Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date	Cal. Due date
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	29-Mar-2024	28-Mar-2025
☐	EXA Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	27-Oct-2023	26-Oct-2024
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	27-Oct-2023	26-Oct-2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage(V)	Relative Humidity (%)
NT/NV	+15 to +35	3.7	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Conducted Peak Output Power	22.4	53.2	100.1	S202404243231-ZJA02/2	Allen Zhou
20 dB Bandwidth					
Carrier Frequencies Separation					
Number of Hopping Channel					
Dwell Time					
Conducted Out of Band Emission	23.1	54.4	100.1	S202408074088-ZJC01/4	Fire Huo
Radiated Emissions					
Band Edge Measurement					

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
π /4DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK/ π /4DQPSK	1Tx	1. Keep the EUT in continuously transmitting with Modulation test single 2. Keep the EUT in continuously transmitting with Modulation test Hopping Frequency.

Power Setting (Provided by the customer)
Power Setting: 9

Test Software (Provided by the customer)
FCC Assist 1.0.2.2

4.4 PRE-SCAN

4.4.1 Pre-scan under all packets at middle channel

Conducted Average Power (dBm) for packets						
Type of Modulation	GFSK			$\pi/4$ DQPSK		
Packets	1-DH1	1-DH3	1-DH5	2-DH1	2-DH3	2-DH5
Power (dBm)	-8.61	-5.34	-4.65	-9.41	-6.62	-6.21

4.4.2 Worst-case data packets

Type of Modulation	Worst-case data rates
GFSK	1-DH5
$\pi/4$ DQPSK	2-DH5

4.4.3 Tested channel detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data packets and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Type of Modulation	GFSK			$\pi/4$ DQPSK		
Data Packets	1-DH1	1-DH3	1-DH5	2-DH1	2-DH3	2-DH5
Available Channel						
Test Item	Test channel and choose of data packets					
AC Power Line Conducted Emission	Frequency Hopping Channel 0 to 78					
	Link					
Conducted Peak Output	Channel 0 & 39 & 78					
Power	☐	☐	☒	☐	☐	☒
20 dB Bandwidth	Channel 0 & 39 & 78					
	☐	☐	☒	☐	☐	☒
Carrier Frequencies Separation	Frequency Hopping Channel 0 to 78					
	☐	☐	☒	☐	☐	☒
Number of Hopping Channel	Frequency Hopping Channel 0 to 78					
	☐	☐	☒	☐	☐	☒
Dwell Time	Channel 39					
	☒	☒	☒	☒	☒	☒
Conducted Out of Band Emission	Channel 0 & 39 & 78					
	☐	☐	☒	☐	☐	☒
Radiated Emissions	Channel 0 & 39 & 78					
	☐	☐	☒	☐	☐	☐
Band Edge Measurements (Radiated)	Channel 0 & 78					
	☐	☐	☒	☐	☐	☐
Remark:						
1. The mark "☑" means is chosen for testing;						
2. The mark "☐" means is not chosen for testing.						

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz







Figure 2. 30MHz to 1GHz





4.5.2 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in orientation.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna: Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 3.59 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(1)

Test Method: ANSI C63.10-2013 Section 7.8.5

Limit: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately 5 x 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW ≥ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Results: **PASS**

Left Earbud

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	-3.063	0.494	-4.25	≤30	PASS
		39	-3.386	0.459	-4.65		PASS
		78	-4.057	0.393	-5.52		PASS
π/4DQPSK	2-DH5	0	-2.087	0.618	-5.66	≤20.97	PASS
		39	-2.366	0.580	-6.21		PASS
		78	-3.057	0.495	-6.89		PASS

Right Earbud

Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	-3.069	0.493	-4.29	≤30	PASS
		39	-3.393	0.458	-4.71		PASS
		78	-4.064	0.392	-5.55		PASS
π/4DQPSK	2-DH5	0	-2.099	0.617	-5.68	≤20.97	PASS
		39	-2.383	0.578	-6.39		PASS
		78	-3.079	0.492	-6.82		PASS

Note:

- 1、 The antenna gain of 3.59 dBi less than 6dBi maximum permission antenna gain value based on 125 mW peak output power limit.
- 2、 This AIR COUTURE EARBUDS BUNDLE share the same circuit diagram. The only difference is that PCB is a mirror image. Based on the above output power data, the test data of the conduction method comes from the left earbud.

5.420 DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)

Test Method: ANSI C63.10-2013 Section 6.9.2

Limit: None; for reporting purposes only.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

- a) Span = approximately 2 to 5 times the OBW, centered on a hopping channel.
- b) RBW = 1% to 5% of the OBW.
- c) VBW $\geq 3 \times$ RBW
- d) Sweep = auto;
- e) Detector function = peak
- f) Trace = max hold
- g) All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

5.5 CARRIER FREQUENCIES SEPARATION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)

Test Method: ANSI C63.10-2013 Section 7.8.2

Limit: Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.
Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.
- h) Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

5.6 NUMBER OF HOPPING CHANNEL

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247(a)(1)(iii)
Test Method:	ANSI C63.10-2013 Section 7.8.3
Limit:	Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen. b) RBW < 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. c) VBW ≥ RBW. d) Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize. Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.5.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	Please refer to Appendix A

5.7 DWELL TIME

Test Requirement:	FCC 47 CFR Part 15 Subpart C Section 15.247(a)(1)
Test Method:	ANSI C63.10-2013 Section 7.8.4
Limit:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
Test Procedure:	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: a) Span = zero span, centered on a hopping channel b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel. c) Sweep = As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel. d) Detector function = peak e) Trace = max hold f) Use the marker-delta function to determine the dwell time Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
Test Setup:	Refer to section 4.5.3 for details.
Instruments Used:	Refer to section 3 for details
Test Mode:	Link mode
Test Results:	Please refer to Appendix A

5.8 CONDUCTED OUT OF BAND EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(d)
Test Method: ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8
Limit: In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.
Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

Step 1: Measurement Procedure REF

- a) Set instrument center frequency to 2400 MHz or 2483.5 MHz.
- b) Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Sweep points $\geq 2 \times$ Span/RBW
- h) Trace mode = max hold.
- i) Allow the trace to stabilize.
- j) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

Step 2: Measurement Procedure OOBE

- a) Set RBW = 100 kHz.
- b) Set VBW ≥ 300 kHz.
- c) Detector = peak.
- d) Sweep = auto couple.
- e) Trace Mode = max hold.
- f) Allow trace to fully stabilize.
- g) Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.
Instruments Used: Refer to section 3 for details
Test Mode: Hopping Frequencies Transmitter mode
Test Results: Please refer to Appendix A

5.9 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dB μ V/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB μ V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

- 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

- 2) Test the EUT in the lowest channel, middle channel, the Highest channel
- 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
- 4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:

Radiated Emission Test Data (9 kHz ~ 30 MHz):


The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

For Left Earbud

Radiated Emission Test Data (30 MHz ~ 1 GHz):


Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	168.997	48.27	-12.16	36.11	43.50	-7.39	QP
2	193.137	46.46	-11.38	35.08	43.50	-8.42	QP
3	216.120	47.51	-10.93	36.58	46.00	-9.42	QP
4	334.126	47.03	-7.51	39.52	46.00	-6.48	QP
5	398.296	43.20	-4.87	38.33	46.00	-7.67	QP
6	421.329	42.57	-4.30	38.27	46.00	-7.73	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.425	28.19	-4.88	23.31	40.00	-16.69	QP
2	201.454	37.58	-11.00	26.58	43.50	-16.92	QP
3	336.482	45.02	-7.47	37.55	46.00	-8.45	QP
4	398.296	37.78	-4.87	32.91	46.00	-13.09	QP
5	421.329	37.42	-4.30	33.12	46.00	-12.88	QP
6	445.693	36.94	-4.01	32.93	46.00	-13.07	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-RF-FCCPART15.247-V1.1

For Right Earbud

Radiated Emission Test Data (30 MHz ~ 1 GHz):

Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	144.790	46.69	-14.92	31.77	43.50	-11.73	QP
2	168.997	47.30	-12.16	35.14	43.50	-8.36	QP
3	193.137	44.08	-11.38	32.70	43.50	-10.80	QP
4	331.786	46.51	-7.56	38.95	46.00	-7.05	QP
5	398.296	43.56	-4.87	38.69	46.00	-7.31	QP
6	421.329	43.70	-4.30	39.40	46.00	-6.60	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888


Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.212	27.10	-4.47	22.63	40.00	-17.37	QP
2	168.997	35.90	-12.16	23.74	43.50	-19.76	QP
3	222.281	36.34	-10.84	25.50	46.00	-20.50	QP
4	334.126	40.88	-7.51	33.37	46.00	-12.63	QP
5	421.329	38.36	-4.30	34.06	46.00	-11.94	QP
6	445.693	37.56	-4.01	33.55	46.00	-12.45	QP

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

For Left Earbud

Radiated Emission Test Data (Above 1GHz):

Lowest Channel:

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804	38.03	-2.08	35.95	54.00	-18.05	Average	Horizontal
2	4804	55.59	-2.08	53.51	74.00	-20.49	Peak	Horizontal
3	9608	35.22	3.11	38.33	54.00	-15.67	Average	Horizontal
4	9608	52.24	3.11	55.35	74.00	-18.65	Peak	Horizontal
5	4804	38.07	-2.08	35.99	54.00	-18.01	Average	Vertical
6	4804	54.96	-2.08	52.88	74.00	-21.12	Peak	Vertical
7	9608	35.52	3.11	38.63	54.00	-15.37	Average	Vertical
8	9608	51.12	3.11	54.23	74.00	-19.77	Peak	Vertical

Middle Channel:

1	4882	38.36	-2.05	36.31	54.00	-17.69	Average	Horizontal
2	4882	55.03	-2.05	52.98	74.00	-21.02	Peak	Horizontal
3	9764	36.45	3.19	39.64	54.00	-14.36	Average	Horizontal
4	9764	52.96	3.19	56.15	74.00	-17.85	Peak	Horizontal
5	4882	37.67	-2.05	35.62	54.00	-18.38	Average	Vertical
6	4882	53.00	-2.05	50.95	74.00	-23.05	Peak	Vertical
7	9764	35.53	3.19	38.72	54.00	-15.28	Average	Vertical
8	9764	50.64	3.19	53.83	74.00	-20.17	Peak	Vertical

Highest Channel:

1	4960	37.91	-2.02	35.89	54.00	-18.11	Average	Horizontal
2	4960	53.74	-2.02	51.72	74.00	-22.28	Peak	Horizontal
3	9920	35.67	3.29	38.96	54.00	-15.04	Average	Horizontal
4	9920	52.36	3.29	55.65	74.00	-18.35	Peak	Horizontal
5	4960	37.06	-2.02	35.04	54.00	-18.96	Average	Vertical
6	4960	51.81	-2.02	49.79	74.00	-24.21	Peak	Vertical
7	9920	34.82	3.29	38.11	54.00	-15.89	Average	Vertical
8	9920	50.46	3.29	53.75	74.00	-20.25	Peak	Vertical

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

For Right Earbud

Radiated Emission Test Data (Above 1GHz):

Lowest Channel:

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804	39.13	-2.08	37.05	54.00	-16.95	Average	Horizontal
2	4804	55.78	-2.08	53.70	74.00	-20.30	Peak	Horizontal
3	9608	35.52	3.11	38.63	54.00	-15.37	Average	Horizontal
4	9608	52.94	3.11	56.05	74.00	-17.95	Peak	Horizontal
5	4804	38.19	-2.08	36.11	54.00	-17.89	Average	Vertical
6	4804	55.01	-2.08	52.93	74.00	-21.07	Peak	Vertical
7	9608	34.44	3.11	37.55	54.00	-16.45	Average	Vertical
8	9608	50.12	3.11	53.23	74.00	-20.77	Peak	Vertical

Middle Channel:

1	4882	38.31	-2.05	36.26	54.00	-17.74	Average	Horizontal
2	4882	54.97	-2.05	52.92	74.00	-21.08	Peak	Horizontal
3	9764	36.32	3.19	39.51	54.00	-14.49	Average	Horizontal
4	9764	52.63	3.19	55.82	74.00	-18.18	Peak	Horizontal
5	4882	38.59	-2.05	36.54	54.00	-17.46	Average	Vertical
6	4882	53.13	-2.05	51.08	74.00	-22.92	Peak	Vertical
7	9764	35.60	3.19	38.79	54.00	-15.21	Average	Vertical
8	9764	51.45	3.19	54.64	74.00	-19.36	Peak	Vertical

Highest Channel:

1	4960	37.88	-2.02	35.86	54.00	-18.14	Average	Horizontal
2	4960	54.58	-2.02	52.56	74.00	-21.44	Peak	Horizontal
3	9920	35.67	3.29	38.96	54.00	-15.04	Average	Horizontal
4	9920	54.12	3.29	57.41	74.00	-16.59	Peak	Horizontal
5	4960	36.86	-2.02	34.84	54.00	-19.16	Average	Vertical
6	4960	51.23	-2.02	49.21	74.00	-24.79	Peak	Vertical
7	9920	34.66	3.29	37.95	54.00	-16.05	Average	Vertical
8	9920	49.27	3.29	52.56	74.00	-21.44	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

5.10 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Section 6.10.5

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dB μ V/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).


1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Equipment Used: Refer to section 3 for details.



Test Result: Pass

The worst measurement data as follows:



Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal		
Frequency (MHz)	Peak level (dBuV/m)	Peak Limit (dBuV/m)	AV level (dBuV/m)	AV Limit (dBuV/m)	Conclusion
2390.000	51.77	74.00	36.29	54.00	Pass



UTTR-RF-FCCPART15.247-V1.1



For Right Earbud



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China



Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-RF-FCCPART15.247-V1.1

APPENDIX A RF TEST DATA

A.1 20DB BANDWIDTH

Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9613
	39	2441 MHz	0.9548
	78	2480 MHz	0.9567
$\pi/4$ DQPSK	0	2402 MHz	1.286
	39	2441 MHz	1.305
	78	2480 MHz	1.308


Test Graphs



A.2 CARRIER FREQUENCIES SEPARATION

Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Limit (MHz)	Result
GFSK	DH5	2439.9706	2440.9694	0.9988	0.641	PASS
$\pi/4$ DQPSK	2-DH5	2440.1443	2441.1467	1.0024	0.857	PASS

Test Graphs



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1

A.3 CONDUCTED OUT OF BAND EMISSION


Non-Hopping


Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2400.00	-52.413	-23.09	-29.323	PASS
			9607.87	-29.260	-23.09	-6.170	PASS
		39	9763.93	-31.374	-23.57	-7.804	PASS
		78	2483.50	-61.789	-24.28	-37.509	PASS
			9919.99	-31.148	-24.28	-6.868	PASS
$\pi/4$ DQPSK	2-DH5	0	2400.00	-53.627	-23.16	-30.467	PASS
			9607.87	-29.181	-23.16	-6.021	PASS
		39	9763.93	-31.604	-23.59	-8.014	PASS
		78	2483.50	-62.292	-24.14	-38.152	PASS
			9919.99	-30.954	-24.14	-6.814	PASS


Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2400.00	-54.220	-23.04	-31.180	PASS
			2483.50	-62.322	-24.27	-38.052	PASS
$\pi/4$ DQPSK	2-DH5	Hopping	2400.00	-57.118	-23.15	-33.968	PASS
			2483.50	-61.903	-24.24	-37.663	PASS


Test Graphs









Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping




Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping


A.4 DUTY CYCLE

Modulation	Packets	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)
GFSK	DH5	0	2.886	3.748	77.00	0.7700	1.1351
		39	2.886	3.748	77.00	0.7700	1.1351
		78	2.886	3.748	77.00	0.7700	1.1351
π /4DQPSK	2-DH5	0	2.890	3.748	77.11	0.7711	1.1289
		39	2.892	3.748	77.16	0.7716	1.1261
		78	2.892	3.748	77.16	0.7716	1.1261

Test Graphs




GFSK(DH5)_Channel 0




Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-FCCPART15.247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-FCCPART15.247-V1.1







Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China
Tel: +86-755-28230888 Fax: +86-755-28230886 E-mail: info@uttlab.com <http://www.uttlab.com>
UTTR-RF-FCCPART15.247-V1.1

A.5 DWELL TIME

Modulation	Packet	Channel	Pulse Width (ms)	Number of Pulses in 31.6 seconds	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	CH0 (2402MHz)	0.3804	318	120.97	< 400	PASS
	DH1	CH78 (2480MHz)	0.3804	310	117.92		PASS
	DH3	CH0 (2402MHz)	1.632	163	266.02		PASS
	DH3	CH78 (2480MHz)	1.632	150	244.8		PASS
	DH5	CH0 (2402MHz)	2.872	93	267.1		PASS
	DH5	CH78 (2480MHz)	2.896	100	289.6		PASS
$\pi/4$ DQPSK	2-DH1	CH0 (2402MHz)	0.3912	317	124.01		PASS
	2-DH1	CH78 (2480MHz)	0.3900	317	123.63		PASS
	2-DH3	CH0 (2402MHz)	1.632	162	264.38		PASS
	2-DH3	CH78 (2480MHz)	1.632	170	277.44		PASS
	2-DH5	CH0 (2402MHz)	2.896	113	327.25		PASS
	2-DH5	CH78 (2480MHz)	2.896	115	333.04		PASS

Test Graphs

	
Number of Pulses in 31.6 seconds GFSK_DH1	Pulse Width GFSK_DH1
	
Number of Pulses in 31.6 seconds GFSK_DH1	Pulse Width GFSK_DH1

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART15.247-V1.1



Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China


Tel: +86-755-28230888

Fax: +86-755-28230886


E-mail: info@uttlab.com

<http://www.uttlab.com>


UTTR-RF-FCCPART15.247-V1.1




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH1




Pulse Width
 $\pi/4$ DQPSK_2-DH1




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH1




Pulse Width
 $\pi/4$ DQPSK_2-DH1




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH3




Pulse Width
 $\pi/4$ DQPSK_2-DH3



Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH3




Pulse Width
 $\pi/4$ DQPSK_2-DH3



A.6 NUMBER OF HOPPING CHANNEL

Modulation	Packet	Number of Hopping Channel	Limit	Result
GFSK	DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS

Test Graphs



APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
