



■ Report No.: DDT-R19061107-1E1

■ Issued Date: Nov. 15, 2019

# FCC CERTIFICATION TEST REPORT

## FOR

|                             |   |   |
|-----------------------------|---|---|
| <b>Applicant</b>            | : | Guangdong Sygole Intelligent Technology Co.,Ltd   |
| <b>Address</b>              | : | Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province |
| <b>Equipment under test</b> | : | HF RFID Reader  |
| <b>Model No.</b>            | : | SG-HR-I5  |
| <b>Trade Mark</b>           | : | N/A   |
| <b>FCC ID</b>               | : | 2ATQ4SGHRI5   |
| <b>Manufacturer</b>         | : | Guangdong Sygole Intelligent Technology Co.,Ltd   |
| <b>Address</b>              | : | Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province |

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

**Tel:** +86-0769-89201699, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

**REPORT**

## TABLE OF CONTENTS

|      |  |    |
|------|--|----|
|      | Test report declares.....                        | 3  |
| 1    | Summary of test results .....                    | 5  |
| 2    | General test information .....                   | 6  |
| 2.1. | Description of EUT .....                         | 6  |
| 2.2. | Accessories of EUT.....                          | 6  |
| 2.3. | Assistant equipment used for test .....          | 6  |
| 2.4. | Block diagram of EUT configuration for test..... | 6  |
| 2.5. | Deviations of test standard.....                 | 6  |
| 2.6. | Test environment conditions .....                | 6  |
| 2.7. | Test laboratory .....                            | 7  |
| 2.8. | Measurement uncertainty .....                    | 7  |
| 3    | Equipment used during test .....                 | 8  |
| 4    | 20dB Bandwidth and 99% Bandwidth .....           | 9  |
| 4.1. | Block diagram of test setup.....                 | 9  |
| 4.2. | Limits .....                                     | 9  |
| 4.3. | Test Procedure.....                              | 9  |
| 4.4. | Test Result.....                                 | 9  |
| 4.5. | Original test data.....                          | 10 |
| 5    | Frequency Tolerance .....                        | 10 |
| 5.1. | Limit .....                                      | 10 |
| 5.2. | Block diagram of test setup.....                 | 10 |
| 5.3. | Test Procedure.....                              | 11 |
| 5.4. | Test result .....                                | 11 |
| 6    | Radiated emission.....                           | 12 |
| 6.1. | Block diagram of test setup.....                 | 12 |
| 6.2. | Limit .....                                      | 13 |
| 6.3. | Test Procedure.....                              | 14 |
| 6.4. | Test result .....                                | 15 |
| 7    | Power Line Conducted Emission .....              | 18 |
| 7.1. | Block diagram of test setup.....                 | 18 |
| 7.2. | Power Line Conducted Emission Limits .....       | 18 |
| 7.3. | Test Procedure.....                              | 18 |
| 7.4. | Test Result.....                                 | 19 |
| 8    | Antenna Requirements .....                       | 19 |

## TEST REPORT DECLARE

|                             |   |   |
|-----------------------------|---|---|
| <b>Applicant</b>            | : | Guangdong Sygole Intelligent Technology Co.,Ltd   |
| <b>Address</b>              | : | Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province |
| <b>Equipment under Test</b> | : | HF RFID Reader  |
| <b>Model No.</b>            | : | SG-HR-I5  |
| <b>Trade Mark</b>           | : | N/A   |
| <b>Manufacturer</b>         | : | Guangdong Sygole Intelligent Technology Co.,Ltd   |
| <b>Address</b>              | : | Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province |

**Test Standard Used:**

FCC Rules and Regulations Part 15 Subpart C

**Test procedure used:**

ANSI C63.10:2013

**We Declare:**

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC.**

|                         |                   |                      |                               |
|-------------------------|-------------------|----------------------|-------------------------------|
| <b>Report No.:</b>      | DDT-R19061107-1E1 |                      |                               |
| <b>Date of Receipt:</b> | Jun. 11, 2019     | <b>Date of Test:</b> | Jun. 11, 2019 ~ Nov. 09, 2019 |

**Prepared By:**



**Talent Zhang/Engineer**

**Approved By:**



**Damon Hu /EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

## Revision history

| Rev. | Revisions     | Issue Date    | Revised By |
|------|---------------|---------------|------------|
| ---  | Initial issue | Nov. 15, 2019 |            |
|      |               |               |            |

## 1 Summary of test results

| Description of Test Item         | Standard   | Results |
|----------------------------------|--|---------|
| 20dB Bandwidth and 99% Bandwidth | FCC Part 15: 15.215<br>ANSI C63.10:2013                        | PASS    |
| Frequency tolerance              | FCC Part 15:15.225<br>ANSI C63.10:2013                         | PASS    |
| Radiated Emission                | FCC Part 15: 15.209<br>FCC Part 15: 15.225<br>ANSI C63.10:2013 | PASS    |
| Power Line Conducted Emissions   | FCC Part 15: 15.207<br>ANSI C63.10:2013                        | N/A     |
| Antenna requirement              | FCC Part 15: 15.203<br>ANSI C63.10:2013                        | PASS    |

Note: N/A is an abbreviation for Not Applicable.

## 2 General test information

### 2.1. Description of EUT

|                          |   |   |
|--------------------------|---|---|
| EUT* Name                | : | HF RFID Reader                              |
| Model Number             | : | SG-HR-I5                                    |
| EUT function description | : | Please reference user manual of this device |
| Power supply             | : | DC 24V                                      |
| Operation frequency      | : | 13.56MHz                                    |
| Antenna Type             | : | Dedicated antenna                           |
| Sample Type              | : | Series production                           |

Note: EUT is the ab. of equipment under test.

### 2.2. Accessories of EUT

| Description of Accessories | Manufacturer | Model number | Serial No. | Mark |
|----------------------------|--------------|--------------|------------|------|
| N/A                        | N/A          | N/A          | N/A        | N/A  |

### 2.3. Assistant equipment used for test

| Assistant equipment | Manufacturer | Model number | Serial No. | Other |
|---------------------|--------------|--------------|------------|-------|
| Notebook            | N/A          | N/A          | N/A        | N/A   |
| Profinet cable      | N/A          | N/A          | N/A        | N/A   |
| Cable               | N/A          | N/A          | N/A        | N/A   |

### 2.4. Block diagram of EUT configuration for test



The EUT is connected to the 24 V DC power supply using the cable and to the measurement PC using the profinet cable.

### 2.5. Deviations of test standard

No Deviation.

### 2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

| /                  | Normal Conditions | Extreme Conditions |
|--------------------|-------------------|--------------------|
| Temperature range: | 21-25°C           | 0°C and 70°C       |
| Humidity range:    | 40-75%            | 40-75%             |
| Pressure range:    | 86-106kPa         | 86-106kPa          |
| Power supply       | DC 24V            | DC 20.4 and 27.6V  |

Note: The Extreme temperature range and extreme voltages are declared by the manufacturer.

## 2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-89201699 <http://www.dgddt.com>

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

## 2.8. Measurement uncertainty

| Test Item  | Uncertainty                   |
|--|-------------------------------|
| Uncertainty for Radiation Emission test<br>(9kHz-30MHz)    | 3.32dB (150KHz-30MHz)         |
|  | 3.72dB (9KHz-150KHz)          |
| Uncertainty for Radiation Emission test<br>(30MHz-1GHz)    | 4.70 dB (Antenna Polarize: V) |
|  | 4.84 dB (Antenna Polarize: H) |
| Uncertainty for Radiation Emission test<br>(1GHz to 18GHz) | 4.10dB(1-6GHz)                |
|  | 4.40dB (6GHz-18GHz)           |
| Bandwidth  | 1.1%                          |
| Uncertainty for radio frequency (RBW<20KHz)                | $3 \times 10^{-8}$            |


Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3 Equipment used during test

| Equipment   | Manufacturer | Model No.         | Serial No.        | Last Cal.     | Cal. Interval |
|---|--------------|-------------------|-------------------|---------------|---------------|
| <b>RF Connected Test (Tonscend RF Measurement System)</b> |              |                   |                   |               |               |
| Spectrum analyzer   | R&S          | FSU26             | 200071            | Sep. 29, 2019 | 1 Year        |
| Wideband Radio Communication tester                       | R&S          | CMW500            | 117491            | Jun. 25, 2019 | 1 Year        |
| Vector Signal Generator                                   | Agilent      | E8267D            | US49060192        | Sep. 29, 2019 | 1 Year        |
| Vector Signal Generator                                   | Agilent      | N5182A            | MY48180737        | Jun. 25, 2019 | 1 Year        |
| Power Sensor  | Agilent      | U2021XA           | MY55150010        | Jun. 28, 2019 | 1 Year        |
| Power Sensor  | Agilent      | U2021XA           | MY55150011        | Jun. 28, 2019 | 1 Year        |
| DC Power Source   | MATRIS       | MPS-3005L-3       | D813058W          | Jun. 25, 2019 | 1 Year        |
| RF Cable  | Micable      | C10-01-01-1       | 100309            | Sep. 29, 2019 | 1 Year        |
| Temp&Humi Programmable                                    | ZHIXIANG     | ZXGDJS-150L       | ZX170110-A        | Oct. 23, 2019 | 1 Year        |
| Test Software   | JS Tonscend  | JS1120-3          | Ver.2.7           | N/A           | N/A           |
| <b>Radiation 1#chamber</b>                                |              |                   |                   |               |               |
| EMI Test Receiver   | R&S          | ESU8              | 100316            | Sep. 28, 2019 | 1 Year        |
| Spectrum analyzer   | Agilent      | E4447A            | MY50180031        | Jun. 25, 2019 | 1 Year        |
| Trilog Broadband Antenna                                  | Schwarzbeck  | VULB9163          | 9163-462          | Nov. 09, 2019 | 1 Year        |
| Active Loop antenna                                       | Schwarzbeck  | FMZB-1519         | 1519-038          | Oct. 20, 2019 | 1 Year        |
| Double Ridged Horn Antenna                                | R&S          | HF907             | 100276            | Nov. 16, 2019 | 1 Year        |
| Broad Band Horn Antenna                                   | Schwarzbeck  | BBHA 9170         | 790               | Oct. 25, 2019 | 1 Year        |
| Pre-amplifier   | A.H.         | PAM-0118          | 360               | Sep. 29, 2019 | 1 Year        |
| Pre-amplifier   | TERA-MW      | TRLA-0040 G35     | 101303            | Sep. 29, 2019 | 1 Year        |
| RF Cable  | HUBSER       | CP-X2+ CP-X1      | W11.03+ W12.02    | Sep. 29, 2019 | 1 Year        |
| RF Cable  | N/A          | SMAJ-SMAJ-1M+ 11M | 17070133+17070131 | Sep. 29, 2019 | 1 Year        |
| MI Cable  | HUBSER       | C10-01-01-1M      | 1091629           | Sep. 29, 2019 | 1 Year        |
| Test software   | Audix        | E3                | V 6.11111b        | N/A           | N/A           |

## 4 20dB Bandwidth and 99% Bandwidth

### 4.1. Block diagram of test setup



### 4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:


|                |          |
|----------------|----------|
| RBW:           | 10Hz     |
| VBW:           | 30Hz     |
| Detector Mode: | Peak     |
| Sweep time:    | auto     |
| Trace mode     | Max hold |

(3) Allow the trace to stabilize, measure the 6dB and 99% bandwidth of signal.

### 4.4. Test Result

| Mode | Freq.<br>(MHz) | 20dB bandwidth<br>Result (Hz) | 99% bandwidth<br>Result (Hz) | Conclusion |
|------|----------------|-------------------------------|------------------------------|------------|
| ASK  | 13.56          | 27.24                         | 491.98                       | PASS       |

## 4.5. Original test data




## 5 Frequency Tolerance

### 5.1. Limit

As contained in § 15.225 the frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply Voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.2. Block diagram of test setup



### 5.3. Test Procedure

(1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 10 KHz.

Video BW: 10 KHz.

Span: 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

(2) When the trace is complete, find the peak value of the power envelope and record the frequency.

### 5.4. Test result


| Mode               | Condition            |                | Result            |                    |                    | Limit<br>ppm |
|--------------------|----------------------|----------------|-------------------|--------------------|--------------------|--------------|
|                    | Temperature<br>(°C ) | Voltage<br>(V) | Measured<br>(MHz) | Tolerance<br>(kHz) | Tolerance<br>(ppm) |              |
| Carrier Tx<br>Mode | NT                   | NV             | 13.5598           | -0.20              | -14.75             | 100          |
|                    | -20                  | NV             | 13.5601           | 0.10               | 7.37               | 100          |
|                    | 50                   | NV             | 13.5602           | 0.20               | 14.75              | 100          |
|                    | NT                   | 20.4           | 13.5600           | 0.00               | 0.00               | 100          |
|                    | NT                   | 27.6           | 13.5607           | 0.70               | 51.62              | 100          |
|                    | -20                  | 20.4           | 13.5602           | 0.20               | 14.75              | 100          |
|                    | 50                   | 20.4           | 13.5597           | -0.30              | -22.12             | 100          |
|                    | -20                  | 27.6           | 13.5603           | 0.30               | 22.12              | 100          |
|                    | 50                   | 27.6           | 13.5604           | 0.40               | 18.50              | 100          |

Note: NT:20°C, NV:24V


## 6 Radiated emission

### 6.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9kHz~30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz~1GHz



## 6.2. Limit

Operation within the band 13.110-14.010 MHz as contained in §15.225:

- (a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

| FREQUENCY<br>MHz | DISTANCE<br>Meters | FIELD STRENGTHS LIMIT |               |
|------------------|--------------------|-----------------------|---------------|
|                  |                    | μV/m                  | dB(μV)/m      |
| 0.009 ~ 0.490    | 300                | 2400/F(KHz)           | 67.6-20log(F) |
| 0.490 ~ 1.705    | 30                 | 24000/F(KHz)          | 87.6-20log(F) |
| 1.705 ~ 13.110   | 30                 | 30                    | 29.54         |
| 13.110 ~ 13.410  | 30                 | 106                   | 40.51         |
| 13.410~ 13.553   | 30                 | 334                   | 50.47         |
| 13.553~13.567    | 30                 | 15848                 | 84.00         |
| 13.567~13.710    | 30                 | 334                   | 50.47         |
| 13.710~14.010    | 30                 | 106                   | 40.51         |
| 14.010~30        | 30                 | 30                    | 29.54         |
| 30 ~ 88          | 3                  | 100                   | 40.0          |
| 88 ~ 216         | 3                  | 150                   | 43.5          |
| 216 ~ 960        | 3                  | 200                   | 46.0          |
| 960 ~ 1000       | 3                  | 500                   | 54.0          |

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz.Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV}/\text{m}) = \text{Limit}_{300m}(\text{dBuV}/\text{m}) + 40\text{Log}(300m/3m) = \text{Limit}_{300m}(\text{dBuV}/\text{m}) + 80$$

$$\text{Limit}_{3m}(\text{dBuV}/\text{m}) = \text{Limit}_{30m}(\text{dBuV}/\text{m}) + 40\text{Log}(30m/3m) = \text{Limit}_{30m}(\text{dBuV}/\text{m}) + 40$$

| FREQUENCY<br>MHz | DISTANCE<br>Meters | FIELD STRENGTHS<br>LIMIT<br>dB( $\mu$ V)/m |
|------------------|--------------------|--|
| 0.009 ~ 0.490    | 3                  | 147.6-20log(F)                             |
| 0.490 ~ 1.705    | 3                  | 127.6-20log(F)                             |
| 1.705 ~ 13.110   | 3                  | 69.54                                      |
| 13.110 ~ 13.410  | 3                  | 80.51                                      |
| 13.410 ~ 13.553  | 3                  | 90.47                                      |
| 13.553 ~ 13.567  | 3                  | 124.00                                     |
| 13.567 ~ 13.710  | 3                  | 90.47                                      |
| 13.710 ~ 14.010  | 3                  | 80.51                                      |
| 14.010 ~ 30      | 3                  | 69.54                                      |
| 30 ~ 88          | 3                  | 40.00                                      |
| 88 ~ 216         | 3                  | 43.50                                      |
| 216 ~ 960        | 3                  | 46.00                                      |
| 960 ~ 1000       | 3                  | 54.00                                      |

### 6.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 100 cm above the ground plane inside a semi-anechoic chamber.
- (2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

| Test frequency range | Test antenna used        | Test antenna distance |
|----------------------|--------------------------|-----------------------|
| 9KHz-30MHz           | Active Loop antenna      | 3m                    |
| 30MHz-1GHz           | Trilog Broadband Antenna | 3m                    |

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 1GHz:
  - (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)
  - (b) Change work frequency or channel of device if practicable.
  - (c) Change modulation type of device if practicable.
  - (d) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement

produces highest emissions. Spectrum frequency from 9KHz to 1GHz (tenth harmonic of fundamental frequency) was investigated.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

| Frequency band | RBW    |
|----------------|--------|
| 9KHz-150KHz    | 200Hz  |
| 150KHz-30MHz   | 9KHz   |
| 30MHz-1GHz     | 120KHz |

#### 6.4. Test result

**PASS. (See below detailed test result)**

**Below 30MHz:**

| Frequency (MHz) | Result @3m (dBuV/m) | Limit @3m (dBuV/m) | Detector | Conclusion |
|-----------------|---------------------|--------------------|----------|------------|
| 0.030           | 16.93               | 118.05             | Average  | PASS       |
| 0.030           | 17.33               | 138.05             | Peak     | PASS       |
| 0.080           | 2.83                | 109.54             | Average  | PASS       |
| 0.080           | 3.76                | 129.54             | Peak     | PASS       |
| 0.100           | -3.26               | 107.60             | QP       | PASS       |
| 4.330           | -0.35               | 69.54              | QP       | PASS       |
| 13.110          | -2.54               | 69.54              | QP       | PASS       |
| 13.410          | 8.33                | 69.54              | QP       | PASS       |
| 13.550          | 33.59               | 80.50              | QP       | PASS       |
| 13.560          | 36.56               | 124.00             | QP       | PASS       |
| 13.570          | 31.00               | 90.47              | QP       | PASS       |
| 13.710          | 10.15               | 90.47              | QP       | PASS       |
| 14.010          | 2.16                | 90.50              | QP       | PASS       |
| 18.510          | -3.09               | 69.54              | QP       | PASS       |

Above 30MHz:

## TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19061107-1E SG-HR-I5\FCC  
30M-1G.EM6

Test Date : 2019-10-20

Tested By : Jack

EUT : HF RFID Reader


Model Number : SG-HR-I5

Power Supply : DC 24V

Test Mode : TX mode

Condition : Temp:24.5'C,Humi:55%,Press:100.1kPa Antenna/Distance : 2018 VULB 9163 1#/3m/HORIZONTAL

Memo : 1#



| Item<br>(Mark) | Freq.<br>(MHz) | Read<br>Level<br>(dB $\mu$ V) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>dB | Result<br>Level<br>(dB $\mu$ V/m) | Limit<br>Line<br>(dB $\mu$ V/m) | Over<br>Limit<br>(dB) | Detector | Polarization |
|----------------|----------------|-------------------------------|-----------------------------|---------------------|-----------------------------------|---------------------------------|-----------------------|----------|--------------|
| 1              | 31.96          | 15.38                         | 11.60                       | 3.67                | 30.65                             | 40.00                           | -9.35                 | QP       | HORIZONTAL   |
| 2              | 47.66          | 12.40                         | 14.34                       | 3.85                | 30.59                             | 40.00                           | -9.41                 | QP       | HORIZONTAL   |
| 3              | 148.96         | 20.76                         | 8.43                        | 4.51                | 33.70                             | 43.50                           | -9.80                 | QP       | HORIZONTAL   |
| 4              | 176.27         | 19.97                         | 9.41                        | 4.71                | 34.09                             | 43.50                           | -9.41                 | QP       | HORIZONTAL   |
| 5              | 298.27         | 16.52                         | 13.96                       | 5.18                | 35.66                             | 46.00                           | -10.34                | QP       | HORIZONTAL   |
| 6              | 325.60         | 14.68                         | 14.46                       | 5.28                | 34.42                             | 46.00                           | -11.58                | QP       | HORIZONTAL   |


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2019-10-20  
**Tested By** : Jack  
**EUT** : HF RFID Reader  
**Model Number** : SG-HR-I5  
**Power Supply** : DC 24V  
**Test Mode** : TX mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/VERTICAL  
**Memo** : 1#



| Item<br>(Mark) | Freq.<br>(MHz) | Read<br>Level<br>(dB $\mu$ V) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>dB | Result<br>Level<br>(dB $\mu$ V/m) | Limit<br>Line<br>(dB $\mu$ V/m) | Over<br>Limit<br>(dB) | Detector | Polarization |
|----------------|----------------|-------------------------------|-----------------------------|---------------------|-----------------------------------|---------------------------------|-----------------------|----------|--------------|
| 1              | 30.85          | 15.02                         | 11.32                       | 3.65                | 29.99                             | 40.00                           | -10.01                | QP       | VERTICAL     |
| 2              | 50.41          | 8.31                          | 14.46                       | 3.87                | 26.64                             | 40.00                           | -13.36                | QP       | VERTICAL     |
| 3              | 148.96         | 21.96                         | 8.43                        | 4.51                | 34.90                             | 43.50                           | -8.60                 | QP       | VERTICAL     |
| 4              | 162.61         | 21.00                         | 8.83                        | 4.61                | 34.44                             | 43.50                           | -9.06                 | QP       | VERTICAL     |
| 5              | 176.27         | 18.79                         | 9.41                        | 4.71                | 32.91                             | 43.50                           | -10.59                | QP       | VERTICAL     |
| 6              | 203.52         | 15.81                         | 11.51                       | 4.83                | 32.15                             | 43.50                           | -11.35                | QP       | VERTICAL     |


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

## 7 Power Line Conducted Emission

### 7.1. Block diagram of test setup



### 7.2. Power Line Conducted Emission Limits

| Frequency       | Quasi-Peak Level<br>dB(µV) | Average Level<br>dB(µV) |
|-----------------|----------------------------|-------------------------|
| 150kHz ~ 500kHz | 66 ~ 56*                   | 56 ~ 46*                |
| 500kHz ~ 5MHz   | 56                         | 46                      |
| 5MHz ~ 30MHz    | 60                         | 50                      |

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 7.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

#### 7.4. Test Result

Not Applicable

According to 15.207(C): Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ DC power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

### 8 Antenna Requirements

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**END OF REPORT**